

Ostwald-Optimalfarben (o), maximales (m) C _{AB} für P60, Y _N =0, Y _W =100, Y _M =520...770													
i ₁	λ ₁	i ₂	λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d	λ _d	Code
0	405	32	563	31.65	53.56	93.3	0.1773	0.3	0.5226	192.2	16	483	38 590 Cm
6	435	32	563	28.3	54.12	74.65	0.1801	0.3445	0.4752	174.7	17	487	44 621
10	450	33	565	22.96	54.12	45.12	0.1877	0.4432	0.3689	140.1	19	497	-1 497c
11	460	33	566	22.85	55.45	37.84	0.1967	0.4774	0.3258	130.5	20	502	-1 502c
13	465	33	568	21.78	56.12	24.97	0.2117	0.5455	0.2427	117.2	22	513	-1 513c
14	470	34	570	22.2	57.09	19.98	0.2236	0.575	0.2012	111.9	24	521	-1 521c Gm
15	475	34	574	24.59	59.7	16.0	0.2451	0.5952	0.1595	106.1	25	529	-1 529c
15	480	36	580	28.98	63.87	16.01	0.2662	0.5866	0.147	102.2	27	535	-1 535c
17	485	39	595	39.81	70.8	10.63	0.3283	0.5839	0.0877	88.4	29	549	-1 549c
18	490	-1 490c	72.35	85.0	8.89	4.4352	0.5113	0.0534	57.3	33	566	11 459	
19	495	-1 495c	72.31	83.76	7.55	0.4419	0.5119	0.0461	56.3	33	567	12 461	
20	500	-1 500c	72.29	82.2	6.51	0.449	0.5105	0.0404	54.5	33	568	12 464	
22	510	-1 510c	72.19	77.89	5.14	0.465	0.5017	0.0331	49.9	34	570	13 469	
24	520	-1 520c	71.62	71.91	4.45	0.4839	0.4859	0.0301	43.5	34	572	14 473 Ym	
25	530	-1 529c	71.04	68.43	4.25	0.4943	0.4761	0.0295	39.9	34	574	15 475	
27	540	-1 539c	69.15	60.8	3.99	0.5162	0.4539	0.0298	32.1	35	578	15 478	
29	545	-1 545c	66.16	52.69	3.87	0.539	0.4293	0.0315	24.2	36	582	16 480	
29	550	-1 549c	66.16	52.69	3.87	0.539	0.4293	0.0315	24.2	36	582	16 480	
30	555	-1 554c	64.21	48.59	3.84	0.5504	0.4165	0.0329	20.3	36	584	16 481	
32	560	-1 560c	59.36	40.5	3.81	0.5725	0.3906	0.0367	13.2	37	589	16 483	
32	563	0	405	65.41	46.43	11.27	0.5312	0.3771	0.0915	12.2	38	590	16 483 Rm
32	563	6	435	68.76	45.87	29.92	0.4756	0.3173	0.2069	35.47	44	621	17 487
33	565	10	450	74.1	45.79	59.44	0.4131	0.2553	0.3314	320.2	-1 497c	19 497	
33	566	11	460	74.21	44.54	66.72	0.4001	0.2401	0.3597	310.6	-1 502c	20 502	
33	568	13	465	75.28	43.87	79.59	0.3787	0.2207	0.4004	297.2	-1 513c	22 513	
34	570	14	470	74.86	42.9	84.59	0.3699	0.212	0.418	291.9	-1 521c	24 521 Mm	
34	574	15	475	72.47	40.29	88.56	0.3599	0.2001	0.4398	286.2	-1 529c	25 529	
36	580	15	480	68.08	36.12	88.55	0.3531	0.1874	0.4594	282.3	-1 535c	27 535	
39	595	17	485	57.25	29.19	93.93	0.3173	0.1618	0.5207	268.5	-1 549c	29 549	
-1 490c	18	490	54.71	14.99	95.68	0.1825	0.1107	0.7067	237.7	11 459	33	566 min	
-1 495c	19	495	24.75	16.23	97.02	0.1793	0.1176	0.7029	236.3	12	461	33 567	
-1 500c	20	500	24.77	17.79	98.05	0.1761	0.1265	0.6972	234.6	12	464	33 568	
-1 510c	22	510	24.87	22.1	99.42	0.1699	0.1509	0.679	229.9	13	469	34 570	
-1 520c	24	520	25.44	28.08	100.11	0.1655	0.1827	0.6516	223.6	14	473	34 572 Bm	
-1 529c	25	530	26.02	31.56	100.32	0.1647	0.1999	0.6353	219.9	15	475	34 574	
-1 539c	27	540	29.91	39.19	100.57	0.1664	0.2337	0.5997	212.2	15	478	35 578	
-1 545c	29	545	30.9	47.3	100.69	0.1727	0.2644	0.5628	204.2	16	480	36 582	
-1 549c	29	550	30.9	47.3	100.69	0.1727	0.2644	0.5628	204.2	16	480	36 582	
-1 554c	30	555	32.85	51.4	100.72	0.1776	0.2778	0.5445	200.4	16	481	36 584	
-1 560c	32	560	37.7	59.49	100.75	0.1904	0.3005	0.5089	193.2	16	483	37 589	
W0	380	770	97.06	99.99	104.57	0.3218	0.3315	0.3466	0.0				
N0	380	770	3.88	3.99	4.18	0.3218	0.3315	0.3466	0.0				

Ostwald-Optimalfarben (o), maximales (m) C _{AB} für P60, Y _N =0, Y _W =100, Y _M =520...770													
i ₁	λ ₁	i ₂	λ ₂	Y	A	B	C _{AB}	a	b	h _{xy}	i _d	λ _d	Code
0	405	32	563	53.56	-50.83	-37.27	63.03	0.5907	-0.6965	216.2	16	483	38 590 Cm
6	435	32	563	54.12	-60.57	-11.04	63.2	0.5227	-0.5515	196.5	17	487	44 621
10	450	33	565	54.2	-74.11	11.55	74.99	0.4236	-0.3329	171.1	19	497	-1 497c
11	460	33	566	55.45	-77.42	20.13	79.99	0.4119	-0.2729	165.4	20	502	-1 502c
13	465	33	568	56.12	-81.71	33.7	88.38	0.388	-0.1779	157.5	22	513	-1 513c
14	470	34	570	57.09	-83.01	39.7	92.02	0.3888	-0.1399	154.4	24	521	-1 521c Gm
15	475	34	574	59.7	-83.37	46.41	95.41	0.4118	-0.1072	150.8	25	529	-1 529c
15	480	36	580	63.87	-82.5	50.76	96.86	0.4537	-0.1002	148.3	27	535	-1 535c
17	485	39	595	70.8	-72.25	63.39	96.12	0.5622	-0.06	138.7	29	549	-1 549c
18	490	-1 490c	85.0	8.89	73.98	83.91	0.8509	-0.0418	107.6	33	566	11 459 max	
19	495	-1 495c	83.76	7.55	83.76	83.11	0.8631	-0.036	105.6	33	567	12 461	
20	500	-1 500c	82.2	6.51	82.2	81.59	0.8793	-0.0316	103.2	33	568	12 464	
22	510	-1 510c	77.89	5.14	77.89	76.76	0.9265	-0.0264	96.3	34	570	13 469	
24	520	-1 520c	71.91	4.55	70.72	70.87	0.9957	-0.0247	86.3	34	572	14 473 Ym	
25	530	-1 529c	68.43	11.56	67.29	68.27	1.038	-0.0248	80.2	34	574	15 475	
27	540	-1 539c	60.8	25.33	59.57	64.73	1.137	-0.0262	66.9	35	578	15 478	
29	545	-1 545c	52.69	37.52	51.21	63.48	1.2552	-0.0294	53.7	36	582	16 480	
29	550	-1 549c	52.69	37.52	51.21	63.48	1.2552	-0.0294	53.7	36	582	16 480	
30	555	-1 554c	48.59	42.61	46.95	63.4	1.3211	-0.0316	47.7	36	584	16 481	
32	560	-1 560c	40.5	50.12	38.52	63.21	1.4654	-0.0376	37.5	37	589	16 483	
32	563	0	405	46.43	50.84	37.27	63.04	1.4083	-0.097	36.2	38	590	16 483 Rm
32	563	6	435	45.87	60.57	18.04	63.2	1.4985	-0.2608	16.5	44	621	17 487
33	565	10	450	45.79	74.08	-11.55	74.98	1.6175	-0.519	35.1	-1 497c	19 497	
33	566	11	460	44.54	77.4	-20.13	79.98	1.6655	-0.5989	34.5	-1 502c	20 502	
33	568	13	465	43.87	81.68	-33.69	88.36	1.7151	-0.7253	33.75	-1 513c	22 513	
34	570	14	470	42.9	82.98	-39.69	91.99	1.7441	-0.7882	33.44	-1 521c	24 521 Mm	
34	574	15	475	40.29	83.34	-46.39	95.38	1.7977	-0.8786	33.08	-1 529c	25 529	
36	580	15	480	36.12	82.47	-50.74	96.83	1.8835	-0.9799	32.83	-1 535c	27 535	
39	595	17	485	29.19	72.22	-63.36	96.08	1.9601	-1.2864	31.87	-1 549c	29 549	
-1 490c	18	490	14.99	25.36	-79.92	83.85	1.6471	-2.5507	287.6	11 459	33	566 min	
-1 495c	19	495	16.23	22.44	-79.96	83.05	1.5234	-2.3881	285.6	12 461	33	567	
-1 500c	20	500	17.79	18.7	-79.37	81.54	1.3907	-2.2019	283.2	12 464	33	568	
-1 510c	22	510	22.1	8.53	-76.24	76.72	1.1247	-1.7979	276.3	13 469	34	570	
-1 520c	24	520	28.08	-4.55	-70.7	70.84	0.9055	-1.4253	266.3	14 473	34	572 Bm	
-1 529c	25	530	31.56	-11.56	-67.27	68.25	0.8238	-1.2706	260.5	15 475	34	574	
-1 539c	27	540	39.19	-25.32	-59.55	64.72	0.7119	-1.0259	246.9	15 478	35	578	
-1 545c	29	545	47.3	-37.51	-51.2	63.47	0.6531	-0.8511	233.7	16 480	36	582	
-1 549c	29	550	47.3	-37.51	-51.2	63.47	0.6531	-0.8511	233.7	16 480	36	582	
-1 554c	30	555	51.4	-42.6	-46.94	63.4	0.6388	-0.7834	227.7	16 481	36	584	
-1 560c	32	560	59.49	-50.11	-38.52	63.21	0.6334	-0.6771	217.5	16 483	37	589	
W0	380	770	99.99	0.0	0.0	0.0	0.9704	-0.4181	0.0	B _c =1,000			
N0	380	770	3.99	0.0	0.0	0.0	0.9704	-0.4181	0.0	x _c =0,000			