

Oswald-Optimalfarben (o), maximales (m) C _{AB} für P60, Y _N =0, Y _W =100, Y _m =520...770																
i ₁	λ ₁	i ₂	λ ₂	Y	A ₁	B ₁	C _{AB,1}	a ₁	b ₁	h _{xy,1}	i _d	λ _d	i _c	λ _c	Code	
0	405	32	563	53.56	-55.49	-37.27	66.85	0.2242	-0.6965	213.8	16	483	38	590	Cm	
6	435	32	563	54.12	-58.87	-18.04	61.57	0.2036	-0.5515	197.0	17	487	44	621		
10	450	33	565	54.2	-62.77	11.55	63.82	0.1754	-0.3329	169.5	19	497	-1	497c		
11	460	33	566	55.45	-63.36	20.13	66.49	0.1816	-0.2729	162.3	20	502	-1	502c		
13	465	33	568	56.12	-63.45	33.7	71.85	0.1864	-0.1779	152.0	22	513	-1	513c		
14	470	34	570	57.09	-62.96	39.7	74.43	0.1975	-0.1399	147.7	24	521	-1	521c	Gm	
15	475	34	574	59.7	-61.44	46.41	76.99	0.227	-0.1072	142.9	25	529	-1	529c		
15	480	36	580	63.87	-59.47	50.76	78.18	0.2662	-0.1002	139.5	27	535	-1	535c		
17	485	39	595	70.8	-46.88	63.39	78.84	0.3738	-0.06	126.4	29	549	-1	549c		
18	490	-1	490c	85.0	-0.59	79.98	79.98	0.6358	-0.0418	90.4	33	566	11	459	max	
19	495	-1	495c	83.76	2.0	80.01	80.04	0.6482	-0.036	88.5	33	567	12	461		
20	500	-1	500c	82.2	5.18	79.42	79.59	0.6639	-0.0316	86.2	33	568	12	464		
22	510	-1	510c	77.89	13.38	76.28	77.44	0.7074	-0.0264	80.0	34	570	13	469		
24	520	-1	520c	71.91	23.5	70.72	74.53	0.7694	-0.0247	71.6	34	572	14	473	Ym	
25	530	-1	529c	68.43	28.79	67.29	73.19	0.807	-0.0248	66.8	34	574	15	475		
27	540	-1	539c	60.8	38.92	59.57	71.16	0.8947	-0.0262	56.8	35	578	15	478		
29	545	-1	545c	52.69	47.47	51.21	69.83	0.999	-0.0294	47.1	36	582	16	480		
29	550	-1	549c	52.69	47.47	51.21	69.83	0.999	-0.0294	47.1	36	582	16	480		
30	555	-1	554c	48.59	50.83	46.95	69.2	1.0571	-0.0316	42.7	36	584	16	481		
32	560	-1	560c	40.5	55.2	38.52	67.31	1.1839	-0.0376	34.9	37	589	16	483		
32	563	0	405	46.43	55.49	37.27	66.85	1.1167	-0.097	33.8	38	590	16	483	Rm	
32	563	6	435	45.87	58.87	18.04	61.57	1.152	-0.2608	17.0	44	621	17	487		
33	565	10	450	45.79	62.76	-11.55	63.81	1.1869	-0.519	349.5	-1	497c	19	497		
33	566	11	460	44.54	63.35	-20.13	66.47	1.2076	-0.5989	342.3	-1	502c	20	502		
33	568	13	465	43.87	63.44	-33.69	71.83	1.217	-0.7253	332.0	-1	513c	22	513		
34	570	14	470	42.9	62.94	-39.69	74.41	1.2255	-0.7882	327.7	-1	521c	24	521	Mm	
34	574	15	475	40.29	61.42	-46.39	76.97	1.2483	-0.8786	322.9	-1	529c	25	529		
36	580	15	480	36.12	59.44	-50.74	78.16	1.2969	-0.9799	319.5	-1	535c	27	535		
39	595	17	485	29.19	46.85	-63.36	78.8	1.2808	-1.2864	306.4	-1	549c	29	549		
-1	490c	18	490	14.99	0.59	-79.92	79.92	0.6546	-2.5507	270.4	11	459	33	566	min	
-1	495c	19	495	16.23	-2.0	-79.96	79.99	0.5892	-2.3881	268.5	12	461	33	567		
-1	500c	20	500	17.79	-5.17	-79.37	79.54	0.5223	-2.2019	266.2	12	464	33	568		
-1	510c	22	510	22.1	-13.37	-76.24	77.41	0.3966	-1.7979	260.0	13	469	34	570		
-1	520c	24	520	28.08	-23.49	-70.77	74.5	0.304	-1.4253	251.6	14	473	34	572	Bm	
-1	529c	25	530	31.56	-28.78	-67.27	73.17	0.2738	-1.2706	246.8	15	475	34	574		
-1	539c	27	540	39.19	-38.91	-59.55	71.14	0.2415	-1.0259	236.8	15	478	35	578		
-1	545c	29	545	47.3	-47.46	-51.2	69.82	0.2372	-0.8511	227.1	16	480	36	582		
-1	549c	29	550	47.3	-47.46	-51.2	69.82	0.2372	-0.8511	227.1	16	480	36	582		
-1	554c	30	555	51.4	-50.83	-46.94	69.19	0.2431	-0.7834	222.7	16	481	36	584		
-1	560c	32	560	59.49	-55.19	-38.52	67.31	0.2676	-0.6771	214.9	16	483	37	589		
W0	380	770	99.99	0.0	0.0	0.0	0.0	0.6386	-0.4181	0.0	Bc=1,000					
N0	380	770	3.99	0.0	0.0	0.0	0.0	0.6386	-0.4181	0.0	x _c =0,110					

CGAB2-79

Oswald-Optimalfarben (o), maximales (m) C _{AB} für P60, Y _N =0, Y _W =100, Y _m =520..770																
i ₁	λ ₁	i ₂	λ ₂	Y	A ₂	B ₂	C _{AB,2}	a ₂	b ₂	h _{xy,2}	i _d	λ _d	i _c	λ _c	Code	
0	405	32	563	53.56	-55.49	-29.81	62.99	0.2242	-0.6965	208.2	16	483	38	590	Cm	
6	435	32	563	54.12	-58.87	-14.43	60.61	0.2036	-0.5515	193.7	17	487	44	621		
10	450	33	565	54.2	-62.77	9.24	63.45	0.1754	-0.3329	171.6	19	497	-1	497c		
11	460	33	566	55.45	-63.36	16.11	65.38	0.1816	-0.2729	165.7	20	502	-1	502c		
13	465	33	568	56.12	-63.45	26.96	68.94	0.1864	-0.1779	156.9	22	513	-1	513c		
14	470	34	570	57.09	-62.96	31.76	70.52	0.1975	-0.1399	153.2	24	521	-1	521c	Gm	
15	475	34	574	59.7	-61.44	37.12	71.78	0.227	-0.1072	148.8	25	529	-1	529c		
15	480	36	580	63.87	-59.47	40.6	72.01	0.2662	-0.1002	145.6	27	535	-1	535c		
17	485	39	595	70.8	-46.88	50.71	69.06	0.3738	-0.06	132.7	29	549	-1	549c		
18	490	-1	490c	85.0	-0.59	63.98	63.98	0.6358	-0.0418	90.5	33	566	11	459	max	
19	495	-1	495c	83.76	2.0	64.01	64.04	0.6482	-0.036	88.2	33	567	12	461		
20	500	-1	500c	82.2	5.18	63.53	63.74	0.6639	-0.0316	85.3	33	568	12	464		
22	510	-1	510c	77.89	13.38	61.02	62.47	0.7074	-0.0264	77.6	34	570	13	469		
24	520	-1	520c	71.91	23.5	56.58	61.26	0.7694	-0.0247	67.4	34	572	14	473	Ym	
25	530	-1	529c	68.43	28.79	53.83	61.05	0.807	-0.0248	61.8	34	574	15	475		
27	540	-1	539c	60.8	38.92	47.65	61.03	0.8947	-0.0262	50.7	35	578	15	478		
29	545	-1	545c	52.69	47.47	40.97	62.7	0.999	-0.0294	40.7	36	582	16	480		
29	550	-1	549c	52.69	47.47	40.97	62.7	0.999	-0.0294	40.7	36	582	16	480		
30	555	-1	554c	48.59	50.83	37.56	63.2	1.0571	-0.0316	36.4	36	584	16	481		
32	560	-1	560c	40.5	55.2	30.82	63.22	1.1839	-0.0376	29.1	37	589	16	483		
32	563	0	405	46.43	55.49	29.82	63.0	1.1167	-0.097	28.2	38	590	16	483	Rm	
32	563	6	435	45.87	58.87	14.43	60.61	1.152	-0.2608	13.7	44	621	17	487		
33	565	10	450	45.79	62.76	-9.24	63.44	1.1869	-0.519	351.6	-1	497c	19	497		
33	566	11	460	44.54	63.35	-16.1	65.37	1.2076	-0.5989	345.7	-1	502c	20	502		
33	568	13	465	43.87	63.44	-26.95	68.92	1.217	-0.7253	336.9	-1	513c	22	513		
34	570	14	470	42.9	62.94	-31.75	70.5	1.2255	-0.7882	333.2	-1	521c	24	521	Mm	
34	574	15	475	40.29	61.42	-37.11	71.76	1.2483	-0.8786	328.8	-1	529c	25	529		
36	580	15	480	36.12	59.44	-40.59	71.98	1.2969	-0.9799	325.6	-1	535c	27	535		
39	595	17	485	29.19	46.85	-50.68	69.03	1.2808	-1.2864	312.7	-1	549c	29	549		
-1	490c	18	490	14.99	0.59	-63.93	63.94	0.6546	-2.5507	270.5	11	459	33	566	min	
-1	495c	19	495	16.23	-2.0	-63.97	64.0	0.5892	-2.3881	268.2	12	461	33	567		
-1	500c	20	500	17.79	-5.17	-63.49	63.71	0.5223	-2.2019	265.3	12	464	33	568		
-1	510c	22	510	22.1	-13.37	-60.99	62.44	0.3966	-1.7979	257.6	13	469	34	570		
-1	520c	24	520	28.08	-23.49	-56.56	61.24	0.304	-1.4253	247.4	14	473	34	572	Bm	
-1	529c	25	530	31.56	-28.78	-53.81	61.03	0.2738	-1.2706	241.8	15	475	34	574		
-1	539c	27	540	39.19	-38.91	-47.64	61.52	0.2415	-1.0259	230.7	15	478	35	578		
-1	545c	29	545	47.3	-47.46	-40.96	62.7	0.2372	-0.8511	220.7	16	480	36	582		
-1	549c	29	550	47.3	-47.46	-40.96	62.7	0.2372	-0.8511	220.7	16	480	36	582		
-1	554c	30	555	51.4	-50.83	-37.55	63.2	0.2431	-0.7834	216.4	16	481	36	584		
-1	560c	32	560	59.49	-55.19	-30.81	63.21	0.2676	-0.6771	209.1	16	483	37	589		
W0	380	770	99.99	0.0	0.0	0.0	0.0	0.6386	-0.3345	0.0					Be=0.800	
N0	380	770	3.99	0.0	0.0	0.0	0.0	0.6386	-0.3345	0.0					x _c =0.110	