

Ostwald optimal colours (o) of maximum (m) C_{AB} for P60, Y_w=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{ab}	i _d , λ _d	i _c , λ _c	Code
0 405	32 563	57.75	−23.52	−17.29	29.19	0.5634	−0.7177	216.3	16 483	38 590	Cm
6 435	32 563	58.29	−28.0	−8.43	29.24	0.4903	−0.5629	196.7	17 487	44 621	
10 450	33 565	58.9	−34.37	5.49	34.81	0.3871	−0.325	170.9	19 497	−1 497c	
11 460	33 566	60.12	−35.87	9.37	37.07	0.374	−0.2624	165.3	20 502	−1 502c	
13 465	33 568	60.68	−37.82	15.56	40.9	0.3474	−0.1618	157.6	22 513	−1 513c	
14 470	34 570	62.18	−38.45	18.5	42.67	0.3521	−0.1207	154.3	24 521	−1 521c	
15 475	34 574	64.7	−38.6	21.39	44.13	0.374	−0.0875	151.0	25 529	−1 529c	Gm
15 480	36 580	69.95	−38.16	23.59	44.86	0.4251	−0.081	148.2	27 535	−1 535c	
17 485	39 595	78.0	−33.31	29.44	44.46	0.5435	−0.0407	138.5	29 549	−1 549c	
18 490	−1 490c	94.22	−11.76	37.03	38.86	0.8458	−0.0251	107.6	33 566	11 459	max
19 495	−1 495c	92.78	−10.41	37.05	38.49	0.8584	−0.0188	105.6	33 567	12 461	
20 500	−1 500c	90.97	−8.67	36.78	37.78	0.8753	−0.0139	103.2	33 568	12 464	
22 510	−1 510c	85.98	−3.96	35.32	35.54	0.9246	−0.0074	96.3	34 570	13 469	
24 520	−1 520c	79.07	2.1	32.75	32.82	0.9972	−0.004	86.3	34 572	14 473	Ym
25 530	−1 529c	75.03	5.34	31.16	31.61	1.0419	−0.0029	80.2	34 574	15 475	
27 540	−1 539c	66.2	11.72	27.58	29.97	1.1478	−0.0016	66.9	35 578	15 478	
29 545	−1 545c	56.82	17.37	23.71	29.39	1.2763	−0.0009	53.7	36 582	16 480	
29 550	−1 549c	56.82	17.37	23.71	29.39	1.2763	−0.0009	53.7	36 582	16 480	
30 555	−1 554c	52.07	19.73	21.74	29.36	1.3495	−0.0007	47.7	36 584	16 481	
32 560	−1 560c	42.7	23.2	17.84	29.27	1.5141	−0.0005	37.5	37 589	16 483	
32 563	0 405	42.24	23.52	17.29	29.19	1.5274	−0.0089	36.3	38 590	16 483	Rm
32 563	6 435	41.7	28.0	8.43	29.24	1.642	−0.216	16.7	44 621	17 487	
33 565	10 450	41.09	34.37	−5.49	34.81	1.8072	−0.5519	350.9	−1 497c	19 497	
33 566	11 460	39.87	35.87	−9.37	37.07	1.8703	−0.6532	345.3	−1 502c	20 502	
33 568	13 465	39.31	37.82	−15.56	40.9	1.9328	−0.8142	337.6	−1 513c	22 513	
34 570	14 470	37.81	38.45	−18.5	42.67	1.9876	−0.9074	334.3	−1 521c	24 521	
34 574	15 475	35.29	38.6	−21.39	44.13	2.0643	−1.0244	331.0	−1 529c	25 529	Mm
36 580	15 480	30.04	38.16	−23.59	44.86	2.2411	−1.2035	328.2	−1 535c	27 535	
39 595	17 485	21.99	33.31	−29.44	44.46	2.4851	−1.7567	318.5	−1 549c	29 549	
−1 490c	18 490	5.77	11.76	−37.03	38.86	3.0068	−6.8297	287.6	11 459	33 566	min
−1 495c	19 495	7.21	10.41	−37.05	38.49	2.413	−5.5515	285.6	12 461	33 567	
−1 500c	20 500	9.02	8.67	−36.78	37.78	1.9318	−4.493	283.2	12 464	33 568	
−1 510c	22 510	14.01	3.96	−35.32	35.54	1.2533	−2.9397	276.3	13 469	34 570	
−1 520c	24 520	20.92	−2.1	−32.75	32.82	0.8702	−1.9835	266.3	14 473	34 572	Bm
−1 529c	25 530	24.96	−5.34	−31.16	31.61	0.7564	−1.6667	260.2	15 475	34 574	
−1 539c	27 540	33.79	−11.72	−27.58	29.97	0.6237	−1.2346	246.9	15 478	35 578	
−1 545c	29 545	43.17	−17.37	−23.71	29.39	0.5683	−0.9676	233.7	16 480	36 582	
−1 549c	29 550	43.17	−17.37	−23.71	29.39	0.5683	−0.9676	233.7	16 480	36 582	
−1 554c	30 555	47.92	−19.73	−21.74	29.36	0.559	−0.872	227.7	16 481	36 584	
−1 560c	32 560	57.29	−23.2	−17.84	29.27	0.5655	−0.7297	217.5	16 483	37 589	
380	770	99.99	0.0	0.0	0.01	0.9706	−0.4182	0.0			