

http://farbe.li-tu-berlin.de/DEF4/DEF4L01.TXT /PS; only vector graphic VG; start output
N: no 3D-linearization (OL) in file (F) or PS-startup (S), page 2/1

Oswald optimal colours (o), maximum (m) C _{AB} for D50, Y _N =3.6, Y _W =90, Y _m =520_770															
i	λ _i	i ₂	λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d	λ _d	i _c	λ _c	Code
1	405	32	564	26.33	48.45	66.13	0.1869	0.3438	0.4692	185.2	17	486	38	592	Cm
7	435	33	565	23.41	48.25	52.04	0.1892	0.39	0.4207	168.6	18	490	46	631	
10	450	33	566	20.93	48.75	35.69	0.1986	0.4625	0.3387	144.6	19	497	-1	497c	
12	460	33	567	19.83	49.37	24.66	0.2113	0.5259	0.2626	128.7	21	506	-1	506c	
13	465	33	568	19.81	50.0	19.91	0.2208	0.5572	0.2218	122.1	22	512	-1	512c	
14	470	34	570	19.94	50.5	15.93	0.2308	0.5846	0.1844	116.9	23	519	-1	519c	
15	475	34	573	21.53	52.24	12.71	0.2489	0.6064	0.1469	111.4	25	527	-1	527c Gm	
15	480	35	578	24.67	55.34	12.71	0.266	0.5968	0.1371	108.4	26	532	-1	532c	
17	485	37	587	30.59	59.41	8.37	0.3109	0.6039	0.0851	98.0	28	544	-1	544c	
18	490	44	620	53.95	71.6	6.98	0.407	0.5402	0.0526	71.3	32	561	-1	561c	
19	495	-1	495c	67.75	76.06	5.88	0.4525	0.5081	0.0393	54.4	33	568	12	463	max
20	500	-1	500c	67.73	74.76	5.02	0.4591	0.5067	0.034	52.5	33	569	13	466	
22	510	-1	510c	67.65	71.15	3.88	0.4741	0.4986	0.0272	47.4	34	571	14	471	
23	520	-1	519c	67.48	68.78	3.54	0.4826	0.492	0.0253	44.2	34	572	14	473	Ym
25	530	-1	529c	66.65	62.96	3.11	0.5021	0.4743	0.0234	36.4	35	575	15	477	
27	540	-1	539c	64.95	56.11	2.88	0.524	0.4527	0.0232	27.8	35	579	16	480	
28	545	-1	544c	63.73	52.49	2.81	0.5353	0.4409	0.0236	23.4	36	581	16	481	
29	550	-1	549c	62.23	48.77	2.77	0.5469	0.4286	0.0244	19.1	36	583	16	483	
30	555	-1	554c	60.45	45.01	2.74	0.5586	0.4159	0.0254	15.0	37	585	16	484	
32	560	-1	560c	56.05	37.66	2.71	0.5812	0.3905	0.0281	7.7	38	590	17	486	
32	564	1	405	60.44	41.54	8.11	0.5489	0.3773	0.0736	5.2	38	592	17	486	Rm
33	565	7	435	63.36	41.74	22.19	0.4977	0.3279	0.1743	348.6	46	631	18	490	
33	566	10	450	65.84	41.24	38.54	0.452	0.2832	0.2646	324.7	-1	497c	19	497	
33	567	12	460	66.94	40.62	49.58	0.4259	0.2585	0.3155	308.7	-1	506c	21	506	
33	568	13	465	66.96	39.99	54.33	0.4151	0.2479	0.3368	302.1	-1	512c	22	512	
34	570	14	470	66.83	39.49	58.3	0.4059	0.2398	0.3541	296.9	-1	519c	23	519	
34	573	15	475	65.25	37.75	61.53	0.3965	0.2294	0.3739	291.5	-1	527c	25	527	Mm
35	578	15	480	62.1	34.65	61.52	0.3923	0.2189	0.3887	288.5	-1	532c	26	532	
37	587	17	485	56.18	30.58	65.87	0.368	0.2003	0.4315	278.0	-1	544c	28	544	
44	620	18	490	32.82	18.39	67.26	0.277	0.1552	0.5677	251.3	-1	561c	32	561	
-1	495c	19	495	19.02	13.93	68.36	0.1877	0.1375	0.6746	234.4	12	463	33	568	min
-1	500c	20	500	19.04	15.23	69.22	0.1839	0.1471	0.6688	232.5	13	466	33	569	
-1	510c	22	510	19.13	18.84	70.36	0.1765	0.1739	0.6494	227.5	14	471	34	571	
-1	519c	23	520	19.29	21.21	70.7	0.1735	0.1907	0.6357	224.2	14	473	34	572	Bm
-1	529c	25	530	20.12	27.03	71.13	0.1701	0.2285	0.6013	216.5	15	477	35	575	
-1	539c	27	540	21.82	33.88	71.36	0.1717	0.2666	0.5615	207.8	16	480	35	579	
-1	544c	28	545	23.04	37.5	71.42	0.1746	0.2841	0.5412	203.5	16	481	36	581	
-1	549c	29	550	24.54	41.22	71.47	0.1788	0.3004	0.5207	199.2	16	483	36	583	
-1	554c	30	555	26.32	44.98	71.49	0.1843	0.315	0.5006	195.0	16	484	37	585	
-1	560c	32	560	30.72	52.33	71.52	0.1987	0.3385	0.4627	187.7	17	486	38	590	
W0	380	770	86.78	90.0	74.24	0.3457	0.3585	0.2957	0.0						
N0	380	770	3.47	3.6	2.96	0.3457	0.3585	0.2957	0.0						

Oswald optimal colours (o), maximum (m) C _{AB} for D50, Y _N =3.6, Y _W =90, Y _m =520_770															
i	λ _i	i ₂	λ ₂	Y	A	B	C _{AB}	a	b	h _{xy}	i _d	λ _d	i _c	λ _c	Code
1	405	32	564	48.45	-50.93	-26.15	57.25	0.5434	-0.5457	20.71	17	486	38	592	Cm
7	435	33	565	48.25	-57.75	-12.23	59.04	0.4851	-0.4313	19.19	18	490	46	631	
10	450	33	566	48.75	-65.15	45.1	65.3	0.4294	-0.2928	17.60	19	497	-1	497c	
12	460	33	567	49.37	-69.39	16.06	71.23	0.4017	-0.1997	16.69	21	506	-1	506c	
13	465	33	568	50.0	-70.98	21.33	74.12	0.3961	-0.1592	16.32	22	512	-1	512c	
14	470	34	570	50.5	-71.87	25.72	76.33	0.3947	-0.1261	16.03	23	519	-1	519c	
15	475	34	573	52.24	-72.08	30.37	78.22	0.412	-0.0973	15.71	25	527	-1	527c Gm	
15	480	35	578	55.34	-71.71	32.93	78.91	0.4456	-0.0919	15.53	26	532	-1	532c	
17	485	37	587	59.41	-66.71	40.63	78.11	0.5148	-0.0563	14.86	28	544	-1	544c	
18	490	44	620	71.6	-37.69	52.07	64.28	0.7534	-0.0389	12.58	32	561	-1	561c	
19	495	-1	495c	67.06	-13.96	56.84	58.53	0.8905	-0.0309	10.37	33	568	12	463	max
20	500	-1	500c	74.76	-10.86	56.63	57.67	0.9058	-0.0268	10.08	33	569	13	466	
22	510	-1	510c	71.15	-2.38	54.4	54.85	0.9505	-0.0128	9.24	34	571	14	471	
23	520	-1	519c	68.78	2.89	53.19	53.27	0.9808	-0.0205	8.68	34	572	14	473	Ym
25	530	-1	529c	62.96	14.87	48.81	51.03	1.0584	-0.0197	7.30	35	575	15	477	
27	540	-1	539c	56.11	27.1	43.4	51.17	1.1571	-0.0205	5.80	35	579	16	480	
28	545	-1	544c	52.49	32.78	40.47	52.09	1.2137	-0.0214	5.09	36	581	16	481	
29	550	-1	549c	48.77	38.02	37.44	53.36	1.2758	-0.0227	4.45	36	583	16	483	
30	555	-1	554c	45.01	42.62	34.37	54.76	1.3427	-0.0244	3.88	37	585	16	484	
32	560	-1	560c	37.66	49.33	28.34	56.89	1.4878	-0.0288	2.98	38	590	17	486	
32	564	1	405	41.54	50.93	26.15	57.26	1.4543	-0.078	2.71	38	592	17	486	Rm
33	565	7	435	41.74	57.75	12.23	59.03	1.5173	-0.2126	1.19	46	631	18	490	
33	566	10	450	41.24	65.14	-4.51	65.29	1.5956	-0.3736	356.0	-1	497c	19	497	
33	567	12	460	40.62	69.38	-16.06	71.22	1.6471	-0.488	346.9	-1	506c	21	506	
33	568	13	465	39.99	70.96	-21.33	74.1	1.6737	-0.5432	343.2	-1	512c	22	512	
34	570	14	470	39.49	71.85	-25.71	76.31	1.6917	-0.5903	340.3	-1	519c	23	519	
34	573	15	475	37.75	72.06	-30.36	78.2	1.7274	-0.6516	337.1	-1	527c	25	527	Mm
35	578	15	480	34.65	71.69	-32.92	78.89	1.7916	-0.7099	335.3	-1	532c	26	532	
37	587	17	485	30.58	66.69	-40.61	78.08	1.8361	-0.861	328.6	-1	544c	28	544	
44	620	18	490	18.39	37.67	-52.05	64.25	1.7832	-1.4618	305.8	-1	561c	32	561	
-1	495c	19	495	13.93	13.95	-56.81	58.5	1.3645	-1.9609	283.7	12	463	33	568	min
-1	500c	20	500	15.23	10.86	-56.61	57.64	1.2492	-1.8165	280.8	13	466	33	569	
-1	510c	22	510	18.84	2.38	-54.78	54.83	1.0145	-1.4926	272.4	14	471	34	571	
-1	519c	23	520	21.21	-2.89	-53.17	53.25	0.9092	-1.3327	266.8	14	473	34	572	Bm
-1	529c	25	530	27.03	-14.86	-48.8	51.01	0.744	-1.0518	253.0	15	477	35	575	
-1	539c	27	540	33.88	-27.1	-43.39	51.16	0.644	-0.8422	238.0	16	480	35	579	
-1	544c	28	545	37.5	-32.78	-40.47	52.08	0.6142	-0.7615	230.9	16	481	36	581	
-1	549c	29	550	41.22	-38.02	-37.44	53.36	0.595	-0.6931	224.5	16	483	36	583	
-1	554c	30	555	44.98	-42.62	-34.37	54.75	0.5849	-0.6355	218.8	16	484	37	585	
-1	560c	32	560	52.33	-49.32	-28.34	56.89	0.5869	-0.5465	209.8	17	486	38	590	
W0	380	770	90.0		0.0	0.0	0.0	0.9639	-0.3298	0.0				Bc=1,000	
N0	380	770	3.6		0.0	0.0	0.0	0.9639	-0.3298	0.0				x _c =0,000	