

Oswald optimal colours (o), maximum (m) $C_{AB,10}$ for D65, $Y_N=3.6$, $Y_W=90$, $Y_M=520-770$															
λ_1	λ_2	λ_3	λ_4	λ_5	λ_6	λ_7	λ_8	λ_9	λ_{10}	λ_{11}	λ_{12}	λ_{13}	λ_{14}	λ_{15}	Code
0	405	31	556	27.66	47.10	86.31	0.1717	0.2924	0.5358	195.1	15	476	37	585	Cm
6	435	31	557	24.87	47.93	68.5	0.176	0.3391	0.4847	176.5	16	480	44	621	
10	450	31	559	20.39	48.21	39.65	0.1883	0.4453	0.3662	137.6	18	492	-1	492c	
11	460	32	562	20.41	49.33	32.48	0.1996	0.4825	0.3177	126.9	19	498	-1	498c	
12	465	33	565	20.63	50.4	26.01	0.2126	0.5193	0.268	118.2	21	506	-1	506c	
14	470	34	570	22.02	52.1	15.93	0.2445	0.5785	0.1769	105.6	24	522	-1	522c	
15	475	35	579	27.8	56.8	12.45	0.2864	0.5852	0.1282	96.1	26	534	-1	534c	Gm
16	480	41	606	44.97	66.9	9.88	0.3693	0.5494	0.0811	75.6	30	550	-1	550c	
16	485	-1	484c	62.99	75.01	9.88	0.4259	0.5072	0.0668	57.5	32	560	10	454	
18	490	-1	490c	62.84	72.49	6.74	0.4423	0.5102	0.0474	54.3	32	562	11	459	max
19	495	-1	495c	62.83	70.93	5.79	0.4502	0.5082	0.0415	52.4	32	563	12	461	
19	500	-1	499c	62.83	70.93	5.79	0.4502	0.5082	0.0415	52.4	32	563	12	461	
22	510	-1	510c	62.5	64.74	4.26	0.4752	0.4923	0.0324	44.9	33	566	13	466	
23	520	-1	519c	62.17	62.19	4.01	0.4842	0.4844	0.0312	41.9	33	568	13	468	Ym
26	530	-1	530c	59.95	53.14	3.6	0.5137	0.4553	0.0309	31.8	34	573	14	472	
27	540	-1	539c	58.76	49.82	3.54	0.524	0.4443	0.0316	28.3	35	576	14	473	
28	545	-1	544c	57.31	46.42	3.5	0.5343	0.4328	0.0327	24.7	35	578	14	474	
29	550	-1	549c	55.6	42.99	3.48	0.5447	0.4211	0.0341	21.3	36	580	15	475	
31	555	-1	555c	51.4	36.18	3.47	0.5644	0.3973	0.0381	14.8	37	586	15	476	
32	560	10	451	57.83	34.36	48.64	0.4106	0.2439	0.3453	318.1	-1	491c	18	491	
31	556	0	405	57.66	42.89	10.28	0.5202	0.3869	0.0927	15.1	37	585	15	476	Rm
31	557	6	435	60.45	42.06	28.09	0.4628	0.322	0.215	35.65	44	621	16	480	
31	559	10	460	64.93	41.78	56.94	0.3967	0.2553	0.3479	317.6	-1	492c	18	492	
32	562	11	450	64.93	40.66	64.11	0.3825	0.2396	0.3778	307.0	-1	498c	19	498	
33	565	12	465	64.69	39.59	70.58	0.3699	0.2264	0.4036	298.2	-1	506c	21	506	
34	570	14	470	63.31	37.89	80.66	0.348	0.2083	0.4435	285.6	-1	522c	24	522	
35	575	15	475	57.32	33.19	84.15	0.3289	0.1898	0.4812	276.1	-1	534c	26	534	Mm
41	606	16	480	40.35	23.09	86.71	0.2687	0.1537	0.5774	255.7	-1	550c	30	550	
-1	484c	16	485	22.33	14.98	86.71	0.18	0.1208	0.699	237.5	10	452	34	560	
-1	490c	18	490	22.48	17.5	89.85	0.1731	0.1348	0.692	234.3	11	459	32	562	min
-1	495c	19	495	22.5	19.06	90.8	0.1699	0.144	0.6859	232.4	12	461	32	563	
-1	499c	20	499	22.5	19.06	90.8	0.1699	0.144	0.6859	232.4	12	461	32	563	
-1	510c	22	510	22.82	25.25	92.33	0.1625	0.1798	0.6576	225.0	13	466	33	566	
-1	519c	23	520	23.15	27.8	92.58	0.1613	0.1936	0.6449	222.0	13	468	33	568	Bm
-1	530c	26	530	25.37	36.85	92.99	0.1634	0.2374	0.599	211.8	14	472	34	573	
-1	539c	27	540	26.57	40.17	93.05	0.1662	0.2514	0.5823	208.3	14	473	35	576	
-1	544c	28	545	28.01	43.57	93.09	0.1701	0.2645	0.5652	204.8	14	474	35	578	
-1	549c	29	550	29.72	47.0	93.11	0.175	0.2767	0.5482	201.3	15	475	36	580	
-1	555c	31	555	33.92	53.81	93.12	0.1875	0.2975	0.5148	194.8	15	476	37	586	
10	451	32	560	27.49	55.63	47.96	0.2097	0.4244	0.3658	138.0	18	491	-1	491c	
W0	380	770	85.33	90.0	96.6	0.3137	0.3309	0.3552	0.0						
W0	380	770	3.41	3.6	3.86	0.3137	0.3309	0.3552	0.0						

