

Ostwald optimal colours (o), maximum (m) $C_{AB,10}$ for A00, $Y_N=3.6$, $Y_W=90$, $Y_M=520-770$																
λ_i	λ_1	λ_2	λ_3	λ_4	λ_5	λ_6	λ_7	λ_8	λ_9	λ_{10}	λ_{11}	λ_{12}	λ_{13}	λ_{14}	Code	
1	405	34	570	24.76	43.62	28.22	0.2563	0.4515	0.2921	166.8	17	487	39	597	Cm	
2	435	34	570	23.9	43.83	22.06	0.2661	0.4881	0.2457	156.0	18	491	47	637	Cm	
3	450	34	571	23.57	44.13	17.83	0.2755	0.5159	0.2084	147.9	19	495	-1	495c	Cm	
4	460	34	572	23.13	44.4	11.08	0.2942	0.5648	0.1409	134.6	21	505	-1	505c	Cm	
5	465	34	573	23.55	44.87	9.04	0.304	0.5792	0.1167	130.3	22	512	-1	512c	Cm	
6	470	34	574	24.54	45.75	7.28	0.3163	0.5897	0.0938	126.2	24	520	-1	520c	Cm	
7	475	35	576	25.89	46.7	5.84	0.3301	0.5953	0.0744	122.5	25	528	-1	528c	Cm	
8	480	36	581	29.14	49.04	4.7	0.3516	0.5915	0.0568	118.1	27	537	-1	537c	Gm	
9	485	37	588	36.35	53.77	3.82	0.3869	0.5723	0.0407	111.0	29	547	-1	547c	Cm	
10	490	41	609	56.68	64.8	3.15	0.4547	0.5199	0.0253	88.1	32	561	-1	561c	Cm	
11	495	-1	495c	85.8	76.7	2.63	0.5195	0.4644	0.0159	40.5	34	573	13	465	Cm	
12	500	-1	500c	85.78	75.66	2.24	0.524	0.4622	0.0136	37.6	34	573	13	468	max	
13	510	-1	509c	85.72	74.4	1.94	0.5289	0.459	0.0119	34.3	34	574	14	470	Cm	
14	520	-1	520c	85.0	69.14	1.41	0.5464	0.4444	0.0091	22.0	35	577	15	476	Ym	
15	530	-1	529c	84.45	66.89	1.32	0.5531	0.4381	0.0086	17.5	35	578	15	477	Cm	
16	540	-1	539c	82.72	61.69	1.2	0.568	0.4236	0.0082	8.6	36	581	16	480	Cm	
17	545	-1	545c	79.95	55.7	1.15	0.5843	0.4071	0.0084	0.5	37	585	16	483	Cm	
18	550	-1	550c	78.09	52.48	1.14	0.5928	0.3984	0.0086	356.9	37	587	16	484	Cm	
19	555	-1	555c	75.87	49.13	1.14	0.6014	0.3895	0.009	353.7	37	589	17	485	Cm	
20	560	-1	560c	73.26	45.69	1.14	0.61	0.3804	0.0094	350.9	38	592	17	486	Cm	
21	570	1	405	75.26	46.37	3.45	0.6016	0.3707	0.0276	346.8	39	597	17	487	Rm	
22	570	7	435	76.13	46.16	9.61	0.5771	0.3499	0.0278	336.0	47	637	18	491	Cm	
23	571	9	450	75.45	45.86	13.84	0.5615	0.3368	0.016	327.9	-1	495c	19	495	Cm	
24	572	12	460	76.89	45.59	20.59	0.5374	0.3186	0.0139	314.6	-1	495c	21	505	Cm	
25	573	13	465	76.48	45.12	22.63	0.5302	0.3128	0.0159	310.3	-1	512c	22	512	Cm	
26	574	14	470	75.48	44.24	24.39	0.5237	0.3069	0.0192	306.2	-1	520c	24	520	Cm	
27	575	15	475	74.13	43.29	25.83	0.5174	0.3022	0.0218	302.6	-1	528c	25	528	Mm	
28	581	16	480	70.88	40.95	26.97	0.5106	0.295	0.0242	298.2	-1	537c	27	537	Cm	
29	588	17	485	63.67	36.22	27.85	0.4984	0.2835	0.0218	291.1	-1	547c	29	547	Cm	
30	609	18	490	43.34	25.19	28.52	0.4465	0.2595	0.2938	268.2	-1	561c	32	561	Cm	
31	-1	495c	19	495	14.22	13.29	29.04	0.2515	0.235	0.5134	220.5	13	465	34	573	min
32	-1	500c	20	500	14.24	14.33	29.04	0.2455	0.247	0.5073	217.6	13	468	34	573	min
33	-1	509c	21	510	14.3	15.59	29.73	0.2399	0.2614	0.4986	214.3	14	470	34	574	Cm
34	-1	520c	24	520	15.03	20.85	30.26	0.2272	0.3152	0.4574	202.0	15	476	35	577	Bm
35	-1	529c	25	530	15.57	23.1	30.35	0.2256	0.3346	0.4397	197.5	15	477	35	578	Cm
36	-1	539c	27	540	17.3	28.3	30.47	0.2274	0.3719	0.4005	188.6	16	480	36	581	Cm
37	-1	545c	29	545	20.08	34.29	30.52	0.2365	0.4038	0.3595	180.5	16	483	37	585	Cm
38	-1	550c	30	550	21.93	37.51	30.53	0.2437	0.4168	0.3393	176.9	16	484	37	587	Cm
39	-1	555c	31	555	24.15	40.86	30.53	0.2528	0.4276	0.3195	173.7	17	485	37	589	Cm
40	-1	560c	32	560	26.76	44.3	30.53	0.2634	0.436	0.3005	170.8	17	486	38	592	Cm
41	W0	380	770	100.03	89.99	31.67	0.4511	0.4059	0.1428	0.0						
42	N0	380	770	4.0	3.59	1.26	0.4511	0.4059	0.1428	0.0						

