

Ostwald-Optimalfarben (o), maximales (m) C _{AB} für D65, Y _N =3,6, Y _W =90, Y _m =520_770													
i ₁ , λ ₁	i ₂ , λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d , λ _d	i _c , λ _c	Code		
0 405	32 561	28.34	48.4	87.6	0.1724	0.2945	0.533	193.8	16 483	37 589	Cm		
6 435	32 562	25.69	48.95	72.52	0.1746	0.3326	0.4927	178.5	17 486	42 610			
10 450	32 563	21.01	49.59	44.25	0.1829	0.4317	0.3852	141.6	19 496	−1 496c			
12 460	33 565	19.15	49.94	29.98	0.1933	0.504	0.3026	124.2	21 505	−1 505c			
12 465	33 567	20.12	51.15	29.99	0.1987	0.5051	0.2961	122.8	21 506	−1 506c			
14 470	33 569	19.94	52.23	19.06	0.2186	0.5724	0.2089	111.1	24 520	−1 520c			
15 475	34 573	21.65	54.1	15.12	0.2382	0.5953	0.1664	105.6	25 528	−1 528c	Gm		
16 480	36 580	25.4	57.45	12.12	0.2674	0.6048	0.1276	99.2	27 537	−1 537c			
17 485	39 595	35.62	64.35	9.93	0.3241	0.5855	0.0903	87.4	29 548	−1 548c			
18 490	−1 490c	63.02	76.18	8.3	0.4272	0.5164	0.0562	58.5	33 565	11 459	max		
19 495	−1 495c	62.98	75.01	7.04	0.4342	0.5171	0.0485	57.1	33 566	12 462			
20 500	−1 500c	62.97	73.55	6.07	0.4416	0.5158	0.0425	55.3	33 567	12 464			
22 510	−1 510c	62.87	69.55	4.8	0.4581	0.5068	0.035	50.6	33 569	13 469			
23 520	−1 519c	62.69	66.99	4.43	0.4674	0.4995	0.033	47.7	34 570	14 471	Ym		
25 530	−1 529c	61.81	60.81	3.97	0.4882	0.4803	0.0314	40.7	34 573	15 475			
27 540	−1 539c	60.05	53.7	3.73	0.511	0.4571	0.0318	32.8	35 577	15 478			
28 545	−1 544c	58.8	49.99	3.67	0.5228	0.4445	0.0326	28.7	35 579	15 479			
29 550	−1 549c	57.28	46.21	3.62	0.5347	0.4313	0.0338	24.7	36 582	16 480			
30 555	−1 554c	55.49	42.43	3.6	0.5465	0.4179	0.0354	20.8	36 584	16 481			
32 560	−1 560c	51.12	35.12	3.57	0.5691	0.391	0.0397	13.6	37 589	16 483			
32 561	0 405	57.19	41.59	10.39	0.5238	0.3809	0.0951	13.8	37 589	16 483	Rm		
32 562	6 435	59.84	41.04	25.47	0.4735	0.3248	0.2016	358.5	42 610	17 486			
32 563	10 450	64.52	40.4	53.74	0.4066	0.2546	0.3387	321.6	−1 496c	19 496			
33 565	12 460	66.38	40.05	68.01	0.3805	0.2295	0.3898	304.3	−1 505c	21 505			
33 567	12 465	65.41	38.84	68.01	0.3797	0.2254	0.3947	302.9	−1 506c	21 506			
33 569	14 470	65.59	37.76	78.93	0.3598	0.2071	0.433	291.1	−1 520c	24 520			
34 573	15 475	63.88	35.89	82.87	0.3497	0.1964	0.4537	285.6	−1 528c	25 528	Mm		
36 580	16 480	60.13	32.54	85.87	0.3367	0.1822	0.4809	279.3	−1 537c	27 537			
39 595	17 485	49.91	25.64	88.06	0.305	0.1567	0.5382	267.4	−1 548c	29 548			
−1 490c	18 490	22.51	13.81	89.7	0.1786	0.1096	0.7117	238.5	11 459	33 565	min		
−1 495c	19 495	22.55	14.98	90.95	0.1755	0.1166	0.7078	237.1	12 462	33 566			
−1 500c	20 500	22.56	16.44	91.92	0.1723	0.1256	0.702	235.4	12 464	33 567			
−1 510c	22 510	22.66	20.44	93.19	0.1662	0.1499	0.6837	230.7	13 469	33 569			
−1 519c	23 520	22.84	23.0	93.56	0.1638	0.165	0.6711	227.7	14 471	34 570	Bm		
−1 529c	25 530	23.72	29.18	94.02	0.1614	0.1986	0.6399	220.7	15 475	34 573			
−1 539c	27 540	25.48	36.29	94.26	0.1633	0.2325	0.604	212.8	15 478	35 577			
−1 544c	28 545	26.73	40.0	94.33	0.1659	0.2483	0.5856	208.8	15 479	35 579			
−1 549c	29 550	28.25	43.78	94.37	0.1697	0.2631	0.567	204.7	16 480	36 582			
−1 554c	30 555	30.04	47.56	94.4	0.1746	0.2765	0.5488	200.8	16 481	36 584			
−1 560c	32 560	34.41	54.87	94.43	0.1873	0.2986	0.5139	193.6	16 483	37 589			
W0 380	770	85.53	90.0	98.0	0.3127	0.329	0.3582	0.0					
N0 380	770	3.42	3.6	3.92	0.3127	0.329	0.3582	0.0					

DGF40-7N