






L^*_{CIELAB} (absolut)	18,0	37,5	57,0	76,5	96,0	N_0 (min.)	W_1 (max.)
							
$L^*_{\text{CIELAB}, r}$ (relativ)	0,000	0,250	0,500	0,750	1,000	N_0 (min.)	W_1 (max.)
							

L^*_{CIELAB} (absolut)	18,0	23,2	28,4	33,6	38,8	44,0	49,2	54,4	59,6	64,8	70,0	75,2	80,4	85,6	90,8	96,0
Hex-Code	F	E	D	C	B	A	9	8	7	6	5	4	3	2	1	0
$l^*_{\text{CIELAB}, r}$ (relativ)	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000

Prüfvorlage Nr. 3 für Farbkopierer nach ISO 15775/ed-2, siehe <http://standards.iso.org/iso/15775/ed-2/index.html>



	120	128	136	144	152	160	168	176	184	192	200	208	216	224	232	240	
120 (+8)																	240
60 (+4)																	120
30 (+2)																	60
15 (+1)																	30
	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	
Rasterweite in lpi																	

Bild C5: Linienraster unter 45° (oder 135°); PS-Operator: w^* *setgray*

Rasterweite in lpi

Bild C6: Linienraster unter 90° (oder 0°); PS-Operator: `w* setgray`