

Ostwald-Optimalfarben (o), maximales (m) C _{AB,10} für D65, Y _{N,10} =3.6, Y _{W,10} =90, Y _m =520, 770												
i, λ ₁	i, λ ₂	Y ₁₀	A _{1,10}	B _{1,10}	C _{AB,10}	B _{1,10}	b _{xy,1,10}	l _c	λ _c	Code		
0 405	31 556	47.1	-47.62	-35.74	59.54	0.2111	-0.7327	216.8	15 476	37 585 Cm		
6 435	31 557	47.93	-50.44	-17.05	53.25	0.1946	-0.5715	198.6	16 480	44 621		
10 450	31 559	48.21	-52.98	12.08	54.34	0.1759	-0.3289	167.1	18 492	-1 492c		
11 460	32 562	49.33	-53.01	20.46	56.82	0.1857	-0.2632	158.8	19 498	-1 498c		
12 465	33 565	50.4	-52.67	28.07	59.69	0.1975	-0.2064	151.9	21 506	-1 506c		
14 470	34 570	52.1	-49.89	39.97	63.93	0.2325	-0.1223	141.3	24 522	-1 522c		
15 475	35 579	56.8	-44.6	48.5	65.89	0.3015	-0.0876	132.5	26 534	-1 534c Gm		
16 480	41 606	66.9	-24.01	61.91	66.4	0.472	-0.059	111.2	30 550	-1 550c		
16 485	-1 484c	75.01	1.34	70.61	70.62	0.6227	-0.0526	88.9	32 560	10 454		
18 490	-1 490c	72.49	6.44	71.04	71.33	0.6511	-0.0372	84.8	32 562	11 459 max		
19 495	-1 495c	70.93	9.51	70.31	70.95	0.6692	-0.0326	82.2	32 563	12 461		
19 500	-1 499c	70.93	9.51	70.31	70.95	0.6692	-0.0326	82.2	32 563	12 461		
22 510	-1 510c	64.74	20.42	65.21	68.33	0.7417	-0.0263	72.6	33 566	13 466		
23 520	-1 519c	62.19	24.38	62.72	67.29	0.7724	-0.0258	68.7	33 568	13 468 Ym		
26 530	-1 530c	53.14	35.99	53.41	64.41	0.8865	-0.0271	56.0	34 573	14 472		
27 540	-1 539c	49.82	39.36	49.91	63.57	0.9316	-0.0284	51.7	35 576	14 473		
28 545	-1 544c	46.42	42.31	46.31	62.73	0.9801	-0.0302	47.5	35 578	14 474		
29 550	-1 549c	42.99	44.75	42.64	61.81	1.0319	-0.0324	43.6	36 580	15 475		
31 555	-1 555c	36.18	47.74	35.35	59.41	1.1433	-0.0384	36.5	37 586	15 476		
32 560	10 451	34.36	52.93	-11.75	54.22	1.2318	-0.566	34.74	-1 491c	18 491		
31 556	0 405	42.89	47.63	35.74	59.55	1.0597	-0.0958	36.8	37 585	15 476 Rm		
31 557	6 435	42.06	50.44	17.05	53.25	1.0952	-0.267	18.6	44 621	16 480		
31 559	10 450	41.78	52.97	-12.08	54.34	1.1227	-0.5448	34.71	-1 492c	18 492		
32 562	11 460	40.66	53.0	-20.46	56.81	1.1369	-0.6304	33.88	-1 498c	19 498		
33 565	12 465	39.59	52.66	-28.07	59.67	1.1476	-0.7128	33.19	-1 506c	21 506		
34 570	14 470	37.89	49.88	-39.95	63.91	1.142	-0.8509	32.13	-1 522c	24 522		
35 575	15 475	33.19	44.58	-49.89	65.87	1.1529	-1.0135	31.25	-1 534c	26 534 Mm		
41 606	16 480	23.09	24.0	-61.88	66.37	1.0313	-1.5009	29.12	-1 550c	30 550		
-1 484c	16 485	14.98	-1.34	-70.56	70.57	0.5796	-2.3126	268.9	10 454	32 560		
-1 490c	18 490	17.5	-6.44	-71.0	71.29	0.4682	-2.0519	264.8	11 459	32 562 min		
-1 495c	19 495	19.06	-9.5	-70.28	70.92	0.4161	-1.9035	262.2	12 461	32 563		
-1 499c	19 500	19.06	-9.5	-70.28	70.92	0.4161	-1.9035	262.2	12 461	32 563		
-1 510c	22 510	25.25	-20.41	-65.19	68.31	0.2921	-1.4619	252.6	13 466	33 566		
-1 519c	23 520	27.8	-24.37	-62.7	67.27	0.2648	-1.3312	248.7	13 468	33 568 Bm		
-1 530c	26 530	36.85	-35.98	-53.4	64.39	0.225	-1.0087	236.0	14 472	34 573		
-1 539c	27 540	40.17	-39.36	-49.9	63.56	0.2237	-0.926	231.7	14 473	35 576		
-1 544c	28 545	43.57	-42.3	-46.3	62.72	0.2271	-0.8543	227.5	14 474	35 578		
-1 549c	29 550	47.0	-44.74	-42.63	61.81	0.2348	-0.792	223.6	15 475	36 580		
-1 555c	31 555	53.81	-47.74	-35.35	59.4	0.2607	-0.6919	216.5	15 476	37 586		
10 451	32 560	55.63	-52.94	11.75	54.23	0.2349	-0.3447	167.4	18 491	-1 491c		
W0 380	770 90.0	0.0	0.0	0.0	0.0	0.6155	-0.4292	0.0	B _c =1,000			
N0 380	770 3.6	0.0	0.0	0.0	0.0	0.6155	-0.4292	0.0	x _c =0,110			

DGJ2-7N

Ostwald-Optimalfarben (o), maximales (m) C _{AB,10} für D65, Y _{N,10} =3,6, Y _{W,10} =90, Y _m =520, 770													
i	λ ₁	i	λ ₂	Y ₁₀	A _{2,10}	B _{2,10}	C _{AB2,10}	B _{2,10}	b _{xy,2,10}	l _c	λ _c	Code	
0	405	31	556	47.1	-47.62	-28.59	55.55	0.2111	-0.7327	210.9	15	476	37 585 Cm
6	435	31	557	47.93	-50.44	-13.64	52.26	0.1946	-0.5715	195.1	16	480	44 621
10	450	31	559	48.21	-52.98	9.66	53.86	0.1759	-0.3289	169.6	18	492	-1 492c
11	460	32	562	49.33	-53.01	16.37	55.48	0.1857	-0.2632	162.8	19	498	-1 498c
12	465	33	565	50.4	-52.67	22.46	57.26	0.1975	-0.2064	156.9	21	506	-1 506c
14	470	34	570	52.1	-49.89	31.97	59.26	0.2325	-0.1223	147.3	24	522	-1 522c
15	475	35	579	56.8	-44.6	38.8	59.12	0.3015	-0.0876	138.9	26	534	-1 534c Gm
16	480	41	606	66.9	-24.01	49.52	50.04	0.472	-0.059	115.3	30	550	-1 550c
16	485	-1	484c	75.01	1.34	56.48	56.5	0.6227	-0.0526	88.6	32	560	10 454
18	490	-1	490c	72.49	6.44	56.83	57.2	0.6511	-0.0372	83.5	32	562	11 459 max
19	495	-1	495c	70.93	9.51	56.25	57.05	0.6692	-0.0326	80.4	32	563	12 461
19	500	-1	499c	70.93	9.51	56.25	57.05	0.6692	-0.0326	80.4	32	563	12 461
22	510	-1	510c	64.74	20.42	52.17	56.02	0.7417	-0.0263	68.6	33	566	13 466
23	520	-1	519c	62.19	24.38	50.17	55.79	0.7724	-0.0258	64.0	33	568	13 468 Ym
26	530	-1	530c	53.14	35.99	42.73	55.87	0.8865	-0.0271	49.8	34	573	14 472
27	540	-1	539c	49.82	39.36	39.93	56.07	0.9316	-0.0284	45.4	35	576	14 473
28	545	-1	544c	46.42	42.31	37.04	56.24	0.9801	-0.0302	41.2	35	578	14 474
29	550	-1	549c	42.99	44.75	34.11	56.27	1.0319	-0.0324	37.3	36	580	15 475
31	555	-1	555c	36.18	47.74	28.28	55.49	1.1433	-0.0384	30.6	37	586	15 476
32	560	10	451	34.36	52.93	-9.4	53.76	1.2318	-0.566	34.99	-1	491c	18 491
31	556	0	405	42.89	47.63	28.59	55.55	1.0597	-0.0958	30.9	37	585	15 476 Rm
31	557	6	435	42.06	50.44	13.64	52.26	1.0952	-0.267	15.1	44	621	16 480
31	559	10	450	41.78	52.97	-9.66	53.85	1.1227	-0.5448	34.96	-1	492c	18 492
32	562	11	460	40.66	53.0	-16.36	55.47	1.1369	-0.6304	34.28	-1	498c	19 498
33	565	12	465	39.59	52.66	-22.45	57.25	1.1476	-0.7128	33.69	-1	506c	21 506
34	570	14	470	37.89	49.88	-31.96	59.24	1.142	-0.8509	32.73	-1	522c	24 522
35	575	15	475	33.19	44.58	-38.79	59.09	1.1529	-1.0135	31.89	-1	534c	26 534 Mm
41	606	16	480	23.09	24.0	-49.45	55.01	1.0313	-1.5009	295.8	-1	550c	30 550
-1	484c	16	485	14.98	-1.34	-56.45	56.46	0.5796	-2.3126	268.6	10	454	32 560
-1	490c	18	490	17.5	-6.44	-56.8	57.17	0.4682	-2.0519	263.5	11	459	32 562 min
-1	495c	19	495	19.06	-9.5	-56.22	57.02	0.4161	-1.9035	260.4	12	461	32 563
-1	499c	19	500	19.06	-9.5	-56.22	57.02	0.4161	-1.9035	260.4	12	461	32 563
-1	510c	22	510	25.25	-20.41	-52.15	56.0	0.2921	-1.4619	248.6	13	466	33 566
-1	519c	23	520	27.8	-24.37	-50.16	55.77	0.2648	-1.3312	244.0	13	468	33 568 Bm
-1	530c	26	530	36.85	-35.98	-42.72	55.86	0.225	-1.0087	229.8	14	472	34 573
-1	539c	27	540	40.17	-39.36	-39.92	56.06	0.2237	-0.926	225.4	14	473	35 576
-1	544c	28	545	43.57	-42.3	-37.04	56.23	0.2271	-0.8543	221.2	14	474	35 578
-1	549c	29	550	47.0	-44.74	-34.11	56.26	0.2348	-0.792	217.3	15	475	36 580
-1	555c	31	555	53.81	-47.74	-28.28	55.48	0.2607	-0.6919	210.6	15	476	37 586
10	451	32	560	55.63	-52.94	9.4	53.77	0.2349	-0.3447	169.9	18	491	-1 491c
W0	380	770	90.0	0.0	0.0	0.0	0.0	0.6155	-0.3433	0.0	B _c =0,800		
N0	380	770	3.6	0.0	0.0	0.0	0.0	0.6155	-0.3433	0.0	x _c =0,110		

DGJ2-7N