

Siehe ähnliche Dateien: <http://farbe.li.tu-berlin.de/DGJ5/DGJ5.HTM>
Technische Information: <http://farbe.li.tu-berlin.de> oder <http://color.li.tu-berlin.de>

Ostwald-Optimalfarben (o), maximale (m) C _{AB,10} für D50, Y _{N,10} =3,6, Y _{W,10} =90, Y _m =520_770														
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀	A _{1,10}	B _{1,10}	CA1B1,10	a _{1,10}	b _{1,10}	h _{xy,1,10}	i _d , λ _d	i _c , λ _c	Code			
1 405	31 559	47.0	-50.88	-26.73	57.48	0.228	-0.553	207.7	15 479	37 589	Cm			
7 435	32 561	46.96	-52.93	-10.89	54.04	0.2102	-0.4183	191.6	16 484	58 693				
10 450	32 562	47.28	-54.11	6.28	54.47	0.2033	-0.2723	173.3	18 493	-1 493c				
12 460	32 564	48.08	-53.96	17.62	56.76	0.2122	-0.1789	161.9	20 503	-1 503c				
13 465	33 566	48.62	-53.19	22.52	57.76	0.2235	-0.1402	157.0	22 511	-1 511c				
14 470	34 570	50.16	-51.86	27.47	58.69	0.2476	-0.1064	152.0	24 521	-1 521c				
15 475	35 576	53.3	-48.65	32.91	58.74	0.2959	-0.0785	145.9	26 531	-1 531c	Gm			
16 480	38 590	59.74	-39.64	40.31	56.54	0.3956	-0.0556	134.5	28 543	-1 543c				
17 485	-1 485c	75.24	4.45	54.49	54.67	0.6847	-0.0358	85.3	32 563	11 458				
18 490	-1 490c	74.08	6.93	54.68	55.12	0.6985	-0.0303	82.7	32 564	12 460				
19 495	-1 495c	72.69	9.8	54.39	55.27	0.715	-0.0262	79.7	33 565	12 462	max			
20 500	-1 500c	71.07	13.03	53.69	55.25	0.7344	-0.0233	76.3	33 566	12 464				
21 510	-1 509c	69.2	16.56	52.61	55.16	0.7568	-0.0214	72.5	33 567	13 466				
24 520	-1 520c	62.01	28.43	47.49	55.35	0.8445	-0.0192	59.0	34 571	14 471	Ym			
25 530	-1 529c	59.09	32.53	45.24	55.72	0.8813	-0.0193	54.2	34 573	14 473				
28 540	-1 540c	49.37	43.45	37.51	57.4	1.0131	-0.0216	40.8	35 579	15 476				
29 545	-1 545c	45.94	46.27	34.74	57.86	1.064	-0.023	36.9	36 581	15 477				
29 550	-1 549c	45.94	46.27	34.74	57.86	1.064	-0.023	36.9	36 581	15 477				
31 555	-1 555c	39.06	50.07	29.15	57.94	1.1738	-0.027	30.2	37 587	15 479				
32 560	2 411	35.74	51.14	24.95	56.9	1.2335	-0.0463	26.0	38 591	16 480				
31 559	1 405	42.99	50.88	26.73	57.48	1.1345	-0.0768	27.7	37 589	15 479	Rm			
32 561	7 435	43.03	52.92	10.89	54.03	1.153	-0.2243	11.6	58 693	16 484				
32 562	10 450	42.71	54.1	-6.28	54.46	1.1677	-0.3844	353.3	-1 493c	18 493				
32 564	12 460	41.91	53.95	-17.62	56.75	1.1759	-0.4937	341.9	-1 503c	20 503				
33 566	13 465	41.37	53.18	-22.51	57.75	1.1751	-0.5432	337.0	-1 511c	22 511				
34 570	14 470	39.83	51.84	-27.46	58.67	1.1818	-0.6014	332.0	-1 521c	24 521				
35 576	15 475	36.69	48.64	-32.9	58.72	1.1913	-0.6842	325.9	-1 531c	26 531	Mm			
38 590	16 480	30.25	39.63	-40.3	56.52	1.1851	-0.8584	314.5	-1 543c	28 543				
-1 485c	17 485	14.75	-4.45	-54.46	54.65	0.5404	-1.8023	265.3	11 458	32 563				
-1 490c	18 490	15.91	-6.93	-54.65	55.09	0.4869	-1.699	262.7	12 460	32 564				
-1 495c	19 495	17.3	-9.79	-54.37	55.24	0.4345	-1.5826	259.7	12 462	33 565	min			
-1 500c	20 500	18.92	-13.02	-53.67	55.23	0.3857	-1.4599	256.3	12 464	33 566				
-1 509c	21 510	20.79	-16.56	-52.59	55.14	0.3425	-1.3372	252.5	13 466	33 567				
-1 520c	24 520	27.98	-28.42	-47.48	55.34	0.2547	-1.0044	239.0	14 471	34 571	Bm			
-1 529c	25 530	30.9	-32.52	-45.23	55.71	0.2401	-0.9111	234.2	14 473	34 573				
-1 540c	28 540	40.62	-43.44	-37.51	57.39	0.2333	-0.6948	220.8	15 476	35 579				
-1 545c	29 545	44.05	-46.26	-34.74	57.86	0.241	-0.6409	216.9	15 477	36 581				
-1 549c	29 550	44.05	-46.26	-34.74	57.86	0.241	-0.6409	216.9	15 477	36 581				
-1 555c	31 555	50.93	-50.07	-29.15	57.94	0.2679	-0.5545	210.2	15 479	37 587				
2 411	32 560	54.25	-51.14	-24.95	56.9	0.284	-0.5094	206.0	16 480	38 591				
W0	380	770	89.99	0.0	0.0	0.0	0.6611	-0.3255	0.0	B _c =1,000				
N0	380	770	3.59	0.0	0.0	0.0	0.6611	-0.3255	0.0	x _c =0,110				

DGJ50-7N

Ostwald-Optimalfarben (o), maximale (m) C _{AB,10} für D50, Y _{N,10} =3,6, Y _{W,10} =90, Y _m =520_770														
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀	A _{2,10}	B _{2,10}	CA2B2,10	a _{2,10}	b _{2,10}	h _{xy,2,10}	i _d , λ _d	i _c , λ _c	Code			
1 405	31 559	47.0	-50.88	-26.73	57.48	0.228	-0.553	207.7	15 479	37 589	Cm			
7 435	32 561	46.96	-52.93	-10.89	54.04	0.2102	-0.4183	191.6	16 484	58 693				
10 450	32 562	47.28	-54.11	6.28	54.47	0.2033	-0.2723	173.3	18 493	-1 493c				
12 460	32 564	48.08	-53.96	17.62	56.76	0.2122	-0.1789	161.9	20 503	-1 503c				
13 465	33 566	48.62	-53.19	22.52	57.76	0.2235	-0.1402	157.0	22 511	-1 511c				
14 470	34 570	50.16	-51.86	27.47	58.69	0.2476	-0.1064	152.0	24 521	-1 521c				
15 475	35 576	53.3	-48.65	32.91	58.74	0.2959	-0.0785	145.9	26 531	-1 531c	Gm			
16 480	38 590	59.74	-39.64	40.31	56.54	0.3956	-0.0556	134.5	28 543	-1 543c				
17 485	-1 485c	75.24	4.45	54.49	54.67	0.6847	-0.0358	85.3	32 563	11 458				
18 490	-1 490c	74.08	6.93	54.68	55.12	0.6985	-0.0303	82.7	32 564	12 460				
19 495	-1 495c	72.69	9.8	54.39	55.27	0.715	-0.0262	79.7	33 565	12 462	max			
20 500	-1 500c	71.07	13.03	53.69	55.25	0.7344	-0.0233	76.3	33 566	12 464				
21 510	-1 509c	69.2	16.56	52.61	55.16	0.7568	-0.0214	72.5	33 567	13 466				
24 520	-1 520c	62.01	28.43	47.49	55.35	0.8445	-0.0192	59.0	34 571	14 471	Ym			
25 530	-1 529c	59.09	32.53	45.24	55.72	0.8813	-0.0193	54.2	34 573	14 473				
28 540	-1 540c	49.37	43.45	37.51	57.4	1.0131	-0.0216	40.8	35 579	15 476				
29 545	-1 545c	45.94	46.27	34.74	57.86	1.064	-0.023	36.9	36 581	15 477				
29 550	-1 549c	45.94	46.27	34.74	57.86	1.064	-0.023	36.9	36 581	15 477				
31 555	-1 555c	39.06	50.07	29.15	57.94	1.1738	-0.027	30.2	37 587	15 479				
32 560	2 411	35.74	51.14	24.95	56.9	1.2335	-0.0463	26.0	38 591	16 480				
31 559	1 405	42.99	50.88	26.73	57.48	1.1345	-0.0768	27.7	37 589	15 479	Rm			
32 561	7 435	43.03	52.92	10.89	54.03	1.153	-0.2243	11.6	58 693	16 484				
32 562	10 450	42.71	54.1	-6.28	54.46	1.1677	-0.3844	353.3	-1 493c	18 493				
32 564	12 460	41.91	53.95	-17.62	56.75	1.1759	-0.4937	341.9	-1 503c	20 503				
33 566	13 465	41.37	53.18	-22.51	57.75	1.1751	-0.5432	337.0	-1 511c	22 511				
34 570	14 470	39.83	51.84	-27.46	58.67	1.1818	-0.6014	332.0	-1 521c	24 521				
35 576	15 475	36.69	48.64	-32.9	58.72	1.1913	-0.6842	325.9	-1 531c	26 531	Mm			
38 590	16 480	30.25	39.63	-40.3	56.52	1.1851	-0.8584	314.5	-1 543c	28 543				
-1 485c	17 485	14.75	-4.45	-54.46	54.65	0.5404	-1.8023	265.3	11 458	32 563				
-1 490c	18 490	15.91	-6.93	-54.65	55.09	0.4869	-1.699	262.7	12 460	32 564				
-1 495c	19 495													