

Oswald-Optimalfarben (o), maximales (m) C _{AB,10} für A00, Y _{N,10} =3.6, Y _{W,10} =90, Y _m =520..770													
i, λ ₁	i ₂	λ ₂	X ₁₀	Y ₁₀	Z ₁₀	x ₁₀	y ₁₀	z ₁₀	h _{xy,10}	i _d	λ _d	i _c	Code
1 405	34	570	24.76	43.62	28.22	0.2563	0.4515	0.2921	166.8	17	487	39	597 Cm
7 435	34	570	23.9	43.83	22.06	0.2661	0.4881	0.2457	156.0	18	491	47	637
9 450	34	571	23.57	44.13	17.86	0.2755	0.5159	0.2084	147.9	19	495	-1	495c
12 460	34	572	23.13	44.4	11.08	0.2942	0.5648	0.1409	134.6	21	505	-1	505c
13 465	34	573	23.55	44.87	9.04	0.304	0.5792	0.1167	130.3	22	512	-1	512c
14 470	34	574	24.54	45.75	7.28	0.3163	0.5897	0.0938	126.2	24	520	-1	520c
15 475	35	576	25.89	46.7	5.84	0.3301	0.5953	0.0744	122.5	25	528	-1	528c Gm
16 480	36	581	29.14	49.04	4.7	0.3516	0.5915	0.0568	118.1	27	537	-1	537c
17 485	37	588	36.35	53.77	3.82	0.3869	0.5723	0.0407	111.0	29	547	-1	547c
18 490	41	609	56.68	64.8	3.15	0.4547	0.5199	0.0253	88.1	32	561	-1	561c
19 495	-1	495c	85.8	76.7	2.63	0.5195	0.4644	0.0159	40.5	34	573	13	465
20 500	-1	500c	85.78	75.66	2.24	0.524	0.4622	0.0136	37.6	34	573	13	468 max
21 510	-1	509c	85.72	74.4	1.94	0.5289	0.459	0.0119	34.3	34	574	14	470
24 520	-1	520c	85.0	69.14	1.41	0.5464	0.4444	0.0091	22.0	35	577	15	476 Ym
25 530	-1	529c	84.45	66.89	1.32	0.5531	0.4381	0.0086	17.5	35	578	15	477
27 540	-1	539c	82.72	61.69	1.2	0.568	0.4236	0.0082	8.6	36	581	16	480
29 545	-1	545c	79.95	55.7	1.15	0.5843	0.4071	0.0084	0.5	37	585	16	483
30 550	-1	550c	78.09	52.48	1.14	0.5928	0.3984	0.0086	356.9	37	587	16	484
31 555	-1	555c	75.87	49.13	1.14	0.6014	0.3895	0.009	353.7	37	589	17	485
32 560	-1	560c	73.26	45.69	1.14	0.61	0.3804	0.0094	350.9	38	592	17	486
34 570	1 405	75.26	46.37	3.45	0.6016	0.3707	0.0276	346.8	39	597	17	487	Rm
34 570	7 435	76.13	46.16	9.61	0.5771	0.3499	0.0728	336.0	47	637	18	491	
34 571	9 450	76.45	45.86	13.84	0.5615	0.3368	0.1016	327.9	-1	495c	19	495	
34 572	12 460	76.89	45.59	20.59	0.5374	0.3186	0.1439	314.6	-1	505c	21	505	
34 573	13 465	76.48	45.12	22.63	0.5302	0.3128	0.1569	310.3	-1	512c	22	512	
34 574	14 470	75.48	44.24	24.39	0.5237	0.3069	0.1692	306.2	-1	520c	24	520	
35 576	15 475	74.13	43.29	25.83	0.5174	0.3022	0.1803	302.6	-1	528c	25	528	Mm
36 581	16 480	70.88	40.95	26.97	0.5106	0.295	0.1942	298.2	-1	537c	27	537	
37 588	17 485	63.67	36.22	27.85	0.4984	0.2835	0.218	291.1	-1	547c	29	547	
41 609	18 490	43.34	25.19	28.52	0.4465	0.2595	0.2938	268.2	-1	561c	32	561	
-1 495c	19 495	14.22	13.29	29.04	0.2515	0.235	0.5134	220.5	13	465	34	573	
-1 500c	20 500	14.24	14.33	29.43	0.2455	0.247	0.5073	217.6	13	468	34	573	min
-1 509c	21 510	14.3	15.59	29.73	0.2399	0.2614	0.4986	214.3	14	470	34	574	
-1 520c	24 520	15.03	20.85	30.26	0.2272	0.3152	0.4574	202.0	15	476	35	577	Bm
-1 529c	25 530	15.57	23.1	30.35	0.2256	0.3346	0.4397	197.5	15	477	35	578	
-1 539c	27 540	17.3	28.3	30.47	0.2274	0.3719	0.4005	188.6	16	480	36	581	
-1 545c	29 545	20.08	34.29	30.52	0.2365	0.4038	0.3595	180.5	16	483	37	585	
-1 550c	30 550	21.93	37.51	30.53	0.2437	0.4168	0.3393	176.9	16	484	37	587	
-1 555c	31 555	24.15	40.86	30.53	0.2528	0.4276	0.3195	173.7	17	485	37	589	
-1 560c	32 560	26.76	44.3	30.53	0.2634	0.436	0.3005	170.8	17	486	38	592	
W0	380	770	100.03	89.99	31.67	0.4511	0.4059	0.1428	0.0				
N0	380	770	4.0	3.59	1.26	0.4511	0.4059	0.1428	0.0				

DGJ7-7N

Oswald-Optimalfarben (o), maximales (m) C _{AB,10} für A00, Y _{N,10} =3.6, Y _{W,10} =90, Y _m =520..770														
i	λ ₁	i ₂	λ ₂	A ₁₀	B ₁₀	C _{AB,10}	a ₁₀	b ₁₀	h _{xy,10}	i _d	λ _d	i _c	λ _c	Code
1	405	34	570	43.62	-59.28	-12.86	60.66	0.5676	-0.2587	192.2	17	487	39 597	Cm
7	435	34	570	43.83	-62.03	-6.63	62.38	0.5451	-0.2012	186.1	18	491	47 637	
9	450	34	571	44.13	-63.68	-2.29	63.72	0.534	-0.1615	182.0	19	495	-1 495c	
12	460	34	572	44.4	-65.53	4.54	65.69	0.5208	-0.0998	176.0	21	505	-1 505c	
13	465	34	573	44.87	-65.79	6.74	66.13	0.5247	-0.0806	174.1	22	512	-1 512c	
14	470	34	574	45.75	-65.76	8.82	66.35	0.5363	-0.0636	172.3	24	520	-1 520c	
15	475	35	576	46.7	-65.0	10.59	65.86	0.5544	-0.05	170.7	25	528	-1 528c	Gm
16	480	36	581	49.04	-63.37	12.54	64.6	0.5942	-0.0384	168.7	27	537	-1 537c	
17	485	37	588	53.77	-58.52	15.09	60.43	0.6759	-0.0284	165.5	29	547	-1 547c	
18	490	41	609	64.8	-38.35	19.65	43.1	0.8744	-0.0194	152.8	32	561	-1 561c	
19	495	-1 495c	76.7	1.37	24.35	24.39	1.1184	-0.0137	86.7	34	573	13 465		
20	500	-1 500c	75.66	4.22	24.38	24.74	1.1335	-0.0118	80.1	34	573	13 468	max	
21	510	-1 509c	74.4	7.56	24.24	25.39	1.1519	-0.0104	72.6	34	574	14 470		
24	520	-1 520c	69.14	20.36	22.91	30.65	1.229	-0.0081	48.3	35	577	15 476	Ym	
25	530	-1 529c	66.89	25.25	22.22	33.63	1.2622	-0.0078	41.3	35	578	15 477		
27	540	-1 539c	61.69	35.37	20.51	40.88	1.3405	-0.0077	30.1	36	581	16 480		
29	545	-1 545c	55.7	45.06	18.45	48.7	1.4348	-0.0082	22.2	37	585	16 483		
30	550	-1 550c	52.48	49.37	17.32	52.32	1.4875	-0.0087	19.3	37	587	16 484		
31	555	-1 555c	49.13	53.13	16.15	55.53	1.5437	-0.0092	16.9	37	589	17 485		
32	560	-1 560c	45.69	56.17	14.94	58.12	1.6029	-0.0099	14.8	38	592	17 486		
34	570	1 405	46.37	59.28	12.86	60.66	1.6225	-0.0298	12.2	39	597	17 487		Rm
34	570	7 435	46.16	62.02	6.63	62.38	1.6486	-0.0832	6.1	47	637	18 491		
34	571	9 450	45.86	63.67	2.29	63.71	1.6666	-0.1207	2.0	-1 495c	19 495			
34	572	12 460	45.59	65.52	-4.54	65.68	1.6861	-0.1806	356.0	-1 505c	21 505			
34	573	13 465	45.12	65.78	-6.74	66.12	1.6943	-0.2005	354.1	-1 512c	22 512			
34	574	14 470	44.24	65.75	-8.82	66.34	1.7057	-0.2205	352.3	-1 520c	24 520			
35	576	15 475	43.29	64.99	-10.59	65.85	1.7116	-0.2386	350.7	-1 528c	25 528			Mm
36	581	16 480	40.95	63.36	-12.54	64.59	1.73	-0.2632	348.7	-1 537c	27 537			
37	588	17 485	36.22	58.5	-15.09	60.42	1.7573	-0.3074	345.5	-1 547c	29 547			
41	609	18 490	25.19	38.35	-19.65	43.09	1.7202	-0.4528	332.8	-1 561c	32 561			
-1 495c	19 495	13.29	-1.37	-24.35	24.39	1.0697	-0.8734	266.7	13 465	34 573				
-1 500c	20 500	14.33	-4.22	-24.38	24.74	0.9934	-0.8209	260.1	13 468	34 573	min			
-1 509c	21 510	15.59	-7.56	-24.23	25.38	0.9171	-0.7624	252.6	14 470	34 574				
-1 520c	24 520	20.85	-20.35	-22.91	30.65	0.7207	-0.5802	228.3	15 476	35 577	Bm			
-1 529c	25 530	23.1	-25.24	-22.22	33.63	0.674	-0.5254	221.3	15 477	35 578				
-1 539c	27 540	28.3	-35.36	-20.51	40.88	0.6113	-0.4306	210.1	16 480	36 581				
-1 545c	29 545	34.29	-45.06	-18.45	48.7	0.5855	-0.356	202.2	16 483	37 585				
-1 550c	30 550	37.51	-49.37	-17.32	52.32	0.5847	-0.3255	199.3	16 484	37 587				
-1 555c	31 555	40.86	-53.13	-16.15	55.53	0.591	-0.2988	196.9	17 485	37 589				
-1 560c	32 560	44.3	-56.17	-14.94	58.12	0.604	-0.2756	194.8	17 486	38 592				
W0	380	770	89.99	0.0	0.0	0.0	1.1112	-0.1407	0.0	B _c =1,000				
N0	380	770	3.59	0.0	0.0	0.0	1.1112	-0.1407	0.0	x _c =0,000				

DGJ7-7N