

Farbmetrische "Norm-Daten": Fernseh-Lichtfarben-System TLS11 für Helligkeit $L^*=11$ von Schwarz für Lichtart D65															
System TLS11	Farbe	$r=ol\vee*_1$	$g=ol\vee*_2$	$b=ol\vee*_3$	$L^*=LAB*_1$	$a^*=LAB*_2$	$b^*=LAB*_3$	$C^*_{ab}=LAB*_r$	h_{ab}	$X=XYZ_1$	$Y=XYZ_2$	$Z=XYZ_3$	x	y	Y/88.59
LCD-Monitor	00 o00y	1.0	0.0	0.0	54.21	78.64	58.52	98.03	37	42.14	22.17	3.33	0.623	0.3278	0.2503
	01 o13y	1.0	0.125	0.0	54.91	76.45	59.02	96.58	38	42.42	22.84	3.44	0.6174	0.3325	0.2579
	02 o25y	1.0	0.25	0.0	57.87	68.1	61.12	91.5	42	43.91	25.83	3.96	0.5958	0.3505	0.2916
	03 o38y	1.0	0.375	0.0	62.22	56.16	64.44	85.47	49	46.26	30.66	4.75	0.5664	0.3754	0.3461
	04 o50y	1.0	0.5	0.0	67.48	42.42	68.19	80.31	58	49.48	37.27	5.91	0.534	0.4022	0.4207
	05 o63y	1.0	0.625	0.0	73.63	27.43	72.96	77.94	70	53.85	46.12	7.39	0.5016	0.4296	0.5206
	06 o75y	1.0	0.75	0.0	80.08	12.73	77.89	78.93	81	59.14	56.82	9.2	0.4725	0.454	0.6414
	07 o88y	1.0	0.875	0.0	86.52	-1.05	82.98	82.99	91	65.14	69.03	11.22	0.448	0.4748	0.7793
	08 y00l	1.0	1.0	0.0	94.11	-15.83	89.38	90.77	101	73.43	85.54	13.8	0.425	0.4951	0.9655
	09 y13l	0.875	1.0	0.0	92.0	-27.1	86.39	90.55	108	64.07	80.71	13.54	0.4047	0.5098	0.911
	10 y25l	0.75	1.0	0.0	90.22	-37.49	83.97	91.96	115	56.47	76.78	13.28	0.3854	0.524	0.8667
	11 y38l	0.625	1.0	0.0	88.56	-48.25	81.77	94.94	122	49.55	73.23	13.01	0.3649	0.5393	0.8266
	12 y50l	0.5	1.0	0.0	87.07	-58.61	79.85	99.06	128	43.6	70.14	12.75	0.3447	0.5545	0.7917
	13 y63l	0.375	1.0	0.0	85.89	-67.53	78.43	103.5	132	39.02	67.76	12.51	0.3271	0.568	0.7649
	14 y75l	0.25	1.0	0.0	84.97	-74.95	77.13	107.56	136	35.55	65.95	12.4	0.3121	0.579	0.7444
	15 y88l	0.125	1.0	0.0	84.37	-79.89	76.36	110.52	138	33.36	64.77	12.3	0.3021	0.5865	0.7312
	16 l00c	0.0	1.0	0.0	84.21	-81.1	76.13	111.24	138	32.83	64.47	12.29	0.2996	0.5883	0.7278
	17 l13c	0.0	1.0	0.125	84.25	-80.71	73.57	109.22	139	32.98	64.54	13.31	0.2976	0.5823	0.7285
	18 l25c	0.0	1.0	0.25	84.35	-78.62	63.95	101.35	143	33.71	64.74	17.66	0.2903	0.5576	0.7308
	19 l38c	0.0	1.0	0.375	84.61	-75.49	51.46	91.37	148	34.93	65.24	24.72	0.2797	0.5224	0.7365
	20 l50c	0.0	1.0	0.5	84.97	-71.46	38.14	81.01	154	36.59	65.95	34.2	0.2676	0.4823	0.7444
	21 l63c	0.0	1.0	0.625	85.43	-66.43	24.55	70.83	163	38.75	66.85	46.23	0.2552	0.4403	0.7546
	22 l75c	0.0	1.0	0.75	85.97	-61.24	11.9	62.39	173	41.15	67.93	59.93	0.2435	0.4019	0.7668
	23 l88c	0.0	1.0	0.875	86.54	-56.04	0.7	56.06	183	43.7	69.07	74.31	0.2336	0.3692	0.7796
	24 c00v	0.0	1.0	1.0	87.18	-51.1	-9.41	51.97	195	46.37	70.38	89.45	0.2249	0.3413	0.7944
	25 c13v	0.0	0.875	1.0	78.68	-38.63	-22.32	44.62	213	38.35	54.38	86.97	0.2134	0.3026	0.6138
	26 c25v	0.0	0.75	1.0	71.08	-26.3	-33.97	42.97	233	32.33	42.3	84.93	0.2026	0.2651	0.4775
	27 c38v	0.0	0.675	1.0	63.12	-11.97	-46.39	47.92	254	27.09	31.73	83.16	0.1908	0.2235	0.3582
	28 c50v	0.0	0.5	1.0	54.95	4.19	-59.11	59.26	272	22.65	22.88	81.29	0.1786	0.1804	0.2582
	29 c63v	0.0	0.375	1.0	47.37	21.46	-71.55	74.71	284	19.44	16.3	80.45	0.1673	0.1403	0.184
	30 c75v	0.0	0.25	1.0	40.2	39.44	-83.05	91.95	294	16.99	11.37	79.32	0.1578	0.1056	0.1284
	31 c88v	0.0	0.125	1.0	34.57	55.15	-92.53	107.73	299	15.49	8.29	79.02	0.1507	0.0806	0.0935
	32 v00m	0.0	0.0	1.0	33.09	59.26	-94.9	111.9	301	15.11	7.58	78.79	0.1489	0.0747	0.0856
	33 v13m	0.125	0.0	1.0	33.6	60.17	-94.39	111.95	301	15.63	7.82	79.26	0.1522	0.0761	0.0882
	34 v25m	0.25	0.0	1.0	35.64	62.25	-90.58	109.92	303	17.57	8.82	78.88	0.1669	0.0838	0.0996
	35 v38m	0.375	0.0	1.0	38.78	65.67	-85.41	107.74	306	20.9	10.53	79.21	0.1889	0.0952	0.1189
	36 v50m	0.5	0.0	1.0	42.38	69.54	-79.14	105.36	310	25.19	12.75	79.11	0.2152	0.1089	0.1439
	37 v63m	0.625	0.0	1.0	46.58	74.48	-72.19	103.73	315	31.01	15.7	79.49	0.2457	0.1244	0.1772
	38 v75m	0.75	0.0	1.0	50.83	79.05	-64.9	102.28	320	37.61	19.12	79.55	0.276	0.1403	0.2158
	39 v88m	0.875	0.0	1.0	54.98	83.66	-57.89	101.74	324	44.97	22.91	79.74	0.3046	0.1552	0.2586
	40 m00o	1.0	0.0	1.0	59.56	89.09	-50.27	102.3	329	54.26	27.64	80.12	0.3349	0.1706	0.312
	41 m13o	1.0	0.0	0.875	58.35	87.39	-40.57	96.35	334	51.59	26.33	65.42	0.3599	0.1837	0.2972
	42 m25o	1.0	0.0	0.75	57.23	85.38	-29.34	90.29	340	49.04	25.16	51.28	0.3908	0.2005	0.284
	43 m38o	1.0	0.0	0.675	56.14	83.38	-16.14	84.93	348	46.62	24.05	37.77	0.4299	0.2218	0.2715
	44 m50o	1.0	0.0	0.5	55.19	81.22	-0.89	81.23	359	44.43	23.11	25.72	0.4764	0.2478	0.2609
	45 m63o	1.0	0.0	0.375	54.35	79.62	15.44	81.1	11	42.67	22.31	16.14	0.526	0.275	0.2518
	46 m75o	1.0	0.0	0.25	53.75	78.41	33.44	85.24	24	41.41	21.74	8.91	0.5747	0.3017	0.2454
	47 m88o	1.0	0.0	0.125	53.35	77.5	51.81	93.22	34	40.55	21.37	4.23	0.613	0.323	0.2412
	48 o00y	1.0	0.0	0.0	54.21	78.64	58.52	98.03	37	42.14	22.17	3.33	0.623	0.3278	0.2503
	49 n00w	0.0	0.0	0.0	10.76	5.51	-3.96	6.79	0	1.34	1.23	1.71	0.3134	0.2867	0.0139
	50 n13w	0.125	0.125	0.125	16.56	4.87	-3.31	5.9	169	2.33	2.21	2.86	0.3146	0.2988	0.025
	51 n25w	0.25	0.25	0.25	30.75	4.15	-2.76	4.99	269	6.61	6.54	7.89	0.3142	0.311	0.0739
	52 n38w	0.375	0.375	0.375	43.53	4.11	-2.65	4.9	292	13.48	13.52	15.89	0.3142	0.3152	0.1526
	53 n50w	0.5	0.5	0.5	55.06	4.06	-2.42	4.73	297	22.73	22.99	26.55	0.3145	0.3181	0.2595
	54 n63w	0.625	0.625	0.625	66.15	3.69	-1.8	4.11	298	34.83	35.52	40.18	0.3151	0.3214	0.401
	55 n75w	0.75	0.75	0.75	76.28	3.24	-0.77	3.34	301	49.03	50.35	55.64	0.3163	0.3248	0.5683
	56 n88w	0.875	0.875	0.875	85.51	2.1	0.82	2.26	299	64.62	67.02	71.95	0.3174	0.3292	0.7565
	57 n99w	1.0	1.0	1.0	95.41	-0.21	4.78	4.79	0	84.08	88.59	89.43	0.3208	0.338	1.0