

Interpretation *rgb* $\rightarrow$ *ol**v**- und CIELAB-Daten

sRGB-Display mit der Leuchtdichte-Reflexion $L_r=1,2\%$

Buntonkreis mit 6 Geräte-Bunttönen *OYLCVM*:

$h_{ab,a} = 36.9, 103.0, 136.4, 196.4, 305.2, 328.1$

Elementar-Bunttöne *RJGB*: $h_{ab,a} = 25.4, 92.3, 162.2, 271.7$

<i>Code</i>	L^*	a^*_a	b^*_a	C^*_{ab}	$h_{ab,a}$	<i>rgb</i> $\rightarrow$ <i>ol</i> <i>v</i> *
<i>m00o=M</i>	58.1	91.8	-57.0	108.0	328.1	1.00 0.00 1.00
<i>m12o</i>	56.5	87.7	-42.7	97.5	334.0	1.00 0.00 0.87
<i>m25o</i>	55.1	84.1	-27.7	88.5	341.7	1.00 0.00 0.75
<i>m37o</i>	54.0	81.0	-12.1	81.9	351.4	1.00 0.00 0.62
<i>m50o</i>	53.1	78.4	3.9	78.5	2.9	1.00 0.00 0.50
<i>m62o</i>	52.4	76.5	20.3	79.2	14.8	1.00 0.00 0.37
<i>m75o</i>	52.0	75.2	36.0	83.4	25.6	1.00 0.00 0.25
<i>m87o</i>	51.7	74.5	48.9	89.1	33.3	1.00 0.00 0.12

R