

***rgb* -> *rgb**- und CIE-Daten von Elementar-Bunttonkreis nach CIE R1-47:2009 für Laserdrucker**

<i>Code</i>	<i>L*</i> _a	<i>a*</i> _a	<i>b*</i> _a	<i>C*</i> _{ab,a}	<i>h</i> _{ab}	<i>rgb</i> -> <i>rgb*</i>
Elementar-Bunttonkreis <i>RJGB</i>: <i>h</i>_{ab} = 25.4, 92.3, 162.2, 271.7						
<i>r00j</i> = <i>R</i>	45.1	61.9	29.5	68.6	25.4	1.00 0.00 0.00
<i>r25j</i>	51.5	57.4	52.1	77.5	42.2	1.00 0.25 0.00
<i>r50j</i>	61.7	37.6	62.4	72.9	58.9	1.00 0.50 0.00
<i>r75j</i>	72.0	18.4	71.8	74.1	75.6	1.00 0.75 0.00
5-stufige gleichabständige Graureihe: <i>L*</i> = 13.0, 34.0, 55.0, 76.1, 97.1						
<i>n000w</i> = <i>N</i>	14.0	0.0	0.1	0.1	85.7	0.00 0.00 0.00
<i>n025w</i>	34.1	0.0	-0.9	0.9	270.7	0.25 0.25 0.25
<i>n050w</i>	55.1	0.1	-1.0	1.0	277.2	0.50 0.50 0.50
<i>n075w</i>	76.1	0.2	-0.6	0.6	289.2	0.75 0.75 0.75
<i>n100w</i> = <i>W</i>	97.2	0.0	0.1	0.1	110.1	1.00 1.00 1.00