

Interpretation *rgb* $\rightarrow$ *olv**- und
für Laserdrucker, Drucker-Separation *olv**

Buntonkreis mit 6 Geräte-Bunttönen OYLCVM:

$h_{ab,a} = 33.0, 100.4, 143.3, 206.6, 264.0, 351.1$

Elementar-Bunttöne **RJGB**: $h_{ab,a} = 25.4, 92.3, 162.2, 271.7$

<i>Code</i>	<i>L</i> *	<i>a</i> * _a	<i>b</i> * _a	<i>C</i> * _{ab}	<i>h</i> _{ab,a}	<i>rgb</i> $\rightarrow$ <i>olv</i> *
<i>m00o</i> = <i>M</i>	48.2	72.1	-11.2	73.0	351.1	1.00 0.00 1.00
<i>m12o</i>	48.2	75.4	-6.6	75.7	354.9	1.00 0.00 0.87
<i>m25o</i>	47.8	73.7	-0.5	73.7	359.6	1.00 0.00 0.75
<i>m37o</i>	48.0	71.1	7.2	71.4	5.8	1.00 0.00 0.62
<i>m50o</i>	48.2	69.3	12.9	70.5	10.6	1.00 0.00 0.50
<i>m62o</i>	47.9	67.3	20.1	70.2	16.6	1.00 0.00 0.37
<i>m75o</i>	48.1	65.5	28.5	71.5	23.5	1.00 0.00 0.25
<i>m87o</i>	48.3	64.8	36.7	74.5	29.5	1.00 0.00 0.12

R