





See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
 Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1.1, CIELAB




<http://130.149.60.45/~farbmetrik/OE50/OE50L0NA.TXT> /PS; linearized output, Page 2/3
 F: Output Linearization (OL) data OE50/OE50L0NA.TXT /PS in File (F)



TUB registration: 20110801-OE50/OE50L0NA.TXT /PS
 application for output of displays: monitor systems or data projector systems

TUB material: code=rh4ta



Test for the best visual linearized output of Picture A7-130-0 Yes/No
Output test with the computer display () or the external display ()
Test of the radial grating according to picture A1-130-0
 N-W-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
 W-N-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
 N-Z-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
 W-Z-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
Test of 5 visual equidistant L*-grey steps according to picture A2-130-0
 Are the 5 steps on the upper rows distinguishable? Yes/No
 If No: How many steps can be distinguished? Steps
 of the given 5 steps:
Test of 16 visual equidistant L*-grey steps according to picture A3-130-0
 Are the 16 steps on the upper rows distinguishable? Yes/No
 If No: How many steps can be distinguished? Steps
 of the given 16 steps:

Part 1 OE500-3N-130-1

Documentation of file format, hardware and software for this test:
PDF-File: <http://130.149.60.45/farbmetrik/OE50/OE50L0NP.PDF> underline Yes/No
PS-File: <http://130.149.60.45/farbmetrik/OE50/OE50L0NA.PS> or underline Yes/No

Used computer operating system:
 either one of Windows/Mac/Unix/other and version:.....
This evaluation is for the device output: underline monitor/data projector/printer
 Device model, driver and version:.....
Device output with PDF/PS-file: underline PDF/PS-file
For device output with PDF-file OE50L0NP.PDF:
 either PDF-file transfer "download, copy" to PDF device.....
 or with computer system interpretation by "Display-PDF":.....
 or with software e. g. Adobe-Reader/-Acrobat and version:.....
 or with software e. g. Ghostscript and version:.....
For device output with PS-file OE50L0NA.PS:
 either PS-file transfer "download, copy" to PS device.....
 or with computer system interpretation by "Display-PS":.....
 or with software e. g. Ghostscript and version:.....
 or with software e. g. Mac-Yap and version:.....
 Special remarks: Special remarks, e. g. output of Landscape (L)

Part 3 OE500-7N-130-1



OE50: Form A for test chart according to ISO 9241-306; 1MR, DH input: 000n (->rgb*_d) setcmk
 Viewing Y contrast $Y_W:Y_N=88,9:0,31$; Y_N range 0,0 to <0,46 output 130-1: $g_P=1.0$; $g_N=1.0$

Test for the best visual linearized output of Picture A7-130-0 Yes/No
Output test with the computer display () or the external display ()
Test of the Landolt-rings N-W according to picture A4-130-0
 N-W-radial grating:
 Is the recognition frequency of the Landolt-rings > 50% (5 of 8 at least)?
 background – ring
 0 – 1 Yes/No
 7 – 8 Yes/No
 E – F Yes/No
 2 – 0 Yes/No
 8 – 6 Yes/No
 F – D Yes/No
Test of the radial grating under 45° according to picture A5-130-0
 Can equally spaced lines be seen?
 Visual testing: for radial diameter from 15 to 60 lpi Yes/No
 Test with a magnifying glass (e.g. 6x): – from 15 lpi: to lpi
Test of the radial grating under 90° according to picture A6-130-0
 Can equally spaced lines be seen?
 Visual testing: for radial diameter from 15 to 60 lpi Yes/No
 Test with a magnifying glass (e.g. 6x): – from 15 lpi: to lpi

Part 2 OE501-3N-130-1

Documentation of assessor colour vision properties for visual assessment
 The assessor has normal colour vision according to one test: underline Yes/No
 either according to DIN 6160:1996 with Anomaloskop of Nagel underline Yes/unknown
 or with test charts using colour points according to Ishihara underline Yes/unknown
 or tested with, please specify: underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output
 Office workplace illumination is daylight (clouded/north sky) underline Yes/No
PDF file: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PDF> underline Yes/No
PS file: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PS> underline Yes/No
Picture A7-130-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)
 compare standard print output according to ISO/IEC 15775 with range F:0 underline range
 Remark: In daylighted offices the contrast range is in many cases:
 on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)

Only for optional colorimetric specification with PDF/PS file output

PDF-File: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PDF> underline Yes/No
picture A7-130-2
PS-File: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PS> or underline Yes/No
picture A7-130-2

colour measurement and specification for:
 CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: underline Yes/No
 If No, please give other parameters:

Colorimetric specification with PS file for colours in the columns A to T
 Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer
 of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF underline Yes/No
 If No, please describe other method:

Part 4

OE501-7N-130-1



Test for the best visual linearized output of Picture A7-131-0		Yes/No
Output test with the computer display () or the external display ()		
Test of the radial grating according to picture A1-131-0		
N-W-radial grating:	Is the resolution diameter < 6 mm?	Yes/No
	Test with magnifying glass (e.g. 6x) mm
	resolution diameter	Yes/No
W-N-radial grating:	Is the resolution diameter < 6 mm?	Yes/No
	Test with magnifying glass (e.g. 6x) mm
	resolution diameter	Yes/No
N-Z-radial grating:	Is the resolution diameter < 6 mm?	Yes/No
	Test with magnifying glass (e.g. 6x) mm
	resolution diameter	Yes/No
W-Z-radial grating:	Is the resolution diameter < 6 mm?	Yes/No
	Test with magnifying glass (e.g. 6x) mm
	resolution diameter mm
Test of 5 visual equidistant L*-grey steps according to picture A2-131-0		
Are the 5 steps on the upper rows distinguishable?		Yes/No
If No: How many steps can be distinguished?	 Steps
of the given 5 steps:	 Steps
Test of 16 visual equidistant L*-grey steps according to picture A3-131-0		
Are the 16 steps on the upper rows distinguishable?		Yes/No
If No: How many steps can be distinguished?	 Steps
of the given 16 steps:	 Steps

Part 1 OE500-3N-131-1

Documentation of file format, hardware and software for this test:

PDF-File: <http://130.149.60.45/farbmetrik/OE50/OE50L0NP.PDF> underline Yes/No

PS-File: <http://130.149.60.45/farbmetrik/OE50/OE50L0NA.PS> or underline Yes/No

Used computer operating system:

either one of Windows/Mac/Unix/other and version:.....

This evaluation is for the device output: underline monitor/data projector/printer

Device model, driver and version:.....

Device output with PDF/PS-file: underline PDF/PS-file

For device output with PDF-file OE50L0NP.PDF:

either PDF-file transfer "download, copy" to PDF device:.....

or with computer system interpretation by "Display-PDF":.....

or with software e. g. Adobe-Reader/-Acrobat and version:.....

or with software e. g. Ghostscript and version:.....

For device output with PS-file OE50L0NA.PS:

either PS-file transfer "download, copy" to PS device:.....

or with computer system interpretation by "Display-PS":.....

or with software e. g. Ghostscript and version:.....

or with software e. g. Mac-Yap and version:.....

Special remarks: Special remarks, e. g. output of Landscape (L)

.....

.....

.....

.....

.....

.....

.....

.....

.....

Test for the best visual linearized output of Picture A7-131-0		Yes/No
Output test with the computer display () or the external display ()		
Test of the Landolt-rings N-W according to picture A4-131-0		
N-W-radial grating:		
Is the recognition frequency of the Landolt-rings > 50% (5 of 8 at least)?		
background - ring		Yes/No
0 - 1		Yes/No
7 - 8		Yes/No
E - F		Yes/No
2 - 0		Yes/No
8 - 6		Yes/No
F - D		Yes/No
Test of the radial grating under 45° according to picture A5-131-0		
Can equally spaced lines be seen?		
Visual testing: for radial diameter from 15 to 60 lpi		Yes/No
Test with a magnifying glass (e.g. 6x): - from 15 lpi:		to lpi
Test of the radial grating under 90° according to picture A6-131-0		
Can equally spaced lines be seen?		
Visual testing: for radial diameter from 15 to 60 lpi		Yes/No
Test with a magnifying glass (e.g. 6x): - from 15 lpi:		to lpi

Part 2 OE501-3N-131-1

Documentation of assessor colour vision properties for visual assessment

The assessor has **normal** colour vision according to one test:

either according to DIN 6160:1996 with Anomaloskop of Nagel

or with test charts using colour points according to Ishihara

or tested with, please specify:

underline Yes/No

underline Yes/unknown

underline Yes/unknown

underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)

PDF file: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PDF>

PS file: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PS>

Picture A7-131-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)

compare standard print output according to ISO/IEC 15775 with range F:0

Remark: In daylighted offices the contrast range is in many cases:

on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)

Only for optional colorimetric specification with PDF/PS file output

PDF-File: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PDF>

picture A7-131-2

underline Yes/No

PS-File: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PS>

picture A7-131-2

or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:

If No, please give other parameters:

underline Yes/No

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer

of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF

If No, please describe other method:

underline Yes/No

Part 3 OE500-7N-131-1

OE50: Form A for test chart according to ISO 9241-306; 1MR, DH input: 000n (->rgb*_d) setcmk
Viewing Y contrast $Y_W:Y_N=88,9:0,62$; Y_N range 0,46 to <0,93 output 131-1: $g_P=0,92$; $g_N=1,0$

Part 4 OE501-7N-131-1

Test for the best visual linearized output of Picture A7-132-0		Yes/No
Output test with the computer display () or the external display ()		
Test of the radial grating according to picture A1-132-0		
N-W-radial grating:	Is the resolution diameter < 6 mm?	Yes/No
	Test with magnifying glass (e.g. 6x) mm
	resolution diameter	Yes/No
W-N-radial grating:	Is the resolution diameter < 6 mm? mm
	Test with magnifying glass (e.g. 6x)	Yes/No
	resolution diameter mm
N-Z-radial grating:	Is the resolution diameter < 6 mm?	Yes/No
	Test with magnifying glass (e.g. 6x) mm
	resolution diameter	Yes/No
W-Z-radial grating:	Is the resolution diameter < 6 mm? mm
	Test with magnifying glass (e.g. 6x)	Yes/No
	resolution diameter mm
Test of 5 visual equidistant L*-grey steps according to picture A2-132-0		
Are the 5 steps on the upper rows distinguishable?		Yes/No
If No: How many steps can be distinguished?	 Steps
of the given 5 steps:	 Steps
Test of 16 visual equidistant L*-grey steps according to picture A3-132-0		
Are the 16 steps on the upper rows distinguishable?		Yes/No
If No: How many steps can be distinguished?	 Steps
of the given 16 steps:	 Steps

Part 1

OE500-3N-132-1

Documentation of file format, hardware and software for this test:

PDF-File: http://130.149.60.45/farbmetrik/OE50/OE50L0NP.PDF underline Yes/No

PS-File: http://130.149.60.45/farbmetrik/OE50/OE50L0NA.PS or underline Yes/No

Used computer operating system:

either one of Windows/Mac/Unix/other and version:.....

This evaluation is for the device output: underline monitor/data projector/printer

Device model, driver and version:.....

Device output with PDF/PS-file: underline PDF/PS-file

For device output with PDF-file OE50L0NP.PDF:

either PDF-file transfer "download, copy" to PDF device:.....

or with computer system interpretation by "Display-PDF":.....

or with software e. g. Adobe-Reader/-Acrobat and version:.....

or with software e. g. Ghostscript and version:.....

For device output with PS-file OE50L0NA.PS:

either PS-file transfer "download, copy" to PS device:.....

or with computer system interpretation by "Display-PS":.....

or with software e. g. Ghostscript and version:.....

or with software e. g. Mac-Yap and version:.....

Special remarks:Special remarks, e. g. output of Landscape (L)

.....

.....

.....

Part 3

OE500-7N-132-1

OE50: Form A for test chart according to ISO 9241-306; 1MR, DH input: 000n (->rgb*_d) setcmk
Viewing Y contrast $Y_W:Y_N=88,9:1,25$; Y_N range 0,93 to <1,87 output 132-1: $g_P=0.85$; $g_N=1.0$

Test for the best visual linearized output of Picture A7-132-0		Yes/No
Output test with the computer display () or the external display ()		
Test of the Landolt-rings N-W according to picture A4-132-0		
N-W-radial grating:		
Is the recognition frequency of the Landolt-rings > 50% (5 of 8 at least)?		
	background - ring	Yes/No
	0 - 1	Yes/No
	7 - 8	Yes/No
	E - F	Yes/No
	2 - 0	Yes/No
	8 - 6	Yes/No
	F - D	Yes/No
Test of the radial grating under 45° according to picture A5-132-0		
Can equally spaced lines be seen?		
Visual testing: for radial diameter from 15 to 60 lpi		Yes/No
Test with a magnifying glass (e.g. 6x): - from 15 lpi:		to lpi
Test of the radial grating under 90° according to picture A6-132-0		
Can equally spaced lines be seen?		
Visual testing: for radial diameter from 15 to 60 lpi		Yes/No
Test with a magnifying glass (e.g. 6x): - from 15 lpi:		to lpi

Part 2

OE501-3N-132-1

Documentation of assessor colour vision properties for visual assessment

The assessor has **normal** colour vision according to one test:

either according to DIN 6160:1996 with Anomaloskop of Nagel

or with test charts using colour points according to Ishihara

or tested with, please specify:

underline Yes/No

underline Yes/unknown

underline Yes/unknown

underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)

PDF file: http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PDF

PS file: http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PS

Picture A7-132-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)

compare standard print output according to ISO/IEC 15775 with range F:0

Remark: In daylighted offices the contrast range is in many cases:

on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PDF

picture A7-132-2

underline Yes/No

PS-File: http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PS

picture A7-132-2

or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:

If No, please give other parameters:

underline Yes/No

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer

of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF

If No, please describe other method:

underline Yes/No

Part 4

OE501-7N-132-1

Test for the best visual linearized output of Picture A7-133-0 Yes/No
Output test with the computer display () or the external display ()
Test of the radial grating according to picture A1-133-0
N-W-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
W-N-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
N-Z-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
W-Z-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
Test of 5 visual equidistant L*-grey steps according to picture A2-133-0
 Are the 5 steps on the upper rows distinguishable? Yes/No
 If No: How many steps can be distinguished? of the given 5 steps: Steps
Test of 16 visual equidistant L*-grey steps according to picture A3-133-0
 Are the 16 steps on the upper rows distinguishable? Yes/No
 If No: How many steps can be distinguished? of the given 16 steps: Steps

Part 1

OE500-3N-133-1

Documentation of file format, hardware and software for this test:

PDF-File: <http://130.149.60.45/farbmetrik/OE50/OE50L0NP.PDF> underline Yes/No

PS-File: <http://130.149.60.45/farbmetrik/OE50/OE50L0NA.PS> or underline Yes/No

Used computer operating system:

either one of Windows/Mac/Unix/other and version:.....

This evaluation is for the device output: underline monitor/data projector/printer

Device model, driver and version:.....

Device output with PDF/PS-file: underline PDF/PS-file

For device output with PDF-file OE50L0NP.PDF:

either PDF-file transfer "download, copy" to PDF device.....
 or with computer system interpretation by "Display-PDF":.....
 or with software e. g. Adobe-Reader/-Acrobat and version:.....
 or with software e. g. Ghostscript and version:.....

For device output with PS-file OE50L0NA.PS:

either PS-file transfer "download, copy" to PS device.....
 or with computer system interpretation by "Display-PS":.....
 or with software e. g. Ghostscript and version:.....
 or with software e. g. Mac-Yap and version:.....

Special remarks:Special remarks, e. g. output of Landscape (L)

.....

Part 3

OE500-7N-133-1

OE50: Form A for test chart according to ISO 9241-306; 1MR, DH input: 000n (->rgb*_d) setcmk
 Viewing Y contrast $Y_W:Y_N=88,9:2,5$; Y_N range 1,87 to <3,75 output 133-1: $g_P=0.77$; $g_N=1.0$

Test for the best visual linearized output of Picture A7-133-0 Yes/No
Output test with the computer display () or the external display ()
Test of the Landolt-rings N-W according to picture A4-133-0
N-W-radial grating:
 Is the recognition frequency of the Landolt-rings > 50% (5 of 8 at least)?
 background – ring
 0 – 1 Yes/No
 7 – 8 Yes/No
 E – F Yes/No
 2 – 0 Yes/No
 8 – 6 Yes/No
 F – D Yes/No
Test of the radial grating under 45° according to picture A5-133-0
 Can equally spaced lines be seen?
 Visual testing: for radial diameter from 15 to 60 lpi Yes/No
 Test with a magnifying glass (e.g. 6x): – from 15 lpi: to lpi
Test of the radial grating under 90° according to picture A6-133-0
 Can equally spaced lines be seen?
 Visual testing: for radial diameter from 15 to 60 lpi Yes/No
 Test with a magnifying glass (e.g. 6x): – from 15 lpi: to lpi

Part 2

OE501-3N-133-1

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:

either according to DIN 6160:1996 with Anomaloskop of Nagel

or with test charts using colour points according to Ishihara

or tested with, please specify:

underline Yes/No

underline Yes/unknown

underline Yes/unknown

underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)

PDF file: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PDF>

PS file: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PS>

Picture A7-133-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)

compare standard print output according to ISO/IEC 15775 with range F:0 underline range

Remark: In daylighted offices the contrast range is in many cases:

on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)

Only for optional colorimetric specification with PDF/PS file output

PDF-File: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PDF>

picture A7-133-2

underline Yes/No

PS-File: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PS>

picture A7-133-2

or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:

If No, please give other parameters:

underline Yes/No

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer

of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF

If No, please describe other method:

underline Yes/No

Part 4

OE501-7N-133-1

Test for the best visual linearized output of Picture A7-134-0 Yes/No
Output test with the computer display () or the external display ()
Test of the radial grating according to picture A1-134-0
N-W-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
W-N-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
N-Z-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
W-Z-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
Test of 5 visual equidistant L*-grey steps according to picture A2-134-0
 Are the 5 steps on the upper rows distinguishable? Yes/No
 If No: How many steps can be distinguished? Steps
Test of 16 visual equidistant L*-grey steps according to picture A3-134-0
 Are the 16 steps on the upper rows distinguishable? Yes/No
 If No: How many steps can be distinguished? Steps

Part 1

OE500-3N-134-1

Documentation of file format, hardware and software for this test:

PDF-File: http://130.149.60.45/farbmetrik/OE50/OE50L0NP.PDF underline Yes/No

PS-File: http://130.149.60.45/farbmetrik/OE50/OE50L0NA.PS or underline Yes/No

Used computer operating system:

either one of Windows/Mac/Unix/other and version:.....

This evaluation is for the device output: underline monitor/data projector/printer

Device model, driver and version:.....

Device output with PDF/PS-file: underline PDF/PS-file

For device output with PDF-file OE50L0NP.PDF:

either PDF-file transfer "download, copy" to PDF device.....
 or with computer system interpretation by "Display-PDF":.....
 or with software e. g. Adobe-Reader/-Acrobat and version:.....
 or with software e. g. Ghostscript and version:.....

For device output with PS-file OE50L0NA.PS:

either PS-file transfer "download, copy" to PS device.....
 or with computer system interpretation by "Display-PS":.....
 or with software e. g. Ghostscript and version:.....
 or with software e. g. Mac-Yap and version:.....

Special remarks:Special remarks, e. g. output of Landscape (L)

Part 3

OE500-7N-134-1

OE50: Form A for test chart according to ISO 9241-306; 1MR, DH input: 000n (->rgb*_d) setcmk
 Viewing Y contrast $Y_W:Y_N=88,9:5$; Y_N range 3,75 to <7,5
 output 134-1: $g_P=0.7$; $g_N=1.0$

Test for the best visual linearized output of Picture A7-134-0 Yes/No
Output test with the computer display () or the external display ()
Test of the Landolt-rings N-W according to picture A4-134-0
N-W-radial grating:
 Is the recognition frequency of the Landolt-rings > 50% (5 of 8 at least)?
 background – ring
 0 – 1 Yes/No
 7 – 8 Yes/No
 E – F Yes/No
 2 – 0 Yes/No
 8 – 6 Yes/No
 F – D Yes/No
Test of the radial grating under 45° according to picture A5-134-0
 Can equally spaced lines be seen?
 Visual testing: for radial diameter from 15 to 60 lpi Yes/No
 Test with a magnifying glass (e.g. 6x): – from 15 lpi: to lpi
Test of the radial grating under 90° according to picture A6-134-0
 Can equally spaced lines be seen?
 Visual testing: for radial diameter from 15 to 60 lpi Yes/No
 Test with a magnifying glass (e.g. 6x): – from 15 lpi: to lpi

Part 2

OE501-3N-134-1

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:

either according to DIN 6160:1996 with Anomaloskop of Nagel

or with test charts using colour points according to Ishihara

or tested with, please specify:

underline Yes/No

underline Yes/unknown

underline Yes/unknown

underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)

underline Yes/No

PDF file: http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PDF

underline Yes/No

PS file: http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PS

underline Yes/No

Picture A7-134-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)

compare standard print output according to ISO/IEC 15775 with range F:0 underline range

Remark: In daylighted offices the contrast range is in many cases:

on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PDF

underline Yes/No

PS-File: http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PS

or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:

underline Yes/No

If No, please give other parameters:

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer


of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF

underline Yes/No


If No, please describe other method:

Part 4


OE501-7N-134-1



See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
 Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1.1, CIELAB




<http://130.149.60.45/~farbmetrik/OE50/OE50L0NA.TXT> /PS; linearized output, Page 2/3
 F: Output Linearization (OL) data OE50/OE50L0NA.TXT /PS in File (F)



TUB registration: 20110801-OE50/OE50L0NA.TXT /PS
 application for output of displays: monitor systems or data projector systems

TUB material: code=rh4ta



Test for the best visual linearized output of Picture A7-135-0 Yes/No
Output test with the computer display () or the external display ()
Test of the radial grating according to picture A1-135-0
 N-W-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
 W-N-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
 N-Z-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
 W-Z-radial grating: Is the resolution diameter < 6 mm? Yes/No
 Test with magnifying glass (e.g. 6x) resolution diameter mm
Test of 5 visual equidistant L*-grey steps according to picture A2-135-0
 Are the 5 steps on the upper rows distinguishable? Yes/No
 If No: How many steps can be distinguished? Steps
 of the given 5 steps:
Test of 16 visual equidistant L*-grey steps according to picture A3-135-0
 Are the 16 steps on the upper rows distinguishable? Yes/No
 If No: How many steps can be distinguished? Steps
 of the given 16 steps:

Part 1 OE500-3N-135-1

Documentation of file format, hardware and software for this test:

PDF-File: <http://130.149.60.45/farbmetrik/OE50/OE50L0NP.PDF> underline Yes/No

PS-File: <http://130.149.60.45/farbmetrik/OE50/OE50L0NA.PS> or underline Yes/No

Used computer operating system:

either one of Windows/Mac/Unix/other and version:.....

This evaluation is for the device output: underline monitor/data projector/printer

Device model, driver and version:.....

Device output with PDF/PS-file: underline PDF/PS-file

For device output with PDF-file OE50L0NP.PDF:

either PDF-file transfer "download, copy" to PDF device.....
 or with computer system interpretation by "Display-PDF":.....
 or with software e. g. Adobe-Reader/-Acrobat and version:.....
 or with software e. g. Ghostscript and version:.....

For device output with PS-file OE50L0NA.PS:

either PS-file transfer "download, copy" to PS device.....
 or with computer system interpretation by "Display-PS":.....
 or with software e. g. Ghostscript and version:.....
 or with software e. g. Mac-Yap and version:.....

Special remarks:Special remarks, e. g. output of Landscape (L)

.....

Part 3

OE500-7N-135-1

Test for the best visual linearized output of Picture A7-135-0 Yes/No
Output test with the computer display () or the external display ()
Test of the Landolt-rings N-W according to picture A4-135-0
 N-W-radial grating:
 Is the recognition frequency of the Landolt-rings > 50% (5 of 8 at least)?
 background – ring
 0 – 1 Yes/No
 7 – 8 Yes/No
 E – F Yes/No
 2 – 0 Yes/No
 8 – 6 Yes/No
 F – D Yes/No
Test of the radial grating under 45° according to picture A5-135-0
 Can equally spaced lines be seen?
 Visual testing: for radial diameter from 15 to 60 lpi Yes/No
 Test with a magnifying glass (e.g. 6x): – from 15 lpi: to lpi
Test of the radial grating under 90° according to picture A6-135-0
 Can equally spaced lines be seen?
 Visual testing: for radial diameter from 15 to 60 lpi Yes/No
 Test with a magnifying glass (e.g. 6x): – from 15 lpi: to lpi

Part 2 OE501-3N-135-1

Documentation of assessor colour vision properties for visual assessment

The assessor has **normal** colour vision according to one test:

either according to DIN 6160:1996 with Anomaloskop of Nagel

or with test charts using colour points according to Ishihara

or tested with, please specify:

underline Yes/No

underline Yes/unknown

underline Yes/unknown

underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)

underline Yes/No

PDF file: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PDF>

underline Yes/No

PS file: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PS>

underline Yes/No

Picture A7-135-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)

compare standard print output according to ISO/IEC 15775 with range F:0 underline range

Remark: In daylighted offices the contrast range is in many cases:

on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)

Only for optional colorimetric specification with PDF/PS file output

PDF-File: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PDF>

underline Yes/No

PS-File: <http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PS>

or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:

underline Yes/No

If No, please give other parameters:

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer

of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF

underline Yes/No

If No, please describe other method:

Part 4

OE501-7N-135-1

OE50: Form A for test chart according to ISO 9241-306; 1MR, DH input: 000n (→rgb*d) setcmk
 Viewing Y contrast $Y_W:Y_N=88,9:10$; Y_N range 7,5 to <15 output 135-1: $g_P=0.62$; $g_N=1.0$

Test for the best visual linearized output of Picture A7-136-0		Yes/No
Output test with the computer display () or the external display ()		
Test of the radial grating according to picture A1-136-0		
N-W-radial grating:	Is the resolution diameter < 6 mm?	Yes/No
	Test with magnifying glass (e.g. 6x) mm
	resolution diameter	Yes/No
W-N-radial grating:	Is the resolution diameter < 6 mm? mm
	Test with magnifying glass (e.g. 6x)	Yes/No
	resolution diameter mm
N-Z-radial grating:	Is the resolution diameter < 6 mm?	Yes/No
	Test with magnifying glass (e.g. 6x) mm
	resolution diameter	Yes/No
W-Z-radial grating:	Is the resolution diameter < 6 mm? mm
	Test with magnifying glass (e.g. 6x)	Yes/No
	resolution diameter mm
Test of 5 visual equidistant L*-grey steps according to picture A2-136-0		
Are the 5 steps on the upper rows distinguishable?		Yes/No
If No: How many steps can be distinguished?	 Steps
of the given 5 steps:	 Steps
Test of 16 visual equidistant L*-grey steps according to picture A3-136-0		
Are the 16 steps on the upper rows distinguishable?		Yes/No
If No: How many steps can be distinguished?	 Steps
of the given 16 steps:	 Steps

Part 1

OE500-3N-136-1

Documentation of file format, hardware and software for this test:

PDF-File: http://130.149.60.45/farbmetrik/OE50/OE50L0NP.PDF underline Yes/No

PS-File: http://130.149.60.45/farbmetrik/OE50/OE50L0NA.PS or underline Yes/No

Used computer operating system:

either one of Windows/Mac/Unix/other and version:.....

This evaluation is for the device output: underline monitor/data projector/printer

Device model, driver and version:.....

Device output with PDF/PS-file: underline PDF/PS-file

For device output with PDF-file OE50L0NP.PDF:

either PDF-file transfer "download, copy" to PDF device.....
or with computer system interpretation by "Display-PDF":.....
or with software e. g. Adobe-Reader/-Acrobat and version:.....
or with software e. g. Ghostscript and version:.....

For device output with PS-file OE50L0NA.PS:

either PS-file transfer "download, copy" to PS device.....
or with computer system interpretation by "Display-PS":.....
or with software e. g. Ghostscript and version:.....
or with software e. g. Mac-Yap and version:.....

Special remarks: Special remarks, e. g. output of Landscape (L)

.....
.....
.....

Part 3

OE500-7N-136-1

OE50: Form A for test chart according to ISO 9241-306; 1MR, DH input: 000n (->rgb*_d) setcmk
Viewing Y contrast $Y_W:Y_N=88,9:20$; Y_N range 15 to <30
output 136-1: $g_P=0.55$; $g_N=1.0$

Test for the best visual linearized output of Picture A7-136-0		Yes/No
Output test with the computer display () or the external display ()		
Test of the Landolt-rings N-W according to picture A4-136-0		
N-W-radial grating:		
Is the recognition frequency of the Landolt-rings > 50% (5 of 8 at least)?		
	background - ring	Yes/No
	0 - 1	Yes/No
	7 - 8	Yes/No
	E - F	Yes/No
	2 - 0	Yes/No
	8 - 6	Yes/No
	F - D	Yes/No
Test of the radial grating under 45° according to picture A5-136-0		
Can equally spaced lines be seen?		
Visual testing: for radial diameter from 15 to 60 lpi		Yes/No
Test with a magnifying glass (e.g. 6x): - from 15 lpi:		to lpi
Test of the radial grating under 90° according to picture A6-136-0		
Can equally spaced lines be seen?		
Visual testing: for radial diameter from 15 to 60 lpi		Yes/No
Test with a magnifying glass (e.g. 6x): - from 15 lpi:		to lpi

Part 2

OE501-3N-136-1

Documentation of assessor colour vision properties for visual assessment

The assessor has **normal** colour vision according to one test:

either according to DIN 6160:1996 with Anomaloskop of Nagel

or with test charts using colour points according to Ishihara

or tested with, please specify:

underline Yes/No

underline Yes/unknown

underline Yes/unknown

underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)

PDF file: http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PDF

PS file: http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PS

Picture A7-136-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)

compare standard print output according to ISO/IEC 15775 with range F:0 underline range

Remark: In daylighted offices the contrast range is in many cases:

on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PDF

picture A7-136-2

underline Yes/No

PS-File: http://130.149.60.45/farbmetrik/OE50/OE50F1P2.PS

picture A7-136-2

or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:

If No, please give other parameters:

underline Yes/No

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer

of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF

If No, please describe other method:

underline Yes/No

Part 4

OE501-7N-136-1

Part 1	OE500-3N-137-1
--------	----------------

Part 3 OE500-7N-137-1

Part 2
OE501-3N-137-1

Part 4
OE501-7N-137-1