


See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE^*	Start output S1
1	0.0	0.0	0.0	0.0	0.0	0.01
2	6.36	0.0	0.07	6.36	0.0	0.01
3	12.72	0.0	0.13	12.72	0.0	0.01
4	19.08	0.0	0.2	19.08	0.0	0.01
5	25.44	0.0	0.27	25.44	0.0	0.01
6	31.8	0.0	0.33	31.8	0.0	0.01
7	38.16	0.0	0.4	38.16	0.0	0.01
8	44.52	0.0	0.47	44.52	0.0	0.01
9	50.89	0.0	0.53	50.89	0.0	0.01
10	57.25	0.0	0.6	57.25	0.0	0.01
11	63.61	0.0	0.67	63.61	0.0	0.01
12	69.97	0.0	0.73	69.97	0.0	0.01
13	76.33	0.0	0.8	76.33	0.0	0.01
14	82.69	0.0	0.87	82.69	0.0	0.01
15	89.05	0.0	0.93	89.05	0.0	0.01
16	95.41	0.0	1.0	95.41	0.0	0.01
17	0.0	0.0	0.0	0.0	0.0	0.01
18	23.85	0.0	0.25	23.85	0.0	0.01
19	47.71	0.0	0.5	47.71	0.0	0.01
20	71.56	0.0	0.75	71.56	0.0	0.01
21	95.41	0.0	1.0	95.41	0.0	0.01
Mean lightness difference (16 steps)						$\Delta E^*_{\text{CIELAB}} = 0.0$
Mean lightness difference (5 steps)						$\Delta L^*_{\text{CIELAB}} = 0.0$
Mean colour reproduction index:						$R^*_{\text{ab,m}} = 100$

OE540-3N-120-8: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE541-3N-120-8: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y^*_{\text{intended}}$ (absolute)	0.0/0.0	6.4/0.7	12.7/1.5	19.1/2.8	25.4/4.6	31.8/7.0	38.2/10.2	44.5/14.2	50.9/19.2	57.2/25.2	63.6/32.3	70.0/40.7	76.3/50.4	82.7/61.6	89.0/74.3	95.4/88.6
$n^*n^*n^*0$ setcmk $g_P=1.0$																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
w^*_{intended} w^*_{out}	0.000 0.0	0.067 0.067	0.133 0.133	0.200 0.2	0.267 0.267	0.333 0.333	0.400 0.4	0.467 0.467	0.533 0.533	0.600 0.6	0.667 0.667	0.733 0.733	0.800 0.8	0.867 0.867	0.933 0.933	1.000 1.0

OE540-7N, Picture A7-120-8: 16 visual equidistant L^* -grey steps; PS operator: $n^*n^*n^*0$ setcmkcolor

OE54: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast $Y_W:Y_N=88,9:0,31$; Y_N range 0,0 to <0,46


input: all ($\rightarrow \text{rgb}^*_d$) setrgbcOLOR
output 130-8: $g_P=1.0$; $g_N=1.0$

TUB registration: 20110801-OE54/OE54L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1.1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*
1	5.69 0.0 0.0	0.0 0.0 0.0	5.69 0.0 0.0	0.0 0.0 0.0	0.01
2	11.67 0.0 0.0	0.05 10.49 0.0	0.0 -1.17 0.0	0.0 0.0 0.0	1.18
3	17.65 0.0 0.0	0.11 15.85 0.0	0.0 -1.79 0.0	0.0 0.0 0.0	1.8
4	23.63 0.0 0.0	0.18 21.44 0.0	0.0 -2.19 0.0	0.0 0.0 0.0	2.2
5	29.62 0.0 0.0	0.24 27.18 0.0	0.0 -2.42 0.0	0.0 0.0 0.0	2.43
6	35.6 0.0 0.0	0.3 33.05 0.0	0.0 -2.54 0.0	0.0 0.0 0.0	2.55
7	41.58 0.0 0.0	0.37 39.01 0.0	0.0 -2.56 0.0	0.0 0.0 0.0	2.57
8	47.56 0.0 0.0	0.44 45.05 0.0	0.0 -2.5 0.0	0.0 0.0 0.0	2.51
9	53.54 0.0 0.0	0.51 51.16 0.0	0.0 -2.37 0.0	0.0 0.0 0.0	2.38
10	59.52 0.0 0.0	0.58 57.34 0.0	0.0 -2.17 0.0	0.0 0.0 0.0	2.18
11	65.5 0.0 0.0	0.65 63.57 0.0	0.0 -1.92 0.0	0.0 0.0 0.0	1.93
12	71.48 0.0 0.0	0.72 69.85 0.0	0.0 -1.62 0.0	0.0 0.0 0.0	1.63
13	77.47 0.0 0.0	0.79 76.18 0.0	0.0 -1.28 0.0	0.0 0.0 0.0	1.29
14	83.45 0.0 0.0	0.86 82.55 0.0	0.0 -0.89 0.0	0.0 0.0 0.0	0.9
15	89.43 0.0 0.0	0.93 88.96 0.0	0.0 -0.46 0.0	0.0 0.0 0.0	0.47
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
17	5.69 0.0 0.0	0.0 5.69 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	28.12 0.0 0.0	0.22 25.74 0.0	0.0 -2.37 0.0	0.0 0.0 0.0	2.38
19	50.55 0.0 0.0	0.47 48.1 0.0	0.0 -2.44 0.0	0.0 0.0 0.0	2.45
20	72.98 0.0 0.0	0.73 71.43 0.0	0.0 -1.54 0.0	0.0 0.0 0.0	1.55
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					ΔE* _{CIELAB} = 1.6
Mean lightness difference (5 steps)					ΔL* _{CIELAB} = 1.3
Mean colour reproduction index:					R* _{ab,m} = 93

OE540-3N-121-8: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE541-3N-121-8: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	5.7/0.6	11.7/1.4	17.7/2.4	23.6/4.0	29.6/6.1	35.6/8.8	41.6/12.2	47.6/16.5	53.5/21.5	59.5/27.6	65.5/34.7	71.5/42.9	77.5/52.3	83.4/63.0	89.4/75.1	95.4/88.6
$n^*n^*n^*0$ setcmk $g_N=1.08$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{\text{CIELAB},r}$ (relative)																
w^*_{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.054	0.113	0.176	0.24	0.305	0.371	0.439	0.506	0.576	0.645	0.715	0.786	0.857	0.928	1.0

OE540-7N, Picture A7-121-8: 16 visual equidistant L^* -grey steps; PS operator: $n^*n^*n^*0$ setcmkcolor

OE54: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast $Y_W:Y_N=88,9:0,62$; Y_N range 0,46 to <0,93

input: all ($\rightarrow rgb^*_d$) setrgbcOLOR
output 130-8: $g_P=1.0$; $g_N=1.08$

TUB registration: 20110801-OE54/OE54L0NA.TXT /.PS
TUB material: code=rh4ta
application for output of displays: monitor systems or data projector systems

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1.1, CIELAB


i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start output S1
1	10.99	0.0	0.0	0.0	0.0	0.01
2	16.62	0.0	0.04	-2.13	0.0	2.14
3	22.25	0.0	0.09	-3.36	0.0	3.37
4	27.88	0.0	0.15	-4.16	0.0	4.17
5	33.5	0.0	0.21	-4.67	0.0	4.68
6	39.13	0.0	0.27	-4.95	0.0	4.96
7	44.76	0.0	0.34	-5.03	0.0	5.04
8	50.39	0.0	0.41	-4.95	0.0	4.96
9	56.02	0.0	0.48	-4.72	0.0	4.73
10	61.64	0.0	0.55	-4.36	0.0	4.37
11	67.27	0.0	0.62	-3.88	0.0	3.89
12	72.9	0.0	0.69	-3.29	0.0	3.3
13	78.53	0.0	0.77	-2.6	0.0	2.61
14	84.15	0.0	0.85	-1.81	0.0	1.82
15	89.78	0.0	0.92	-0.94	0.0	0.95
16	95.41	0.0	1.0	0.0	0.0	0.01
17	10.99	0.0	0.0	0.0	0.0	0.01
18	32.1	0.0	0.2	-4.57	0.0	4.58
19	53.2	0.0	0.44	-4.85	0.0	4.86
20	74.31	0.0	0.71	-3.12	0.0	3.13
21	95.41	0.0	1.0	0.0	0.0	0.01

Mean lightness difference (16 steps) $\Delta E^*_{\text{CIELAB}} = 3.2$

Mean lightness difference (5 steps) $\Delta L^*_{\text{CIELAB}} = 2.5$

Mean colour reproduction index: $R^*_{\text{ab,m}} = 86$

OE540-3N-122-8: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE541-3N-122-8: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y^*_{\text{intended}}$ (absolute)	11.0/1.3	16.6/2.2	22.2/3.6	27.9/5.4	33.5/7.8	39.1/10.7	44.8/14.4	50.4/18.7	56.0/23.9	61.6/30.0	67.3/37.0	72.9/45.0	78.5/54.1	84.2/64.4	89.8/75.8	95.4/88.6
$n^* n^* n^* 0$ setcmk $g_N=1.18$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = [L^*_{\text{CIELAB}}]^r$ (relative)	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.042	0.093	0.151	0.211	0.274	0.34	0.408	0.477	0.548	0.621	0.694	0.769	0.845	0.922	1.0

OE540-7N, Picture A7-122-8: 16 visual equidistant L^* -grey steps; PS operator: $n^* n^* n^* 0$ setcmkcolor

OE54: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast $Y_W:Y_N=88,9:1,25$; Y_N range 0,93 to <1,87


input: all ($\rightarrow rgb^*_d$) setrgbcolor
output 130-8: $g_P=1.0$; $g_N=1.17$

TUB registration: 20110801-OE54/OE54L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref			l*out			LAB*out			LAB*out/c-ref			ΔE*	Start output S1
1	18.01	0.0	0.0	0.0	18.01	0.0	0.0	0.0	0.0	0.0	0.0	0.01	Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G	
2	23.17	0.0	0.0	0.03	20.36	0.0	0.0	-2.8	0.0	0.0	2.81			
3	28.33	0.0	0.0	0.07	23.76	0.0	0.0	-4.56	0.0	0.0	4.57			
4	33.49	0.0	0.0	0.13	27.71	0.0	0.0	-5.77	0.0	0.0	5.78			
5	38.65	0.0	0.0	0.18	32.07	0.0	0.0	-6.57	0.0	0.0	6.58			
6	43.81	0.0	0.0	0.24	36.76	0.0	0.0	-7.04	0.0	0.0	7.05			
7	48.97	0.0	0.0	0.31	41.74	0.0	0.0	-7.22	0.0	0.0	7.23			
8	54.13	0.0	0.0	0.37	46.96	0.0	0.0	-7.16	0.0	0.0	7.17			
9	59.29	0.0	0.0	0.44	52.4	0.0	0.0	-6.88	0.0	0.0	6.89			
10	64.45	0.0	0.0	0.52	58.05	0.0	0.0	-6.39	0.0	0.0	6.4			
11	69.61	0.0	0.0	0.59	63.88	0.0	0.0	-5.72	0.0	0.0	5.73			
12	74.77	0.0	0.0	0.67	69.88	0.0	0.0	-4.88	0.0	0.0	4.89			
13	79.93	0.0	0.0	0.75	76.05	0.0	0.0	-3.87	0.0	0.0	3.88			
14	85.09	0.0	0.0	0.83	82.36	0.0	0.0	-2.72	0.0	0.0	2.73			
15	90.25	0.0	0.0	0.91	88.82	0.0	0.0	-1.42	0.0	0.0	1.43	Mean lightness difference (16 steps)		
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.01	ΔE*CIELAB = 4.6		
17	18.01	0.0	0.0	0.0	18.01	0.0	0.0	0.0	0.0	0.0	0.01	Mean lightness difference (5 steps)		
18	37.36	0.0	0.0	0.17	30.95	0.0	0.0	-6.4	0.0	0.0	6.41			
19	56.71	0.0	0.0	0.41	49.66	0.0	0.0	-7.04	0.0	0.0	7.05			
20	76.06	0.0	0.0	0.69	71.41	0.0	0.0	-4.64	0.0	0.0	4.65			
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.01		ΔL*CIELAB = 3.6	
Mean colour reproduction index:													R* _{ab,m} = 80	

OE540-3N-123-8: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE541-3N-123-8: File: Measure unknown; Device: Device unknown; Date: Date unknown

L*/Y _{intended} (absolute)	18.0/2.5	23.2/3.8	28.3/5.6	33.5/7.8	38.6/10.5	43.8/13.7	49.0/17.6	54.1/22.1	59.3/27.3	64.4/33.4	69.6/40.2	74.8/47.9	79.9/56.6	85.1/66.2	90.2/76.8	95.4/88.6
n*n*n*0 setcmk g _N =1.29																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
w*=l* CIELAB, r (relative)																
w* _{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w* _{out}	0,0	0,031	0,074	0,125	0,182	0,242	0,307	0,374	0,444	0,517	0,593	0,67	0,75	0,832	0,914	1,0

OE540-7N, Picture A7-123-8: 16 visual equidistant L*-grey steps; PS operator: n*n*n*0 setcmkcolor

OE54: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast Y_W:Y_N=88,9:2,5; Y_N range 1,87 to <3,75


input: all (->rgb*_d) setrgbcolor
output 130-8: g_P=1.0; g_N=1.29

TUB registration: 20110801-OE54/OE54L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1.1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start output S1
1	26.85	0.0	0.0	26.85	0.0	0.0
2	31.42	0.0	0.02	28.28	0.0	-3.13
3	35.99	0.0	0.06	30.7	0.0	-5.28
4	40.56	0.0	0.1	33.73	0.0	-6.82
5	45.13	0.0	0.15	37.22	0.0	-7.9
6	49.7	0.0	0.21	41.12	0.0	-8.57
7	54.27	0.0	0.27	45.37	0.0	-8.9
8	58.84	0.0	0.34	49.93	0.0	-8.91
9	63.41	0.0	0.41	54.78	0.0	-8.63
10	67.99	0.0	0.48	59.9	0.0	-8.08
11	72.56	0.0	0.56	65.27	0.0	-7.28
12	77.13	0.0	0.64	70.87	0.0	-6.25
13	81.7	0.0	0.73	76.7	0.0	-4.99
14	86.27	0.0	0.82	82.73	0.0	-3.52
15	90.84	0.0	0.91	88.97	0.0	-1.85
16	95.41	0.0	1.0	95.41	0.0	0.0
17	26.85	0.0	0.0	26.85	0.0	0.0
18	43.99	0.0	0.14	36.31	0.0	-7.67
19	61.13	0.0	0.37	52.32	0.0	-8.8
20	78.27	0.0	0.66	72.31	0.0	-5.95
21	95.41	0.0	1.0	95.41	0.0	0.0
Mean lightness difference (16 steps)					ΔE*CIELAB = 5.6	
Mean lightness difference (5 steps)					ΔE*CIELAB = 4.5	
Mean colour reproduction index:					R* _{ab,m} = 75	

OE540-3N-124-8: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE541-3N-124-8: File: Measure unknown; Device: Device unknown; Date: Date unknown

L*/Y _{intended} (absolute)	26.8/5.0	31.4/6.8	36.0/9.0	40.6/11.6	45.1/14.6	49.7/18.2	54.3/22.2	58.8/26.9	63.4/32.1	68.0/38.0	72.6/44.5	77.1/51.7	81.7/59.7	86.3/68.5	90.8/78.1	95.4/88.6
n*n*n*0 setcmk g _N =1.43																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
w*=l* CIELAB, r (relative)																
w* _{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w* _{out}	0.0	0.021	0.056	0.1	0.152	0.208	0.27	0.337	0.407	0.482	0.561	0.642	0.727	0.816	0.906	1.0

OE540-7N, Picture A7-124-8: 16 visual equidistant L*-grey steps; PS operator: n*n*n*0 setcmkcolor

OE54: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast Y_W:Y_N=88,9:5; Y_N range 3,75 to <7,5

input: all (->rgb*d) setrgbcOLOR
output 130-8: g_P=1.0; g_N=1.42

TUB registration: 20110801-OE54/OE54L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1.1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*			
1	37.99	0.0	0.0	37.99	0.0	0.0	0.0	0.01
2	41.81	0.0	0.0	0.01	38.74	0.0	0.0	3.07
3	45.64	0.0	0.0	0.04	40.27	0.0	0.0	5.37
4	49.47	0.0	0.0	0.08	42.36	0.0	0.0	7.11
5	53.3	0.0	0.0	0.12	44.91	0.0	0.0	8.38
6	57.13	0.0	0.0	0.17	47.89	0.0	0.0	9.24
7	60.96	0.0	0.0	0.23	51.24	0.0	0.0	9.71
8	64.78	0.0	0.0	0.3	54.95	0.0	0.0	9.83
9	68.61	0.0	0.0	0.37	58.99	0.0	0.0	9.62
10	72.44	0.0	0.0	0.44	63.34	0.0	0.0	9.1
11	76.27	0.0	0.0	0.52	68.0	0.0	0.0	8.27
12	80.1	0.0	0.0	0.61	72.95	0.0	0.0	7.15
13	83.93	0.0	0.0	0.7	78.17	0.0	0.0	5.76
14	87.75	0.0	0.0	0.8	83.66	0.0	0.0	4.09
15	91.58	0.0	0.0	0.9	89.41	0.0	0.0	2.17
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.01
17	37.99	0.0	0.0	0.0	37.99	0.0	0.0	0.01
18	52.34	0.0	0.0	0.11	44.23	0.0	0.0	8.11
19	66.7	0.0	0.0	0.33	56.93	0.0	0.0	9.77
20	81.05	0.0	0.0	0.63	74.23	0.0	0.0	6.83
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.01
Mean colour reproduction index:								R* _{ab,m} = 73

Start output S1

Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G


Mean lightness difference (16 steps)

ΔE*_{CIELAB} = 6.2

Mean lightness difference (5 steps)

ΔL*_{CIELAB} = 4.9

OE540-3N-125-8: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE541-3N-125-8: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	38.0/10.1	41.8/12.4	45.6/15.0	49.5/18.0	53.3/21.3	57.1/25.1	61.0/29.2	64.8/33.8	68.6/38.8	72.4/44.3	76.3/50.3	80.1/56.9	83.9/63.9	87.8/71.6	91.6/79.8	95.4/88.6
$n^*n^*n^*0$ setcmk $g_N=1.6$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{\text{CIELAB},r}$ (relative)																
w^*_{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0.0	0.013	0.04	0.076	0.121	0.172	0.231	0.296	0.365	0.442	0.523	0.608	0.7	0.796	0.895	1.0

OE540-7N, Picture A7-125-8: 16 visual equidistant L^* -grey steps; PS operator: $n^*n^*n^*0$ setcmkcolor

OE54: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast $Y_W:Y_N=88,9:10$; Y_N range 7,5 to <15


input: all ($\rightarrow \text{rgb}^*_d$) setrgbcolor
output 130-8: $g_P=1.0$; $g_N=1.6$

TUB registration: 20110801-OE54/OE54L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start output S1
1	52.02 0.0 0.0	0.0 0.0 0.0	52.02 0.0 0.0	0.0 0.0 0.0	0.01	Specification according to
2	54.91 0.0 0.0	0.01 52.33 0.0	0.0 -2.57 0.0	0.0 0.0 0.0	2.58	ISO/IEC 15775 Annex G
3	57.8 0.0 0.0	0.03 53.13 0.0	0.0 -4.66 0.0	0.0 0.0 0.0	4.67	and DIN 33866-1 Annex G
4	60.7 0.0 0.0	0.05 54.34 0.0	0.0 -6.34 0.0	0.0 0.0 0.0	6.35	
5	63.59 0.0 0.0	0.09 55.94 0.0	0.0 -7.64 0.0	0.0 0.0 0.0	7.65	
6	66.48 0.0 0.0	0.14 57.9 0.0	0.0 -8.57 0.0	0.0 0.0 0.0	8.58	
7	69.37 0.0 0.0	0.19 60.22 0.0	0.0 -9.15 0.0	0.0 0.0 0.0	9.16	
8	72.27 0.0 0.0	0.25 62.87 0.0	0.0 -9.39 0.0	0.0 0.0 0.0	9.4	
9	75.16 0.0 0.0	0.32 65.85 0.0	0.0 -9.3 0.0	0.0 0.0 0.0	9.31	
10	78.05 0.0 0.0	0.4 69.16 0.0	0.0 -8.88 0.0	0.0 0.0 0.0	8.89	
11	80.95 0.0 0.0	0.48 72.78 0.0	0.0 -8.16 0.0	0.0 0.0 0.0	8.17	
12	83.84 0.0 0.0	0.57 76.71 0.0	0.0 -7.12 0.0	0.0 0.0 0.0	7.13	
13	86.73 0.0 0.0	0.67 80.94 0.0	0.0 -5.78 0.0	0.0 0.0 0.0	5.79	
14	89.62 0.0 0.0	0.77 85.47 0.0	0.0 -4.15 0.0	0.0 0.0 0.0	4.16	
15	92.52 0.0 0.0	0.88 90.29 0.0	0.0 -2.21 0.0	0.0 0.0 0.0	2.22	Mean lightness difference (16 steps)
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	ΔE*CIELAB = 5.9
17	52.02 0.0 0.0	0.0 0.0 0.0	52.02 0.0 0.0	0.0 0.0 0.0	0.01	
18	62.87 0.0 0.0	0.08 55.51 0.0	0.0 -7.35 0.0	0.0 0.0 0.0	7.36	
19	73.71 0.0 0.0	0.28 64.32 0.0	0.0 -9.38 0.0	0.0 0.0 0.0	9.39	
20	84.56 0.0 0.0	0.59 77.74 0.0	0.0 -6.82 0.0	0.0 0.0 0.0	6.83	Mean lightness difference (5 steps)
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	ΔL*CIELAB = 4.7
Mean colour reproduction index:					R* _{ab,m} = 74	

OE540-3N-126-8: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE541-3N-126-8: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	52.0/20.2	54.9/22.8	57.8/25.8	60.7/28.9	63.6/32.3	66.5/36.0	69.4/39.9	72.3/44.1	75.2/48.5	78.1/53.3	80.9/58.4	83.8/63.8	86.7/69.5	89.6/75.5	92.5/81.9	95.4/88.6
$n^* n^* n^* 0$ setcmk $g_N=1.82$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{\text{CIELAB},r}$ (relative)																
w^*_{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0,0	0,007	0,026	0,054	0,091	0,135	0,189	0,25	0,319	0,395	0,479	0,569	0,666	0,771	0,882	1,0

OE540-7N, Picture A7-126-8: 16 visual equidistant L^* -grey steps; PS operator: $n^* n^* n^* 0$ setcmkcolor

OE54: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast $Y_W:Y_N=88,9:20$; Y_N range 15 to <30

input: all ($\rightarrow rgb^*_d$) setrgbcolor
output 130-8: $g_P=1.0$; $g_N=1.81$

TUB registration: 20110801-OE54/OE54L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start output S1
1	69.7	0.0	0.0	0.0	0.0	0.01
2	71.41	0.0	0.0	0.0	0.0	1.63
3	73.13	0.0	0.0	0.0	0.0	3.06
4	74.84	0.0	0.0	0.0	0.0	4.27
5	76.55	0.0	0.0	0.0	0.0	5.27
6	78.27	0.0	0.0	0.0	0.0	6.03
7	79.98	0.0	0.0	0.0	0.0	6.55
8	81.7	0.0	0.0	0.0	0.0	6.83
9	83.41	0.0	0.0	0.0	0.0	6.87
10	85.12	0.0	0.0	0.0	0.0	6.66
11	86.84	0.0	0.0	0.0	0.0	6.19
12	88.55	0.0	0.0	0.0	0.0	5.47
13	90.27	0.0	0.0	0.0	0.0	4.5
14	91.98	0.0	0.0	0.0	0.0	3.26
15	93.7	0.0	0.0	0.0	0.0	1.76
16	95.41	0.0	0.0	0.0	0.0	0.01
17	69.7	0.0	0.0	0.0	0.0	0.01
18	76.13	0.0	0.0	0.0	0.0	5.04
19	82.55	0.0	0.0	0.0	0.0	6.88
20	88.98	0.0	0.0	0.0	0.0	5.25
21	95.41	0.0	0.0	0.0	0.0	0.01


Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G

Mean lightness difference (16 steps) $\Delta E^*_{CIELAB} = 4.3$

Mean lightness difference (5 steps) $\Delta L^*_{CIELAB} = 3.4$

Mean colour reproduction index: $R^*_{ab,m} = 81$

OE540-3N-127-8: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE541-3N-127-8: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y^*_{intended}$ (absolute)	69.7/40.3	71.4/42.8	73.1/45.4	74.8/48.0	76.6/50.8	78.3/53.7	80.0/56.6	81.7/59.7	83.4/62.9	85.1/66.3	86.8/69.7	88.6/73.2	90.3/76.9	92.0/80.7	93.7/84.6	95.4/88.6
$n^* n^* n^* 0$ setcmk $g_N=2.11$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = l^*_{CIELAB, r}$ (relative)																
$w^*_{intended}$	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.003	0.014	0.034	0.062	0.099	0.145	0.201	0.266	0.341	0.426	0.52	0.625	0.74	0.864	1.0

OE540-7N, Picture A7-127-8: 16 visual equidistant L^* -grey steps; PS operator: $n^* n^* n^* 0$ setcmkcolor

OE54: In-output relation according to ISO 9241-306; 1MR, DH
Viewing Y contrast $Y_W:Y_N=88,9:40$; Y_N range 30 to <60

input: all ($\rightarrow rgb^*_d$) setrgbcolor
output 130-8: $g_P=1.0$; $g_N=2.1$

TUB registration: 20110801-OE54/OE54L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta