

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-000-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-000-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-000-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-010-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-010-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-010-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-020-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-020-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-020-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-030-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-030-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-030-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-001-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-001-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-001-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-011-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-011-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-011-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-021-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-021-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-021-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-031-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-031-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-031-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-002-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-002-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-002-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-012-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-012-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-012-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-022-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-022-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-022-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-032-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-032-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-032-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-003-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-003-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-003-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-013-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-013-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-013-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-023-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-023-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-023-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-033-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-033-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-033-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-004-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-004-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-004-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-014-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-014-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-014-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-024-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-024-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-024-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-034-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-034-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-034-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-005-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-005-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-005-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment
The assessor has **normal** colour vision according to one test:
either according to DIN 6160:1996 with Anomaloskop of *Nagel*
or with test charts using colour points according to *Ishihara*
or tested with, please specify:
underline Yes/No
underline Yes/unknown
underline Yes/unknown
underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output
Office workplace illumination is daylight (clouded/north sky) **underline Yes/No**
PDF file: <http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF> **underline Yes/No**
PS file: <http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS> **underline Yes/No**
Picture A7-015-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)
compare standard print output according to ISO/IEC 15775 with range F:0 **underline range**
Remark: In daylighted offices the contrast range is in many cases:
on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)

Only for optional colorimetric specification with PDF/PS file output
PDF-File: <http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF>
picture A7-015-2 **underline Yes/No**
PS-File: <http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS>
picture A7-015-2 **or underline Yes/No**

colour measurement and specification for:
CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: **underline Yes/No**
If No, please give other parameters:

Colorimetric specification with PS file for colours in the columns A to T
Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF **underline Yes/No**
If No, please describe other method:

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-025-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-025-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-025-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-035-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-035-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-035-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-006-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-006-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-006-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-016-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-016-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-016-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-026-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-026-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-026-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment
The assessor has **normal** colour vision according to one test:
either according to DIN 6160:1996 with Anomaloskop of *Nagel*
or with test charts using colour points according to *Ishihara*
or tested with, please specify:
underline Yes/No
underline Yes/unknown
underline Yes/unknown
underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output
Office workplace illumination is daylight (clouded/north sky) **underline Yes/No**
PDF file: <http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF> **underline Yes/No**
PS file: <http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS> **underline Yes/No**
Picture A7-036-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)
compare standard print output according to ISO/IEC 15775 with range F:0 **underline range**
Remark: In daylighted offices the contrast range is in many cases:
on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)

Only for optional colorimetric specification with PDF/PS file output
PDF-File: <http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF>
picture A7-036-2 **underline Yes/No**
PS-File: <http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS>
picture A7-036-2 **or underline Yes/No**

colour measurement and specification for:
CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: **underline Yes/No**
If No, please give other parameters:

Colorimetric specification with PS file for colours in the columns A to T
Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF **underline Yes/No**
If No, please describe other method:

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-007-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases:</i>	
<i>on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-007-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-007-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-017-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-017-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-017-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of Nagel	underline Yes/unknown
or with test charts using colour points according to Ishihara	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-027-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-027-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-027-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	underline Yes/No
Picture A7-037-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF	
picture A7-037-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS	
picture A7-037-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

