Test for the best visual linearized output of Picture A7-010-0 **Yes/No**
Output test with the computer display ( ) or the external display ( )
Test of the radial grating according to picture A1-010-0

N−W-radial grating:	Is the resolution diameter < 6 mm?	**Yes/No**
	Test with magnifying glass (e.g. 6x) resolution diameter	**..... mm**
W−N-radial grating:	Is the resolution diameter < 6 mm?	**Yes/No**
	Test with magnifying glass (e.g. 6x) resolution diameter	**..... mm**
N−Z-radial grating:	Is the resolution diameter < 6 mm?	**Yes/No**
	Test with magnifying glass (e.g. 6x) resolution diameter	**..... mm**
W−Z-radial grating:	Is the resolution diameter < 6 mm?	**Yes/No**
	Test with magnifying glass (e.g. 6x) resolution diameter	**..... mm**

Test of 5 visual equidistant *L-grey steps according to picture A2**-010-0
Are the 5 steps on the upper rows distinguishable? **Yes/No**
If No: How many steps can be distinguished?
of the given 5 steps: **..... Steps**
Test of 16 visual equidistant *L-grey steps according to picture A3**-010-0
Are the 16 steps on the upper rows distinguishable? **Yes/No**
If No: How many steps can be distinguished?
of the given 16 steps: **.... Steps**

Part 1 OE640−3N-010-4

Test for the best visual linearized output of Picture A7-010-0 **Yes/No**
Output test with the computer display ( ) or the external display ( )

Test of the *Landolt*-rings *N−W* according to picture A4-010-0
N−W-radial grating:
Is the recognition frequency of the *Landolt*-rings > 50% (5 of 8 at least)?

background − ring	
0 − 1	**Yes/No**
7 − 8	**Yes/No**
E − F	**Yes/No**
2 − 0	**Yes/No**
8 − 6	**Yes/No**
F − D	**Yes/No**

Test of the radial grating under 45° according to picture A5-010-0
Can equally spaced lines be seen?
Visual testing: for radial diameter from 15 to 60 lpi **Yes/No**
Test with a magnifying glass (e.g. 6x): − from 15 lpi: **to ..... lpi**

Test of the radial grating under 90° according to picture A6-010-0
Can equally spaced lines be seen?
Visual testing: for radial diameter from 15 to 60 lpi **Yes/No**
Test with a magnifying glass (e.g. 6x): − from 15 lpi: **to ..... lpi**

Part 2 OE641−3N-010-4

Documentation of file format, hardware and software for this test:

PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64L5NP.PDF **underline Yes/No**

PS-File: http://130.149.60.45/farbmetrik/OE64/OE64L5NA.PS **or underline Yes/No**

Used computer operating system:
either one of Windows/Mac/Unix/other and version:.....

This evaluation is for the device output: **underline monitor/data projector/printer**
Device model, driver and version:.....

Device output with PDF/PS-file: **underline PDF/PS-file**
For device output with PDF-file OE64L5NP.PDF:
either PDF-file transfer "download, copy" to PDF device.....
or with computer system interpretation by "Display-PDF":.....
or with software. e. g. Adobe-Reader/-Acrobat and version:.....
or with software e. g. Ghostscript and version:.....
For device output with PS-file OE64L5NA.PS:
either PS-file transfer "download, copy" to PS device.....
or with computer system interpretation by "Display-PS":.....
or with software e. g. Ghostscript and version:.....
or with software e. g. Mac-Yap and version:.....

Special remarks:Special remarks, e. g. output of Landscape (L)
.....
.....
.....

Part 3 OE640−7N-010-4

Documentation of assessor colour vision properties for visual assessment
The assessor has **normal** colour vision according to one test: **underline Yes/No**
either according to DIN 6160:1996 with Anomaloskop of *Nagel* **underline Yes/unknown**
or with test charts using colour points according to *Ishihara* **underline Yes/unknown**
or tested with, please specify: ..... **underline Yes/unknown**

For visual evaluation of the display (monitor, data projector) output
Office workplace illumination is daylight (clouded/north sky) **underline Yes/No**
PDF file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF **underline Yes/No**
PS file: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS **underline Yes/No**
Picture A7-010-2: **contrast range:** (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)
compare standard print output according to ISO/IEC 15775 with range F:0 **underline range**
Remark: In daylighted offices the contrast range is in many cases:
on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)

Only for optional colorimetric specification with PDF/PS file output
PDF-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF
picture A7-010-2 **underline Yes/No**
PS-File: http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS
picture A7-010-2 **or underline Yes/No**
colour measurement and specification for:
CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: **underline Yes/No**
If No, please give other parameters: .....
Colorimetric specification with PS file for colours in the columns A to T
Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF **underline Yes/No**
If No, please describe other method: .....

Part 4 OE641−7N-010-4