

Test for the best visual linearized output of Picture A7-020-0		Yes/No
Output test with the computer display () or the external display ()		
Test of the radial grating according to picture A1-020-0		
N-W-radial grating:	Is the resolution diameter < 6 mm?	Yes/No
	Test with magnifying glass (e.g. 6x) resolution diameter mm
W-N-radial grating:	Is the resolution diameter < 6 mm?	Yes/No
	Test with magnifying glass (e.g. 6x) resolution diameter mm
N-Z-radial grating:	Is the resolution diameter < 6 mm?	Yes/No
	Test with magnifying glass (e.g. 6x) resolution diameter mm
W-Z-radial grating:	Is the resolution diameter < 6 mm?	Yes/No
	Test with magnifying glass (e.g. 6x) resolution diameter mm
Test of 5 visual equidistant L*-grey steps according to picture A2-020-0		
Are the 5 steps on the upper rows distinguishable?		Yes/No
If No: How many steps can be distinguished?	 Steps
Test of 16 visual equidistant L*-grey steps according to picture A3-020-0		
Are the 16 steps on the upper rows distinguishable?		Yes/No
If No: How many steps can be distinguished?	 Steps

Part 1 OE640-3N-020-7

Documentation of file format, hardware and software for this test:

PDF-File: <http://130.149.60.45/farbmetrik/OE64/OE64L8NP.PDF> Yes/No

PS-File: <http://130.149.60.45/farbmetrik/OE64/OE64L8NA.PS> or underline Yes/No

Used computer operating system:
either one of Windows/Mac/Unix/other and version:.....

This evaluation is for the device output: monitor/data projector/printer
Device model, driver and version:.....

Device output with PDF/PS-file: PDF/PS-file

For device output with PDF-file OE64L8NP.PDF:
either PDF-file transfer "download, copy" to PDF device.....
or with computer system interpretation by "Display-PDF":.....
or with software e. g. Adobe-Reader/-Acrobat and version:.....
or with software e. g. Ghostscript and version:.....

For device output with PS-file OE64L8NA.PS:
either PS-file transfer "download, copy" to PS device.....
or with computer system interpretation by "Display-PS":.....
or with software e. g. Ghostscript and version:.....
or with software e. g. Mac-Yap and version:.....

Special remarks:Special remarks, e. g. output of Landscape (L)
.....
.....
.....

Part 3 OE640-7N-020-7

OE64: Form A for test chart according to ISO 9241-306; DH
Viewing Y contrast $Y_W:Y_N=88,9:0,31$; Y_N range 0,0 to <0,46

Test for the best visual linearized output of Picture A7-020-0		Yes/No
Output test with the computer display () or the external display ()		
Test of the Landolt-rings N-W according to picture A4-020-0		
N-W-radial grating:		
Is the recognition frequency of the Landolt-rings > 50% (5 of 8 at least)?		
	background - ring	Yes/No
	0 - 1	Yes/No
	7 - 8	Yes/No
	E - F	Yes/No
	2 - 0	Yes/No
	8 - 6	Yes/No
	F - D	Yes/No
Test of the radial grating under 45° according to picture A5-020-0		
Can equally spaced lines be seen?		
Visual testing: for radial diameter from 15 to 60 lpi		Yes/No
Test with a magnifying glass (e.g. 6x): - from 15 lpi:		to lpi
Test of the radial grating under 90° according to picture A6-020-0		
Can equally spaced lines be seen?		
Visual testing: for radial diameter from 15 to 60 lpi		Yes/No
Test with a magnifying glass (e.g. 6x): - from 15 lpi:		to lpi

Part 2 OE641-3N-020-7

Documentation of assessor colour vision properties for visual assessment

The assessor has **normal** colour vision according to one test:
either according to DIN 6160:1996 with Anomaloskop of Nagel Yes/No
or with test charts using colour points according to Ishihara Yes/unknown
or tested with, please specify: Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky) Yes/No

PDF file: <http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF> Yes/No

PS file: <http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS> Yes/No

Picture A7-020-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)
compare standard print output according to ISO/IEC 15775 with range F:0 underline range

*Remark: In daylighted offices the contrast range is in many cases:
on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)*

Only for optional colorimetric specification with PDF/PS file output

PDF-File: <http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PDF> Yes/No

PS-File: <http://130.149.60.45/farbmetrik/OE64/OE64F1P2.PS> Yes/No

colour measurement and specification for:
CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: Yes/No
If No, please give other parameters:

Colorimetric specification with PS file for colours in the columns A to T
Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF Yes/No
If No, please describe other method:

Part 4

input: all (->rgb*_d) setrgbcolor
output 030-7: no change

OE641-7N-020-7