

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS	underline Yes/No
Picture A7-100-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF	
picture A7-100-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS	
picture A7-100-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment
The assessor has **normal** colour vision according to one test:
either according to DIN 6160:1996 with Anomaloskop of Nagel
or with test charts using colour points according to Ishihara
or tested with, please specify:
underline Yes/No
underline Yes/unknown
underline Yes/unknown
underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output
Office workplace illumination is daylight (clouded/north sky) **underline Yes/No**
PDF file: <http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF> **underline Yes/No**
PS file: <http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS> **underline Yes/No**
Picture A7-101-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)
compare standard print output according to ISO/IEC 15775 with range F:0 **underline range**
*Remark: In daylighted offices the contrast range is in many cases:
on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)*

Only for optional colorimetric specification with PDF/PS file output
PDF-File: <http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF>
picture A7-101-2 **underline Yes/No**
PS-File: <http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS>
picture A7-101-2 **or underline Yes/No**

colour measurement and specification for:
CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: **underline Yes/No**
If No, please give other parameters:

Colorimetric specification with PS file for colours in the columns A to T
Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF **underline Yes/No**
If No, please describe other method:

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS	underline Yes/No
Picture A7-102-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF	
picture A7-102-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS	
picture A7-102-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS	underline Yes/No
Picture A7-103-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF	
picture A7-103-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS	
picture A7-103-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS	underline Yes/No
Picture A7-104-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF	
picture A7-104-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS	
picture A7-104-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment
The assessor has **normal** colour vision according to one test:
either according to DIN 6160:1996 with Anomaloskop of Nagel
or with test charts using colour points according to Ishihara
or tested with, please specify:
underline Yes/No
underline Yes/unknown
underline Yes/unknown
underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output
Office workplace illumination is daylight (clouded/north sky) **underline Yes/No**
PDF file: <http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF> **underline Yes/No**
PS file: <http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS> **underline Yes/No**
Picture A7-105-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)
compare standard print output according to ISO/IEC 15775 with range F:0 **underline range**
*Remark: In daylighted offices the contrast range is in many cases:
on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)*

Only for optional colorimetric specification with PDF/PS file output
PDF-File: <http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF>
picture A7-105-2 **underline Yes/No**
PS-File: <http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS>
picture A7-105-2 **or underline Yes/No**

colour measurement and specification for:
CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: **underline Yes/No**
If No, please give other parameters:

Colorimetric specification with PS file for colours in the columns A to T
Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF **underline Yes/No**
If No, please describe other method:

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF file: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF	underline Yes/No
PS file: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS	underline Yes/No
Picture A7-106-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
compare standard print output according to ISO/IEC 15775 with range F:0	underline range
<i>Remark: In daylighted offices the contrast range is in many cases: on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF	
picture A7-106-2	underline Yes/No
PS-File: http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS	
picture A7-106-2	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer	
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF	underline Yes/No
If No, please describe other method:	

Documentation of assessor colour vision properties for visual assessment
The assessor has **normal** colour vision according to one test:
either according to DIN 6160:1996 with Anomaloskop of *Nagel*
or with test charts using colour points according to *Ishihara*
or tested with, please specify:
underline Yes/No
underline Yes/unknown
underline Yes/unknown
underline Yes/unknown

For visual evaluation of the display (monitor, data projector) output
Office workplace illumination is daylight (clouded/north sky) **underline Yes/No**
PDF file: <http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF> **underline Yes/No**
PS file: <http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS> **underline Yes/No**
Picture A7-107-2: contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)
compare standard print output according to ISO/IEC 15775 with range F:0 **underline range**
Remark: In daylighted offices the contrast range is in many cases:
on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)

Only for optional colorimetric specification with PDF/PS file output
PDF-File: <http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PDF>
picture A7-107-2 **underline Yes/No**
PS-File: <http://130.149.60.45/farbmetrik/OE67/OE67F1P2.PS>
picture A7-107-2 **or underline Yes/No**

colour measurement and specification for:
CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: **underline Yes/No**
If No, please give other parameters:

Colorimetric specification with PS file for colours in the columns A to T
Exchange of CIELAB data in file www.ps.bam.de/De17/10L/L17e00NP.PS and transfer
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF **underline Yes/No**
If No, please describe other method:

