





















**Documentation of assessor colour vision properties for visual assessment**

|                                                                      |                              |
|----------------------------------------------------------------------|------------------------------|
| The assessor has <b>normal</b> colour vision according to one test:  | <b>underline</b> Yes/No      |
| either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>   | <b>underline</b> Yes/unknown |
| or with test charts using colour points according to <i>Ishihara</i> | <b>underline</b> Yes/unknown |
| or tested with, please specify: .....                                | <b>underline</b> Yes/unknown |

**For visual evaluation of the display (monitor, data projector) output**

|                                                                                                                                                           |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Office workplace illumination is daylight (clouded/north sky)                                                                                             | <b>underline</b> Yes/No |
| <b>PDF file:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF</a>                        | <b>underline</b> Yes/No |
| <b>PS file:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS</a>                           | <b>underline</b> Yes/No |
| <b>Picture A7-030-2: contrast range:</b> (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)                                              |                         |
| compare standard print output according to ISO/IEC 15775 with range F:0                                                                                   | <b>underline</b> range  |
| <i>Remark: In daylighted offices the contrast range is in many cases:<br/>on display between: &gt;F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i> |                         |

**Only for optional colorimetric specification with PDF/PS file output**

|                                                                                                                                    |                            |
|------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| <b>PDF-File:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF</a> |                            |
| <b>picture A7-030-2</b>                                                                                                            | <b>underline</b> Yes/No    |
| <b>PS-File:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS</a>    |                            |
| <b>picture A7-030-2</b>                                                                                                            | <b>or underline</b> Yes/No |

**colour measurement and specification for:**

|                                                                    |                         |
|--------------------------------------------------------------------|-------------------------|
| CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: | <b>underline</b> Yes/No |
| If No, please give other parameters: .....                         |                         |

**Colorimetric specification with PS file for colours in the columns A to T**

|                                                                                                                                         |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Exchange of CIELAB data in file <a href="http://www.ps.bam.de/De17/10L/L17e00NP.PS">www.ps.bam.de/De17/10L/L17e00NP.PS</a> and transfer |                         |
| of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF                                                                                     | <b>underline</b> Yes/No |
| If No, please describe other method: .....                                                                                              |                         |























**Documentation of assessor colour vision properties for visual assessment**

|                                                                      |                              |
|----------------------------------------------------------------------|------------------------------|
| The assessor has <b>normal</b> colour vision according to one test:  | <b>underline</b> Yes/No      |
| either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>   | <b>underline</b> Yes/unknown |
| or with test charts using colour points according to <i>Ishihara</i> | <b>underline</b> Yes/unknown |
| or tested with, please specify: .....                                | <b>underline</b> Yes/unknown |

**For visual evaluation of the display (monitor, data projector) output**

|                                                                                                                                                           |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Office workplace illumination is daylight (clouded/north sky)                                                                                             | <b>underline</b> Yes/No |
| <b>PDF file:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF</a>                        | <b>underline</b> Yes/No |
| <b>PS file:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS</a>                           | <b>underline</b> Yes/No |
| <b>Picture A7-031-2: contrast range:</b> (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)                                              |                         |
| compare standard print output according to ISO/IEC 15775 with range F:0                                                                                   | <b>underline</b> range  |
| <i>Remark: In daylighted offices the contrast range is in many cases:<br/>on display between: &gt;F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i> |                         |

**Only for optional colorimetric specification with PDF/PS file output**

|                                                                                                                                    |                            |
|------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| <b>PDF-File:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF</a> |                            |
| <b>picture A7-031-2</b>                                                                                                            | <b>underline</b> Yes/No    |
| <b>PS-File:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS</a>    |                            |
| <b>picture A7-031-2</b>                                                                                                            | <b>or underline</b> Yes/No |

**colour measurement and specification for:**

|                                                                    |                         |
|--------------------------------------------------------------------|-------------------------|
| CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: | <b>underline</b> Yes/No |
| If No, please give other parameters: .....                         |                         |

**Colorimetric specification with PS file for colours in the columns A to T**

|                                                                                                                                         |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Exchange of CIELAB data in file <a href="http://www.ps.bam.de/De17/10L/L17e00NP.PS">www.ps.bam.de/De17/10L/L17e00NP.PS</a> and transfer |                         |
| of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF                                                                                     | <b>underline</b> Yes/No |
| If No, please describe other method: .....                                                                                              |                         |























**Documentation of assessor colour vision properties for visual assessment**  
The assessor has **normal** colour vision according to one test:  
either according to DIN 6160:1996 with Anomaloskop of Nagel  
or with test charts using colour points according to Ishihara  
or tested with, please specify: .....  
**underline Yes/No**  
**underline Yes/unknown**  
**underline Yes/unknown**  
**underline Yes/unknown**

**For visual evaluation of the display (monitor, data projector) output**  
Office workplace illumination is daylight (clouded/north sky) **underline Yes/No**  
**PDF file:** <http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF> **underline Yes/No**  
**PS file:** <http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS> **underline Yes/No**  
**Picture A7-032-2: contrast range:** (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)  
compare standard print output according to ISO/IEC 15775 with range F:0 **underline range**  
*Remark: In daylighted offices the contrast range is in many cases:  
on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)*

**Only for optional colorimetric specification with PDF/PS file output**  
**PDF-File:** <http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF>  
**picture A7-032-2** **underline Yes/No**  
**PS-File:** <http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS>  
**picture A7-032-2** **or underline Yes/No**

**colour measurement and specification for:**  
CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: **underline Yes/No**  
If No, please give other parameters: .....

**Colorimetric specification with PS file for colours in the columns A to T**  
Exchange of CIELAB data in file [www.ps.bam.de/De17/10L/L17e00NP.PS](http://www.ps.bam.de/De17/10L/L17e00NP.PS) and transfer  
of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF **underline Yes/No**  
If No, please describe other method: .....























**Documentation of assessor colour vision properties for visual assessment**

|                                                                     |                              |
|---------------------------------------------------------------------|------------------------------|
| The assessor has <b>normal</b> colour vision according to one test: | <b>underline</b> Yes/No      |
| either according to DIN 6160:1996 with Anomaloskop of Nagel         | <b>underline</b> Yes/unknown |
| or with test charts using colour points according to Ishihara       | <b>underline</b> Yes/unknown |
| or tested with, please specify: .....                               | <b>underline</b> Yes/unknown |

**For visual evaluation of the display (monitor, data projector) output**

|                                                                                                                                                           |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Office workplace illumination is daylight (clouded/north sky)                                                                                             | <b>underline</b> Yes/No |
| <b>PDF file:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF</a>                        | <b>underline</b> Yes/No |
| <b>PS file:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS</a>                           | <b>underline</b> Yes/No |
| <b>Picture A7-033-2: contrast range:</b> (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)                                              |                         |
| compare standard print output according to ISO/IEC 15775 with range F:0                                                                                   | <b>underline</b> range  |
| <i>Remark: In daylighted offices the contrast range is in many cases:<br/>on display between: &gt;F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i> |                         |

**Only for optional colorimetric specification with PDF/PS file output**

|                                                                                                                                    |                            |
|------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| <b>PDF-File:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF</a> |                            |
| <b>picture A7-033-2</b>                                                                                                            | <b>underline</b> Yes/No    |
| <b>PS-File:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS</a>    |                            |
| <b>picture A7-033-2</b>                                                                                                            | <b>or underline</b> Yes/No |

**colour measurement and specification for:**

|                                                                    |                         |
|--------------------------------------------------------------------|-------------------------|
| CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: | <b>underline</b> Yes/No |
| If No, please give other parameters: .....                         |                         |

**Colorimetric specification with PS file for colours in the columns A to T**

|                                                                                                                                         |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Exchange of CIELAB data in file <a href="http://www.ps.bam.de/De17/10L/L17e00NP.PS">www.ps.bam.de/De17/10L/L17e00NP.PS</a> and transfer |                         |
| of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF                                                                                     | <b>underline</b> Yes/No |
| If No, please describe other method: .....                                                                                              |                         |























**Documentation of assessor colour vision properties for visual assessment**

|                                                                      |                              |
|----------------------------------------------------------------------|------------------------------|
| The assessor has <b>normal</b> colour vision according to one test:  | <b>underline</b> Yes/No      |
| either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>   | <b>underline</b> Yes/unknown |
| or with test charts using colour points according to <i>Ishihara</i> | <b>underline</b> Yes/unknown |
| or tested with, please specify: .....                                | <b>underline</b> Yes/unknown |

**For visual evaluation of the display (monitor, data projector) output**

|                                                                                                                                                           |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Office workplace illumination is daylight (clouded/north sky)                                                                                             | <b>underline</b> Yes/No |
| <b>PDF file:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF</a>                        | <b>underline</b> Yes/No |
| <b>PS file:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS</a>                           | <b>underline</b> Yes/No |
| <b>Picture A7-034-2: contrast range:</b> (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)                                              |                         |
| compare standard print output according to ISO/IEC 15775 with range F:0                                                                                   | <b>underline</b> range  |
| <i>Remark: In daylighted offices the contrast range is in many cases:<br/>on display between: &gt;F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i> |                         |

**Only for optional colorimetric specification with PDF/PS file output**

|                                                                                                                                    |                            |
|------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| <b>PDF-File:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF</a> |                            |
| <b>picture A7-034-2</b>                                                                                                            | <b>underline</b> Yes/No    |
| <b>PS-File:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS</a>    |                            |
| <b>picture A7-034-2</b>                                                                                                            | <b>or underline</b> Yes/No |

**colour measurement and specification for:**

|                                                                    |                         |
|--------------------------------------------------------------------|-------------------------|
| CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: | <b>underline</b> Yes/No |
| If No, please give other parameters: .....                         |                         |

**Colorimetric specification with PS file for colours in the columns A to T**

|                                                                                                                                         |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Exchange of CIELAB data in file <a href="http://www.ps.bam.de/De17/10L/L17e00NP.PS">www.ps.bam.de/De17/10L/L17e00NP.PS</a> and transfer |                         |
| of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF                                                                                     | <b>underline</b> Yes/No |
| If No, please describe other method: .....                                                                                              |                         |























**Documentation of assessor colour vision properties for visual assessment**

|                                                                      |                              |
|----------------------------------------------------------------------|------------------------------|
| The assessor has <b>normal</b> colour vision according to one test:  | <b>underline</b> Yes/No      |
| either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>   | <b>underline</b> Yes/unknown |
| or with test charts using colour points according to <i>Ishihara</i> | <b>underline</b> Yes/unknown |
| or tested with, please specify: .....                                | <b>underline</b> Yes/unknown |

**For visual evaluation of the display (monitor, data projector) output**

|                                                                                                                                                           |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Office workplace illumination is daylight (clouded/north sky)                                                                                             | <b>underline</b> Yes/No |
| <b>PDF file:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF</a>                        | <b>underline</b> Yes/No |
| <b>PS file:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS</a>                           | <b>underline</b> Yes/No |
| <b>Picture A7-035-2: contrast range:</b> (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)                                              |                         |
| compare standard print output according to ISO/IEC 15775 with range F:0                                                                                   | <b>underline</b> range  |
| <i>Remark: In daylighted offices the contrast range is in many cases:<br/>on display between: &gt;F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i> |                         |

**Only for optional colorimetric specification with PDF/PS file output**

|                                                                                                                                    |                            |
|------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| <b>PDF-File:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF</a> |                            |
| <b>picture A7-035-2</b>                                                                                                            | <b>underline</b> Yes/No    |
| <b>PS-File:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS</a>    |                            |
| <b>picture A7-035-2</b>                                                                                                            | <b>or underline</b> Yes/No |

**colour measurement and specification for:**

|                                                                    |                         |
|--------------------------------------------------------------------|-------------------------|
| CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: | <b>underline</b> Yes/No |
| If No, please give other parameters: .....                         |                         |

**Colorimetric specification with PS file for colours in the columns A to T**

|                                                                                                                                         |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Exchange of CIELAB data in file <a href="http://www.ps.bam.de/De17/10L/L17e00NP.PS">www.ps.bam.de/De17/10L/L17e00NP.PS</a> and transfer |                         |
| of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF                                                                                     | <b>underline</b> Yes/No |
| If No, please describe other method: .....                                                                                              |                         |























**Documentation of assessor colour vision properties for visual assessment**

|                                                                      |                              |
|----------------------------------------------------------------------|------------------------------|
| The assessor has <b>normal</b> colour vision according to one test:  | <b>underline</b> Yes/No      |
| either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>   | <b>underline</b> Yes/unknown |
| or with test charts using colour points according to <i>Ishihara</i> | <b>underline</b> Yes/unknown |
| or tested with, please specify: .....                                | <b>underline</b> Yes/unknown |

**For visual evaluation of the display (monitor, data projector) output**

|                                                                                                                                                           |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Office workplace illumination is daylight (clouded/north sky)                                                                                             | <b>underline</b> Yes/No |
| <b>PDF file:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF</a>                        | <b>underline</b> Yes/No |
| <b>PS file:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS</a>                           | <b>underline</b> Yes/No |
| <b>Picture A7-036-2: contrast range:</b> (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)                                              |                         |
| compare standard print output according to ISO/IEC 15775 with range F:0                                                                                   | <b>underline</b> range  |
| <i>Remark: In daylighted offices the contrast range is in many cases:<br/>on display between: &gt;F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i> |                         |

**Only for optional colorimetric specification with PDF/PS file output**

|                                                                                                                                    |                            |
|------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| <b>PDF-File:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF</a> |                            |
| <b>picture A7-036-2</b>                                                                                                            | <b>underline</b> Yes/No    |
| <b>PS-File:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS</a>    |                            |
| <b>picture A7-036-2</b>                                                                                                            | <b>or underline</b> Yes/No |

**colour measurement and specification for:**

|                                                                    |                         |
|--------------------------------------------------------------------|-------------------------|
| CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: | <b>underline</b> Yes/No |
| If No, please give other parameters: .....                         |                         |

**Colorimetric specification with PS file for colours in the columns A to T**

|                                                                                                                                         |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Exchange of CIELAB data in file <a href="http://www.ps.bam.de/De17/10L/L17e00NP.PS">www.ps.bam.de/De17/10L/L17e00NP.PS</a> and transfer |                         |
| of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF                                                                                     | <b>underline</b> Yes/No |
| If No, please describe other method: .....                                                                                              |                         |























**Documentation of assessor colour vision properties for visual assessment**

|                                                                      |                              |
|----------------------------------------------------------------------|------------------------------|
| The assessor has <b>normal</b> colour vision according to one test:  | <b>underline</b> Yes/No      |
| either according to DIN 6160:1996 with Anomaloskop of <i>Nagel</i>   | <b>underline</b> Yes/unknown |
| or with test charts using colour points according to <i>Ishihara</i> | <b>underline</b> Yes/unknown |
| or tested with, please specify: .....                                | <b>underline</b> Yes/unknown |

**For visual evaluation of the display (monitor, data projector) output**

|                                                                                                                                                           |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Office workplace illumination is daylight (clouded/north sky)                                                                                             | <b>underline</b> Yes/No |
| <b>PDF file:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF</a>                        | <b>underline</b> Yes/No |
| <b>PS file:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS</a>                           | <b>underline</b> Yes/No |
| <b>Picture A7-037-2: contrast range:</b> (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)                                              |                         |
| compare standard print output according to ISO/IEC 15775 with range F:0                                                                                   | <b>underline</b> range  |
| <i>Remark: In daylighted offices the contrast range is in many cases:<br/>on display between: &gt;F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i> |                         |

**Only for optional colorimetric specification with PDF/PS file output**

|                                                                                                                                    |                            |
|------------------------------------------------------------------------------------------------------------------------------------|----------------------------|
| <b>PDF-File:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PDF</a> |                            |
| <b>picture A7-037-2</b>                                                                                                            | <b>underline</b> Yes/No    |
| <b>PS-File:</b> <a href="http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS">http://130.149.60.45/farbmetrik/OE73/OE73F1P2.PS</a>    |                            |
| <b>picture A7-037-2</b>                                                                                                            | <b>or underline</b> Yes/No |

**colour measurement and specification for:**

|                                                                    |                         |
|--------------------------------------------------------------------|-------------------------|
| CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: | <b>underline</b> Yes/No |
| If No, please give other parameters: .....                         |                         |

**Colorimetric specification with PS file for colours in the columns A to T**

|                                                                                                                                         |                         |
|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------|
| Exchange of CIELAB data in file <a href="http://www.ps.bam.de/De17/10L/L17e00NP.PS">www.ps.bam.de/De17/10L/L17e00NP.PS</a> and transfer |                         |
| of the PS-file L17e00NP.PS in PDF-file L17e00NP.PDF                                                                                     | <b>underline</b> Yes/No |
| If No, please describe other method: .....                                                                                              |                         |

