


See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref			l*out			LAB*out			LAB*out/c-ref			ΔE*	Start output S1 Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G
1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
2	6.36	0.0	0.0	0.07	6.36	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
3	12.72	0.0	0.0	0.13	12.72	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
4	19.08	0.0	0.0	0.2	19.08	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
5	25.44	0.0	0.0	0.27	25.44	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
6	31.8	0.0	0.0	0.33	31.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
7	38.16	0.0	0.0	0.4	38.16	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
8	44.52	0.0	0.0	0.47	44.52	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
9	50.89	0.0	0.0	0.53	50.89	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
10	57.25	0.0	0.0	0.6	57.25	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
11	63.61	0.0	0.0	0.67	63.61	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
12	69.97	0.0	0.0	0.73	69.97	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
13	76.33	0.0	0.0	0.8	76.33	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
14	82.69	0.0	0.0	0.87	82.69	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
15	89.05	0.0	0.0	0.93	89.05	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	Mean lightness difference (16 steps)
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	ΔE* _{CIELAB} = 0.0
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
18	23.85	0.0	0.0	0.25	23.85	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
19	47.71	0.0	0.0	0.5	47.71	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
20	71.56	0.0	0.0	0.75	71.56	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	Mean lightness difference (5 steps)
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	ΔL* _{CIELAB} = 0.0
Mean colour reproduction index:													R* _{ab,m} = 100	

OE820-3N-130-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE821-3N-130-11: File: Measure unknown; Device: Device unknown; Date: Date unknown

L*/Y _{intended} (absolute)	0.0/0.0	6.4/0.7	12.7/1.5	19.1/2.8	25.4/4.6	31.8/7.0	38.2/10.2	44.5/14.2	50.9/19.2	57.2/25.2	63.6/32.3	70.0/40.7	76.3/50.4	82.7/61.6	89.0/74.3	95.4/88.6
w* w* w* setrgb g _p =1.0																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
w*=l* CIELAB, r (relative)																
w* _{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w* _{out}	0.0	0.067	0.133	0.2	0.267	0.333	0.4	0.467	0.533	0.6	0.667	0.733	0.8	0.867	0.933	1.0

OE820-7N, Picture A7-130-11: 16 visual equidistant L*-grey steps; PS operator: w* w* w* setrgbcolor

OE82: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast Y_W:Y_N=88,9:0,31; Y_N range 0,0 to <0,46


input: *rgb* (->*rgb**_{de}) setrgbcolor
output 130-11: g_p=1.0; g_N=1.0

TUB registration: 20110801-OE82/OE82L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*
1	5.69 0.0 0.0	0.0 0.0 0.0	5.69 0.0 0.0	0.0 0.0 0.0	0.01
2	11.67 0.0 0.0	0.0 0.04 9.36	0.0 0.0 0.0	-2.3 0.0 0.0	2.31
3	17.65 0.0 0.0	0.0 0.09 14.01	0.0 0.0 0.0	-3.63 0.0 0.0	3.64
4	23.63 0.0 0.0	0.0 0.15 19.12	0.0 0.0 0.0	-4.5 0.0 0.0	4.51
5	29.62 0.0 0.0	0.0 0.21 24.55	0.0 0.0 0.0	-5.06 0.0 0.0	5.07
6	35.6 0.0 0.0	0.0 0.27 30.23	0.0 0.0 0.0	-5.36 0.0 0.0	5.37
7	41.58 0.0 0.0	0.0 0.34 36.12	0.0 0.0 0.0	-5.45 0.0 0.0	5.46
8	47.56 0.0 0.0	0.0 0.41 42.19	0.0 0.0 0.0	-5.36 0.0 0.0	5.37
9	53.54 0.0 0.0	0.0 0.48 48.42	0.0 0.0 0.0	-5.11 0.0 0.0	5.12
10	59.52 0.0 0.0	0.0 0.55 54.79	0.0 0.0 0.0	-4.72 0.0 0.0	4.73
11	65.5 0.0 0.0	0.0 0.62 61.29	0.0 0.0 0.0	-4.2 0.0 0.0	4.21
12	71.48 0.0 0.0	0.0 0.69 67.91	0.0 0.0 0.0	-3.56 0.0 0.0	3.57
13	77.47 0.0 0.0	0.0 0.77 74.64	0.0 0.0 0.0	-2.82 0.0 0.0	2.83
14	83.45 0.0 0.0	0.0 0.84 81.47	0.0 0.0 0.0	-1.97 0.0 0.0	1.98
15	89.43 0.0 0.0	0.0 0.92 88.4	0.0 0.0 0.0	-1.02 0.0 0.0	1.03
16	95.41 0.0 0.0	0.0 1.0 95.41	0.0 0.0 0.0	0.0 0.0 0.0	0.01
17	5.69 0.0 0.0	0.0 0.0 5.69	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	28.12 0.0 0.0	0.0 0.19 23.17	0.0 0.0 0.0	-4.94 0.0 0.0	4.95
19	50.55 0.0 0.0	0.0 0.44 45.29	0.0 0.0 0.0	-5.25 0.0 0.0	5.26
20	72.98 0.0 0.0	0.0 0.71 69.58	0.0 0.0 0.0	-3.39 0.0 0.0	3.4
21	95.41 0.0 0.0	0.0 1.0 95.41	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					ΔE* _{CIELAB} = 3.4
Mean lightness difference (5 steps)					ΔL* _{CIELAB} = 2.7
Mean colour reproduction index:					R* _{ab,m} = 85

OE820-3N-131-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE821-3N-131-11: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	5.7/0.6	11.7/1.4	17.7/2.4	23.6/4.0	29.6/6.1	35.6/8.8	41.6/12.2	47.6/16.5	53.5/21.5	59.5/27.6	65.5/34.7	71.5/42.9	77.5/52.3	83.4/63.0	89.4/75.1	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_N=1.18$																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{\text{CIELAB},r}$ (relative)																
w^*_{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0,0	0,041	0,093	0,15	0,211	0,273	0,339	0,407	0,476	0,547	0,62	0,693	0,769	0,845	0,921	1,0

OE820-7N, Picture A7-131-11: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor


OE82: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast $Y_W:Y_N=88,9:0,62$; Y_N range 0,46 to <0,93

input: $rgb \rightarrow rgb^*_{de}$ setrgbcolor
output 130-11: $g_P=1,0$; $g_N=1,08$

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*
1	10.99 0.0 0.0	0.0 10.99 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	16.62 0.0 0.0	0.03 13.12 0.0	0.0 0.0 0.0	-3.49 0.0 0.0	3.5
3	22.25 0.0 0.0	0.06 16.44 0.0	0.0 0.0 0.0	-5.8 0.0 0.0	5.81
4	27.88 0.0 0.0	0.11 20.45 0.0	0.0 0.0 0.0	-7.41 0.0 0.0	7.42
5	33.5 0.0 0.0	0.17 24.98 0.0	0.0 0.0 0.0	-8.51 0.0 0.0	8.52
6	39.13 0.0 0.0	0.22 29.94 0.0	0.0 0.0 0.0	-9.18 0.0 0.0	9.19
7	44.76 0.0 0.0	0.29 35.27 0.0	0.0 0.0 0.0	-9.48 0.0 0.0	9.49
8	50.39 0.0 0.0	0.35 40.93 0.0	0.0 0.0 0.0	-9.44 0.0 0.0	9.45
9	56.02 0.0 0.0	0.43 46.9 0.0	0.0 0.0 0.0	-9.11 0.0 0.0	9.12
10	61.64 0.0 0.0	0.5 53.13 0.0	0.0 0.0 0.0	-8.5 0.0 0.0	8.51
11	67.27 0.0 0.0	0.58 59.63 0.0	0.0 0.0 0.0	-7.63 0.0 0.0	7.64
12	72.9 0.0 0.0	0.66 66.36 0.0	0.0 0.0 0.0	-6.53 0.0 0.0	6.54
13	78.53 0.0 0.0	0.74 73.31 0.0	0.0 0.0 0.0	-5.2 0.0 0.0	5.21
14	84.15 0.0 0.0	0.82 80.48 0.0	0.0 0.0 0.0	-3.66 0.0 0.0	3.67
15	89.78 0.0 0.0	0.91 87.85 0.0	0.0 0.0 0.0	-1.92 0.0 0.0	1.93
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
17	10.99 0.0 0.0	0.0 10.99 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	32.1 0.0 0.0	0.15 23.81 0.0	0.0 0.0 0.0	-8.28 0.0 0.0	8.29
19	53.2 0.0 0.0	0.39 43.88 0.0	0.0 0.0 0.0	-9.31 0.0 0.0	9.32
20	74.31 0.0 0.0	0.68 68.08 0.0	0.0 0.0 0.0	-6.22 0.0 0.0	6.23
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					ΔE* _{CIELAB} = 6.0
Mean lightness difference (5 steps)					ΔL* _{CIELAB} = 4.8
Mean colour reproduction index:					R* _{ab,m} = 74

OE820-3N-132-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE821-3N-132-11: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	11.0/1.3	16.6/2.2	22.2/3.6	27.9/5.4	33.5/7.8	39.1/10.7	44.8/14.4	50.4/18.7	56.0/23.9	61.6/30.0	67.3/37.0	72.9/45.0	78.5/54.1	84.2/64.4	89.8/75.8	95.4/88.6
$w^* w^* w^*$ setrgb $g_N=1.36$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*$ _{CIELAB, r} (relative)	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{intended} w^*_{out}	0,000 0,0	0,067 0,025	0,133 0,064	0,200 0,112	0,267 0,166	0,333 0,224	0,400 0,288	0,467 0,355	0,533 0,425	0,600 0,499	0,667 0,577	0,733 0,655	0,800 0,738	0,867 0,824	0,933 0,91	1,000 1,0

OE820-7N, Picture A7-132-11: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE82: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast $Y_W:Y_N=88,9:1,25$; Y_N range 0,93 to <1,87


input: $rgb \rightarrow rgb^*_{de}$ setrgbcolor
output 130-11: $g_P=1.0$; $g_N=1.17$

TUB registration: 20110801-OE82/OE82L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*
1	18.01 0.0 0.0	0.0 18.01 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	23.17 0.0 0.0	0.02 19.2 0.0	0.0 -3.95 0.0	0.0 0.0 0.0	3.96
3	28.33 0.0 0.0	0.04 21.49 0.0	0.0 -6.83 0.0	0.0 0.0 0.0	6.84
4	33.49 0.0 0.0	0.08 24.5 0.0	0.0 -8.98 0.0	0.0 0.0 0.0	8.99
5	38.65 0.0 0.0	0.13 28.12 0.0	0.0 -10.52 0.0	0.0 0.0 0.0	10.53
6	43.81 0.0 0.0	0.18 32.26 0.0	0.0 -11.53 0.0	0.0 0.0 0.0	11.54
7	48.97 0.0 0.0	0.24 36.89 0.0	0.0 -12.07 0.0	0.0 0.0 0.0	12.08
8	54.13 0.0 0.0	0.31 41.94 0.0	0.0 -12.18 0.0	0.0 0.0 0.0	12.19
9	59.29 0.0 0.0	0.38 47.41 0.0	0.0 -11.87 0.0	0.0 0.0 0.0	11.88
10	64.45 0.0 0.0	0.46 53.25 0.0	0.0 -11.19 0.0	0.0 0.0 0.0	11.2
11	69.61 0.0 0.0	0.54 59.46 0.0	0.0 -10.14 0.0	0.0 0.0 0.0	10.15
12	74.77 0.0 0.0	0.62 66.02 0.0	0.0 -8.74 0.0	0.0 0.0 0.0	8.75
13	79.93 0.0 0.0	0.71 72.9 0.0	0.0 -7.02 0.0	0.0 0.0 0.0	7.03
14	85.09 0.0 0.0	0.8 80.1 0.0	0.0 -4.98 0.0	0.0 0.0 0.0	4.99
15	90.25 0.0 0.0	0.9 87.61 0.0	0.0 -2.63 0.0	0.0 0.0 0.0	2.64
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					
17	18.01 0.0 0.0	0.0 18.01 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	37.36 0.0 0.0	0.12 27.16 0.0	0.0 -10.19 0.0	0.0 0.0 0.0	10.2
19	56.71 0.0 0.0	0.34 44.63 0.0	0.0 -12.07 0.0	0.0 0.0 0.0	12.08
20	76.06 0.0 0.0	0.64 67.71 0.0	0.0 -8.34 0.0	0.0 0.0 0.0	8.35
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (5 steps)					
Mean colour reproduction index: $R^*_{ab,m} = 66$					

OE820-3N-133-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE821-3N-133-11: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolute)	18.0/2.5	23.2/3.8	28.3/5.6	33.5/7.8	38.6/10.5	43.8/13.7	49.0/17.6	54.1/22.1	59.3/27.3	64.4/33.4	69.6/40.2	74.8/47.9	79.9/56.6	85.1/66.2	90.2/76.8	95.4/88.6
$w^* w^* w^*$ setrgb $g_N=1.54$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*$ CIELAB, r (relative)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0,0	0,016	0,045	0,084	0,131	0,184	0,244	0,31	0,379	0,455	0,536	0,62	0,709	0,803	0,899	1,0

OE820-7N, Picture A7-133-11: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE82: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast $Y_W:Y_N=88,9:2,5$; Y_N range 1,87 to <3,75


input: $rgb \rightarrow rgb^*_{de}$ setrgbcolor
output 130-11: $g_P=1.0$; $g_N=1.29$

TUB registration: 20110801-OE82/OE82L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*
1	26.85 0.0 0.0	0.0 26.85 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	31.42 0.0 0.0	0.01 27.5 0.0	0.0 -3.91 0.0	0.0 0.0 0.0	3.92
3	35.99 0.0 0.0	0.03 28.99 0.0	0.0 -6.99 0.0	0.0 0.0 0.0	7.0
4	40.56 0.0 0.0	0.06 31.15 0.0	0.0 -9.4 0.0	0.0 0.0 0.0	9.41
5	45.13 0.0 0.0	0.1 33.91 0.0	0.0 -11.21 0.0	0.0 0.0 0.0	11.22
6	49.7 0.0 0.0	0.15 37.21 0.0	0.0 -12.48 0.0	0.0 0.0 0.0	12.49
7	54.27 0.0 0.0	0.21 41.03 0.0	0.0 -13.24 0.0	0.0 0.0 0.0	13.25
8	58.84 0.0 0.0	0.27 45.33 0.0	0.0 -13.5 0.0	0.0 0.0 0.0	13.51
9	63.41 0.0 0.0	0.34 50.1 0.0	0.0 -13.3 0.0	0.0 0.0 0.0	13.31
10	67.99 0.0 0.0	0.42 55.33 0.0	0.0 -12.65 0.0	0.0 0.0 0.0	12.66
11	72.56 0.0 0.0	0.5 60.98 0.0	0.0 -11.56 0.0	0.0 0.0 0.0	11.57
12	77.13 0.0 0.0	0.59 67.06 0.0	0.0 -10.05 0.0	0.0 0.0 0.0	10.06
13	81.7 0.0 0.0	0.68 73.56 0.0	0.0 -8.13 0.0	0.0 0.0 0.0	8.14
14	86.27 0.0 0.0	0.78 80.45 0.0	0.0 -5.81 0.0	0.0 0.0 0.0	5.82
15	90.84 0.0 0.0	0.89 87.74 0.0	0.0 -3.09 0.0	0.0 0.0 0.0	3.1
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					
17	26.85 0.0 0.0	0.0 26.85 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	43.99 0.0 0.0	0.09 33.17 0.0	0.0 -10.81 0.0	0.0 0.0 0.0	10.82
19	61.13 0.0 0.0	0.3 47.66 0.0	0.0 -13.46 0.0	0.0 0.0 0.0	13.47
20	78.27 0.0 0.0	0.61 68.65 0.0	0.0 -9.61 0.0	0.0 0.0 0.0	9.62
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (5 steps)					
Mean colour reproduction index: $R^*_{ab,m} = 63$					

OE820-3N-134-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE821-3N-134-11: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolute)	26.8/5.0	31.4/6.8	36.0/9.0	40.6/11.6	45.1/14.6	49.7/18.2	54.3/22.2	58.8/26.9	63.4/32.1	68.0/38.0	72.6/44.5	77.1/51.7	81.7/59.7	86.3/68.5	90.8/78.1	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_N=1.72$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*$ CIELAB, r (relative)																
$w^*_{intended}$	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.01	0.031	0.063	0.103	0.151	0.207	0.27	0.339	0.415	0.498	0.586	0.681	0.782	0.888	1.0

OE820-7N, Picture A7-134-11: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor


OE82: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast $Y_W:Y_N=88,9:5$; Y_N range 3,75 to <7,5

input: $rgb \rightarrow rgb^*_{de}$ setrgbcolor
output 130-11: $g_P=1.0$; $g_N=1.42$

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*
1	37.99 0.0 0.0	0.0 37.99 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	41.81 0.0 0.0	0.01 38.32 0.0	0.0 0.0 -3.48	0.0 0.0 0.0	3.49
3	45.64 0.0 0.0	0.02 39.23 0.0	0.0 0.0 -6.4	0.0 0.0 0.0	6.41
4	49.47 0.0 0.0	0.05 40.68 0.0	0.0 0.0 -8.78	0.0 0.0 0.0	8.79
5	53.3 0.0 0.0	0.08 42.65 0.0	0.0 0.0 -10.64	0.0 0.0 0.0	10.65
6	57.13 0.0 0.0	0.12 45.11 0.0	0.0 0.0 -12.01	0.0 0.0 0.0	12.02
7	60.96 0.0 0.0	0.18 48.06 0.0	0.0 0.0 -12.89	0.0 0.0 0.0	12.9
8	64.78 0.0 0.0	0.24 51.48 0.0	0.0 0.0 -13.29	0.0 0.0 0.0	13.3
9	68.61 0.0 0.0	0.3 55.38 0.0	0.0 0.0 -13.22	0.0 0.0 0.0	13.23
10	72.44 0.0 0.0	0.38 59.74 0.0	0.0 0.0 -12.69	0.0 0.0 0.0	12.7
11	76.27 0.0 0.0	0.46 64.56 0.0	0.0 0.0 -11.69	0.0 0.0 0.0	11.7
12	80.1 0.0 0.0	0.55 69.84 0.0	0.0 0.0 -10.25	0.0 0.0 0.0	10.26
13	83.93 0.0 0.0	0.65 75.57 0.0	0.0 0.0 -8.35	0.0 0.0 0.0	8.36
14	87.75 0.0 0.0	0.76 81.74 0.0	0.0 0.0 -6.0	0.0 0.0 0.0	6.01
15	91.58 0.0 0.0	0.88 88.35 0.0	0.0 0.0 -3.22	0.0 0.0 0.0	3.23
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					
17	37.99 0.0 0.0	0.0 37.99 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	52.34 0.0 0.0	0.07 42.11 0.0	0.0 0.0 -10.22	0.0 0.0 0.0	10.23
19	66.7 0.0 0.0	0.27 53.37 0.0	0.0 0.0 -13.32	0.0 0.0 0.0	13.33
20	81.05 0.0 0.0	0.58 71.23 0.0	0.0 0.0 -9.81	0.0 0.0 0.0	9.82
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (5 steps)					
Mean colour reproduction index: $R^*_{ab,m} = 64$					

OE820-3N-135-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE821-3N-135-11: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	38.0/10.1	41.8/12.4	45.6/15.0	49.5/18.0	53.3/21.3	57.1/25.1	61.0/29.2	64.8/33.8	68.6/38.8	72.4/44.3	76.3/50.3	80.1/56.9	83.9/63.9	87.8/71.6	91.6/79.8	95.4/88.6
$w^* w^* w^*$ setrgb $g_N=1.9$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*$ CIELAB, r (relative)																
w^*_{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.006	0.022	0.047	0.081	0.124	0.175	0.235	0.303	0.379	0.463	0.554	0.654	0.762	0.877	1.0

OE820-7N, Picture A7-135-11: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE82: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast $Y_W:Y_N=88,9:10$; Y_N range 7,5 to <15


input: $rgb \rightarrow rgb^*_{de}$ setrgbcolor
output 130-11: $g_P=1.0$; $g_N=1.6$

TUB registration: 20110801-OE82/OE82L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*
1	52.02 0.0 0.0	0.0 52.02 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	54.91 0.0 0.0	0.0 52.17 0.0	0.0 0.0 0.0	-2.73 0.0 0.0	2.74
3	57.8 0.0 0.0	0.02 52.67 0.0	0.0 0.0 0.0	-5.12 0.0 0.0	5.13
4	60.7 0.0 0.0	0.04 53.54 0.0	0.0 0.0 0.0	-7.14 0.0 0.0	7.15
5	63.59 0.0 0.0	0.06 54.79 0.0	0.0 0.0 0.0	-8.79 0.0 0.0	8.8
6	66.48 0.0 0.0	0.1 56.43 0.0	0.0 0.0 0.0	-10.04 0.0 0.0	10.05
7	69.37 0.0 0.0	0.15 58.47 0.0	0.0 0.0 0.0	-10.89 0.0 0.0	10.9
8	72.27 0.0 0.0	0.2 60.91 0.0	0.0 0.0 0.0	-11.35 0.0 0.0	11.36
9	75.16 0.0 0.0	0.27 63.75 0.0	0.0 0.0 0.0	-11.4 0.0 0.0	11.41
10	78.05 0.0 0.0	0.35 67.01 0.0	0.0 0.0 0.0	-11.03 0.0 0.0	11.04
11	80.95 0.0 0.0	0.43 70.69 0.0	0.0 0.0 0.0	-10.25 0.0 0.0	10.26
12	83.84 0.0 0.0	0.52 74.78 0.0	0.0 0.0 0.0	-9.05 0.0 0.0	9.06
13	86.73 0.0 0.0	0.63 79.3 0.0	0.0 0.0 0.0	-7.42 0.0 0.0	7.43
14	89.62 0.0 0.0	0.74 84.24 0.0	0.0 0.0 0.0	-5.38 0.0 0.0	5.39
15	92.52 0.0 0.0	0.87 89.61 0.0	0.0 0.0 0.0	-2.9 0.0 0.0	2.91
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
17	52.02 0.0 0.0	0.0 52.02 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	62.87 0.0 0.0	0.06 54.44 0.0	0.0 0.0 0.0	-8.41 0.0 0.0	8.42
19	73.71 0.0 0.0	0.24 62.28 0.0	0.0 0.0 0.0	-11.42 0.0 0.0	11.43
20	84.56 0.0 0.0	0.55 75.87 0.0	0.0 0.0 0.0	-8.68 0.0 0.0	8.69
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					ΔE* _{CIELAB} = 7.1
Mean lightness difference (5 steps)					ΔL* _{CIELAB} = 5.7
Mean colour reproduction index:					R* _{ab,m} = 69

OE820-3N-136-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE821-3N-136-11: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolute)	52.0/20.2	54.9/22.8	57.8/25.8	60.7/28.9	63.6/32.3	66.5/36.0	69.4/39.9	72.3/44.1	75.2/48.5	78.1/53.3	80.9/58.4	83.8/63.8	86.7/69.5	89.6/75.5	92.5/81.9	95.4/88.6
$w^* w^* w^*$ setrgb $g_N=2.08$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*$ CIE_{LAB}, r (relative)	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
$w^*_{intended}$ w^*_{out}	0.000	0.004	0.015	0.035	0.064	0.102	0.149	0.205	0.27	0.346	0.431	0.524	0.629	0.743	0.866	1.0

OE820-7N, Picture A7-136-11: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE82: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast $Y_W:Y_N=88,9:20$; Y_N range 15 to <30


input: $rgb \rightarrow rgb^*_{de}$ setrgbcolor
output 130-11: $g_P=1.0$; $g_N=1.81$

TUB registration: 20110801-OE82/OE82L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref			l*out			LAB*out			LAB*out/c-ref			ΔE*	Start output S1
1	69.7	0.0	0.0	0.0	69.7	0.0	0.0	0.0	0.0	0.0	0.0	0.01	Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G	
2	71.41	0.0	0.0	0.0	69.75	0.0	0.0	-1.65	0.0	0.0	1.66			
3	73.13	0.0	0.0	0.01	69.97	0.0	0.0	-3.15	0.0	0.0	3.16			
4	74.84	0.0	0.0	0.03	70.37	0.0	0.0	-4.46	0.0	0.0	4.47			
5	76.55	0.0	0.0	0.05	70.99	0.0	0.0	-5.55	0.0	0.0	5.56			
6	78.27	0.0	0.0	0.08	71.84	0.0	0.0	-6.41	0.0	0.0	6.42			
7	79.98	0.0	0.0	0.13	72.94	0.0	0.0	-7.03	0.0	0.0	7.04			
8	81.7	0.0	0.0	0.18	74.29	0.0	0.0	-7.4	0.0	0.0	7.41			
9	83.41	0.0	0.0	0.24	75.91	0.0	0.0	-7.49	0.0	0.0	7.5			
10	85.12	0.0	0.0	0.32	77.8	0.0	0.0	-7.31	0.0	0.0	7.32			
11	86.84	0.0	0.0	0.4	79.98	0.0	0.0	-6.85	0.0	0.0	6.86			
12	88.55	0.0	0.0	0.5	82.45	0.0	0.0	-6.09	0.0	0.0	6.1			
13	90.27	0.0	0.0	0.6	85.23	0.0	0.0	-5.03	0.0	0.0	5.04			
14	91.98	0.0	0.0	0.72	88.3	0.0	0.0	-3.67	0.0	0.0	3.68			
15	93.7	0.0	0.0	0.86	91.7	0.0	0.0	-1.99	0.0	0.0	2.0	Mean lightness difference (16 steps)		
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.01	ΔE*CIELAB = 4.6		
17	69.7	0.0	0.0	0.0	69.7	0.0	0.0	0.0	0.0	0.0	0.01			
18	76.13	0.0	0.0	0.04	70.82	0.0	0.0	-5.3	0.0	0.0	5.31			
19	82.55	0.0	0.0	0.21	75.07	0.0	0.0	-7.48	0.0	0.0	7.49			
20	88.98	0.0	0.0	0.52	83.12	0.0	0.0	-5.85	0.0	0.0	5.86	Mean lightness difference (5 steps)		
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.01	ΔL*CIELAB = 3.7		
Mean colour reproduction index: R*ab,m = 80														

OE820-3N-137-11: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE821-3N-137-11: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolute)	69.7/40.3	71.4/42.8	73.1/45.4	74.8/48.0	76.6/50.8	78.3/53.7	80.0/56.6	81.7/59.7	83.4/62.9	85.1/66.3	86.8/69.7	88.6/73.2	90.3/76.9	92.0/80.7	93.7/84.6	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_N=2.26$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{CIELAB, r}$ (relative)																
$w^*_{intended}$	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.002	0.01	0.026	0.051	0.083	0.126	0.179	0.241	0.315	0.4	0.496	0.604	0.724	0.855	1.0

OE820-7N, Picture A7-137-11: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE82: In-output relation according to ISO 9241-306; 1MR, DEH
Viewing Y contrast $Y_W:Y_N=88,9:40$; Y_N range 30 to <60

input: $rgb \rightarrow rgb^*_{de}$ setrgbcolor
output 130-11: $g_P=1.0$; $g_N=2.1$