

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*
1	0.0	0.0	0.0	0.0	0.01
2	6.36	0.0	0.07	6.36	0.01
3	12.72	0.0	0.13	12.72	0.01
4	19.08	0.0	0.2	19.08	0.01
5	25.44	0.0	0.27	25.44	0.01
6	31.8	0.0	0.33	31.8	0.01
7	38.16	0.0	0.4	38.16	0.01
8	44.52	0.0	0.47	44.52	0.01
9	50.89	0.0	0.53	50.89	0.01
10	57.25	0.0	0.6	57.25	0.01
11	63.61	0.0	0.67	63.61	0.01
12	69.97	0.0	0.73	69.97	0.01
13	76.33	0.0	0.8	76.33	0.01
14	82.69	0.0	0.87	82.69	0.01
15	89.05	0.0	0.93	89.05	0.01
16	95.41	0.0	1.0	95.41	0.01
17	0.0	0.0	0.0	0.0	0.01
18	23.85	0.0	0.25	23.85	0.01
19	47.71	0.0	0.5	47.71	0.01
20	71.56	0.0	0.75	71.56	0.01
21	95.41	0.0	1.0	95.41	0.01


Start output S1
Specification according to
ISO/IEC 15775 Annex G
and DIN 33866-1 Annex G

Mean lightness difference (16 steps)
 $\Delta E^*_{\text{CIELAB}} = 0.0$

Mean lightness difference (5 steps)
 $\Delta L^*_{\text{CIELAB}} = 0.0$

Mean colour reproduction index: $R^*_{ab,m} = 100$

OE860-3N-130-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE861-3N-130-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	0.0/0.0	6.4/0.7	12.7/1.5	19.1/2.8	25.4/4.6	31.8/7.0	38.2/10.2	44.5/14.2	50.9/19.2	57.2/25.2	63.6/32.3	70.0/40.7	76.3/50.4	82.7/61.6	89.0/74.3	95.4/88.6
$w^* w^* w^*$ setrgb $g_p=1.0$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{\text{CIELAB},r}$ (relative)																
w^*_{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.067	0.133	0.2	0.267	0.333	0.4	0.467	0.533	0.6	0.667	0.733	0.8	0.867	0.933	1.0

OE860-7N, Picture A7-130-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor


OE86: In-output relation according to ISO 9241-306; 1MR, DEH input: $rgb \rightarrow rgb^*_{de}$ setrgbcolor
Viewing Y contrast $Y_W:Y_N=88,9:0,31$; Y_N range 0,0 to <0,46 output 130-2: $g_p=1.0$; $g_N=1.0$

TUB registration: 20110801-OE86/OE86L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*
1	5.69 0.0 0.0	0.0 0.0 0.0	5.69 0.0 0.0	0.0 0.0 0.0	0.01
2	11.67 0.0 0.0	0.04 0.0 0.0	9.36 0.0 0.0	-2.3 0.0 0.0	2.31
3	17.65 0.0 0.0	0.09 0.0 0.0	14.01 0.0 0.0	-3.63 0.0 0.0	3.64
4	23.63 0.0 0.0	0.15 0.0 0.0	19.12 0.0 0.0	-4.5 0.0 0.0	4.51
5	29.62 0.0 0.0	0.21 0.0 0.0	24.55 0.0 0.0	-5.06 0.0 0.0	5.07
6	35.6 0.0 0.0	0.27 0.0 0.0	30.23 0.0 0.0	-5.36 0.0 0.0	5.37
7	41.58 0.0 0.0	0.34 0.0 0.0	36.12 0.0 0.0	-5.45 0.0 0.0	5.46
8	47.56 0.0 0.0	0.41 0.0 0.0	42.19 0.0 0.0	-5.36 0.0 0.0	5.37
9	53.54 0.0 0.0	0.48 0.0 0.0	48.42 0.0 0.0	-5.11 0.0 0.0	5.12
10	59.52 0.0 0.0	0.55 0.0 0.0	54.79 0.0 0.0	-4.72 0.0 0.0	4.73
11	65.5 0.0 0.0	0.62 0.0 0.0	61.29 0.0 0.0	-4.2 0.0 0.0	4.21
12	71.48 0.0 0.0	0.69 0.0 0.0	67.91 0.0 0.0	-3.56 0.0 0.0	3.57
13	77.47 0.0 0.0	0.77 0.0 0.0	74.64 0.0 0.0	-2.82 0.0 0.0	2.83
14	83.45 0.0 0.0	0.84 0.0 0.0	81.47 0.0 0.0	-1.97 0.0 0.0	1.98
15	89.43 0.0 0.0	0.92 0.0 0.0	88.4 0.0 0.0	-1.02 0.0 0.0	1.03
16	95.41 0.0 0.0	1.0 0.0 0.0	95.41 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					ΔE* _{CIELAB} = 3.4
17	5.69 0.0 0.0	0.0 0.0 0.0	5.69 0.0 0.0	0.0 0.0 0.0	0.01
18	28.12 0.0 0.0	0.19 0.0 0.0	23.17 0.0 0.0	-4.94 0.0 0.0	4.95
19	50.55 0.0 0.0	0.44 0.0 0.0	45.29 0.0 0.0	-5.25 0.0 0.0	5.26
20	72.98 0.0 0.0	0.71 0.0 0.0	69.58 0.0 0.0	-3.39 0.0 0.0	3.4
21	95.41 0.0 0.0	1.0 0.0 0.0	95.41 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (5 steps)					ΔL* _{CIELAB} = 2.7
Mean colour reproduction index:					R* _{ab,m} = 85

OE860-3N-131-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE861-3N-131-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

L*/Y _{intended} (absolute)	5.7/0.6	11.7/1.4	17.7/2.4	23.6/4.0	29.6/6.1	35.6/8.8	41.6/12.2	47.6/16.5	53.5/21.5	59.5/27.6	65.5/34.7	71.5/42.9	77.5/52.3	83.4/63.0	89.4/75.1	95.4/88.6
w* w* w* setrgb																
g _N =1.18																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
w*=l* _{CIELAB} , r (relative)																
w* _{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w* _{out}	0.0	0.041	0.093	0.15	0.211	0.273	0.339	0.407	0.476	0.547	0.62	0.693	0.769	0.845	0.921	1.0


OE860-7N, Picture A7-131-2: 16 visual equidistant L*-grey steps; PS operator: w* w* w* setrgbcolor

OE86: In-output relation according to ISO 9241-306; 1MR, DEH input: *rgb* (->*rgb**_{de}) setrgbcolor
Viewing Y contrast Y_W:Y_N=88,9:0,62; Y_N range 0,46 to <0,93 output 130-2: g_P=1.0; g_N=1.08

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*
1	10.99 0.0 0.0	0.0 10.99 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	16.62 0.0 0.0	0.03 13.12 0.0	0.0 0.0 -3.49	0.0 0.0 0.0	3.5
3	22.25 0.0 0.0	0.06 16.44 0.0	0.0 0.0 -5.8	0.0 0.0 0.0	5.81
4	27.88 0.0 0.0	0.11 20.45 0.0	0.0 0.0 -7.41	0.0 0.0 0.0	7.42
5	33.5 0.0 0.0	0.17 24.98 0.0	0.0 0.0 -8.51	0.0 0.0 0.0	8.52
6	39.13 0.0 0.0	0.22 29.94 0.0	0.0 0.0 -9.18	0.0 0.0 0.0	9.19
7	44.76 0.0 0.0	0.29 35.27 0.0	0.0 0.0 -9.48	0.0 0.0 0.0	9.49
8	50.39 0.0 0.0	0.35 40.93 0.0	0.0 0.0 -9.44	0.0 0.0 0.0	9.45
9	56.02 0.0 0.0	0.43 46.9 0.0	0.0 0.0 -9.11	0.0 0.0 0.0	9.12
10	61.64 0.0 0.0	0.5 53.13 0.0	0.0 0.0 -8.5	0.0 0.0 0.0	8.51
11	67.27 0.0 0.0	0.58 59.63 0.0	0.0 0.0 -7.63	0.0 0.0 0.0	7.64
12	72.9 0.0 0.0	0.66 66.36 0.0	0.0 0.0 -6.53	0.0 0.0 0.0	6.54
13	78.53 0.0 0.0	0.74 73.31 0.0	0.0 0.0 -5.2	0.0 0.0 0.0	5.21
14	84.15 0.0 0.0	0.82 80.48 0.0	0.0 0.0 -3.66	0.0 0.0 0.0	3.67
15	89.78 0.0 0.0	0.91 87.85 0.0	0.0 -1.92	0.0 0.0 1.93	Mean lightness difference (16 steps)
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.01	ΔE* _{CIELAB} = 6.0
17	10.99 0.0 0.0	0.0 10.99 0.0	0.0 0.0 0.0	0.0 0.0 0.01	
18	32.1 0.0 0.0	0.15 23.81 0.0	0.0 -8.28	0.0 0.0 8.29	
19	53.2 0.0 0.0	0.39 43.88 0.0	0.0 -9.31	0.0 0.0 9.32	
20	74.31 0.0 0.0	0.68 68.08 0.0	0.0 -6.22	0.0 0.0 6.23	Mean lightness difference (5 steps)
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.01	ΔL* _{CIELAB} = 4.8
Mean colour reproduction index:					R* _{ab,m} = 74

OE860-3N-132-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE861-3N-132-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^{*}/Y_{intended}$ (absolute)	11.0/1.3	16.6/2.2	22.2/3.6	27.9/5.4	33.5/7.8	39.1/10.7	44.8/14.4	50.4/18.7	56.0/23.9	61.6/30.0	67.3/37.0	72.9/45.0	78.5/54.1	84.2/64.4	89.8/75.8	95.4/88.6
$w^{*}w^{*}w^{*}$ setrgb $g_N=1.36$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^{*}=l^{*}$ _{CIELAB, r} (relative)																
$w^{*}_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^{*}_{out}	0,0	0,025	0,064	0,112	0,166	0,224	0,288	0,355	0,425	0,499	0,577	0,655	0,738	0,824	0,91	1,0

OE860-7N, Picture A7-132-2: 16 visual equidistant L^{*} -grey steps; PS operator: $w^{*}w^{*}w^{*}$ setrgbcolor


OE86: In-output relation according to ISO 9241-306; 1MR, DEH input: $rgb \rightarrow rgb^{*}_{de}$ setrgbcolor
Viewing Y contrast $Y_W:Y_N=88,9:1,25$; Y_N range 0,93 to <1,87 output 130-2: $g_P=1,0$; $g_N=1,17$

TUB registration: 20110801-OE86/OE86L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start output S1				
1	18.01	0.0	0.0	18.01	0.0	0.0	0.0	0.0	0.01	Specification according to
2	23.17	0.0	0.0	0.02	19.2	0.0	0.0	-3.95	0.0	ISO/IEC 15775 Annex G
3	28.33	0.0	0.0	0.04	21.49	0.0	0.0	-6.83	0.0	and DIN 33866-1 Annex G
4	33.49	0.0	0.0	0.08	24.5	0.0	0.0	-8.98	0.0	
5	38.65	0.0	0.0	0.13	28.12	0.0	0.0	-10.52	0.0	
6	43.81	0.0	0.0	0.18	32.26	0.0	0.0	-11.53	0.0	
7	48.97	0.0	0.0	0.24	36.89	0.0	0.0	-12.07	0.0	
8	54.13	0.0	0.0	0.31	41.94	0.0	0.0	-12.18	0.0	
9	59.29	0.0	0.0	0.38	47.41	0.0	0.0	-11.87	0.0	
10	64.45	0.0	0.0	0.46	53.25	0.0	0.0	-11.19	0.0	
11	69.61	0.0	0.0	0.54	59.46	0.0	0.0	-10.14	0.0	
12	74.77	0.0	0.0	0.62	66.02	0.0	0.0	-8.74	0.0	
13	79.93	0.0	0.0	0.71	72.9	0.0	0.0	-7.02	0.0	
14	85.09	0.0	0.0	0.8	80.1	0.0	0.0	-4.98	0.0	
15	90.25	0.0	0.0	0.9	87.61	0.0	0.0	-2.63	0.0	Mean lightness difference (16 steps)
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	$\Delta E^*_{\text{CIELAB}} = 7.7$
17	18.01	0.0	0.0	18.01	0.0	0.0	0.0	0.0	0.01	
18	37.36	0.0	0.0	0.12	27.16	0.0	0.0	-10.19	0.0	
19	56.71	0.0	0.0	0.34	44.63	0.0	0.0	-12.07	0.0	
20	76.06	0.0	0.0	0.64	67.71	0.0	0.0	-8.34	0.0	Mean lightness difference (5 steps)
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.01	$\Delta L^*_{\text{CIELAB}} = 6.1$
Mean colour reproduction index:					$R^*_{ab,m} = 66$					

OE860-3N-133-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE861-3N-133-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	18.0/2.5	23.2/3.8	28.3/5.6	33.5/7.8	38.6/10.5	43.8/13.7	49.0/17.6	54.1/22.1	59.3/27.3	64.4/33.4	69.6/40.2	74.8/47.9	79.9/56.6	85.1/66.2	90.2/76.8	95.4/88.6
$w^* w^* w^*$ setrgb $g_N=1.54$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{\text{CIELAB},r}$ (relative)																
w^*_{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.016	0.045	0.084	0.131	0.184	0.244	0.31	0.379	0.455	0.536	0.62	0.709	0.803	0.899	1.0

OE860-7N, Picture A7-133-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE86: In-output relation according to ISO 9241-306; 1MR, DEH input: $rgb \rightarrow rgb^*_{de}$ setrgbcolor
Viewing Y contrast $Y_W:Y_N=88,9:2,5$; Y_N range 1,87 to <3,75 output 130-2: $g_P=1.0$; $g_N=1.29$

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*
1	26.85 0.0 0.0	0.0 26.85 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	31.42 0.0 0.0	0.01 27.5 0.0	0.0 -3.91 0.0	0.0 0.0 0.0	3.92
3	35.99 0.0 0.0	0.03 28.99 0.0	0.0 -6.99 0.0	0.0 0.0 0.0	7.0
4	40.56 0.0 0.0	0.06 31.15 0.0	0.0 -9.4 0.0	0.0 0.0 0.0	9.41
5	45.13 0.0 0.0	0.1 33.91 0.0	0.0 -11.21 0.0	0.0 0.0 0.0	11.22
6	49.7 0.0 0.0	0.15 37.21 0.0	0.0 -12.48 0.0	0.0 0.0 0.0	12.49
7	54.27 0.0 0.0	0.21 41.03 0.0	0.0 -13.24 0.0	0.0 0.0 0.0	13.25
8	58.84 0.0 0.0	0.27 45.33 0.0	0.0 -13.5 0.0	0.0 0.0 0.0	13.51
9	63.41 0.0 0.0	0.34 50.1 0.0	0.0 -13.3 0.0	0.0 0.0 0.0	13.31
10	67.99 0.0 0.0	0.42 55.33 0.0	0.0 -12.65 0.0	0.0 0.0 0.0	12.66
11	72.56 0.0 0.0	0.5 60.98 0.0	0.0 -11.56 0.0	0.0 0.0 0.0	11.57
12	77.13 0.0 0.0	0.59 67.06 0.0	0.0 -10.05 0.0	0.0 0.0 0.0	10.06
13	81.7 0.0 0.0	0.68 73.56 0.0	0.0 -8.13 0.0	0.0 0.0 0.0	8.14
14	86.27 0.0 0.0	0.78 80.45 0.0	0.0 -5.81 0.0	0.0 0.0 0.0	5.82
15	90.84 0.0 0.0	0.89 87.74 0.0	0.0 -3.09 0.0	0.0 0.0 0.0	3.1
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
17	26.85 0.0 0.0	0.0 26.85 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	43.99 0.0 0.0	0.09 33.17 0.0	0.0 -10.81 0.0	0.0 0.0 0.0	10.82
19	61.13 0.0 0.0	0.3 47.66 0.0	0.0 -13.46 0.0	0.0 0.0 0.0	13.47
20	78.27 0.0 0.0	0.61 68.65 0.0	0.0 -9.61 0.0	0.0 0.0 0.0	9.62
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01


Start output S1
Specification according to
ISO/IEC 15775 Annex G
and DIN 33866-1 Annex G

Mean lightness difference (16 steps)
 $\Delta E^*_{\text{CIELAB}} = 8.5$

Mean lightness difference (5 steps)
 $\Delta L^*_{\text{CIELAB}} = 6.8$

Mean colour reproduction index: $R^*_{ab,m} = 63$

OE860-3N-134-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE861-3N-134-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolute)	26.8/5.0	31.4/6.8	36.0/9.0	40.6/11.6	45.1/14.6	49.7/18.2	54.3/22.2	58.8/26.9	63.4/32.1	68.0/38.0	72.6/44.5	77.1/51.7	81.7/59.7	86.3/68.5	90.8/78.1	95.4/88.6
$w^* w^* w^*$ setrgb $g_N=1.72$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{\text{CIELAB},r}$ (relative)	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{intended} w^*_{out}	0.000	0.01	0.031	0.063	0.103	0.151	0.207	0.27	0.339	0.415	0.498	0.586	0.681	0.782	0.888	1.0

OE860-7N, Picture A7-134-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor


OE86: In-output relation according to ISO 9241-306; 1MR, DEH input: $rgb \rightarrow rgb^*_{de}$ setrgbcolor
Viewing Y contrast $Y_W:Y_N=88,9:5$; Y_N range 3,75 to <7,5 output 130-2: $g_P=1.0$; $g_N=1.42$

TUB registration: 20110801-OE86/OE86L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*
1	37.99 0.0 0.0	0.0 37.99 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	41.81 0.0 0.0	0.01 38.32 0.0	0.0 0.0 -3.48	0.0 0.0 0.0	3.49
3	45.64 0.0 0.0	0.02 39.23 0.0	0.0 0.0 -6.4	0.0 0.0 0.0	6.41
4	49.47 0.0 0.0	0.05 40.68 0.0	0.0 0.0 -8.78	0.0 0.0 0.0	8.79
5	53.3 0.0 0.0	0.08 42.65 0.0	0.0 0.0 -10.64	0.0 0.0 0.0	10.65
6	57.13 0.0 0.0	0.12 45.11 0.0	0.0 0.0 -12.01	0.0 0.0 0.0	12.02
7	60.96 0.0 0.0	0.18 48.06 0.0	0.0 0.0 -12.89	0.0 0.0 0.0	12.9
8	64.78 0.0 0.0	0.24 51.48 0.0	0.0 0.0 -13.29	0.0 0.0 0.0	13.3
9	68.61 0.0 0.0	0.3 55.38 0.0	0.0 0.0 -13.22	0.0 0.0 0.0	13.23
10	72.44 0.0 0.0	0.38 59.74 0.0	0.0 0.0 -12.69	0.0 0.0 0.0	12.7
11	76.27 0.0 0.0	0.46 64.56 0.0	0.0 0.0 -11.69	0.0 0.0 0.0	11.7
12	80.1 0.0 0.0	0.55 69.84 0.0	0.0 0.0 -10.25	0.0 0.0 0.0	10.26
13	83.93 0.0 0.0	0.65 75.57 0.0	0.0 0.0 -8.35	0.0 0.0 0.0	8.36
14	87.75 0.0 0.0	0.76 81.74 0.0	0.0 0.0 -6.0	0.0 0.0 0.0	6.01
15	91.58 0.0 0.0	0.88 88.35 0.0	0.0 0.0 -3.22	0.0 0.0 0.0	3.23
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (16 steps)					
17	37.99 0.0 0.0	0.0 37.99 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	52.34 0.0 0.0	0.07 42.11 0.0	0.0 0.0 -10.22	0.0 0.0 0.0	10.23
19	66.7 0.0 0.0	0.27 53.37 0.0	0.0 0.0 -13.32	0.0 0.0 0.0	13.33
20	81.05 0.0 0.0	0.58 71.23 0.0	0.0 0.0 -9.81	0.0 0.0 0.0	9.82
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
Mean lightness difference (5 steps)					
Mean colour reproduction index: $R^*_{ab,m} = 64$					

OE860-3N-135-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE861-3N-135-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolute)	38.0/10.1	41.8/12.4	45.6/15.0	49.5/18.0	53.3/21.3	57.1/25.1	61.0/29.2	64.8/33.8	68.6/38.8	72.4/44.3	76.3/50.3	80.1/56.9	83.9/63.9	87.8/71.6	91.6/79.8	95.4/88.6
$w^* w^* w^*$ setrgb $g_N=1.9$																
No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*$ CIELAB, r (relative)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0,0	0,006	0,022	0,047	0,081	0,124	0,175	0,235	0,303	0,379	0,463	0,554	0,654	0,762	0,877	1,0

OE860-7N, Picture A7-135-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor


OE86: In-output relation according to ISO 9241-306; 1MR, DEH input: $rgb \rightarrow rgb^*_{de}$ setrgbcolor
Viewing Y contrast $Y_W:Y_N=88,9:10$; Y_N range 7,5 to <15 output 130-2: $g_P=1.0$; $g_N=1.6$

TUB registration: 20110801-OE86/OE86L0NA.TXT /.PS
application for output of displays: monitor systems or data projector systems
TUB material: code=rh4ta

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref	l*out			LAB*out			LAB*out/c-ref			ΔE*	Start output S1
1	52.02 0.0 0.0	0.0	0.0	52.02 0.0 0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G
2	54.91 0.0 0.0	0.0	0.0	52.17 0.0 0.0	0.0	0.0	-2.73 0.0 0.0	2.74				
3	57.8 0.0 0.0	0.0	0.02	52.67 0.0 0.0	0.0	0.0	-5.12 0.0 0.0	5.13				
4	60.7 0.0 0.0	0.0	0.04	53.54 0.0 0.0	0.0	0.0	-7.14 0.0 0.0	7.15				
5	63.59 0.0 0.0	0.0	0.06	54.79 0.0 0.0	0.0	0.0	-8.79 0.0 0.0	8.8				
6	66.48 0.0 0.0	0.0	0.1	56.43 0.0 0.0	0.0	0.0	-10.04 0.0 0.0	10.05				
7	69.37 0.0 0.0	0.0	0.15	58.47 0.0 0.0	0.0	0.0	-10.89 0.0 0.0	10.9				
8	72.27 0.0 0.0	0.0	0.2	60.91 0.0 0.0	0.0	0.0	-11.35 0.0 0.0	11.36				
9	75.16 0.0 0.0	0.0	0.27	63.75 0.0 0.0	0.0	0.0	-11.4 0.0 0.0	11.41				
10	78.05 0.0 0.0	0.0	0.35	67.01 0.0 0.0	0.0	0.0	-11.03 0.0 0.0	11.04				
11	80.95 0.0 0.0	0.0	0.43	70.69 0.0 0.0	0.0	0.0	-10.25 0.0 0.0	10.26				
12	83.84 0.0 0.0	0.0	0.52	74.78 0.0 0.0	0.0	0.0	-9.05 0.0 0.0	9.06				
13	86.73 0.0 0.0	0.0	0.63	79.3 0.0 0.0	0.0	0.0	-7.42 0.0 0.0	7.43				
14	89.62 0.0 0.0	0.0	0.74	84.24 0.0 0.0	0.0	0.0	-5.38 0.0 0.0	5.39				
15	92.52 0.0 0.0	0.0	0.87	89.61 0.0 0.0	0.0	0.0	-2.9 0.0 0.0	2.91	Mean lightness difference (16 steps)			
16	95.41 0.0 0.0	0.0	1.0	95.41 0.0 0.0	0.0	0.0	0.0 0.0 0.0	0.0	0.01	ΔE*CIELAB = 7.1		
17	52.02 0.0 0.0	0.0	0.0	52.02 0.0 0.0	0.0	0.0	0.0 0.0 0.0	0.0	0.01			
18	62.87 0.0 0.0	0.0	0.06	54.44 0.0 0.0	0.0	0.0	-8.41 0.0 0.0	0.0	8.42			
19	73.71 0.0 0.0	0.0	0.24	62.28 0.0 0.0	0.0	0.0	-11.42 0.0 0.0	0.0	11.43			
20	84.56 0.0 0.0	0.0	0.55	75.87 0.0 0.0	0.0	0.0	-8.68 0.0 0.0	0.0	8.69	Mean lightness difference (5 steps)		
21	95.41 0.0 0.0	0.0	1.0	95.41 0.0 0.0	0.0	0.0	0.0 0.0 0.0	0.0	0.01	ΔL*CIELAB = 5.7		
Mean colour reproduction index:											R*ab,m = 69	

OE860-3N-136-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE861-3N-136-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolute)	52.0/20.2	54.9/22.8	57.8/25.8	60.7/28.9	63.6/32.3	66.5/36.0	69.4/39.9	72.3/44.1	75.2/48.5	78.1/53.3	80.9/58.4	83.8/63.8	86.7/69.5	89.6/75.5	92.5/81.9	95.4/88.6
$w^* w^* w^*$ setrgb $g_N=2.08$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{CIELAB, r}$ (relative)	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
$w^*_{intended}$ w^*_{out}	0.000	0.004	0.015	0.035	0.064	0.102	0.149	0.205	0.27	0.346	0.431	0.524	0.629	0.743	0.866	1.0


OE860-7N, Picture A7-136-2: 16 visual equidistant L^* -grey steps; PS operator: $w^* w^* w^*$ setrgbcolor

OE86: In-output relation according to ISO 9241-306; 1MR, DEH input: $rgb \rightarrow rgb^*_{de}$ setrgbcolor
Viewing Y contrast $Y_W:Y_N=88,9:20$; Y_N range 15 to <30 output 130-2: $g_P=1.0$; $g_N=1.81$

See similar ISO test charts: <http://www.ps.bam.de/24705TE>, <http://www.ps.bam.de/9241E>
Technical information: <http://www.ps.bam.de/33872E> Version 2.1, io=1,1, CIELAB

i	LAB*ref			l*out			LAB*out			LAB*out/c-ref			ΔE*	Start output S1
1	69.7	0.0	0.0	0.0	69.7	0.0	0.0	0.0	0.0	0.0	0.0	0.01	Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G	
2	71.41	0.0	0.0	0.0	69.75	0.0	0.0	-1.65	0.0	0.0	1.66			
3	73.13	0.0	0.0	0.01	69.97	0.0	0.0	-3.15	0.0	0.0	3.16			
4	74.84	0.0	0.0	0.03	70.37	0.0	0.0	-4.46	0.0	0.0	4.47			
5	76.55	0.0	0.0	0.05	70.99	0.0	0.0	-5.55	0.0	0.0	5.56			
6	78.27	0.0	0.0	0.08	71.84	0.0	0.0	-6.41	0.0	0.0	6.42			
7	79.98	0.0	0.0	0.13	72.94	0.0	0.0	-7.03	0.0	0.0	7.04			
8	81.7	0.0	0.0	0.18	74.29	0.0	0.0	-7.4	0.0	0.0	7.41			
9	83.41	0.0	0.0	0.24	75.91	0.0	0.0	-7.49	0.0	0.0	7.5			
10	85.12	0.0	0.0	0.32	77.8	0.0	0.0	-7.31	0.0	0.0	7.32			
11	86.84	0.0	0.0	0.4	79.98	0.0	0.0	-6.85	0.0	0.0	6.86			
12	88.55	0.0	0.0	0.5	82.45	0.0	0.0	-6.09	0.0	0.0	6.1			
13	90.27	0.0	0.0	0.6	85.23	0.0	0.0	-5.03	0.0	0.0	5.04			
14	91.98	0.0	0.0	0.72	88.3	0.0	0.0	-3.67	0.0	0.0	3.68			
15	93.7	0.0	0.0	0.86	91.7	0.0	0.0	-1.99	0.0	0.0	2.0	Mean lightness difference (16 steps)		
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.01	ΔE*CIELAB = 4.6		
17	69.7	0.0	0.0	0.0	69.7	0.0	0.0	0.0	0.0	0.0	0.01			
18	76.13	0.0	0.0	0.04	70.82	0.0	0.0	-5.3	0.0	0.0	5.31			
19	82.55	0.0	0.0	0.21	75.07	0.0	0.0	-7.48	0.0	0.0	7.49			
20	88.98	0.0	0.0	0.52	83.12	0.0	0.0	-5.85	0.0	0.0	5.86	Mean lightness difference (5 steps)		
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.0	0.01	ΔL*CIELAB = 3.7		
Mean colour reproduction index:													R*ab,m = 80	

OE860-3N-137-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OE861-3N-137-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^{*}/Y_{intended}$ (absolute)	69.7/40.3	71.4/42.8	73.1/45.4	74.8/48.0	76.6/50.8	78.3/53.7	80.0/56.6	81.7/59.7	83.4/62.9	85.1/66.3	86.8/69.7	88.6/73.2	90.3/76.9	92.0/80.7	93.7/84.6	95.4/88.6
$w^{*}w^{*}w^{*}$ setrgb $g_N=2.26$ No. and Hex code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^{*}=l^{*}$ _{CIELAB, r} (relative)	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
$w^{*}_{intended}$ w^{*}_{out}	0.000 0.0	0.067 0.002	0.133 0.01	0.200 0.026	0.267 0.051	0.333 0.083	0.400 0.126	0.467 0.179	0.533 0.241	0.600 0.315	0.667 0.4	0.733 0.496	0.800 0.604	0.867 0.724	0.933 0.855	1.000 1.0

OE860-7N, Picture A7-137-2: 16 visual equidistant L^{*} -grey steps; PS operator: $w^{*}w^{*}w^{*}$ setrgbcolor

OE86: In-output relation according to ISO 9241-306; 1MR, DEH input: $rgb \rightarrow rgb^{*}_{de}$ setrgbcolor
Viewing Y contrast $Y_W:Y_N=88,9:40$; Y_N range 30 to <60 output 130-2: $g_P=1.0$; $g_N=2.1$