


i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	0.0	0.0	0.0	0.0	0.0	Kennzeichnung nach
2	6.36	0.0	0.07	6.36	0.0	ISO/IEC 15775 Anhang G
3	12.72	0.0	0.13	12.72	0.0	und DIN 33866-1 Anhang G
4	19.08	0.0	0.2	19.08	0.0	
5	25.44	0.0	0.27	25.44	0.0	
6	31.8	0.0	0.33	31.8	0.0	
7	38.16	0.0	0.4	38.16	0.0	
8	44.52	0.0	0.47	44.52	0.0	
9	50.89	0.0	0.53	50.89	0.0	
10	57.25	0.0	0.6	57.25	0.0	
11	63.61	0.0	0.67	63.61	0.0	
12	69.97	0.0	0.73	69.97	0.0	
13	76.33	0.0	0.8	76.33	0.0	
14	82.69	0.0	0.87	82.69	0.0	
15	89.05	0.0	0.93	89.05	0.0	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41	0.0	1.0	95.41	0.0	ΔE*CIELAB = 0.0
17	0.0	0.0	0.0	0.0	0.0	
18	23.85	0.0	0.25	23.85	0.0	
19	47.71	0.0	0.5	47.71	0.0	
20	71.56	0.0	0.75	71.56	0.0	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41	0.0	1.0	95.41	0.0	ΔL*CIELAB = 0.0
Mittlerer Farbwiedergabe-Index:					R* _{ab,m} = 100	

OG530-3N-130-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG531-3N-130-2: File: Measure unknown; Device: Device unknown; Date: Date unknown


$L^*/Y^*_{\text{intended}}$ (absolut)	0.0/0.0	6.4/0.7	12.7/1.5	19.1/2.8	25.4/4.6	31.8/7.0	38.2/10.2	44.5/14.2	50.9/19.2	57.2/25.2	63.6/32.3	70.0/40.7	76.3/50.4	82.7/61.6	89.0/74.3	95.4/88.6
$w^* w^* w^*$ setrgb $g_P=1.0$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = [L^*_{\text{CIELAB}}]^r$ (relativ)																
w^*_{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.067	0.133	0.2	0.267	0.333	0.4	0.467	0.533	0.6	0.667	0.733	0.8	0.867	0.933	1.0

OG530-7N, Bild A7-130-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* \text{setrgbcolor}$

OG53: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH Eingabe: $rgb \rightarrow rgb_d$ setrgbcolor
Gesehener Y-Kontrast $Y_W:Y_N=88,9:0,31$; Y_N -Bereich 0,0 to <0,46Ausgabe 130-2: $g_P=1.0$; $g_N=1.0$

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	5.69	0.0	0.0	5.69	0.0	0.0
2	11.67	0.0	0.05	10.49	0.0	1.18
3	17.65	0.0	0.11	15.85	0.0	1.8
4	23.63	0.0	0.18	21.44	0.0	2.2
5	29.62	0.0	0.24	27.18	0.0	2.43
6	35.6	0.0	0.3	33.05	0.0	2.55
7	41.58	0.0	0.37	39.01	0.0	2.57
8	47.56	0.0	0.44	45.05	0.0	2.51
9	53.54	0.0	0.51	51.16	0.0	2.38
10	59.52	0.0	0.58	57.34	0.0	2.18
11	65.5	0.0	0.65	63.57	0.0	1.93
12	71.48	0.0	0.72	69.85	0.0	1.63
13	77.47	0.0	0.79	76.18	0.0	1.29
14	83.45	0.0	0.86	82.55	0.0	0.9
15	89.43	0.0	0.93	88.96	0.0	0.47
16	95.41	0.0	1.0	95.41	0.0	0.01
17	5.69	0.0	0.0	5.69	0.0	0.01
18	28.12	0.0	0.22	25.74	0.0	2.38
19	50.55	0.0	0.47	48.1	0.0	2.45
20	72.98	0.0	0.73	71.43	0.0	1.55
21	95.41	0.0	1.0	95.41	0.0	0.01
Mittlerer Helligkeitsabstand (16 Stufen)					ΔE*CIELAB =	1.6
Mittlerer Helligkeitsabstand (5 Stufen)					ΔL*CIELAB =	1.3
Mittlerer Farbwiedergabe-Index:					R* _{ab,m} =	93

OG530-3N-131-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG531-3N-131-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolut)	5.7/0.6	11.7/1.4	17.7/2.4	23.6/4.0	29.6/6.1	35.6/8.8	41.6/12.2	47.6/16.5	53.5/21.5	59.5/27.6	65.5/34.7	71.5/42.9	77.5/52.3	83.4/63.0	89.4/75.1	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_N=1.08$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=L^*_{\text{CIELAB}, r}$ (relativ)																
w^*_{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.054	0.113	0.176	0.24	0.305	0.371	0.439	0.506	0.576	0.645	0.715	0.786	0.857	0.928	1.0

OG530-7N, Bild A7-131-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* \text{setrgbcolor}$

OG53: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH Eingabe: $rgb \rightarrow rgb^*_d$ setrgbcolor
Gesehener Y-Kontrast $Y_W:Y_N=88,9:0,62$; Y_N -Bereich 0,46 to <0,9 Ausgabe 130-2: $g_P=1,0$; $g_N=1,08$


i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	10.99	0.0	0.0	10.99	0.0	0.0
2	16.62	0.0	0.04	14.48	0.0	0.0
3	22.25	0.0	0.09	18.88	0.0	0.0
4	27.88	0.0	0.15	23.7	0.0	0.0
5	33.5	0.0	0.21	28.82	0.0	0.0
6	39.13	0.0	0.27	34.17	0.0	0.0
7	44.76	0.0	0.34	39.72	0.0	0.0
8	50.39	0.0	0.41	45.43	0.0	0.0
9	56.02	0.0	0.48	51.29	0.0	0.0
10	61.64	0.0	0.55	57.28	0.0	0.0
11	67.27	0.0	0.62	63.38	0.0	0.0
12	72.9	0.0	0.69	69.6	0.0	0.0
13	78.53	0.0	0.77	75.92	0.0	0.0
14	84.15	0.0	0.85	82.33	0.0	0.0
15	89.78	0.0	0.92	88.83	0.0	0.0
16	95.41	0.0	1.0	95.41	0.0	0.0
17	10.99	0.0	0.0	10.99	0.0	0.0
18	32.1	0.0	0.2	27.52	0.0	0.0
19	53.2	0.0	0.44	48.34	0.0	0.0
20	74.31	0.0	0.71	71.17	0.0	0.0
21	95.41	0.0	1.0	95.41	0.0	0.0

Mittlerer Helligkeitsabstand (16 Stufen) $\Delta E^*_{CIELAB} = 3.2$

Mittlerer Helligkeitsabstand (5 Stufen) $\Delta L^*_{CIELAB} = 2.5$

Mittlerer Farbwiedergabe-Index: $R^*_{ab,m} = 86$

OG530-3N-132-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG531-3N-132-2: File: Measure unknown; Device: Device unknown; Date: Date unknown


$L^*/Y^*_{intended}$ (absolut)	11.0/1.3	16.6/2.2	22.2/3.6	27.9/5.4	33.5/7.8	39.1/10.7	44.8/14.4	50.4/18.7	56.0/23.9	61.6/30.0	67.3/37.0	72.9/45.0	78.5/54.1	84.2/64.4	89.8/75.8	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_N=1.18$ Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{CIELAB, r}$ (relativ)																
$w^*_{intended}$	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.042	0.093	0.151	0.211	0.274	0.34	0.408	0.477	0.548	0.621	0.694	0.769	0.845	0.922	1.0

OG530-7N, Bild A7-132-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* \text{setrgbcolor}$

OG53: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH Eingabe: $rgb \rightarrow rgb^*_d$ setrgbcolor
Gesehener Y-Kontrast $Y_W:Y_N=88,9:1,25$; Y_N -Bereich 0,93 to <1,8 Ausgabe 130-2: $g_P=1.0$; $g_N=1.17$

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	18.01	0.0	0.0	0.0	0.0	Kennzeichnung nach
2	23.17	0.0	0.03	-2.8	0.0	ISO/IEC 15775 Anhang G
3	28.33	0.0	0.07	-4.56	0.0	und DIN 33866-1 Anhang G
4	33.49	0.0	0.13	-5.77	0.0	
5	38.65	0.0	0.18	-6.57	0.0	
6	43.81	0.0	0.24	-7.04	0.0	
7	48.97	0.0	0.31	-7.22	0.0	
8	54.13	0.0	0.37	-7.16	0.0	
9	59.29	0.0	0.44	-6.88	0.0	
10	64.45	0.0	0.52	-6.39	0.0	
11	69.61	0.0	0.59	-5.72	0.0	
12	74.77	0.0	0.67	-4.88	0.0	
13	79.93	0.0	0.75	-3.87	0.0	
14	85.09	0.0	0.83	-2.72	0.0	
15	90.25	0.0	0.91	-1.42	0.0	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41	0.0	1.0	0.0	0.0	ΔE*CIELAB = 4.6
17	18.01	0.0	0.0	0.0	0.0	
18	37.36	0.0	0.17	-6.4	0.0	
19	56.71	0.0	0.41	-7.04	0.0	
20	76.06	0.0	0.69	-4.64	0.0	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41	0.0	1.0	0.0	0.0	ΔL*CIELAB = 3.6
Mittlerer Farbwiedergabe-Index:					R* _{ab,m} = 80	

OG530-3N-133-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG531-3N-133-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y^*_{\text{intended}}$ (absolut)	18.0/2.5	23.2/3.8	28.3/5.6	33.5/7.8	38.6/10.5	43.8/13.7	49.0/17.6	54.1/22.1	59.3/27.3	64.4/33.4	69.6/40.2	74.8/47.9	79.9/56.6	85.1/66.2	90.2/76.8	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_N=1.29$ Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{\text{CIELAB}, r}$ (relativ)																
w^*_{intended}	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.031	0.074	0.125	0.182	0.242	0.307	0.374	0.444	0.517	0.593	0.67	0.75	0.832	0.914	1.0

OG530-7N, Bild A7-133-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* \text{setrgbcolor}$

OG53: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH Eingabe: $rgb \rightarrow rgb^*_d$ setrgbcolor
Gesehener Y-Kontrast $Y_W:Y_N=88,9:2,5$; Y_N -Bereich 1,87 to <3,75Ausgabe 130-2: $g_P=1.0$; $g_N=1.29$


i	LAB*ref	I*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	26.85	0.0	0.0	26.85	0.0	0.0
2	31.42	0.0	0.02	28.28	0.0	0.0
3	35.99	0.0	0.06	30.7	0.0	0.0
4	40.56	0.0	0.1	33.73	0.0	0.0
5	45.13	0.0	0.15	37.22	0.0	0.0
6	49.7	0.0	0.21	41.12	0.0	0.0
7	54.27	0.0	0.27	45.37	0.0	0.0
8	58.84	0.0	0.34	49.93	0.0	0.0
9	63.41	0.0	0.41	54.78	0.0	0.0
10	67.99	0.0	0.48	59.9	0.0	0.0
11	72.56	0.0	0.56	65.27	0.0	0.0
12	77.13	0.0	0.64	70.87	0.0	0.0
13	81.7	0.0	0.73	76.7	0.0	0.0
14	86.27	0.0	0.82	82.73	0.0	0.0
15	90.84	0.0	0.91	88.97	0.0	0.0
16	95.41	0.0	1.0	95.41	0.0	0.0
17	26.85	0.0	0.0	26.85	0.0	0.0
18	43.99	0.0	0.14	36.31	0.0	0.0
19	61.13	0.0	0.37	52.32	0.0	0.0
20	78.27	0.0	0.66	72.31	0.0	0.0
21	95.41	0.0	1.0	95.41	0.0	0.0

Mittlerer Helligkeitsabstand (16 Stufen) $\Delta E^*_{CIELAB} = 5.6$

Mittlerer Helligkeitsabstand (5 Stufen) $\Delta E^*_{CIELAB} = 4.5$

Mittlerer Farbwiedergabe-Index: $R^*_{ab,m} = 75$

OG530-3N-134-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG531-3N-134-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y^*_{intended}$ (absolut)	26.8/5.0	31.4/6.8	36.0/9.0	40.6/11.6	45.1/14.6	49.7/18.2	54.3/22.2	58.8/26.9	63.4/32.1	68.0/38.0	72.6/44.5	77.1/51.7	81.7/59.7	86.3/68.5	90.8/78.1	95.4/88.6
$w^* w^* w^*$ setrgb $g_N=1.43$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = I^*_{CIELAB, r}$ (relativ)																
$w^*_{intended}$	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.021	0.056	0.1	0.152	0.208	0.27	0.337	0.407	0.482	0.561	0.642	0.727	0.816	0.906	1.0

OG530-7N, Bild A7-134-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* setrgbcolor$

OG53: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH
Gesehener Y-Kontrast $Y_W:Y_N=88,9:5$; Y_N -Bereich 3,75 to <7,5

Eingabe: $rgb (-> rgb^*_d) setrgbcolor$
Ausgabe 130-2: $g_P=1.0$; $g_N=1.42$


i	LAB*ref	I*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	37.99	0.0	0.0	37.99	0.0	0.0
2	41.81	0.0	0.01	38.74	0.0	0.0
3	45.64	0.0	0.04	40.27	0.0	0.0
4	49.47	0.0	0.08	42.36	0.0	0.0
5	53.3	0.0	0.12	44.91	0.0	0.0
6	57.13	0.0	0.17	47.89	0.0	0.0
7	60.96	0.0	0.23	51.24	0.0	0.0
8	64.78	0.0	0.3	54.95	0.0	0.0
9	68.61	0.0	0.37	58.99	0.0	0.0
10	72.44	0.0	0.44	63.34	0.0	0.0
11	76.27	0.0	0.52	68.0	0.0	0.0
12	80.1	0.0	0.61	72.95	0.0	0.0
13	83.93	0.0	0.7	78.17	0.0	0.0
14	87.75	0.0	0.8	83.66	0.0	0.0
15	91.58	0.0	0.9	89.41	0.0	0.0
16	95.41	0.0	1.0	95.41	0.0	0.0
17	37.99	0.0	0.0	37.99	0.0	0.0
18	52.34	0.0	0.11	44.23	0.0	0.0
19	66.7	0.0	0.33	56.93	0.0	0.0
20	81.05	0.0	0.63	74.23	0.0	0.0
21	95.41	0.0	1.0	95.41	0.0	0.0

Mittlerer Helligkeitsabstand (16 Stufen) $\Delta E^*_{CIELAB} = 6.2$

Mittlerer Helligkeitsabstand (5 Stufen) $\Delta L^*_{CIELAB} = 4.9$

Mittlerer Farbwiedergabe-Index: $R^*_{ab,m} = 73$

OG530-3N-135-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG531-3N-135-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y^*_{intended}$ (absolut)	38.0/10.1	41.8/12.4	45.6/15.0	49.5/18.0	53.3/21.3	57.1/25.1	61.0/29.2	64.8/33.8	68.6/38.8	72.4/44.3	76.3/50.3	80.1/56.9	83.9/63.9	87.8/71.6	91.6/79.8	95.4/88.6
$w^* w^* w^*$ setrgb $g_N=1.6$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = l^*_{CIELAB, r}$ (relativ)																
$w^*_{intended}$	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.013	0.04	0.076	0.121	0.172	0.231	0.296	0.365	0.442	0.523	0.608	0.7	0.796	0.895	1.0


OG530-7N, Bild A7-135-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* \text{setrgbcolor}$

OG53: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH
Gesehener Y-Kontrast $Y_W:Y_N=88,9:10$; Y_N -Bereich 7,5 to <15

Eingabe: $rgb (-> rgb^*_d) \text{setrgbcolor}$
Ausgabe 130-2: $g_P=1.0$; $g_N=1.6$

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	52.02 0.0 0.0	0.0 0.0 0.0	52.02 0.0 0.0	0.0 0.0 0.0	0.01	Kennzeichnung nach
2	54.91 0.0 0.0	0.01 52.33 0.0	0.0 -2.57 0.0	0.0 0.0 0.0	2.58	ISO/IEC 15775 Anhang G
3	57.8 0.0 0.0	0.03 53.13 0.0	0.0 -4.66 0.0	0.0 0.0 0.0	4.67	und DIN 33866-1 Anhang G
4	60.7 0.0 0.0	0.05 54.34 0.0	0.0 -6.34 0.0	0.0 0.0 0.0	6.35	
5	63.59 0.0 0.0	0.09 55.94 0.0	0.0 -7.64 0.0	0.0 0.0 0.0	7.65	
6	66.48 0.0 0.0	0.14 57.9 0.0	0.0 -8.57 0.0	0.0 0.0 0.0	8.58	
7	69.37 0.0 0.0	0.19 60.22 0.0	0.0 -9.15 0.0	0.0 0.0 0.0	9.16	
8	72.27 0.0 0.0	0.25 62.87 0.0	0.0 -9.39 0.0	0.0 0.0 0.0	9.4	
9	75.16 0.0 0.0	0.32 65.85 0.0	0.0 -9.3 0.0	0.0 0.0 0.0	9.31	
10	78.05 0.0 0.0	0.4 69.16 0.0	0.0 -8.88 0.0	0.0 0.0 0.0	8.89	
11	80.95 0.0 0.0	0.48 72.78 0.0	0.0 -8.16 0.0	0.0 0.0 0.0	8.17	
12	83.84 0.0 0.0	0.57 76.71 0.0	0.0 -7.12 0.0	0.0 0.0 0.0	7.13	
13	86.73 0.0 0.0	0.67 80.94 0.0	0.0 -5.78 0.0	0.0 0.0 0.0	5.79	
14	89.62 0.0 0.0	0.77 85.47 0.0	0.0 -4.15 0.0	0.0 0.0 0.0	4.16	
15	92.52 0.0 0.0	0.88 90.29 0.0	0.0 -2.21 0.0	0.0 0.0 0.0	2.22	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	ΔE*CIELAB = 5.9
17	52.02 0.0 0.0	0.0 0.0 0.0	52.02 0.0 0.0	0.0 0.0 0.0	0.01	
18	62.87 0.0 0.0	0.08 55.51 0.0	0.0 -7.35 0.0	0.0 0.0 0.0	7.36	
19	73.71 0.0 0.0	0.28 64.32 0.0	0.0 -9.38 0.0	0.0 0.0 0.0	9.39	
20	84.56 0.0 0.0	0.59 77.74 0.0	0.0 -6.82 0.0	0.0 0.0 0.0	6.83	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	ΔL*CIELAB = 4.7
Mittlerer Farbwiedergabe-Index:					R* _{ab,m} = 74	

OG530-3N-136-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG531-3N-136-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

L^*/Y_{intended} (absolut)	52.0/20.2	54.9/22.8	57.8/25.8	60.7/28.9	63.6/32.3	66.5/36.0	69.4/39.9	72.3/44.1	75.2/48.5	78.1/53.3	80.9/58.4	83.8/63.8	86.7/69.5	89.6/75.5	92.5/81.9	95.4/88.6
$w^* w^* w^*$ setrgb																
$g_N=1.82$ Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*$ CIELAB, r (relativ)																
w^*_{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0,0	0,007	0,026	0,054	0,091	0,135	0,189	0,25	0,319	0,395	0,479	0,569	0,666	0,771	0,882	1,0


OG530-7N, Bild A7-136-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* \text{setrgbcolor}$

OG53: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH
Gesehener Y-Kontrast $Y_W:Y_N=88,9:20$; Y_N -Bereich 15 to <30

Eingabe: $rgb (->rgb_d) \text{setrgbcolor}$
Ausgabe 130-2: $g_P=1.0$; $g_N=1.81$

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	69.7 0.0 0.0	69.7 0.0 0.0	69.7 0.0 0.0	0.0 0.0 0.0	0.01	Kennzeichnung nach
2	71.41 0.0 0.0	71.41 0.0 0.0	71.41 0.0 0.0	-1.62 0.0 0.0	1.63	ISO/IEC 15775 Anhang G
3	73.13 0.0 0.0	73.13 0.0 0.0	73.13 0.0 0.0	-3.05 0.0 0.0	3.06	und DIN 33866-1 Anhang G
4	74.84 0.0 0.0	74.84 0.0 0.0	74.84 0.0 0.0	-4.26 0.0 0.0	4.27	
5	76.55 0.0 0.0	76.55 0.0 0.0	76.55 0.0 0.0	-5.26 0.0 0.0	5.27	
6	78.27 0.0 0.0	78.27 0.0 0.0	78.27 0.0 0.0	-6.02 0.0 0.0	6.03	
7	79.98 0.0 0.0	79.98 0.0 0.0	79.98 0.0 0.0	-6.54 0.0 0.0	6.55	
8	81.7 0.0 0.0	81.7 0.0 0.0	81.7 0.0 0.0	-6.82 0.0 0.0	6.83	
9	83.41 0.0 0.0	83.41 0.0 0.0	83.41 0.0 0.0	-6.86 0.0 0.0	6.87	
10	85.12 0.0 0.0	85.12 0.0 0.0	85.12 0.0 0.0	-6.65 0.0 0.0	6.66	
11	86.84 0.0 0.0	86.84 0.0 0.0	86.84 0.0 0.0	-6.18 0.0 0.0	6.19	
12	88.55 0.0 0.0	88.55 0.0 0.0	88.55 0.0 0.0	-5.46 0.0 0.0	5.47	
13	90.27 0.0 0.0	90.27 0.0 0.0	90.27 0.0 0.0	-4.49 0.0 0.0	4.5	
14	91.98 0.0 0.0	91.98 0.0 0.0	91.98 0.0 0.0	-3.25 0.0 0.0	3.26	
15	93.7 0.0 0.0	93.7 0.0 0.0	93.7 0.0 0.0	-1.75 0.0 0.0	1.76	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41 0.0 0.0	95.41 0.0 0.0	95.41 0.0 0.0	0.0 0.0 0.0	0.01	ΔE*CIELAB = 4.3
17	69.7 0.0 0.0	69.7 0.0 0.0	69.7 0.0 0.0	0.0 0.0 0.0	0.01	
18	76.13 0.0 0.0	76.13 0.0 0.0	76.13 0.0 0.0	-5.03 0.0 0.0	5.04	
19	82.55 0.0 0.0	82.55 0.0 0.0	82.55 0.0 0.0	-6.87 0.0 0.0	6.88	
20	88.98 0.0 0.0	88.98 0.0 0.0	88.98 0.0 0.0	-5.24 0.0 0.0	5.25	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41 0.0 0.0	95.41 0.0 0.0	95.41 0.0 0.0	0.0 0.0 0.0	0.01	ΔL*CIELAB = 3.4
Mittlerer Farbwiedergabe-Index:					R* _{ab,m} = 81	

OG530-3N-137-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG531-3N-137-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y^*_{\text{intended}}$ (absolut)	69.7/40.3	71.4/42.8	73.1/45.4	74.8/48.0	76.6/50.8	78.3/53.7	80.0/56.6	81.7/59.7	83.4/62.9	85.1/66.3	86.8/69.7	88.6/73.2	90.3/76.9	92.0/80.7	93.7/84.6	95.4/88.6
$w^* w^* w^*$ setrgb $g_N=2.11$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{\text{CIELAB},r}$ (relativ)																
w^*_{intended}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0,0	0,003	0,014	0,034	0,062	0,099	0,145	0,201	0,266	0,341	0,426	0,52	0,625	0,74	0,864	1,0

OG530-7N, Bild A7-137-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* \text{setrgbcolor}$

OG53: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH
Gesehener Y-Kontrast $Y_W:Y_N=88,9:40$; Y_N -Bereich 30 to <60

Eingabe: $rgb \rightarrow rgb^*_d$ setrgbcolor
Ausgabe 130-2: $g_P=1.0$; $g_N=2.1$