

i	LAB*ref		l*out		LAB*out		LAB*out/c-ref			ΔE*	Start-Ausgabe S1 Kennzeichnung nach ISO/IEC 15775 Anhang G und DIN 33866-1 Anhang G	
1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01		
2	6.36	0.0	0.0	0.07	6.36	0.0	0.0	0.0	0.0	0.01	Mittlerer Helligkeitsabstand (16 Stufen) ΔE*_{CIELAB} = 0.0	
3	12.72	0.0	0.0	0.13	12.72	0.0	0.0	0.0	0.0	0.01		
4	19.08	0.0	0.0	0.2	19.08	0.0	0.0	0.0	0.0	0.01		
5	25.44	0.0	0.0	0.27	25.44	0.0	0.0	0.0	0.0	0.01		
6	31.8	0.0	0.0	0.33	31.8	0.0	0.0	0.0	0.0	0.01		
7	38.16	0.0	0.0	0.4	38.16	0.0	0.0	0.0	0.0	0.01		
8	44.52	0.0	0.0	0.47	44.52	0.0	0.0	0.0	0.0	0.01		
9	50.89	0.0	0.0	0.53	50.89	0.0	0.0	0.0	0.0	0.01		
10	57.25	0.0	0.0	0.6	57.25	0.0	0.0	0.0	0.0	0.01		
11	63.61	0.0	0.0	0.67	63.61	0.0	0.0	0.0	0.0	0.01		
12	69.97	0.0	0.0	0.73	69.97	0.0	0.0	0.0	0.0	0.01		
13	76.33	0.0	0.0	0.8	76.33	0.0	0.0	0.0	0.0	0.01		
14	82.69	0.0	0.0	0.87	82.69	0.0	0.0	0.0	0.0	0.01		
15	89.05	0.0	0.0	0.93	89.05	0.0	0.0	0.0	0.0	0.01	Mittlerer Helligkeitsabstand (5 Stufen) ΔL*_{CIELAB} = 0.0	
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01		
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01		
18	23.85	0.0	0.0	0.25	23.85	0.0	0.0	0.0	0.0	0.01		
19	47.71	0.0	0.0	0.5	47.71	0.0	0.0	0.0	0.0	0.01		
20	71.56	0.0	0.0	0.75	71.56	0.0	0.0	0.0	0.0	0.01		
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01	Mittlerer Farbwiedergabe-Index: R*_{ab,m} = 100	

i	LAB*ref		l*out		LAB*out		LAB*out/c-ref			ΔE*	Start-Ausgabe S1	
1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	Kennzeichnung nach ISO/IEC 15775 Anhang G und DIN 33866-1 Anhang G	
2	6.36	0.0	0.0	0.07	6.36	0.0	0.0	0.0	0.0	0.01		
3	12.72	0.0	0.0	0.13	12.72	0.0	0.0	0.0	0.0	0.01		
4	19.08	0.0	0.0	0.2	19.08	0.0	0.0	0.0	0.0	0.01		
5	25.44	0.0	0.0	0.27	25.44	0.0	0.0	0.0	0.0	0.01		
6	31.8	0.0	0.0	0.33	31.8	0.0	0.0	0.0	0.0	0.01		
7	38.16	0.0	0.0	0.4	38.16	0.0	0.0	0.0	0.0	0.01		
8	44.52	0.0	0.0	0.47	44.52	0.0	0.0	0.0	0.0	0.01		
9	50.89	0.0	0.0	0.53	50.89	0.0	0.0	0.0	0.0	0.01		
10	57.25	0.0	0.0	0.6	57.25	0.0	0.0	0.0	0.0	0.01		
11	63.61	0.0	0.0	0.67	63.61	0.0	0.0	0.0	0.0	0.01		
12	69.97	0.0	0.0	0.73	69.97	0.0	0.0	0.0	0.0	0.01		
13	76.33	0.0	0.0	0.8	76.33	0.0	0.0	0.0	0.0	0.01		
14	82.69	0.0	0.0	0.87	82.69	0.0	0.0	0.0	0.0	0.01		
15	89.05	0.0	0.0	0.93	89.05	0.0	0.0	0.0	0.0	0.01	Mittlerer Helligkeitsabstand (16 Stufen)	
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01		
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	Mittlerer Helligkeitsabstand (5 Stufen)	
18	23.85	0.0	0.0	0.25	23.85	0.0	0.0	0.0	0.0	0.01		
19	47.71	0.0	0.0	0.5	47.71	0.0	0.0	0.0	0.0	0.01		
20	71.56	0.0	0.0	0.75	71.56	0.0	0.0	0.0	0.0	0.01		
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01		
Mittlerer Farbwiedergabe-Index:										R* _{ab,m} = 100		

i	LAB*ref		l*out		LAB*out		LAB*out/c-ref			ΔE*	Start-Ausgabe S1 Kennzeichnung nach ISO/IEC 15775 Anhang G und DIN 33866-1 Anhang G	
1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01		
2	6.36	0.0	0.0	0.07	6.36	0.0	0.0	0.0	0.0	0.01	Mittlerer Helligkeitsabstand (16 Stufen) ΔE*_{CIELAB} = 0.0	
3	12.72	0.0	0.0	0.13	12.72	0.0	0.0	0.0	0.0	0.01		
4	19.08	0.0	0.0	0.2	19.08	0.0	0.0	0.0	0.0	0.01		
5	25.44	0.0	0.0	0.27	25.44	0.0	0.0	0.0	0.0	0.01		
6	31.8	0.0	0.0	0.33	31.8	0.0	0.0	0.0	0.0	0.01		
7	38.16	0.0	0.0	0.4	38.16	0.0	0.0	0.0	0.0	0.01		
8	44.52	0.0	0.0	0.47	44.52	0.0	0.0	0.0	0.0	0.01		
9	50.89	0.0	0.0	0.53	50.89	0.0	0.0	0.0	0.0	0.01		
10	57.25	0.0	0.0	0.6	57.25	0.0	0.0	0.0	0.0	0.01		
11	63.61	0.0	0.0	0.67	63.61	0.0	0.0	0.0	0.0	0.01		
12	69.97	0.0	0.0	0.73	69.97	0.0	0.0	0.0	0.0	0.01		
13	76.33	0.0	0.0	0.8	76.33	0.0	0.0	0.0	0.0	0.01		
14	82.69	0.0	0.0	0.87	82.69	0.0	0.0	0.0	0.0	0.01		
15	89.05	0.0	0.0	0.93	89.05	0.0	0.0	0.0	0.0	0.01	Mittlerer Helligkeitsabstand (5 Stufen) ΔL*_{CIELAB} = 0.0	
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01		
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01		
18	23.85	0.0	0.0	0.25	23.85	0.0	0.0	0.0	0.0	0.01		
19	47.71	0.0	0.0	0.5	47.71	0.0	0.0	0.0	0.0	0.01		
20	71.56	0.0	0.0	0.75	71.56	0.0	0.0	0.0	0.0	0.01		
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01	Mittlerer Farbwiedergabe-Index: R*_{ab,m} = 100	

i	LAB*ref		l*out		LAB*out		LAB*out/c-ref			ΔE*	Start-Ausgabe S1 Kennzeichnung nach ISO/IEC 15775 Anhang G und DIN 33866-1 Anhang G	
1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01		
2	6.36	0.0	0.0	0.07	6.36	0.0	0.0	0.0	0.0	0.01	Mittlerer Helligkeitsabstand (16 Stufen) ΔE*_{CIELAB} = 0.0	
3	12.72	0.0	0.0	0.13	12.72	0.0	0.0	0.0	0.0	0.01		
4	19.08	0.0	0.0	0.2	19.08	0.0	0.0	0.0	0.0	0.01		
5	25.44	0.0	0.0	0.27	25.44	0.0	0.0	0.0	0.0	0.01		
6	31.8	0.0	0.0	0.33	31.8	0.0	0.0	0.0	0.0	0.01		
7	38.16	0.0	0.0	0.4	38.16	0.0	0.0	0.0	0.0	0.01		
8	44.52	0.0	0.0	0.47	44.52	0.0	0.0	0.0	0.0	0.01		
9	50.89	0.0	0.0	0.53	50.89	0.0	0.0	0.0	0.0	0.01		
10	57.25	0.0	0.0	0.6	57.25	0.0	0.0	0.0	0.0	0.01		
11	63.61	0.0	0.0	0.67	63.61	0.0	0.0	0.0	0.0	0.01		
12	69.97	0.0	0.0	0.73	69.97	0.0	0.0	0.0	0.0	0.01		
13	76.33	0.0	0.0	0.8	76.33	0.0	0.0	0.0	0.0	0.01		
14	82.69	0.0	0.0	0.87	82.69	0.0	0.0	0.0	0.0	0.01		
15	89.05	0.0	0.0	0.93	89.05	0.0	0.0	0.0	0.0	0.01	Mittlerer Helligkeitsabstand (5 Stufen) ΔL*_{CIELAB} = 0.0	
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01		
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	Mittlerer Farbwiedergabe-Index: R*_{ab,m} = 100	
18	23.85	0.0	0.0	0.25	23.85	0.0	0.0	0.0	0.0	0.01		
19	47.71	0.0	0.0	0.5	47.71	0.0	0.0	0.0	0.0	0.01		
20	71.56	0.0	0.0	0.75	71.56	0.0	0.0	0.0	0.0	0.01		
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01		

i	LAB*ref		l*out		LAB*out		LAB*out/c-ref			ΔE*	Start-Ausgabe S1 Kennzeichnung nach ISO/IEC 15775 Anhang G und DIN 33866-1 Anhang G
1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01		
2	6.36	0.0	0.0	0.07	6.36	0.0	0.0	0.0	0.0	0.01	
3	12.72	0.0	0.0	0.13	12.72	0.0	0.0	0.0	0.0	0.01	
4	19.08	0.0	0.0	0.2	19.08	0.0	0.0	0.0	0.0	0.01	
5	25.44	0.0	0.0	0.27	25.44	0.0	0.0	0.0	0.0	0.01	
6	31.8	0.0	0.0	0.33	31.8	0.0	0.0	0.0	0.0	0.01	
7	38.16	0.0	0.0	0.4	38.16	0.0	0.0	0.0	0.0	0.01	
8	44.52	0.0	0.0	0.47	44.52	0.0	0.0	0.0	0.0	0.01	
9	50.89	0.0	0.0	0.53	50.89	0.0	0.0	0.0	0.0	0.01	
10	57.25	0.0	0.0	0.6	57.25	0.0	0.0	0.0	0.0	0.01	
11	63.61	0.0	0.0	0.67	63.61	0.0	0.0	0.0	0.0	0.01	
12	69.97	0.0	0.0	0.73	69.97	0.0	0.0	0.0	0.0	0.01	
13	76.33	0.0	0.0	0.8	76.33	0.0	0.0	0.0	0.0	0.01	
14	82.69	0.0	0.0	0.87	82.69	0.0	0.0	0.0	0.0	0.01	
15	89.05	0.0	0.0	0.93	89.05	0.0	0.0	0.0	0.0	0.01	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01	ΔE*CIELAB = 0.0
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
18	23.85	0.0	0.0	0.25	23.85	0.0	0.0	0.0	0.0	0.01	
19	47.71	0.0	0.0	0.5	47.71	0.0	0.0	0.0	0.0	0.01	
20	71.56	0.0	0.0	0.75	71.56	0.0	0.0	0.0	0.0	0.01	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01	ΔL*CIELAB = 0.0
Mittlerer Farbwiedergabe-Index:										R*ab,m = 100	

i	LAB*ref		l*out		LAB*out		LAB*out/c-ref			ΔE^*	Start-Ausgabe S1 Kennzeichnung nach ISO/IEC 15775 Anhang G und DIN 33866-1 Anhang G
1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01		
2	6.36	0.0	0.0	0.07	6.36	0.0	0.0	0.0	0.01		
3	12.72	0.0	0.0	0.13	12.72	0.0	0.0	0.0	0.0	0.01	
4	19.08	0.0	0.0	0.2	19.08	0.0	0.0	0.0	0.0	0.01	
5	25.44	0.0	0.0	0.27	25.44	0.0	0.0	0.0	0.0	0.01	
6	31.8	0.0	0.0	0.33	31.8	0.0	0.0	0.0	0.0	0.01	
7	38.16	0.0	0.0	0.4	38.16	0.0	0.0	0.0	0.0	0.01	
8	44.52	0.0	0.0	0.47	44.52	0.0	0.0	0.0	0.0	0.01	
9	50.89	0.0	0.0	0.53	50.89	0.0	0.0	0.0	0.0	0.01	
10	57.25	0.0	0.0	0.6	57.25	0.0	0.0	0.0	0.0	0.01	
11	63.61	0.0	0.0	0.67	63.61	0.0	0.0	0.0	0.0	0.01	
12	69.97	0.0	0.0	0.73	69.97	0.0	0.0	0.0	0.0	0.01	
13	76.33	0.0	0.0	0.8	76.33	0.0	0.0	0.0	0.0	0.01	
14	82.69	0.0	0.0	0.87	82.69	0.0	0.0	0.0	0.0	0.01	
15	89.05	0.0	0.0	0.93	89.05	0.0	0.0	0.0	0.0	0.01	
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01	
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
18	23.85	0.0	0.0	0.25	23.85	0.0	0.0	0.0	0.0	0.01	
19	47.71	0.0	0.0	0.5	47.71	0.0	0.0	0.0	0.0	0.01	
20	71.56	0.0	0.0	0.75	71.56	0.0	0.0	0.0	0.0	0.01	
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01	
Mittlerer Farbwiedergabe-Index:										$R^*_{\text{ab,m}} = 100$	

i	LAB*ref		l*out		LAB*out		LAB*out/c-ref			ΔE^*	Start-Ausgabe S1 Kennzeichnung nach ISO/IEC 15775 Anhang G und DIN 33866-1 Anhang G
1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01		
2	6.36	0.0	0.0	0.07	6.36	0.0	0.0	0.0	0.01		
3	12.72	0.0	0.0	0.13	12.72	0.0	0.0	0.0	0.0	0.01	
4	19.08	0.0	0.0	0.2	19.08	0.0	0.0	0.0	0.0	0.01	
5	25.44	0.0	0.0	0.27	25.44	0.0	0.0	0.0	0.0	0.01	
6	31.8	0.0	0.0	0.33	31.8	0.0	0.0	0.0	0.0	0.01	
7	38.16	0.0	0.0	0.4	38.16	0.0	0.0	0.0	0.0	0.01	
8	44.52	0.0	0.0	0.47	44.52	0.0	0.0	0.0	0.0	0.01	
9	50.89	0.0	0.0	0.53	50.89	0.0	0.0	0.0	0.0	0.01	
10	57.25	0.0	0.0	0.6	57.25	0.0	0.0	0.0	0.0	0.01	
11	63.61	0.0	0.0	0.67	63.61	0.0	0.0	0.0	0.0	0.01	
12	69.97	0.0	0.0	0.73	69.97	0.0	0.0	0.0	0.0	0.01	
13	76.33	0.0	0.0	0.8	76.33	0.0	0.0	0.0	0.0	0.01	
14	82.69	0.0	0.0	0.87	82.69	0.0	0.0	0.0	0.0	0.01	
15	89.05	0.0	0.0	0.93	89.05	0.0	0.0	0.0	0.0	0.01	
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01	
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
18	23.85	0.0	0.0	0.25	23.85	0.0	0.0	0.0	0.0	0.01	
19	47.71	0.0	0.0	0.5	47.71	0.0	0.0	0.0	0.0	0.01	
20	71.56	0.0	0.0	0.75	71.56	0.0	0.0	0.0	0.0	0.01	
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01	
Mittlerer Farbwiedergabe-Index:										$R^*_{ab,m} = 100$	

i	LAB*ref		l*out		LAB*out		LAB*out/c-ref			ΔE^*	Start-Ausgabe S1 Kennzeichnung nach ISO/IEC 15775 Anhang G und DIN 33866-1 Anhang G
1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01		
2	6.36	0.0	0.0	0.07	6.36	0.0	0.0	0.0	0.01		
3	12.72	0.0	0.0	0.13	12.72	0.0	0.0	0.0	0.0	0.01	
4	19.08	0.0	0.0	0.2	19.08	0.0	0.0	0.0	0.0	0.01	
5	25.44	0.0	0.0	0.27	25.44	0.0	0.0	0.0	0.0	0.01	
6	31.8	0.0	0.0	0.33	31.8	0.0	0.0	0.0	0.0	0.01	
7	38.16	0.0	0.0	0.4	38.16	0.0	0.0	0.0	0.0	0.01	
8	44.52	0.0	0.0	0.47	44.52	0.0	0.0	0.0	0.0	0.01	
9	50.89	0.0	0.0	0.53	50.89	0.0	0.0	0.0	0.0	0.01	
10	57.25	0.0	0.0	0.6	57.25	0.0	0.0	0.0	0.0	0.01	
11	63.61	0.0	0.0	0.67	63.61	0.0	0.0	0.0	0.0	0.01	
12	69.97	0.0	0.0	0.73	69.97	0.0	0.0	0.0	0.0	0.01	
13	76.33	0.0	0.0	0.8	76.33	0.0	0.0	0.0	0.0	0.01	
14	82.69	0.0	0.0	0.87	82.69	0.0	0.0	0.0	0.0	0.01	
15	89.05	0.0	0.0	0.93	89.05	0.0	0.0	0.0	0.0	0.01	
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01	
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
18	23.85	0.0	0.0	0.25	23.85	0.0	0.0	0.0	0.0	0.01	
19	47.71	0.0	0.0	0.5	47.71	0.0	0.0	0.0	0.0	0.01	
20	71.56	0.0	0.0	0.75	71.56	0.0	0.0	0.0	0.0	0.01	
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01	
Mittlerer Farbwiedergabe-Index:										$R^*_{ab,m} = 100$	