


94 ähnliche ISO-Prüfvorlagen: <http://www.ps.bam.de/24705T>, <http://www.ps.bam.de/9241>
Technische Information: <http://www.ps.bam.de/33872> Version 2.1, io=1,1, CIELAB

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	0.0	0.0	0.0	0.0	0.0	Kennzeichnung nach
2	6.36	0.0	0.07	6.36	0.0	ISO/IEC 15775 Anhang G
3	12.72	0.0	0.13	12.72	0.0	und DIN 33866-1 Anhang G
4	19.08	0.0	0.2	19.08	0.0	
5	25.44	0.0	0.27	25.44	0.0	
6	31.8	0.0	0.33	31.8	0.0	
7	38.16	0.0	0.4	38.16	0.0	
8	44.52	0.0	0.47	44.52	0.0	
9	50.89	0.0	0.53	50.89	0.0	
10	57.25	0.0	0.6	57.25	0.0	
11	63.61	0.0	0.67	63.61	0.0	
12	69.97	0.0	0.73	69.97	0.0	
13	76.33	0.0	0.8	76.33	0.0	
14	82.69	0.0	0.87	82.69	0.0	
15	89.05	0.0	0.93	89.05	0.0	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41	0.0	1.0	95.41	0.0	$\Delta E^*_{CIELAB} = 0.0$
17	0.0	0.0	0.0	0.0	0.0	
18	23.85	0.0	0.25	23.85	0.0	
19	47.71	0.0	0.5	47.71	0.0	
20	71.56	0.0	0.75	71.56	0.0	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41	0.0	1.0	95.41	0.0	$\Delta L^*_{CIELAB} = 0.0$

Mittlerer Farbwiedergabe-Index: $R_{ab,m} = 100$

OG920-3N-130-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG921-3N-130-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolut)	0.0/0.0	6.3/0.7	12.7/1.5	19.0/2.7	25.4/4.5	31.8/6.9	38.1/10.1	44.5/14.2	50.8/19.1	57.2/25.1	63.6/32.3	69.9/40.7	76.3/50.4	82.6/61.5	89.0/74.2	95.4/88.5
$w^* w^* w^*$ setrgb $g_p=1.0$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*$ $_{CIELAB, r}$ (relativ)																
$w^*_{intended}$	0.000	0.067	0.133	0.200	0.267	0.333	0.400	0.467	0.533	0.600	0.667	0.733	0.800	0.867	0.933	1.000
w^*_{out}	0.0	0.067	0.133	0.2	0.267	0.333	0.4	0.467	0.533	0.6	0.667	0.733	0.8	0.867	0.933	1.0


OE740-7N, Bild A7-130-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^*$ setrgbcolor

OG92: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH Eingabe: 000n/w/cmy0/rgb (->rgb*d)
Gesehener Y-Kontrast $Y_W:Y_N=88,9:0,31$; Y_N -Bereich 0,0 to <0,46 Ausgabe 130-2: $g_p=1.0$; $g_N=1.0$

94 ähnliche ISO-Prüfvorlagen: <http://www.ps.bam.de/24705T>, <http://www.ps.bam.de/9241>
Technische Information: <http://www.ps.bam.de/33872> Version 2.1, io=1.1, CIELAB

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	5.69 0.0 0.0	0.0 0.0 0.0	5.69 0.0 0.0	0.0 0.0 0.0	0.01	Kennzeichnung nach
2	11.67 0.0 0.0	0.1 0.0 0.0	14.73 0.0 0.0	3.06 0.0 0.0	3.06	ISO/IEC 15775 Anhang G
3	17.65 0.0 0.0	0.18 0.0 0.0	21.96 0.0 0.0	4.3 0.0 0.0	4.3	und DIN 33866-1 Anhang G
4	23.63 0.0 0.0	0.26 0.0 0.0	28.63 0.0 0.0	4.99 0.0 0.0	4.99	
5	29.62 0.0 0.0	0.33 0.0 0.0	34.96 0.0 0.0	5.34 0.0 0.0	5.34	
6	35.6 0.0 0.0	0.39 0.0 0.0	41.05 0.0 0.0	5.46 0.0 0.0	5.46	
7	41.58 0.0 0.0	0.46 0.0 0.0	46.96 0.0 0.0	5.38 0.0 0.0	5.38	
8	47.56 0.0 0.0	0.52 0.0 0.0	52.72 0.0 0.0	5.16 0.0 0.0	5.16	
9	53.54 0.0 0.0	0.59 0.0 0.0	58.36 0.0 0.0	4.82 0.0 0.0	4.82	
10	59.52 0.0 0.0	0.65 0.0 0.0	63.88 0.0 0.0	4.36 0.0 0.0	4.36	
11	65.5 0.0 0.0	0.71 0.0 0.0	69.32 0.0 0.0	3.82 0.0 0.0	3.82	
12	71.48 0.0 0.0	0.77 0.0 0.0	74.67 0.0 0.0	3.19 0.0 0.0	3.19	
13	77.47 0.0 0.0	0.83 0.0 0.0	79.95 0.0 0.0	2.49 0.0 0.0	2.49	
14	83.45 0.0 0.0	0.89 0.0 0.0	85.16 0.0 0.0	1.72 0.0 0.0	1.72	
15	89.43 0.0 0.0	0.94 0.0 0.0	90.31 0.0 0.0	0.89 0.0 0.0	0.89	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41 0.0 0.0	1.0 0.0 0.0	95.41 0.0 0.0	0.0 0.0 0.0	0.01	$\Delta E^*_{CIELAB} = 3.4$
17	5.69 0.0 0.0	0.0 0.0 0.0	5.69 0.0 0.0	0.0 0.0 0.0	0.01	
18	28.12 0.0 0.0	0.31 0.0 0.0	33.4 0.0 0.0	5.28 0.0 0.0	5.28	
19	50.55 0.0 0.0	0.56 0.0 0.0	55.55 0.0 0.0	5.0 0.0 0.0	5.0	
20	72.98 0.0 0.0	0.78 0.0 0.0	76.0 0.0 0.0	3.02 0.0 0.0	3.02	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41 0.0 0.0	1.0 0.0 0.0	95.41 0.0 0.0	0.0 0.0 0.0	0.01	$\Delta L^*_{CIELAB} = 2.7$
Mittlerer Farbwiedergabe-Index:					$R^*_{ab,m} = 85$	

OG920-3N-131-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG921-3N-131-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolut)	5.6/0.6	11.6/1.3	17.6/2.4	23.6/3.9	29.6/6.0	35.5/8.8	41.5/12.2	47.5/16.4	53.5/21.5	59.5/27.5	65.5/34.6	71.4/42.8	77.4/52.3	83.4/63.0	89.4/75.0	95.4/88.5
$w^* w^* w^*$ setrgb $g_p=0.92$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{CIELAB, r}$ (relativ)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0,0	0,082	0,154	0,225	0,294	0,361	0,428	0,494	0,558	0,623	0,687	0,75	0,813	0,876	0,937	1,0

OE740-7N, Bild A7-131-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* setrgbcolor$

OG92: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH Eingabe: 000n/w/cmy0/rgb (->rgb*d)
Gesehener Y-Kontrast $Y_W:Y_N=88,9:0,62$; Y_N -Bereich 0,46 to <0,0 Ausgabe 131-2: $g_p=0.92$; $g_N=1.0$


i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	10.99	0.0	0.0	10.99	0.0	0.0
2	16.62	0.0	0.0	14	22.52	0.0
3	22.25	0.0	0.0	23	30.18	0.0
4	27.88	0.0	0.0	31	36.84	0.0
5	33.5	0.0	0.0	38	42.93	0.0
6	39.13	0.0	0.0	45	48.63	0.0
7	44.76	0.0	0.0	51	54.03	0.0
8	50.39	0.0	0.0	57	59.19	0.0
9	56.02	0.0	0.0	63	64.17	0.0
10	61.64	0.0	0.0	69	68.98	0.0
11	67.27	0.0	0.0	74	73.65	0.0
12	72.9	0.0	0.0	8	78.2	0.0
13	78.53	0.0	0.0	0.85	82.64	0.0
14	84.15	0.0	0.0	0.9	86.98	0.0
15	89.78	0.0	0.0	0.95	91.23	0.0
16	95.41	0.0	0.0	1.0	95.41	0.0
17	10.99	0.0	0.0	10.99	0.0	0.0
18	32.1	0.0	0.0	36	41.45	0.0
19	53.2	0.0	0.0	6	61.7	0.0
20	74.31	0.0	0.0	0.81	79.32	0.0
21	95.41	0.0	0.0	1.0	95.41	0.0

Mittlerer Helligkeitsabstand (16 Stufen)
 $\Delta E^*_{CIELAB} = 6.0$

Mittlerer Helligkeitsabstand (5 Stufen)
 $\Delta L^*_{CIELAB} = 4.6$

Mittlerer Farbwiedergabe-Index: $R_{ab,m} = 74$

OG920-3N-132-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG921-3N-132-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolut)	10.9/1.2	16.6/2.2	22.2/3.5	27.8/5.4	33.5/7.7	39.1/10.7	44.7/14.3	50.3/18.7	56.0/23.9	61.6/29.9	67.2/36.9	72.8/45.0	78.5/54.1	84.1/64.3	89.7/75.8	95.4/88.5
$w^* w^* w^*$ setrgb $g_p=0.85$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{CIELAB, r}$ (relativ)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0.0	0.1	0.18	0.254	0.325	0.392	0.458	0.523	0.585	0.647	0.708	0.767	0.827	0.885	0.942	1.0


OE740-7N, Bild A7-132-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^*$ setrgbcolor

OG92: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH Eingabe: 000n/w/cmy0/rgb (->rgb*d)
Gesehener Y-Kontrast $Y_W:Y_N=88,9:1,25$; Y_N -Bereich 0,93 to <1,0 Ausgabe 132-2: $g_p=0.85$; $g_N=1.0$

94hnliche ISO-Prüfvorlagen: <http://www.ps.bam.de/24705T>, <http://www.ps.bam.de/9241>
Technische Information: <http://www.ps.bam.de/33872> Version 2.1, io=1,1, CIELAB

i	LAB*ref	L*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	18.01 0.0 0.0	0.0 0.0 0.0	18.01 0.0 0.0	0.0 0.0 0.0	0.01	Kennzeichnung nach
2	23.17 0.0 0.0	0.17 31.35 0.0	0.0 0.0 8.18	0.0 0.0 8.18	8.18	ISO/IEC 15775 Anhang G
3	28.33 0.0 0.0	0.27 38.93 0.0	0.0 0.0 10.6	0.0 0.0 10.6	10.6	und DIN 33866-1 Anhang G
4	33.49 0.0 0.0	0.35 45.23 0.0	0.0 0.0 11.74	0.0 0.0 11.74	11.74	
5	38.65 0.0 0.0	0.42 50.82 0.0	0.0 0.0 12.17	0.0 0.0 12.17	12.17	
6	43.81 0.0 0.0	0.49 55.93 0.0	0.0 0.0 12.12	0.0 0.0 12.12	12.12	
7	48.97 0.0 0.0	0.55 60.7 0.0	0.0 0.0 11.73	0.0 0.0 11.73	11.73	
8	54.13 0.0 0.0	0.61 65.2 0.0	0.0 0.0 11.07	0.0 0.0 11.07	11.07	
9	59.29 0.0 0.0	0.66 69.47 0.0	0.0 0.0 10.18	0.0 0.0 10.18	10.18	
10	64.45 0.0 0.0	0.72 73.56 0.0	0.0 0.0 9.11	0.0 0.0 9.11	9.11	
11	69.61 0.0 0.0	0.77 77.49 0.0	0.0 0.0 7.88	0.0 0.0 7.88	7.88	
12	74.77 0.0 0.0	0.82 81.29 0.0	0.0 0.0 6.52	0.0 0.0 6.52	6.52	
13	79.93 0.0 0.0	0.87 84.97 0.0	0.0 0.0 5.04	0.0 0.0 5.04	5.04	
14	85.09 0.0 0.0	0.91 88.54 0.0	0.0 0.0 3.45	0.0 0.0 3.45	3.45	
15	90.25 0.0 0.0	0.96 92.02 0.0	0.0 0.0 1.77	0.0 0.0 1.77	1.77	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	$\Delta E^*_{CIELAB} = 7.6$
17	18.01 0.0 0.0	0.0 18.01 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	
18	37.36 0.0 0.0	0.41 49.47 0.0	0.0 0.0 12.11	0.0 0.0 12.11	12.11	
19	56.71 0.0 0.0	0.64 67.36 0.0	0.0 0.0 10.65	0.0 0.0 10.65	10.65	
20	76.06 0.0 0.0	0.83 82.22 0.0	0.0 0.0 6.16	0.0 0.0 6.16	6.16	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	$\Delta L^*_{CIELAB} = 5.8$
Mittlerer Farbwiedergabe-Index:					$R_{ab,m} = 67$	

OG920-3N-133-2: File: Measure unknown; Device: Device unknown; Date: Date unknown




$L^*/Y_{intended}$ (absolut)	18.0/2.5	23.1/3.8	28.3/5.5	33.4/7.7	38.6/10.4	43.8/13.7	48.9/17.5	54.1/22.0	59.2/27.3	64.4/33.3	69.6/40.1	74.7/47.9	79.9/56.5	85.0/66.1	90.2/76.8	95.4/88.5
$w^* w^* w^*$ setrgb																
$g_p=0.77$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{CIELAB, r}$ (relativ)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0.0	0.123	0.209	0.287	0.359	0.426	0.491	0.554	0.614	0.673	0.73	0.786	0.841	0.895	0.947	1.0

OE740-7N, Bild A7-133-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* setrgbcolor$

OG92: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH Eingabe: 000n/w/cmy0/rgb (->rgb*d)
Gesehener Y-Kontrast $Y_W:Y_N=88,9:2,5$; Y_N -Bereich 1,87 to <3,7; Ausgabe 133-2: $g_p=0.77$; $g_N=1.0$

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	26.85 0.0 0.0	0.0 26.85 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	Kennzeichnung nach
2	31.42 0.0 0.0	0.21 41.05 0.0	0.0 9.63 0.0	0.0 9.63 0.0	9.63	ISO/IEC 15775 Anhang G
3	35.99 0.0 0.0	0.31 48.1 0.0	0.0 12.11 0.0	0.0 12.11 0.0	12.11	und DIN 33866-1 Anhang G
4	40.56 0.0 0.0	0.39 53.75 0.0	0.0 13.18 0.0	0.0 13.18 0.0	13.18	
5	45.13 0.0 0.0	0.46 58.64 0.0	0.0 13.51 0.0	0.0 13.51 0.0	13.51	
6	49.7 0.0 0.0	0.53 63.05 0.0	0.0 13.34 0.0	0.0 13.34 0.0	13.34	
7	54.27 0.0 0.0	0.59 67.09 0.0	0.0 12.82 0.0	0.0 12.82 0.0	12.82	
8	58.84 0.0 0.0	0.64 70.87 0.0	0.0 12.02 0.0	0.0 12.02 0.0	12.02	
9	63.41 0.0 0.0	0.69 74.42 0.0	0.0 11.01 0.0	0.0 11.01 0.0	11.01	
10	67.99 0.0 0.0	0.74 77.79 0.0	0.0 9.81 0.0	0.0 9.81 0.0	9.81	
11	72.56 0.0 0.0	0.79 81.01 0.0	0.0 8.46 0.0	0.0 8.46 0.0	8.46	
12	77.13 0.0 0.0	0.84 84.1 0.0	0.0 6.97 0.0	0.0 6.97 0.0	6.97	
13	81.7 0.0 0.0	0.88 87.07 0.0	0.0 5.37 0.0	0.0 5.37 0.0	5.37	
14	86.27 0.0 0.0	0.92 89.94 0.0	0.0 3.67 0.0	0.0 3.67 0.0	3.67	
15	90.84 0.0 0.0	0.96 92.71 0.0	0.0 1.88 0.0	0.0 1.88 0.0	1.88	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	$\Delta E^*_{CIELAB} = 8.4$
17	26.85 0.0 0.0	0.0 26.85 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	
18	43.99 0.0 0.0	0.45 57.47 0.0	0.0 13.48 0.0	0.0 13.48 0.0	13.48	
19	61.13 0.0 0.0	0.67 72.67 0.0	0.0 11.54 0.0	0.0 11.54 0.0	11.54	
20	78.27 0.0 0.0	0.85 84.85 0.0	0.0 6.58 0.0	0.0 6.58 0.0	6.58	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	$\Delta L^*_{CIELAB} = 6.3$
Mittlerer Farbwiedergabe-Index:					$R_{ab,m} = 64$	

OG920-3N-134-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG921-3N-134-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolut)	26.8/5.0	31.4/6.8	35.9/9.0	40.5/11.5	45.1/14.6	49.7/18.1	54.2/22.2	58.8/26.8	63.4/32.0	67.9/37.9	72.5/44.4	77.1/51.7	81.6/59.7	86.2/68.5	90.8/78.1	95.4/88.5
$w^* w^* w^*$ setrgb $g_p=0.7$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{CIELAB, r}$ (relativ)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0.0	0.15	0.243	0.324	0.396	0.463	0.526	0.586	0.643	0.699	0.753	0.804	0.855	0.904	0.952	1.0

OE740-7N, Bild A7-134-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* setrgbcolor$

OG92: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH Eingabe: 000n/w/cmy0/rgb (->rgb*d)
Gesehener Y-Kontrast $Y_W:Y_N=88,9:5$; Y_N -Bereich 3,75 to <7,5 Ausgabe 134-2: $g_p=0.7$; $g_N=1.0$

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*
1	37.99 0.0 0.0	0.0 37.99 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
2	41.81 0.0 0.0	0.24 51.79 0.0	0.0 0.0 0.0	9.98 0.0 0.0	9.98
3	45.64 0.0 0.0	0.35 57.87 0.0	0.0 0.0 0.0	12.23 0.0 0.0	12.23
4	49.47 0.0 0.0	0.43 62.6 0.0	0.0 0.0 0.0	13.13 0.0 0.0	13.13
5	53.3 0.0 0.0	0.5 66.63 0.0	0.0 0.0 0.0	13.33 0.0 0.0	13.33
6	57.13 0.0 0.0	0.56 70.19 0.0	0.0 0.0 0.0	13.07 0.0 0.0	13.07
7	60.96 0.0 0.0	0.62 73.44 0.0	0.0 0.0 0.0	12.48 0.0 0.0	12.48
8	64.78 0.0 0.0	0.67 76.44 0.0	0.0 0.0 0.0	11.65 0.0 0.0	11.65
9	68.61 0.0 0.0	0.72 79.23 0.0	0.0 0.0 0.0	10.62 0.0 0.0	10.62
10	72.44 0.0 0.0	0.76 81.87 0.0	0.0 0.0 0.0	9.43 0.0 0.0	9.43
11	76.27 0.0 0.0	0.81 84.37 0.0	0.0 0.0 0.0	8.11 0.0 0.0	8.11
12	80.1 0.0 0.0	0.85 86.76 0.0	0.0 0.0 0.0	6.66 0.0 0.0	6.66
13	83.93 0.0 0.0	0.89 89.05 0.0	0.0 0.0 0.0	5.12 0.0 0.0	5.12
14	87.75 0.0 0.0	0.93 91.24 0.0	0.0 0.0 0.0	3.49 0.0 0.0	3.49
15	91.58 0.0 0.0	0.96 93.36 0.0	0.0 0.0 0.0	1.78 0.0 0.0	1.78
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
17	37.99 0.0 0.0	0.0 37.99 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01
18	52.34 0.0 0.0	0.48 65.67 0.0	0.0 0.0 0.0	13.33 0.0 0.0	13.33
19	66.7 0.0 0.0	0.69 77.86 0.0	0.0 0.0 0.0	11.16 0.0 0.0	11.16
20	81.05 0.0 0.0	0.86 87.34 0.0	0.0 0.0 0.0	6.29 0.0 0.0	6.29
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01


Start-Ausgabe S1
Kennzeichnung nach
ISO/IEC 15775 Anhang G
und DIN 33866-1 Anhang G

Mittlerer Helligkeitsabstand (16 Stufen)
 $\Delta E^*_{CIELAB} = 8.2$

Mittlerer Helligkeitsabstand (5 Stufen)
 $\Delta L^*_{CIELAB} = 6.2$

Mittlerer Farbwiedergabe-Index: $R_{ab,m} = 65$

OG920-3N-135-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG921-3N-135-2: File: Measure unknown; Device: Device unknown; Date: Date unknown


$L^*/Y_{intended}$ (absolut)	37.9/10.0	41.8/12.3	45.6/15.0	49.4/17.9	53.2/21.3	57.1/25.0	60.9/29.1	64.7/33.7	68.6/38.8	72.4/44.3	76.2/50.3	80.0/56.8	83.9/63.9	87.7/71.5	91.5/79.7	95.4/88.5
$w^* w^* w^*$ setrgb																
$g_p=0.62$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{CIELAB, r}$ (relativ)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0.0	0.184	0.283	0.365	0.438	0.502	0.564	0.621	0.674	0.726	0.776	0.823	0.869	0.914	0.957	1.0

OE740-7N, Bild A7-135-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* setrgbcolor$

OG92: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH Eingabe: 000n/w/cmy0/rgb (->rgb*d)
Gesehener Y-Kontrast $Y_W:Y_N=88,9:10$; Y_N -Bereich 7,5 to <15 Ausgabe 135-2: $g_p=0.62$; $g_N=1.0$

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	52.02 0.0 0.0	0.0 0.0 0.0	52.02 0.0 0.0	0.0 0.0 0.0	0.01	Kennzeichnung nach
2	54.91 0.0 0.0	0.27 63.82 0.0	0.0 8.91 0.0	0.0 8.91 0.0	8.91	ISO/IEC 15775 Anhang G
3	57.8 0.0 0.0	0.38 68.49 0.0	0.0 10.69 0.0	0.0 10.69 0.0	10.69	und DIN 33866-1 Anhang G
4	60.7 0.0 0.0	0.46 72.03 0.0	0.0 11.34 0.0	0.0 11.34 0.0	11.34	
5	63.59 0.0 0.0	0.53 75.0 0.0	0.0 11.41 0.0	0.0 11.41 0.0	11.41	
6	66.48 0.0 0.0	0.59 77.61 0.0	0.0 11.12 0.0	0.0 11.12 0.0	11.12	
7	69.37 0.0 0.0	0.64 79.95 0.0	0.0 10.57 0.0	0.0 10.57 0.0	10.57	
8	72.27 0.0 0.0	0.69 82.1 0.0	0.0 9.83 0.0	0.0 9.83 0.0	9.83	
9	75.16 0.0 0.0	0.74 84.09 0.0	0.0 8.93 0.0	0.0 8.93 0.0	8.93	
10	78.05 0.0 0.0	0.78 85.96 0.0	0.0 7.91 0.0	0.0 7.91 0.0	7.91	
11	80.95 0.0 0.0	0.82 87.72 0.0	0.0 6.78 0.0	0.0 6.78 0.0	6.78	
12	83.84 0.0 0.0	0.86 89.4 0.0	0.0 5.56 0.0	0.0 5.56 0.0	5.56	
13	86.73 0.0 0.0	0.9 91.0 0.0	0.0 4.26 0.0	0.0 4.26 0.0	4.26	
14	89.62 0.0 0.0	0.93 92.53 0.0	0.0 2.9 0.0	0.0 2.9 0.0	2.9	
15	92.52 0.0 0.0	0.97 93.99 0.0	0.0 1.48 0.0	0.0 1.48 0.0	1.48	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	$\Delta E^*_{CIELAB} = 7.0$
17	52.02 0.0 0.0	0.0 52.02 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	
18	62.87 0.0 0.0	0.51 74.3 0.0	0.0 11.43 0.0	0.0 11.43 0.0	11.43	
19	73.71 0.0 0.0	0.72 83.11 0.0	0.0 9.4 0.0	0.0 9.4 0.0	9.4	
20	84.56 0.0 0.0	0.87 89.81 0.0	0.0 5.24 0.0	0.0 5.24 0.0	5.24	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	$\Delta L^*_{CIELAB} = 5.2$
Mittlerer Farbwiedergabe-Index:					$R_{ab,m} = 70$	

OG920-3N-136-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG921-3N-136-2: File: Measure unknown; Device: Device unknown; Date: Date unknown


$L^*/Y_{intended}$ (absolut)	52.0/20.1	54.9/22.8	57.8/25.7	60.6/28.9	63.5/32.2	66.4/35.9	69.3/39.8	72.2/44.0	75.1/48.5	78.0/53.3	80.9/58.3	83.8/63.7	86.7/69.4	89.6/75.4	92.5/81.8	95.4/88.5
$w^* w^* w^*$ setrgb $g_p=0.55$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{CIELAB, r}$ (relativ)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0.0	0.226	0.329	0.412	0.483	0.546	0.604	0.657	0.707	0.755	0.8	0.842	0.884	0.924	0.962	1.0

OE740-7N, Bild A7-136-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^* setrgbcolor$

OG92: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH Eingabe: 000n/w/cmy0/rgb (->rgb*d)
Gesehener Y-Kontrast $Y_W:Y_N=88,9:20$; Y_N -Bereich 15 to <30 Ausgabe 136-2: $g_p=0.55$; $g_N=1.0$

i	LAB*ref	l*out	LAB*out	LAB*out/c-ref	ΔE*	Start-Ausgabe S1
1	69.7 0.0 0.0	0.0 69.7 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	Kennzeichnung nach
2	71.41 0.0 0.0	0.3 77.46 0.0	0.0 0.0 0.0	6.04 0.0 0.0	6.04	ISO/IEC 15775 Anhang G
3	73.13 0.0 0.0	0.41 80.24 0.0	0.0 0.0 0.0	7.11 0.0 0.0	7.11	und DIN 33866-1 Anhang G
4	74.84 0.0 0.0	0.49 82.31 0.0	0.0 0.0 0.0	7.47 0.0 0.0	7.47	
5	76.55 0.0 0.0	0.56 84.02 0.0	0.0 0.0 0.0	7.47 0.0 0.0	7.47	
6	78.27 0.0 0.0	0.62 85.51 0.0	0.0 0.0 0.0	7.24 0.0 0.0	7.24	
7	79.98 0.0 0.0	0.67 86.84 0.0	0.0 0.0 0.0	6.86 0.0 0.0	6.86	
8	81.7 0.0 0.0	0.71 88.05 0.0	0.0 0.0 0.0	6.35 0.0 0.0	6.35	
9	83.41 0.0 0.0	0.76 89.17 0.0	0.0 0.0 0.0	5.76 0.0 0.0	5.76	
10	85.12 0.0 0.0	0.8 90.21 0.0	0.0 0.0 0.0	5.08 0.0 0.0	5.08	
11	86.84 0.0 0.0	0.84 91.19 0.0	0.0 0.0 0.0	4.35 0.0 0.0	4.35	
12	88.55 0.0 0.0	0.87 92.11 0.0	0.0 0.0 0.0	3.56 0.0 0.0	3.56	
13	90.27 0.0 0.0	0.91 92.99 0.0	0.0 0.0 0.0	2.73 0.0 0.0	2.73	
14	91.98 0.0 0.0	0.94 93.83 0.0	0.0 0.0 0.0	1.85 0.0 0.0	1.85	
15	93.7 0.0 0.0	0.97 94.64 0.0	0.0 0.0 0.0	0.94 0.0 0.0	0.94	Mittlerer Helligkeitsabstand (16 Stufen)
16	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	$\Delta E^*_{CIELAB} = 4.6$
17	69.7 0.0 0.0	0.0 69.7 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	
18	76.13 0.0 0.0	0.54 83.62 0.0	0.0 0.0 0.0	7.5 0.0 0.0	7.5	
19	82.55 0.0 0.0	0.74 88.62 0.0	0.0 0.0 0.0	6.06 0.0 0.0	6.06	
20	88.98 0.0 0.0	0.88 92.34 0.0	0.0 0.0 0.0	3.35 0.0 0.0	3.35	Mittlerer Helligkeitsabstand (5 Stufen)
21	95.41 0.0 0.0	1.0 95.41 0.0	0.0 0.0 0.0	0.0 0.0 0.0	0.01	$\Delta L^*_{CIELAB} = 3.4$
Mittlerer Farbwiedergabe-Index:					$R^*_{ab,m} = 80$	

OG920-3N-137-2: File: Measure unknown; Device: Device unknown; Date: Date unknown



OG921-3N-137-2: File: Measure unknown; Device: Device unknown; Date: Date unknown

$L^*/Y_{intended}$ (absolut)	69.6/40.3	71.4/42.7	73.1/45.3	74.8/48.0	76.5/50.7	78.2/53.6	79.9/56.6	81.6/59.7	83.4/62.9	85.1/66.2	86.8/69.6	88.5/73.2	90.2/76.8	91.9/80.6	93.6/84.5	95.4/88.5
$w^* w^* w^*$ setrgb $g_p=0.47$																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^*=l^*_{CIELAB, r}$ (relativ)																
$w^*_{intended}$	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{out}	0.0	0.276	0.383	0.465	0.534	0.593	0.647	0.696	0.741	0.784	0.825	0.862	0.899	0.934	0.967	1.0

OE740-7N, Bild A7-137-2: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $w^* w^* w^*$ setrgbcolor

OG92: Ein-Ausgabe-Beziehung nach ISO 9241-306; 1MR, DH Eingabe: 000n/w/cmy0/rgb (->rgb*d)
Gesehener Y-Kontrast $Y_W:Y_N=88,9:40$; Y_N -Bereich 30 to <60 Ausgabe 137-2: $g_p=0.47$; $g_N=1.0$