

i	LAB*ref		l*out		LAB*out		LAB*out/c-ref			ΔE*	Start-Ausgabe S1 Kennzeichnung nach ISO/IEC 15775 Anhang G und DIN 33866-1 Anhang G
1	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01		
2	6.36	0.0	0.0	0.07	6.36	0.0	0.0	0.0	0.01		
3	12.72	0.0	0.0	0.13	12.72	0.0	0.0	0.0	0.0	0.01	
4	19.08	0.0	0.0	0.2	19.08	0.0	0.0	0.0	0.0	0.01	
5	25.44	0.0	0.0	0.27	25.44	0.0	0.0	0.0	0.0	0.01	
6	31.8	0.0	0.0	0.33	31.8	0.0	0.0	0.0	0.0	0.01	
7	38.16	0.0	0.0	0.4	38.16	0.0	0.0	0.0	0.0	0.01	
8	44.52	0.0	0.0	0.47	44.52	0.0	0.0	0.0	0.0	0.01	
9	50.89	0.0	0.0	0.53	50.89	0.0	0.0	0.0	0.0	0.01	
10	57.25	0.0	0.0	0.6	57.25	0.0	0.0	0.0	0.0	0.01	
11	63.61	0.0	0.0	0.67	63.61	0.0	0.0	0.0	0.0	0.01	
12	69.97	0.0	0.0	0.73	69.97	0.0	0.0	0.0	0.0	0.01	
13	76.33	0.0	0.0	0.8	76.33	0.0	0.0	0.0	0.0	0.01	
14	82.69	0.0	0.0	0.87	82.69	0.0	0.0	0.0	0.0	0.01	
15	89.05	0.0	0.0	0.93	89.05	0.0	0.0	0.0	0.0	0.01	
16	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01	
17	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.01	
18	23.85	0.0	0.0	0.25	23.85	0.0	0.0	0.0	0.0	0.01	
19	47.71	0.0	0.0	0.5	47.71	0.0	0.0	0.0	0.0	0.01	
20	71.56	0.0	0.0	0.75	71.56	0.0	0.0	0.0	0.0	0.01	
21	95.41	0.0	0.0	1.0	95.41	0.0	0.0	0.0	0.0	0.01	
Mittlerer Farbwiedergabe-Index:										R* _{ab,m} = 100	
										Mittlerer Helligkeitsabstand (16 Stufen) ΔE* _{CIELAB} = 0.0	
										Mittlerer Helligkeitsabstand (5 Stufen) ΔL* _{CIELAB} = 0.0	