

Ein- und Ausgabe: Offset-Reflektiv-System ORS18a

Daten für jede Geräte- (d) oder
 Elementarfarbe (e):


H^*_e

Buntoncode für die Farben
 dieser Seite:

$H^*_e = R00Y_-, R25Y_-, ..., B75R_-$

ORS20a; adaptierte CIELAB-Daten

H^*_e	$L^*=L^*_s a^*_s$	b^*_s	$C^*_{ab,a}$	$h^*_{ab,a}$
R00Y_100_100_	48.4	66.1	40.2	77.3
R25Y_100_100_	56.8	48.0	50.5	69.6
R50Y_100_100_	68.6	25.0	63.9	68.6
R75Y_100_100_	80.6	4.8	77.2	77.3
Y00G_100_100_	90.2	-9.6	88.2	88.7
Y25G_100_100_	83.2	-18.4	79.9	81.9
Y50G_100_100_	73.3	-31.7	62.7	70.2
Y75G_100_100_	62.0	-49.7	43.2	65.8
G00B_100_100_	55.8	-65.2	33.8	73.4
G25B_100_100_	59.3	-50.3	-9.0	51.0
G50B_100_100_	63.0	-30.5	-42.0	51.9
G75B_100_100_	45.7	-5.7	-44.6	44.9
B00R_100_100_	27.5	25.9	-47.3	53.9
B25R_100_100_	38.3	52.6	-28.5	59.8
B50R_100_100_	49.5	73.5	-9.0	74.0
B75R_100_100_	48.9	69.3	12.9	70.4



%Umfang

$u^*_{rel} = 92$



%Regularität

$g^*_{H,rel} = 57$

$g^*_{C,rel} = 58$

ORS18a; adaptierte CIELAB-Daten

Name	$L^*=L^*_s a^*_s$	b^*_s	$C^*_{ab,a}$	$h^*_{ab,a}$
R_18a	47.9	65.3	50.5	82.6
Y_18a	90.3	-10.2	91.7	92.3
G_18a	50.9	-62.8	34.9	71.9
C_18a	58.6	-30.3	-45.0	54.2
B_18a	25.7	31.0	-44.4	54.2
M_18a	48.1	75.2	-8.3	75.7
N_18a	18.0	0.0	0.0	0.0
W_18a	95.4	0.0	0.0	0.0
R_18a	39.9	58.7	27.9	65.0
Y_18a	81.2	-2.8	71.5	71.6
G_18a	52.2	-42.4	13.6	44.5
B_18a	30.5	1.4	-46.4	46.4



0-003030-L0 PG800-7N

TUB-Prüfvorlage PG80; 16 Bunntöne
 Prüfvorlage nach DIN 33872, 3D=0, de=0, sRGB

Eingabe: rgb/cmyk -> rgb/cmyk
 Ausgabe: keine Änderung