

Immettere y uscita: Offset Reflective System ORS18a

Dati del dispositivo (d) o
colori elementari (e):

HIC^*_d

codice di tonalità per i colori
questa pagina:


$H^*_d = R00Y_d, R25Y_d, \dots, B75R_d$

ORS20a; dati atti CIELAB (a)

H^*_d	$L^*=L^*_a a^*_a$	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R00Y_100_100_d	45.4	70.9	44.8	83.9
R25Y_100_100_d	53.0	53.4	54.8	76.5
R50Y_100_100_d	64.9	28.9	68.6	74.5
R75Y_100_100_d	78.6	4.3	84.7	84.8
Y00G_100_100_d	87.8	-10.2	95.4	96.0
Y25G_100_100_d	81.2	-17.0	84.3	86.0
Y50G_100_100_d	70.6	-29.7	66.5	72.8
Y75G_100_100_d	57.9	-48.3	45.8	66.5
G00B_100_100_d	50.0	-65.0	29.6	71.4
G25B_100_100_d	52.9	-48.6	-8.0	49.3
G50B_100_100_d	56.8	-25.5	-41.5	48.7
G75B_100_100_d	41.7	-1.2	-40.6	40.6
B00R_100_100_d	25.0	29.5	-40.4	50.0
B25R_100_100_d	35.6	58.6	-20.7	62.1
B50R_100_100_d	46.1	79.3	-0.2	79.3
B75R_100_100_d	45.9	74.2	21.1	77.1

ORS20a; dati atti CIELAB (a)

name	$L^*=L^*_a a^*_a$	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R _{d, Ma}	45.4	70.9	44.8	83.9
Y _{d, Ma}	87.8	-10.2	95.4	96.0
G _{d, Ma}	50.0	-65.0	29.6	71.4
C _{d, Ma}	56.8	-25.5	-41.5	48.7
B _{d, Ma}	25.0	29.5	-40.4	50.0
M _{d, Ma}	46.1	79.3	-0.2	79.3
N _{d, Ma}	24.3	0.0	0.0	0.0
W _{d, Ma}	95.6	0.0	0.0	0.0
R _{d, CIE}	39.9	58.7	27.9	65.0
Y _{d, CIE}	81.2	-2.8	71.5	71.6
G _{d, CIE}	52.2	-42.4	13.6	44.5
B _{d, CIE}	30.5	1.4	-46.4	46.4





%Gamma

$u^*_{rel} = 92$

%Regularità

$g^*_{H,rel} = 57$

$g^*_{C,rel} = 58$



4-003131-L0 PI860-70

grafico TUB-PI86; cerchio delle tinte a 16 passi
grafico conformemente a DIN 33872, 3D=0, de=0, cmy0

Input: $rgb/cmyk \rightarrow rgb_d$
Output: trasferire a $cmy0_d$

4-003131-F0