

Immettere y uscita: Printer Reflective System FRS06a

Dati del dispositivo (d) o

colori elementari (e):


HIC*-

codice di tonalità per i colori

questa pagina:

H*- = R00Y-, R25Y-, ..., B75R-

ORS20a; dati atti CIELAB (a)						
H*-	L*=L*a	a*a	b*a	C*ab,a	h*ab,a	
R00Y_100_100_	48.4	66.1	40.2	77.3	31	
R25Y_100_100_	56.8	48.0	50.5	69.6	46	
R50Y_100_100_	68.6	25.0	63.9	68.6	68	
R75Y_100_100_	80.6	4.8	77.2	77.3	86	
Y00G_100_100_	90.2	-9.6	88.2	88.7	96	
Y25G_100_100_	83.2	-18.4	79.9	81.9	102	
Y50G_100_100_	73.3	-31.7	62.7	70.2	116	
Y75G_100_100_	62.0	-49.7	43.2	65.8	139	
G00B_100_100_	55.8	-65.2	33.8	73.4	152	
G25B_100_100_	59.3	-50.3	-9.0	51.0	190	
G50B_100_100_	63.0	-30.5	-42.0	51.9	234	
G75B_100_100_	45.7	-5.7	-44.6	44.9	262	
B00R_100_100_	27.5	25.9	-47.3	53.9	298	
B25R_100_100_	38.3	52.6	-28.5	59.8	331	
B50R_100_100_	49.5	73.5	-9.0	74.0	353	
B75R_100_100_	48.9	69.3	12.9	70.4	10	



%Gamma
u*rel = 114
%Regularità
g*H,rel = 28
g*C,rel = 38

FRS06a; dati atti CIELAB (a)					
name	L*=L*a	a*a	b*a	C*ab,a	h*ab,a
R-,Ma	32.5	62.3	46.4	77.7	36
Y-,Ma	82.7	-3.1	113.9	114.0	91
G-,Ma	39.4	-61.8	45.8	76.9	143
C-,Ma	47.8	-26.8	-34.2	43.4	231
B-,Ma	10.1	55.1	-61.0	82.2	312
M-,Ma	34.5	80.6	-33.9	87.5	337
N-,Ma	6.2	0.0	0.0	0.0	0
W-,Ma	91.9	0.0	0.0	0.0	0
R-,CIE	39.9	58.7	27.9	65.0	25
Y-,CIE	81.2	-2.8	71.5	71.6	92
G-,CIE	52.2	-42.4	13.6	44.5	162
B-,CIE	30.5	1.4	-46.4	46.4	271

