

Immettere y uscita: Offset Reflective System ORS18a for relative CIELAB hue $h_{ab,a,rel} = h_{ab}/360 = 127/360 = 0.35$


$H^*_e = Y50G_e$

Dati del dispositivo (d) o colori elementari (e):

HIC^*_e
codice di tonalità per i colori
questa pagina:

$H^*_e = Y50G_e$

triangolo chiarezza T^*



ORS20a; dati atti CIELAB (a)					
Name	$L^*=L^*_a$	a^*_a	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R _e ,Ma	47.6	64.9	30.9	71.9	25
Y _e ,Ma	82.9	-3.5	87.8	87.9	92
G _e ,Ma	52.4	-67.1	21.5	70.5	162
C _e ,Ma	56.6	-39.7	-29.9	49.8	216
B _e ,Ma	37.9	1.3	-45.4	45.4	271
M _e ,Ma	34.8	49.2	-30.0	57.7	328
N _e ,Ma	17.7	0.0	0.0	0.0	0
W _e ,Ma	95.4	0.0	0.0	0.0	0
R _e ,CIE	39.9	58.7	27.9	65.0	25
Y _e ,CIE	81.2	-2.8	71.5	71.6	92
G _e ,CIE	52.2	-42.4	13.6	44.5	162
B _e ,CIE	30.5	1.4	-46.4	46.4	271

Il dati per il massimo colore (Ma):

$LabCh^*_{e,Ma}$: 65 -41 54 68 127

$HIC^*_{e,Ma}$: Y50G_100_100_e

$rgbic^*_{e,Ma}$:

0.32 1.0 0.0 1.0 1.0

triangolo chiarezza T^*

%Gamma



$u^*_{rel} = 92$

%Regularità

$g^*_{H,rel} = 57$

$g^*_{C,rel} = 58$

ORS20a; dati atti CIELAB (a)					
H^*_e	$L^*=L^*_a$	a^*_a	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R00Y_100_100 _e	47.6	64.9	30.9	71.9	25
R25Y_100_100 _e	51.5	54.2	47.2	71.9	41
R50Y_100_100 _e	60.3	35.6	59.0	68.9	58
R75Y_100_100 _e	70.4	17.0	72.2	74.1	76
Y00G_100_100 _e	82.9	-3.5	87.8	87.9	92
Y25G_100_100 _e	76.9	-25.5	75.9	80.1	108
Y50G_100_100 _e	65.8	-41.4	54.4	68.3	127
Y75G_100_100 _e	56.9	-56.3	38.1	68.0	145
G00B_100_100 _e	52.4	-67.1	21.5	70.5	162
G25B_100_100 _e	54.6	-53.2	-9.0	53.9	189
G50B_100_100 _e	56.6	-39.7	-29.9	49.8	216
G75B_100_100 _e	52.7	-21.1	-44.1	48.9	244
B00R_100_100 _e	37.9	1.3	-45.4	45.4	271
B25R_100_100 _e	26.7	26.6	-45.8	52.9	300
B50R_100_100 _e	34.8	49.2	-30.0	57.7	328
B75R_100_100 _e	47.3	71.5	-9.9	72.1	352



4-013130-L0 QI530-71

grafico TUB-QI53; codice di tinte: $H^*_e=Y50G_e$
grafico conformemente a DIN 33872, 3D=0, de=1, cmyk

immettere: $rgb/cmyk \rightarrow rgb_e$
uscita: trasferire a $cmyk_e$

TUB iscrizione: 20130201-QI53/QI53L0NP.PDF /.PS
la domanda per la misura uscita nella stampa di offset, separazionecmyk6 (CMYK)

TUB materiale: code=rha4ta