


Entrée et sortie: Système Laser Reflective LRS18a

Données de couleurs périphériques (d)
ou élémentaires (e):

HIC^*_d
code de teinte pour les cou-
leurs de cette page:
 $H^*_d = R00Y_d, R25Y_d, ..., B75R_d$

LRS18a; données CIELAB (a) adaptées					
H^*_d	$L^*=L^*_a$	a^*_a	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R00Y_100_100_d	47.0	60.1	37.1	70.6	31
R25Y_100_100_d	59.3	41.4	58.7	71.9	54
R50Y_100_100_d	72.6	16.6	70.9	72.8	76
R75Y_100_100_d	84.3	-3.3	76.4	76.5	92
Y00G_100_100_d	91.3	-14.5	82.1	83.4	100
Y25G_100_100_d	91.1	-20.0	90.8	92.9	102
Y50G_100_100_d	74.8	-36.6	64.9	74.5	119
Y75G_100_100_d	61.6	-54.7	43.8	70.1	141
G00B_100_100_d	55.7	-64.0	32.6	71.8	152
G25B_100_100_d	57.5	-47.9	-6.0	48.3	187
G50B_100_100_d	53.0	-31.0	-40.9	51.4	232
G75B_100_100_d	46.1	-11.3	-49.4	50.6	257
B00R_100_100_d	32.3	24.2	-42.5	48.9	299
B25R_100_100_d	35.9	51.1	-28.6	58.6	330
B50R_100_100_d	47.1	71.4	-11.5	72.3	350
B75R_100_100_d	45.9	63.0	11.0	64.0	9



% Gamme
 $u^*_{rel} = 114$
% Régularité
 $g^*_{H,rel} = 28$
 $g^*_{C,rel} = 38$

LRS18a; données CIELAB (a) adaptées					
nom	$L^*=L^*_a$	a^*_a	b^*_a	$C^*_{ab,a}$	$h^*_{ab,a}$
R _{d, Ma}	47.0	60.1	37.1	70.6	31
Y _{d, Ma}	91.3	-14.5	82.1	83.4	100
G _{d, Ma}	55.7	-64.0	32.6	71.8	152
C _{d, Ma}	53.0	-31.0	-40.9	51.4	232
B _{d, Ma}	32.3	24.2	-42.5	48.9	299
M _{d, Ma}	47.1	71.4	-11.5	72.3	350
N _{d, Ma}	14.7	0.0	0.0	0.0	0
W _{d, Ma}	96.3	0.0	0.0	0.0	0
R _{d, CIE}	39.9	58.7	27.9	65.0	25
Y _{d, CIE}	81.2	-2.8	71.5	71.6	92
G _{d, CIE}	52.2	-42.4	13.6	44.5	162
B _{d, CIE}	30.5	1.4	-46.4	46.4	271

