









http://130.149.60.45/~farbmtrik/SE72/SE72L0N1.TXT /PS; start output
N: no 3D-linearization (OL) in file (F) or PS-startup (S), page 1/2

Optimal colours (o) of maximum (m) C_{AB} for D65, $Y_w=100$, $Y_m=495.770$

i	λ_i	λ_2	λ_3	X_{100}	Y_{100}	Z_{100}	x	y	z	x_{356}	y_{356}	z_{356}	i_{45}	i_{48}	i_{49}	i_{50}	Code
0	405	32	561	32.57	58.20	108.12	0.1637	0.2926	0.5436	193.7	16	483	37	589	81	505c	Cm
6	435	32	562	29.09	58.79	88.73	0.1647	0.3328	0.5023	178.4	17	486	42	610			
10	450	32	563	22.93	59.41	52.37	0.1702	0.441	0.3887	141.8	19	496					
12	460	33	565	20.88	60.32	34.02	0.1812	0.5234	0.2952	124.0	21	505					
12	465	33	567	21.95	61.66	34.03	0.1866	0.5241	0.2892	122.8	21	506					
14	470	33	569	21.47	62.72	19.98	0.206	0.602	0.1918	111.3	24	520					
15	475	34	573	23.76	65.29	14.91	0.2285	0.6279	0.1434	105.6	25	528					
16	480	36	580	29.00	69.95	11.05	0.2636	0.6358	0.1005	90.7	27	537					
17	485	39	595	42.11	78.75	8.23	0.3261	0.6099	0.0638	87.2	29	548					
18	490																
18	490																
19	495																
20	500																
22	510																
23	520																
25	530																
27	540																
28	545																
29	550																
30	555																
32	560																
32	561	0	405	62.46	41.79	0.76	0.5948	0.3979	0.0072	13.7	37	589	16	483			Rm
32	562	6	435	65.95	41.2	20.15	0.518	0.3236	0.1583	35.84	42	610	17	486			
32	563	10	450	72.11	41.58	56.51	0.4261	0.2398	0.3339	32.1							
33	565	12	460	74.16	39.67	74.86	0.393	0.2102	0.3967	30.40							
33	567	12	465	73.08	38.33	74.86	0.3923	0.2057	0.4018	30.29							
33	569	14	470	73.57	37.27	88.9	0.3683	0.1865	0.445	29.13							
34	573	15	475	71.57	37.47	93.97	0.3564	0.1735	0.4699	28.57							
36	580	16	480	66.03	30.04	97.83	0.3405	0.1549	0.5045	27.91							
39	595	17	485	52.92	21.24	100.65	0.3027	0.1215	0.5757	26.72							
-1	490	18	490	17.95	6.19	102.75	0.1414	0.487	0.8097	238.5	11	459	53	565			Bm
-1	495	19	495	18.0	7.69	104.36	0.1384	0.0591	0.8024	237.1	12	462	53	566			
-1	500	20	500	18.02	9.57	105.61	0.1352	0.0719	0.7928	235.4	12	464	53	567			
-1	510	22	510	18.14	14.72	107.25	0.1295	0.105	0.7654	230.7	13	469	53	569			
-1	519	23	520	18.37	18.01	107.72	0.1275	0.1249	0.7475	227.7	14	471	54	570			
-1	529	25	530	19.5	25.95	108.31	0.1268	0.1687	0.7043	220.7	15	475	54	573			
-1	539	27	540	21.77	35.09	108.62	0.1315	0.212	0.6563	212.8	15	478	55	577			
-1	544	28	545	23.38	39.86	108.7	0.1359	0.2318	0.6321	208.8	15	479	55	579			
-1	549	29	550	25.33	44.73	108.76	0.1416	0.2501	0.6081	204.7	16	480	56	582			
-1	554	30	555	27.63	49.59	108.79	0.1485	0.2665	0.5848	200.8	16	481	56	584			
-1	560	32	560	32.68	58.99	108.83	0.1654	0.2933	0.5412	193.6	16	483	57	589			
380	770	95.04	100.0	108.89	0.3127	0.329	0.3582	0.0									



TUB-test chart SE72; maximum C_{AB} , $Y_m=495.770$
XYZ, xyz, h data for illuminant D65, $Y_w=100$

input: w/rgb/cmyk -> w/rgb/cmyk
output: no change

TUB registration: 20130201-SE72/SE72L0N1.TXT /PS
application for measurement of display output

TUB material: code=thata