

CIE data for all optimal colours of maximum (m) C _{AB} , D65 and Y _w =88,6, Y _m =495_770													
i ₁ , λ ₁	i ₂ , λ ₂	Y _{88.6}	A _{88.6}	B _{88.6}	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code		
0 405	32 561	51.56	−20.15	−15.85	25.64	0.5596	−0.743	218.1	16 483	37 589	Cm		
6 435	32 562	52.08	−23.73	−8.75	25.29	0.4948	−0.6036	200.2	17 486	42 610			
10 450	32 563	52.64	−29.71	4.36	30.03	0.3859	−0.3525	171.6	19 496	−1 496c			
12 460	33 565	53.43	−32.29	11.21	34.18	0.3461	−0.2256	160.8	21 505	−1 505c			
12 465	33 567	54.62	−32.47	11.73	34.52	0.356	−0.2207	160.1	21 506	−1 506c			
14 470	33 569	55.56	−33.79	17.12	37.88	0.3422	−0.1274	153.1	24 520	−1 520c			
15 475	34 573	57.84	−33.91	19.9	39.33	0.364	−0.0913	149.5	25 528	−1 528c	Gm		
16 480	36 580	61.97	−33.2	23.07	40.43	0.4146	−0.0632	145.2	27 537	−1 537c			
17 485	39 595	69.76	−29.0	27.46	39.94	0.5347	−0.0418	136.5	29 548	−1 548c			
18 490	−1 490c	83.1	−10.68	34.02	35.66	0.8218	−0.0261	107.4	33 565	11 459			
19 495	−1 495c	81.77	−9.46	34.01	35.3	0.8346	−0.0195	105.5	33 566	12 462	Ym		
20 500	−1 500c	80.1	−7.9	33.73	34.64	0.8518	−0.0144	103.1	33 567	12 464			
22 510	−1 510c	75.54	−3.68	32.32	32.53	0.9016	−0.0076	96.5	33 569	13 469			
23 520	−1 519c	72.63	−1.11	31.22	31.24	0.935	−0.0056	92.0	34 570	14 471			
25 530	−1 529c	65.59	4.57	28.36	28.73	1.0201	−0.0031	80.8	34 573	15 475			
27 540	−1 539c	57.49	10.25	24.94	26.97	1.1288	−0.0016	67.6	35 577	15 478			
28 545	−1 544c	53.27	12.85	23.13	26.46	1.1917	−0.0012	60.9	35 579	15 479			
29 550	−1 549c	48.96	15.22	21.27	26.16	1.2613	−0.0009	54.4	36 582	16 480			
30 555	−1 554c	44.65	17.27	19.41	25.98	1.3372	−0.0007	48.3	36 584	16 481			
32 560	−1 560c	36.33	20.2	15.8	25.64	1.5064	−0.0005	38.0	37 589	16 483			
32 561	0 405	48.43	20.15	15.85	25.64	1.3665	−0.1081	38.1	37 589	16 483	Rm		
32 562	6 435	47.91	23.73	8.75	25.29	1.4458	−0.2528	20.2	42 610	17 486			
32 563	10 450	47.35	29.71	−4.36	30.03	1.5779	−0.5277	351.6	−1 496c	19 496			
33 565	12 460	46.56	32.29	−11.21	34.18	1.6439	−0.6765	340.8	−1 505c	21 505			
33 567	12 465	45.37	32.47	−11.73	34.52	1.666	−0.6942	340.1	−1 506c	21 506			
33 569	14 470	44.43	33.79	−17.12	37.88	1.711	−0.8209	333.1	−1 520c	24 520			
34 573	15 475	42.15	33.91	−19.9	39.33	1.755	−0.9078	329.5	−1 528c	25 528	Mm		
36 580	16 480	38.02	33.2	−23.07	40.43	1.8237	−1.0424	325.2	−1 537c	27 537			
39 595	17 485	30.23	29.0	−27.46	39.94	1.9097	−1.3442	316.5	−1 548c	29 548			
−1 490c	18 490	16.89	10.68	−34.02	35.66	1.5831	−2.4491	287.4	11 459	33 565			
−1 495c	19 495	18.22	9.46	−34.01	35.3	1.4699	−2.3016	285.5	12 462	33 566	Bm		
−1 500c	20 500	19.89	7.9	−33.73	34.64	1.3475	−2.1309	283.1	12 464	33 567			
−1 510c	22 510	24.45	3.68	−32.32	32.53	1.101	−1.7576	276.5	13 469	33 569			
−1 519c	23 520	27.36	1.11	−31.22	31.24	0.9912	−1.5765	272.0	14 471	34 570			
−1 529c	25 530	34.4	−4.57	−28.36	28.73	0.8175	−1.2601	260.8	15 475	34 573			
−1 539c	27 540	42.5	−10.25	−24.94	26.97	0.7091	−1.0225	247.6	15 478	35 577			
−1 544c	28 545	46.72	−12.85	−23.13	26.46	0.6753	−0.9306	240.9	15 479	35 579			
−1 549c	29 550	51.03	−15.22	−21.27	26.16	0.6522	−0.8524	234.4	16 480	36 582			
−1 554c	30 555	55.34	−17.27	−19.41	25.98	0.6383	−0.7863	228.3	16 481	36 584			
−1 560c	32 560	63.66	−20.2	−15.8	25.64	0.6331	−0.6837	218.0	16 483	37 589			
380	770	88.59	0.0	0.0	0.01	0.9504	−0.4355	0.0					