

CIE-Daten für alle Optimalfarben von maximalem (m) C _{AB} für D65 und Y _w =100, Y _m =520, 770													
i ₁	i ₂	i ₃	Y ₁₀₀	B ₁₀₀	C _{AB}	a	b	h ₁₈₁	i _d	i _d	i _c	i _c	Code
0	405	32	561	58.2	-22.74	-17.89	28.94	0.5596	-0.743	21.81	16	483	37 589
1	410	32	561	58.23	-22.89	-17.61	28.88	0.5573	-0.738	21.75	16	483	37 589
2	415	32	561	58.26	-23.16	-17.29	28.78	0.5539	-0.726	21.64	16	483	37 589
3	420	32	561	58.33	-23.47	-17.11	28.47	0.5326	-0.687	21.11	16	484	38 594
4	425	32	562	58.47	-24.4	-14.65	28.47	0.5329	-0.6862	21.09	16	484	38 594
5	430	32	562	58.55	-26.72	-9.98	28.53	0.4939	-0.6061	20.04	17	486	41 609
6	435	32	562	58.79	-26.79	-9.88	28.55	0.4948	-0.6036	20.02	17	486	42 610
7	440	32	562	58.88	-30.03	-3.03	30.19	0.4402	-0.871	18.57	18	490	44 90c
8	440	32	563	59.12	-31.81	0.01	31.82	0.4146	-0.4203	17.83	18	492	44 90c
9	450	32	563	59.12	-32.54	4.9	36.24	0.363	-0.352	15.93	19	500	50 000
10	455	32	564	59.81	-35.13	8.9	36.24	0.363	-0.2867	16.20	20	500	50 000
11	460	33	565	60.32	-36.45	12.66	38.58	0.3461	-0.2256	16.08	21	505	51 505c
12	465	33	567	61.66	-36.65	13.24	39.87	0.356	-0.2207	16.01	21	506	51 506c
13	470	33	569	62.72	-38.14	19.32	42.76	0.3422	-0.1274	15.31	24	520	52 000
14	475	34	573	65.29	-38.28	22.47	44.39	0.364	-0.0913	14.95	25	528	52 800
15	480	36	580	69.95	-37.48	26.04	45.64	0.4146	-0.0632	14.52	27	537	53 700
16	485	39	595	78.75	-32.73	31.0	50.09	0.5047	-0.0418	13.24	31	549	54 900
17	490	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
18	495	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
19	495	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
20	500	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
21	505	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
22	510	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
23	515	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
24	520	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
25	525	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
26	530	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
27	535	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
28	540	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
29	545	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
30	550	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
31	555	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
32	560	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
33	565	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
34	570	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
35	575	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
36	580	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
37	585	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
38	590	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
39	595	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
40	600	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
41	605	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
42	610	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
43	615	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
44	620	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
45	625	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
46	630	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
47	635	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
48	640	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
49	645	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
50	650	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
51	655	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
52	660	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
53	665	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
54	670	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
55	675	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
56	680	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
57	685	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
58	690	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
59	695	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
60	700	41	604	93.8	-12.06	38.4	40.25	0.8218	-0.061	10.74	33	565	51 459
380	770	100.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

0-000039-L0

SG64-1

0-000039-L0

SG64-1

TUB-Prüfvorlage SG64; Maximum C_{AB}, Y_m=520, 770
Y_{AB}C_{AB}h-Dateien für Lichtart D65, Y_w=100

Eingabe: w/r/gb/cmyk → w/r/gb/cmyk-
Ausgabe: keine Änderung

Siehe ähnliche Dateien: <http://130.149.60.45/~farbmtrik/SG64/SG64L0N1.TXT> /PS; Start-Ausgabe
Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmtrik>

TUB-Registrierung: 20130201-SG64/SG64L0N1.TXT /PS
Anwendung für Messung von Display-Ausgabe
TUB-Material: Code=th4ta