

http://230.149.60.45/~farbmatrik/SI91/SI91LON1.TXT /PS; cominciare l'uscita
 N: nessun 3D-linearizzazione (OL) nel file (F) o PS-startup (S), pagina 1/2

CIE data for all optimal colours of maximum (m) C _{AB} , D65 and Y _w =88.6, Y _m =495.770														
i ₁	λ ₁	i ₂	λ ₂	Y _{88.6}	A _{88.6}	B _{88.6}	C _{AB}	a	b	h _{AB}	i _d	i _d	i _c	Code
0	405	32	561	51.56	-20.15	-15.85	25.64	0.5596	-0.743	218.1	16	483	37	589 Cm
6	435	32	562	52.08	-23.73	-8.75	25.29	0.4948	-0.6036	200.2	17	486	42	610
10	450	32	563	52.64	-29.71	4.36	30.03	0.3859	-0.3525	171.6	19	496	-1	496c
12	460	33	565	53.43	-32.29	11.21	34.18	0.3461	-0.2256	160.8	21	505	-1	505c
12	465	33	567	54.62	-32.47	17.73	34.52	0.356	-0.2207	160.1	21	506	-1	506c
14	470	33	569	55.56	-33.79	17.12	37.88	0.3422	-0.1274	153.1	24	520	-1	520c
15	475	34	573	57.84	-33.91	19.9	39.33	0.364	-0.0913	149.5	25	528	-1	528c Gm
16	480	36	580	61.97	-33.2	23.07	40.43	0.4146	-0.0632	145.2	27	537	-1	537c
17	485	39	595	69.76	-29.0	27.46	39.94	0.5347	-0.0418	136.5	29	548	-1	548c
18	490	-1	490c	83.1	-10.68	34.02	35.66	0.8218	-0.0261	107.4	33	565	11	459
19	495	-1	495c	81.77	-9.46	34.01	35.3	0.8346	-0.0195	105.5	33	566	12	462 Ym
20	500	-1	500c	80.1	-7.9	33.73	34.64	0.8518	-0.0144	103.1	33	567	12	464
22	510	-1	510c	75.54	-3.68	32.32	32.53	0.9016	-0.0076	96.5	33	569	13	469
23	520	-1	519c	72.63	-1.11	31.22	31.24	0.935	-0.0056	92.0	34	570	14	471
25	530	-1	529c	65.59	4.57	28.36	28.73	1.0201	-0.0031	80.8	34	573	15	475
27	540	-1	539c	57.49	10.25	24.94	26.97	1.1288	-0.0016	67.6	35	577	15	478
28	545	-1	544c	53.27	12.85	23.13	26.46	1.1917	-0.0012	60.9	35	579	15	479
29	550	-1	549c	48.96	15.22	21.27	26.16	1.2613	-0.0009	54.4	36	582	16	480
30	555	-1	554c	44.65	17.27	19.41	25.98	1.3372	-0.0007	48.3	36	584	16	481
32	560	-1	560c	36.33	20.2	15.8	25.64	1.5064	-0.0005	38.0	37	589	16	483
32	561	0	405	48.43	20.15	15.85	25.64	1.3665	-0.1081	38.1	37	589	16	483 Rm
32	562	6	435	47.91	23.73	8.75	25.29	1.4458	-0.2528	20.2	42	610	17	486
32	563	10	450	47.35	29.71	-4.36	30.03	1.5779	-0.5277	35.16	-1	496c	19	496
32	565	12	460	46.56	32.29	-11.21	34.18	1.6439	-0.6765	340.8	-1	505c	21	505
32	567	12	465	45.37	32.47	-11.73	34.52	1.666	-0.6942	340.1	-1	506c	21	506
32	569	14	470	44.43	33.79	-17.12	37.88	1.711	-0.8209	333.1	-1	520c	24	520
34	573	15	475	42.15	33.91	-19.9	39.33	1.755	-0.9078	329.5	-1	528c	25	528
36	580	16	480	38.02	33.2	-23.07	40.43	1.8237	-1.0424	325.2	-1	537c	27	537
39	595	17	485	30.23	29.0	-27.46	39.94	1.9097	-1.3442	316.5	-1	548c	29	548
-1	490c	18	490	16.89	10.68	-34.02	35.66	1.5831	-2.4491	287.4	11	459	33	565
-1	495c	19	495	18.22	9.46	-34.01	35.3	1.4699	-2.3016	285.5	12	462	33	566
-1	500c	20	500	19.89	7.9	-33.73	34.64	1.3475	-2.1309	283.1	12	464	33	567
-1	510c	22	510	24.45	3.68	-32.32	32.53	1.101	-1.7576	276.5	13	469	33	569
-1	519c	23	520	27.36	1.11	-31.22	31.24	0.9912	-1.5765	272.0	14	471	34	570
-1	529c	25	530	34.4	-4.57	-28.36	28.73	0.8175	-1.2601	260.8	15	475	34	573
-1	539c	27	540	42.5	-10.25	-24.94	26.97	0.7091	-1.0225	247.6	15	478	35	577
-1	544c	28	545	46.72	-12.85	-23.13	26.46	0.6753	-0.9306	240.9	15	479	35	579
-1	549c	29	550	51.03	-15.22	-21.27	26.16	0.6522	-0.8524	234.4	16	480	36	582
-1	554c	30	555	55.34	-17.27	-19.41	25.98	0.6383	-0.7863	228.3	16	481	36	584
-1	560c	32	560	63.66	-20.2	-15.8	25.64	0.6331	-0.6837	218.0	16	483	37	589
380	770	88.59	0.0	0.0	0.0	0.0	0.01	0.9504	-0.4355	0.0				

CIE data for all optimal colours of maximum (m) C _{AB} , D65 and Y _w =88.6, Y _m =495.770														
i ₁	λ ₁	i ₂	λ ₂	L [*] _{88.6}	a [*] _{88.6}	b [*] _{88.6}	C [*] _{ab}	a [*]	b [*]	h _{AB}	i _d	λ _d	i _c	Code
0	405	32	561	77.02	-64.87	-31.25	72.01	0.1805	-0.1029	205.7	16	483	37	589 Cm
6	435	32	562	77.34	-78.65	-18.49	80.79	0.1732	-0.096	193.2	17	486	42	610
10	450	32	563	77.66	-104.74	10.98	105.32	0.1595	-0.0803	174.0	19	496	-1	496c
12	460	33	565	78.13	-115.96	31.94	120.28	0.1538	-0.0692	164.5	21	505	-1	505c
12	465	33	567	78.83	-114.06	33.13	118.77	0.1552	-0.0687	163.8	21	506	-1	506c
14	470	33	569	79.37	-118.58	55.25	130.82	0.1532	-0.0572	155.0	24	520	-1	520c
15	475	34	573	80.65	-114.03	67.6	132.56	0.1564	-0.0512	149.3	25	528	-1	528c Gm
16	480	36	580	82.9	-102.97	80.87	130.93	0.1633	-0.0452	141.8	27	537	-1	537c
17	485	39	595	86.88	-77.35	96.11	123.37	0.1778	-0.0394	128.8	29	548	-1	548c
18	490	-1	490c	93.06	-22.24	114.34	116.48	0.2052	-0.0337	101.0	33	565	11	459
19	495	-1	495c	92.47	-19.81	120.45	122.06	0.2062	-0.0306	99.3	33	566	12	462 Ym
20	500	-1	500c	91.73	-16.65	125.95	127.04	0.2076	-0.0277	97.5	33	567	12	464
22	510	-1	510c	88.67	-7.92	134.61	134.84	0.2116	-0.0224	93.3	33	569	13	469
23	520	-1	519c	89.25	-2.43	137.31	137.33	0.2142	-0.0202	91.0	34	570	14	471
25	530	-1	529c	84.79	10.36	138.25	138.64	0.2205	-0.0165	85.7	34	573	15	475
27	540	-1	539c	80.46	24.53	135.02	137.23	0.2281	-0.0134	79.7	35	577	15	478
28	545	-1	544c	78.04	31.74	131.99	135.75	0.2322	-0.0121	76.4	35	579	15	479
29	550	-1	549c	75.43	38.97	128.25	134.04	0.2367	-0.0111	73.0	36	582	16	480
30	555	-1	554c	72.66	46.06	123.97	132.25	0.2413	-0.0103	69.6	36	584	16	481
32	560	-1	560c	66.77	59.19	114.35	128.76	0.2511	-0.0093	62.6	37	589	16	483
32	561	0	405	75.1	50.51	58.31	77.15	0.2431	-0.0541	49.1	37	589	16	483 Rm
32	562	6	435	74.77	58.71	25.94	64.18	0.2477	-0.0718	23.8	42	610	17	486
32	563	10	450	74.42	71.74	-10.3	72.47	0.255	-0.0918	351.8	-1	496c	19	496
32	565	12	460	73.91	77.65	-24.5	81.42	0.2585	-0.0997	342.4	-1	505c	21	505
32	567	12	465	73.14	79.04	-25.83	83.15	0.2597	-0.1006	341.9	-1	506c	21	506
32	569	14	470	72.52	82.59	-35.89	90.05	0.262	-0.1064	335.1	-1	520c	24	520
34	573	15	475	70.98	85.03	-41.59	94.66	0.2642	-0.11	333.9	-1	528c	25	528
36	580	16	480	68.04	87.88	-48.91	100.57	0.2676	-0.1152	330.9	-1	537c	27	537
39	595	17	485	61.86	87.86	-61.19	107.07	0.2718	-0.1254	325.1	-1	548c	29	548
-1	490c	18	490	48.14	51.23	-86.03	100.13	0.2553	-0.1532	300.7	11	459	33	565
-1	495c	19	495	49.78	44.33	-84.1	95.07	0.2491	-0.15	297.7	12	462	33	566
-1	500c	20	500	51.73	36.01	-81.43	98.04	0.242	-0.1462	293.8	12	464	33	567
-1	510c	22	510	56.54	15.71	-74.03	75.68	0.2262	-0.1371	281.9	13	469	33	569
-1	519c	23	520	59.32	4.57	-69.51	69.66	0.2184	-0.1323	273.7	14	471	34	570
-1	529c	25	530	65.28	-17.14	-59.54	61.96	0.2048	-0.1227	253.9	15	475	34	573
-1	539c	27	540	71.22	-34.96	-49.47	60.58	0.1953	-0.1145	234.7	15	478	35	577
-1	544c	28	545	74.02	-41.75	-44.69	61.16	0.1922	-0.1109	226.9	15	479	35	579
-1	549c	29	550	76.7	-47.12	-40.09	61.87	0.19	-0.1077	220.3	16	480	36	582
-1	554c	30	555	79.24	-51.0	-35.73	62.27	0.1886	-0.1049	215.0	16	481	36	584
-1	560c	32	560	83.79	-54.46	-27.9	61.19	0.1881	-0.1001	207.1	16	483	37	589
380	770	95.41	0.0	0.0	0.0	0.0	0.2154	-0.0861	0.0					

grafico TUB-SI91; maximum C_{AB}; Y_m=495.770
 YABCAb & LabCa'b'h data for illuminant D65, Y_w=88.6

immettere: w/rgb/cmyk -> w/rgb/cmyk-
 uscita: nessun cambiamento

TUB iscrizione: 20130201-SI91/SI91LON1.TXT /PS
 la domanda per la misura di stampa di display

TUB