


Entrada i salida: Offset Reflective System ORS18a

Datos del dispositivo (d) o
elemental (e) color:

H^{*}_{IC} -
código de tono para los colores
esta página:



$H^{*}_{IC} = R00Y_{-}, R25Y_{-}, ..., B75R_{-}$

ORS20a; datos adaptados CIELAB (a)						
H^{*}_{IC}	$L^{*}=L^{*}_{s}$	a^{*}_{s}	b^{*}_{s}	$C^{*}_{s,ab}$	$h^{*}_{s,ab}$	
R00Y_100_100_	48.4	66.1	40.2	77.3	31	
R25Y_100_100_	56.8	48.0	50.5	69.6	46	
R50Y_100_100_	68.6	25.0	63.9	68.6	68	
R75Y_100_100_	80.6	4.8	77.2	77.3	86	
Y00G_100_100_	90.2	-9.6	88.2	88.7	96	
Y25G_100_100_	83.2	-18.4	79.9	81.9	102	
Y50G_100_100_	73.3	-31.7	62.7	70.2	116	
Y75G_100_100_	62.0	-49.7	43.2	65.8	139	
G00B_100_100_	55.8	-65.2	33.8	73.4	152	
G25B_100_100_	59.3	-50.3	-9.0	51.0	190	
G50B_100_100_	63.0	-30.5	-42.0	51.9	234	
G75B_100_100_	45.7	-5.7	-44.6	44.9	262	
B00R_100_100_	27.5	25.9	-47.3	53.9	298	
B25R_100_100_	38.3	52.6	-28.5	59.8	331	
B50R_100_100_	49.5	73.5	-9.0	74.0	353	
B75R_100_100_	48.9	69.3	12.9	70.4	10	



$u^{*}_{rel} = 92$
%Regularidad
 $g^{*}_{H,rel} = 57$
 $g^{*}_{C,rel} = 58$

ORS18a; datos adaptados CIELAB (a)						
Name	$L^{*}=L^{*}_{s}$	a^{*}_{s}	b^{*}_{s}	$C^{*}_{s,ab}$	$h^{*}_{s,ab}$	
R_18a	47.9	65.3	50.5	82.6	37	
Y_18a	90.3	-10.2	91.7	92.3	96	
G_18a	50.9	-62.8	34.9	71.9	150	
C_18a	58.6	-30.3	-45.0	54.2	236	
B_18a	25.7	31.0	-44.4	54.2	305	
M_18a	48.1	75.2	-8.3	75.7	353	
N_18a	18.0	0.0	0.0	0.0	0	
W_18a	95.4	0.0	0.0	0.0	0	
R_18a	39.9	58.7	27.9	65.0	25	
Y_18a	81.2	-2.8	71.5	71.6	92	
G_18a	52.2	-42.4	13.6	44.5	162	
B_18a	30.5	1.4	-46.4	46.4	271	



2-003031-L0 SS080-7N

gráfico TUB-SS08; 16 tonos, estándar de papel offset
gráfico según a DIN 33872

entrada: rgb/cmyk -> rgb/cmyk
salida: ningún cambio