









Ostwald couleurs optimaux (o) de la maximum (m) C _{AB} pour D65, Y _w =88.6, Y _m =520, 770									
i ₁	i ₂	i ₃	X _{88.6}	Y _{88.6}	Z _{88.6}	x	y	z	Code
0 405	32 561	28.85	51.95	95.79	0.1637	0.2926	0.5436	193.7	16 483 37 589 Cm
6 435	32 562	25.77	52.08	78.6	0.1647	0.3328	0.5023	178.4	17 486 42 610
10 450	32 563	20.31	52.64	46.4	0.1702	0.441	0.3887	141.8	19 496 -1 496c
12 460	33 565	18.49	53.43	30.14	0.1812	0.5234	0.2952	124.0	21 505 -1 505c
12 465	33 567	19.45	54.62	30.14	0.1866	0.5241	0.2892	122.8	21 506 -1 506c
14 470	33 569	19.02	55.56	17.7	0.206	0.604	0.1918	111.3	24 520 -1 520c
15 475	34 573	21.05	57.84	13.21	0.2285	0.6279	0.1434	105.6	25 528 -1 528c
16 480	36 580	25.69	61.97	9.79	0.2636	0.6358	0.1005	99.0	27 537 -1 537c
17 485	39 595	37.3	69.76	7.29	0.3261	0.6099	0.0638	87.2	29 548 -1 548c
18 490	-1 490c	68.29	83.1	5.43	0.4354	0.5298	0.0346	58.5	33 565 11 459 max
19 495	-1 495c	68.25	81.77	4.0	0.4431	0.5038	0.026	57.1	33 566 12 462
20 500	-1 500c	68.23	80.1	2.89	0.4511	0.5296	0.0191	55.3	33 567 12 464
22 510	-1 510c	68.12	75.54	1.45	0.4694	0.5205	0.01	50.7	33 569 13 469
23 520	-1 519c	67.91	72.63	1.03	0.4797	0.513	0.0072	47.7	34 570 14 471 Ym
25 530	-1 529c	66.91	65.59	0.51	0.503	0.4931	0.0038	40.7	34 573 15 475
27 540	-1 539c	64.9	57.49	0.23	0.5292	0.4688	0.0019	32.8	35 577 15 478
28 545	-1 544c	63.48	53.27	0.16	0.5429	0.4556	0.0014	28.7	35 579 15 479
29 550	-1 549c	61.75	48.96	0.11	0.5571	0.4417	0.001	24.7	36 582 16 480
30 555	-1 554c	59.71	44.65	0.08	0.5716	0.4274	0.0008	20.8	36 584 16 481
32 560	-1 560c	54.73	36.33	0.05	0.6007	0.3987	0.0005	13.6	37 589 16 483
32 561	0 405	66.18	48.43	13.1	0.5182	0.3792	0.1025	13.7	37 589 16 483
32 562	6 435	69.27	47.91	30.28	0.4697	0.3249	0.2053	358.4	42 610 17 486
32 563	10 450	74.73	47.33	62.49	0.4048	0.2565	0.3385	321.8	-1 496c 19 496
33 565	16 480	76.54	46.56	78.74	0.3792	0.2306	0.3901	304.1	-1 505c 21 505
33 567	12 465	75.59	45.37	78.74	0.3785	0.2271	0.3942	302.9	-1 506c 21 506
33 569	14 470	76.02	44.43	91.18	0.3592	0.2099	0.4308	291.3	-1 520c 24 520
34 573	15 475	73.98	42.15	95.67	0.3492	0.199	0.4516	285.7	-1 528c 25 528 Mm
36 580	16 480	69.34	38.02	99.09	0.3358	0.1841	0.4799	279.1	-1 537c 27 537
39 595	17 485	57.73	30.23	101.59	0.3045	0.1594	0.5359	267.2	-1 548c 29 548
-1 490c	18 490	26.74	16.89	103.45	0.1818	0.1148	0.7032	238.5	11 459 33 565 min
-1 495c	19 495	26.79	18.22	104.88	0.1787	0.1215	0.6996	237.1	12 462 33 566
-1 500c	20 500	26.81	19.89	105.99	0.1755	0.1302	0.6941	235.4	12 464 33 567
-1 510c	22 510	26.92	24.45	107.43	0.1695	0.1539	0.6765	230.7	13 469 33 569
-1 519c	23 520	27.12	27.36	107.85	0.167	0.1685	0.6643	227.7	14 471 34 570 Bm
-1 529c	25 530	28.12	34.4	108.38	0.1645	0.2012	0.6341	220.7	15 475 34 573
-1 539c	27 540	30.13	42.5	108.65	0.1662	0.2344	0.5993	212.8	15 478 35 577
-1 544c	28 545	31.55	46.72	108.72	0.1687	0.2498	0.5813	208.8	15 479 35 579
-1 549c	29 550	33.29	51.03	108.77	0.1723	0.2643	0.5632	204.7	16 480 36 582
-1 554c	30 555	35.32	55.34	108.8	0.1771	0.2774	0.5454	200.8	16 481 36 584
-1 560c	32 560	40.31	63.66	108.84	0.1894	0.2991	0.5114	193.6	16 483 37 589

3-000030-L0

TUB-test graphique TF23; maximum C_{AB}, Y_w=520, 770
XYZ, xyz, h data, D65, Y_w=88.6, Parameter: Name



3-000030-L0



3-000030-L0

entrée: w/rgb/cmyk -> w/rgb/cmyk-
sortie: aucun changement