


Radialgitter (Siemenssterne) W-N



Radialgitter (Siemenssterne) W-Z

TG760-3, Bild C1Wdd: Element A: Radialgitter $N-W$, $W-N$, $N-Z$ und $W-Z$; PS-Operator: $rgb/cmy0$

$L^*/Y_{\text{vorgesehen}}$ (absolut)	18.0/18.0	37.3/37.3	56.7/56.7	76.1/76.0	95.4/95.4	N_0 (min.)	W_1 (max.)
$w^*=I^*_{\text{CIELAB}, r}$ (relativ)							
w^*_{Eingabe} w^*_{Ausgabe}	0,000	0,250	0,500	0,750	1,000	N_0 (min.)	W_1 (max.)

TG760-5, Bild C2Wdd: Element B: 5 visuell gleichabständige L^* -Graustufen + $N0$ + $W1$; PS-Operator: $rgb/cmy0$

$L^*/Y_{\text{vorgesehen}}$	18.0/18.0	23.2/23.2	28.3/28.3	33.5/33.5	38.6/38.6	43.8/43.8	49.0/49.0	54.1/54.1	59.3/59.3	64.4/64.4	69.6/69.6	74.8/74.8	79.9/79.9	85.1/85.1	90.2/90.2	95.4/95.4
(absolut)																
Nr. und Hex-Code	00;F	01;E	02;D	03;C	04;B	05;A	06;9	07;8	08;7	09;6	10;5	11;4	12;3	13;2	14;1	15;0
$w^* = L^*_{CIE LAB, r}$																
w^*_{Eingabe}	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000
w^*_{Ausgabe}																

TG760-7, Bild C3Wdd: Element C: 16 visuell gleichabständige L^* -Graustufen; PS-Operator: $rgb/cmy0$



Prüfvorlage TG76; ME16(ISO 9241-306), 3(ISO/IEC 15775)
Achromatische Prüfvorlage N, 3D=1, de=0, *cmYK**

Eingabe: $rgb/cmyk \rightarrow rgb_{dd}$
Ausgabe: 3D-Linearisierung $cmyk^*_{dd}$

0-1
7-8
E-F
2-0
8-6
F-D

Code: Umfeld-Ring

TG761-1, Bild C4Wdd: Element D: Landoltringe W-N; PS-Operator: *rgb/cmy0*

	120	128	136	144	152	160	168	176	184	192	200	208	216	224	232	240	
120 (+8)																	240
60 (+4)																	120
30 (+2)																	60
15 (+1)																	30
	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	
	Rasterweite in lpi																

TG761-3, Bild C5Wdd: Element E: Linienraster unter 45° (oder 135°); PS-Operator: *rgb/cmy0*

	120	128	136	144	152	160	168	176	184	192	200	208	216	224	232	240		
120 (+8)																		240
60 (+4)																		120
30 (+2)																		60
15 (+1)																		30
	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30		
Rasterweite in lpi																		

TG761-5, Bild C6Wdd: Element F: Linienraster unter 90° (oder 0°); PS-Operator: *rgb/cmy0*