

http://130.149.60.45/~farbmatrik/VE31/VE31L0N1.TXT /PS; transfer output
N: no 3D-linearization (OL) in file (F) or PS-startup (S), page 1/1

Ostwald optimal colours (o) of maximum (m) CAB for D50, Y _w =100, Y _m =520_770, LINYAB data														%
i, λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	CAB	a	b	HAB	i _d , λ _d	i _c , λ _c	Code		%	
1	405	32	564	57.81	-26.12	-13.56	29.43	0.5124	-0.5646	207.4	17 486	38 592	Cm	%
7	435	33	565	58.18	-29.76	-6.19	30.4	0.4526	-0.4365	191.7	18 490	46 634		%
10	450	35	566	58.68	-33.54	2.37	33.63	0.3924	-0.2895	175.9	19 497	-1 497c		%
12	460	33	567	59.3	-35.7	8.25	36.64	0.3621	-0.1907	166.9	21 506	-1 506c		%
13	465	33	568	59.95	-36.49	10.91	38.09	0.3555	-0.1478	163.3	22 511	-1 511c		%
14	470	34	570	61.04	-36.99	13.31	39.32	0.3581	-0.1117	160.1	23 519	-1 519c		%
15	475	34	573	62.89	-37.08	15.59	40.23	0.3745	-0.0821	157.2	25 527	-1 527c	Gm	%
15	480	35	578	66.91	-36.91	16.91	40.6	0.4125	-0.0772	155.3	26 531	-1 531c		%
17	485	37	587	72.24	-34.33	20.9	41.09	0.489	-0.0405	148.6	28 544	-1 544c		%
18	490	44	620	88.02	-39.26	26.82	33.02	0.7454	-0.0251	125.6	32 561	-1 561c	max	%
19	495	-1 495c	93.65	-7.19	29.25	30.12	0.8874	-0.0176	103.8	33 568	12 463		%	%
20	500	-1 500c	91.98	-5.59	29.14	29.67	0.9033	-0.0131	100.8	33 569	13 466		%	%
22	510	-1 510c	87.33	-1.23	28.19	28.22	0.95	-0.0071	92.5	34 571	14 471		%	%
23	520	-1 519c	84.29	1.48	27.36	27.41	0.9818	-0.0053	86.8	34 572	14 473		%	%
25	530	-1 529c	76.8	7.64	25.11	26.25	1.0637	-0.0029	73.0	35 575	15 477		Ym	%
27	540	-1 539c	68.0	13.94	22.33	26.32	1.1692	-0.0015	58.8	35 579	16 480			%
28	545	-1 544c	63.34	16.86	20.82	26.82	1.2304	-0.0011	50.9	36 581	17 481			%
29	550	-1 549c	58.55	19.56	19.26	27.45	1.2983	-0.0009	44.5	36 583	16 483			%
30	555	-1 554c	53.72	21.93	17.68	28.17	1.3724	-0.0007	38.8	37 585	16 484			%
32	560	-1 560c	44.27	25.38	14.58	29.27	1.5375	-0.0005	29.8	38 590	17 486			%
380	770	100.0	0.0	0.0	0.0	0.01	0.9642	-0.3299	0.0					%

Ostwald optimal colours (o) of maximum (m) CAB for D50, Y _w =100, Y _m =770_520, LINYAB complementarity %													
i, λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	CAB	a	b	HAB	i _d , λ _d	i _c , λ _c	Code	Rm	%
32 564	1 405	42.18	26.12	13.56	29.43	1.5834	-0.0084	27.4	38 592	17 486	Rm		%
33 565	7 435	41.81	29.76	6.19	30.4	1.6761	-0.1817	11.7	46 634	18 490			%
33 566	10 450	41.31	33.54	-2.37	33.63	1.7761	-0.3874	355.9	-1 497c	19 497			%
33 567	12 460	40.69	35.7	-8.25	36.64	1.8416	-0.5329	346.9	-1 506c	21 506			%
33 568	13 465	40.04	36.49	-10.91	38.09	1.8756	-0.6026	343.3	-1 511c	22 511			%
34 570	14 470	38.95	36.99	-13.31	39.32	1.9138	-0.6718	340.1	-1 519c	23 519			%
34 573	15 475	37.1	37.08	-15.59	40.23	1.9639	-0.7502	337.2	-1 527c	25 527	Mm		%
35 578	15 480	33.08	36.91	-16.91	40.6	2.0799	-0.8412	335.3	-1 531c	26 531			%
37 587	17 485	27.75	34.33	-20.9	41.09	2.201	-1.0832	328.6	-1 544c	28 544			%
44 620	18 490	11.97	19.26	-26.82	33.02	2.572	-2.5696	305.6	-1 561c	32 561	min		%
-1 495c	19 495	6.34	7.19	-29.25	30.12	2.0975	-4.9398	283.8	12 463	33 568			%
-1 500c	20 500	8.01	5.59	-29.14	29.67	1.6629	-3.9666	280.8	13 466	33 569			%
-1 510c	22 510	12.66	1.23	-28.19	28.22	1.0617	-2.5572	72.5	14 471	34 571			%
-1 519c	23 520	15.7	-1.48	-27.36	27.41	0.8696	-2.073	266.8	14 473	34 572	Bm		%
-1 529c	25 530	23.19	-7.64	-25.11	26.25	0.6346	-1.4127	253.0	15 477	35 575			%
-1 539c	27 540	31.99	-13.94	-22.33	26.32	0.5285	-1.0279	238.0	16 480	35 579			%
-1 544c	28 545	36.65	-16.86	-20.82	26.8	0.504	-0.8982	230.9	16 481	36 581			%
-1 549c	29 550	41.44	-19.56	-19.26	27.45	0.4922	-0.7949	224.5	16 483	36 583			%
-1 554c	30 555	46.27	-21.93	-17.68	28.17	0.4903	-0.7122	218.8	16 484	37 585			%
-1 560c	32 560	55.72	-25.38	-14.58	29.27	0.5087	-0.5917	209.8	17 486	38 590			%
380	770	100.0	0.0	0.0	0.01	0.9642	-0.3299	0.0					%

Ostwald optimal colours (o) of maximum (m) CAB for D50, Y _w =100, Y _m =520, 770, LINYAB data														%	
i, λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	CAB	a	b	HAB	i _d , λ _d	i _c , λ _c	Code		%		
1	405	31	559	55.95	-25.08	-13.86	28.66	0.5189	-0.5733	208.9	15 479	37 589	Cm	%	
7	435	32	561	56.42	-28.9	-5.53	29.42	0.455	-0.4238	190.8	16 484	58 693		%	
10	450	32	562	56.65	-32.28	3.24	32.45	0.3973	-0.2684	174.2	18 493	-1 493c		%	
12	460	32	564	57.41	-33.96	8.98	35.12	0.3757	-0.1691	165.1	20 503	-1 503c		%	
13	465	33	566	58.48	-34.34	11.63	36.25	0.38	-0.1267	161.2	22 512	-1 512c		%	
14	470	34	570	60.63	-34.33	14.23	37.16	0.401	-0.0909	157.4	24 521	-1 521c		%	
15	475	35	576	64.51	-33.34	16.97	37.41	0.4504	-0.0624	153.0	26 531	-1 531c	Gm	%	
16	480	38	590	72.88	-29.2	20.81	35.86	0.5665	-0.04	144.5	28 543	-1 543c		%	
17	485	-1 485c	92.6	-6.09	28.04	28.69	0.9014	-0.0228	102.2	32 563	11 458			%	
18	490	-1 490c	91.1	-4.69	28.13	28.52	0.9157	-0.0168	99.4	32 564	12 460	max		%	
19	495	-1 495c	89.32	-2.98	27.98	28.14	0.9338	-0.0123	96.0	33 565	12 462			%	
20	500	-1 500c	87.23	-1.0	27.62	27.64	0.9556	-0.0089	92.0	33 566	12 464			%	
21	510	-1 509c	84.82	1.2	27.07	27.09	0.9814	-0.0065	87.4	33 567	13 466			%	
24	520	-1 520c	75.59	8.88	24.43	26.0	1.0847	-0.0023	70.0	34 571	14 471	Ym		%	
25	530	-1 529c	71.83	11.6	23.28	26.01	1.1288	-0.0015	63.4	34 573	14 473			%	
28	540	-1 540c	59.32	19.15	19.3	27.19	1.29	-0.0002	45.2	35 579	15 476			%	
29	545	-1 545c	54.91	21.22	17.87	27.75	1.3537	-0.0001	40.1	36 581	15 477			%	
29	550	-1 549c	54.91	21.22	17.87	27.75	1.3537	-0.0001	40.1	36 581	15 477			%	
31	555	-1 555c	46.06	24.31	15.0	28.56	1.4949	0.0	31.6	37 587	15 479			%	
32	560	2	411	41.79	25.61	12.8	28.63	1.5801	-0.0192	26.5	38 591	16 480			%
380	770	99.99	0.0	0.0	0.0	0.01	0.9672	-0.3256	0.0					%	

Ostwald optimal colours (o) of maximum (m) CAB for D50, Y _w =100, Y _m =770, 520, LINYAB complementary														
i, λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	CAB	a	b	HAB	i _d , λ _d	i _c , λ _c	Code	%		
31	559	1	405	44.04	25.08	13.86	28.66	1.5368	-0.0108	28.9	37 589	15 479	Rm	%
32	561	7	435	43.57	28.9	5.53	29.42	1.6305	-0.1985	10.8	58 693	16 484		%
32	562	10	450	43.34	32.28	-3.24	32.45	1.7122	-0.4004	354.2	-1 493c	18 493		%
32	564	12	460	42.58	35.95	-8.98	35.12	1.7646	-0.5366	345.1	-1 503c	20 503		%
33	566	13	465	41.51	34.34	-11.63	36.25	1.7943	-0.6057	341.2	-1 512c	22 512		%
34	570	14	470	39.36	34.33	-14.23	37.16	1.8395	-0.6872	337.4	-1 521c	24 521		%
35	576	15	475	35.48	33.34	-16.97	37.41	1.9607	-0.804	333.0	-1 531c	26 531	Mm	%
38	590	16	480	27.11	29.2	-20.81	35.86	2.0442	-1.0933	324.5	-1 543c	28 543		%
-1	485c	17	485	7.39	6.09	-28.04	28.69	1.7911	-1.1155	282.1	11 458	32 563		%
-1	490c	18	490	8.89	4.69	-28.13	28.52	1.4945	-3.4884	279.4	12 460	32 564	min	%
-1	495c	19	495	10.67	2.98	-27.98	28.14	1.247	-2.9472	276.0	12 462	33 565		%
-1	500c	20	500	12.76	1.0	-27.62	27.64	1.0462	-2.49	272.0	12 464	33 566		%
-1	509c	21	510	15.17	-1.2	-27.07	27.09	0.8876	-2.1102	267.4	13 466	33 567		%
-1	520c	24	520	24.4	-8.88	-24.43	26.0	0.6033	-1.3269	250.0	14 471	34 571	Bm	%
-1	529c	25	530	28.16	-11.6	-23.28	26.01	0.555	-1.1521	243.4	14 473	34 573		%
-1	540c	28	540	40.67	-19.15	-19.3	27.19	0.4963	-0.8002	225.2	15 476	35 579		%
-1	545c	29	545	45.08	-21.22	-17.87	27.75	0.4964	-0.7221	220.1	15 477	36 581		%
-1	549c	29	550	45.08	-21.22	-17.87	27.75	0.4964	-0.7221	220.1	15 477	36 581		%
-1	555c	31	555	53.93	-24.31	-15.0	28.56	0.5164	-0.6038	211.6	15 479	37 587		%
2	411	32	560	58.2	-25.61	-12.8	28.63	0.5271	-0.5456	206.5	16 480	38 591		%
380	770	99.99	0.0	0.0	0.0	0.0	0.0	0.9672	-0.3256	0.0				%