

VG000-IN_1											VG000-2N_1											
D65	Range	X	Y	Z	x	y	z	L*	a*	b*	D50	Range	X	Y	Z	x	y	z	L*	a*	b*	
R _m	565	770	61.78	41.0	0.05	0.6007	0.3987	0.0005	70.18	61.3	120.2	R _m	565	770	68.07	44.27	0.0	0.0	0.0	0.0	0.0	0.0
R _m	495	770	70.61	93.8	6.13	0.4354	0.5298	0.0346	97.55	-23.15	119.05	R _m	495	770	71.15	94.46	0.0	0.0	0.0	0.0	0.0	0.0
G _m	475	575	23.69	65.19	10.88	0.1762	0.5987	0.1835	84.58	-118.83	59.74	G _m	475	575	27.33	62.68	1.0	0.0	0.0	0.0	0.0	0.0
C _m	380	565	32.36	58.99	19.83	0.1654	0.2933	0.5412	81.29	-66.96	-32.22	C _m	380	565	28.35	57.52	0.0	0.0	0.0	0.0	0.0	0.0
B _m	380	495	17.95	6.19	102.75	0.1414	0.0487	0.8097	29.91	89.01	-117.0	B _m	380	495	13.26	5.03	7.0	0.0	0.0	0.0	0.0	0.0
M _m	575	475	71.34	34.8	88.79	0.3657	0.1784	0.4557	56.65	102.7	-46.24	M _m	575	475	73.04	37.31	6.0	0.0	0.0	0.0	0.0	0.0
G _o	495	565	15.31	52.79	6.08	0.2063	0.1716	0.0819	77.76	-130.02	85.16	G _o	495	565	15.08	50.69	5.0	0.0	0.0	0.0	0.0	0.0
G _o	565	495	79.73	47.2	102.8	0.347	0.2054	0.4474	74.42	82.25	-40.47	G _o	565	495	81.33	49.3	0.0	0.0	0.0	0.0	0.0	0.0
W ₁	380	770	95.04	100.0	108.89	0.3127	0.329	0.5382	100.0	0.0	0.0	W ₁	380	770	96.42	100.0	8.0	0.0	0.0	0.0	0.0	0.0
D65	Range	X ₉₀	Y ₉₀	Z ₉₀	x	y	z	L* ₉₀	a* ₉₀	b* ₉₀	D50	Range	X ₉₀	Y ₉₀	Z ₉₀	x	y	z	L* ₉₀	a* ₉₀	b* ₉₀	
R _m	565	770	55.6	36.9	0.05	0.6007	0.3987	0.0005	67.21	59.51	115.16	R _m	565	770	61.26	39.84	0.0	0.0	0.0	0.0	0.0	0.0
G _m	495	770	69.38	84.2	5.52	0.4354	0.5298	0.0346	93.63	-22.35	114.94	G _m	495	770	74.84	48.57	0.0	0.0	0.0	0.0	0.0	0.0
C _m	475	575	21.32	58.67	15.99	0.2176	0.5987	0.1835	81.1	-117.43	57.68	C _m	475	575	21.03	56.41	0.0	0.0	0.0	0.0	0.0	0.0
B _m	380	565	29.93	53.09	97.99	0.1654	0.2933	0.5412	77.93	-64.65	-31.11	B _m	380	565	25.51	50.15	7.0	0.0	0.0	0.0	0.0	0.0
M _m	575	495	16.15	57	92.47	0.1414	0.0487	0.8097	28.83	28.93	-112.96	M _m	575	495	16.13	45.52	6.0	0.0	0.0	0.0	0.0	0.0
G _o	495	565	14.21	31.32	80.01	0.3657	0.1784	0.4557	62.78	99.51	-44.64	G _o	495	565	14.74	33.58	5.0	0.0	0.0	0.0	0.0	0.0
G _o	565	495	76.78	47.51	5.47	0.2063	0.1716	0.0819	74.52	-127.46	82.21	G _o	565	495	65.37	45.62	4.0	0.0	0.0	0.0	0.0	0.0
M _o	565	495	71.75	42.48	92.52	0.347	0.2054	0.4474	71.2	79.41	-39.08	M _o	565	495	73.2	44.37	6.0	0.0	0.0	0.0	0.0	0.0
W ₁	380	770	85.53	90.0	108.0	0.3127	0.329	0.5382	96.0	0.0	0.0	W ₁	380	770	86.78	90.0	7.0	0.0	0.0	0.0	0.0	0.0
VG000-IN_1											VG000-2N_1											
P40	Range	X	Y	Z	x	y	z	L*	a*	b*	A00	Range	X	Y	Z	x	y	z	L*	a*	b*	
R _m	565	770	76.14	48.79	0.06	0.6091	0.3903	0.0005	75.53	61.53	128.33	R _m	565	770	91.09	56.18	0.0	0.0	0.0	0.0	0.0	0.0
R _m	495	770	90.61	95.99	4.86	0.4731	0.5013	0.0254	98.43	-10.88	118.82	R _m	495	770	104.5	97.5	0.0	0.0	0.0	0.0	0.0	0.0
G _m	475	575	22.82	59.0	14.1	0.2379	0.615	0.1469	81.1	-147.1	47.37	G _m	475	575	21.59	52.43	0.9	0.0	0.0	0.0	0.0	0.0
C _m	380	565	24.78	51.2	64.62	0.1672	0.3641	0.4595	76.81	-86.88	-39.92	C _m	380	565	21.87	57.5	4.81	0.3	0.0	0.0	0.0	0.0
B _m	380	495	10.31	4.0	59.82	0.1391	0.054	0.8068	23.71	62.64	-126.38	B _m	380	495	5.34	2.49	3.0	0.0	0.0	0.0	0.0	0.0
M _m	575	475	78.1	40.99	50.85	0.4062	0.2416	0.2981	70.18	87.59	-35.68	M _m	575	475	88.25	47.56	5.2	0.0	0.0	0.0	0.0	0.0
G _o	495	565	14.47	47.2	4.8	0.2177	0.171	0.0722	74.32	-125.75	61.5	G _o	495	565	13.41	41.32	4.1	0.0	0.0	0.0	0.0	0.0
G _o	565	495	86.45	52.79	59.88	0.4341	0.2651	0.3007	77.75	70.73	-33.27	G _o	565	495	96.63	48.67	3.0	0.0	0.0	0.0	0.0	0.0
W ₁	380	770	100.93	100.0	64.68	0.3799	0.3764	0.2435	100.0	0.0	0.0	W ₁	380	770	109.84	99.89	0.0	0.0	0.0	0.0	0.0	0.0
P40	Range	X ₉₀	Y ₉₀	Z ₉₀	x	y	z	L* ₉₀	a* ₉₀	b* ₉₀	A00	Range	X ₉₀	Y ₉₀	Z ₉₀	x	y	z	L* ₉₀	a* ₉₀	b* ₉₀	
R _m	565	770	63.91	0.05	0.6091	0.3903	0.0005	72.47	61.4	123.05	R _m	565	770	70.0	57.14	0.0	0.0	0.0	0.0	0.0	0.0	
G _m	495	770	71.55	86.39	4.37	0.4372	0.5013	0.0254	94.48	-10.5	108.94	G _m	495	770	94.05	87.75	0.0	0.0	0.0	0.0	0.0	0.0
C _m	475	575	20.54	53.1	12.69	0.2379	0.615	0.1469	79.14	-110.74	47.5	C _m	475	575	19.43	47.19	0.8	0.0	0.0	0.0	0.0	0.0
B _m	380	565	22.31	46.08	58.1	0.1672	0.3641	0.4595	73.6	-83.88	-38.58	B _m	380	565	16.68	38.93	3.0	0.0	0.0	0.0	0.0	0.0
M _m	575	495	9.28	3.6	53.84	0.1391	0.054	0.8068	22.35	60.47	-122.01	M _m	575	495	8.81	4.24	2.2	0.0	0.0	0.0	0.0	0.0
G _o	495	565	70.29	36.89	45.52	0.4062	0.2416	0.2981	67.2	84.56	-34.44	G _o	495	565	79.43	42.8	2.0	0.0	0.0	0.0	0.0	0.0
G _o	565	495	13.02	42.48	4.32	0.2177	0.171	0.0722	71.2	71.23	-69.17	G _o	565	495	12.07	37.18	3.0	0.0	0.0	0.0	0.0	0.0
M _o	565	495	77.81	47.51	53.9	0.4341	0.2651	0.3007	74.52	68.29	-32.12	M _o	565	495	86.79	52.81	2.2	0.0	0.0	0.0	0.0	0.0
W ₁	380	770	90.83	90.0	58.22	0.3799	0.3764	0.2435	96.0	0.0	0.0	W ₁	380	770	98.86	89.99	0.0	0.0	0.0	0.0	0.0	0.0
VG000-IN_1											VG000-IN_1											
E00	Range	X	Y	Z	x	y	z	L*	a*	b*	C00	Range	X	Y	Z	x	y	z	L*	a*	b*	
R _m	565	770	68.62	44.64	0.05	0.6055	0.3939	0.0005	72.66	58.88	124.34	R _m	565	770	63.1	41.99	0.0	0.0	0.0	0.0	0.0	0.0
R _m	495	770	83.34	94.54	5.63	0.4541	0.5151	0.0307	98.75	-20.19	119.57	R _m	495	770	78.39	93.33	6.0	0.0	0.0	0.0	0.0	0.0
G _m	475	575	23.08	62.07	17.72	0.2243	0.6033	0.1722	82.95	-119.87	58.24	G _m	475	575	24.12	64.46	2.2	0.0	0.0	0.0	0.0	0.0
C _m	380	565	31.37	55.35	99.94	0.1628	0.2965	0.5333	79.25	-70.77	-35.73	C _m	380	565	34.96	58.0	0.0	0.0	0.0	0.0	0.0	0.0

M _m	575	495	16.65	5.45	94.36	0.1249	0.0468	0.8101	28.02	85.37	-120.26
B _m	380	495	75.91	93.92	82.27	0.3902	0.1924	0.4173	67.97	96.17	-41.62
G _m	495	565	14.72	4.9	5.57	0.2097	0.1008	0.7014	76.01	-132.53	82.18
M _o	565	495	85.27	50.09	94.42	0.3791	0.218	0.108	74.73	77.02	-37.36
W ₁	380	770	100.0	100.0	100.0	0.3333	0.3333	0.3333	100.0	0.0	0.0
C00	Range	X ₉₀	Y ₉₀	Z ₉₀	x	y	z	L* ₉₀	a* ₉₀	b* ₉₀	
R _m	565	770	61.76	40.41	0.05	0.6055	0.3939	0.0005	69.6	56.84	119.16

M _m	575	495	16.65	5.45	94.36	0.1249	0.0468	0.8101	28.02	85.37	-120.26
B _m	380	495	75.91	93.92	82.27	0.3902	0.1924	0.4173	67.97	96.17	-41.62
G _m	495	565	14.72	4.9	5.57	0.2097	0.1008	0.7014	76.01	-132.53	82.18
M _o	565	495	85.27	50.09	94.42	0.3791	0.218	0.108	74.73	77.02	-37.36
W ₁	380	770	100.0	100.0	100.0	0.3333	0.3333	0.3333	100.0	0.0	0.0
C00	Range	X ₉₀	Y ₉₀	Z ₉₀	x	y	z	L* ₉₀	a* ₉₀	b* ₉₀	
R _m	565	770	61.76	40.41	0.05	0.6055	0.3939	0.0005	69.6	56.84	119.16
R _m	495	770	81.55	86.39	4.37	0.4732	0.5013	0.0254	94.4	-10.5	108.94
G _m	475	575	20.54	53.1	12.69	0.2379	0.615	0.1469	77.94	-110.74	47.53
C _m	380	565	22.31	46.08	58.16	0.1762	0.3641	0.4955	73.6	-83.88	-38.54
B _m	380	495	9.28	3.6	53.84	0.1391	0.054	0.8068	22.35	60.47	-122.01
M _m	575	475	70.29	36.89	45.52	0.4602	0.2416	0.2981	67.2	84.56	-34.44
G _o	495	565	13.02	42.48	43.2	0.2177	0.1	0.0722	71.21	-123.15	69.17
M _o	565	495	77.81	47.51	53.9	0.4341	0.2651	0.3007	74.52	68.29	-32.12
W ₁	380	770	90.83	90.0	108.22	0.3799	0.3764	0.2435	96.0	0.0	0.0

$\mathbf{C}_m$	495	770	75.01	85.08	5.7	0.4541	0.5151	0.0307	93.92	-19.49	115.44
$\mathbf{G}_m$	475	575	20.77	55.86	15.95	0.2243	0.6033	0.1722	79.94	-114.64	56.23
$\mathbf{C}_m$	380	565	22.33	48.92	89.94	0.186	0.2965	0.3533	75.96	-68.33	-34.5
$\mathbf{B}_m$	380	495	14.98	4.91	84.92	0.1429	0.0468	0.801	25.11	82.41	-116.1
$\mathbf{M}_m$	575	475	69.22	34.13	74.04	0.3902	0.1924	0.4173	65.07	92.85	-41.15
$\mathbf{G}_o$	495	565	13.25	44.91	5.01	0.2097	0.1708	0.0794	72.83	-127.96	79.34
$\mathbf{M}_o$	565	495	76.75	45.08	84.98	0.371	0.218	0.1408	72.95	74.36	-36.07
$\mathbf{W}_1$	380	770	90.0	90.0	90.0	0.3333	0.3333	0.3333	96.0	0.0	0.0

$\mathbf{C}_m$	495	770	70.55	84.8	1	0.4541	0.5151	0.0307	93.92	-19.49	115.44
$\mathbf{G}_m$	475	575	21.77	58.01	1	0.2243	0.6033	0.1722	82.95	-119.78	58.78
$\mathbf{C}_m$	380	565	31.47	52.2	1	0.186	0.2965	0.3533	79.25	-67.77	-35.73
$\mathbf{B}_m$	380	495	17.7	5.9	1	0.1429	0.0468	0.801	28.02	85.37	-120.26
$\mathbf{M}_m$	575	475	66.55	31.98	8	0.3802	0.1924	0.4173	67.97	84.51	-42.63
$\mathbf{G}_o$	495	565	13.76	46.2	5	0.2097	0.1708	0.0794	72.83	-127.96	79.34
$\mathbf{M}_o$	565	495	74.5	43.79	1	0.371	0.218	0.1408	72.95	74.36	-36.07
$\mathbf{W}_1$	380	770	89.9	89.9	1	0.3333	0.3333	0.3333	96.0	0.0	0.0

W1											W1										
380 770 90.0 90.0 90.0 0.3333 0.3333 0.3333 96.0 0.0 0.0											380 770 86.26 90.0 1.0 0.0										
VC6000-5N_1											VG6000-6N_1										
P00	Range	X	Y	Z	x	y	z	L*	a*	b*											
Rm	565 770	74.35	47.6	0.06	0.6093	0.3901	0.0005	74.58	59.47	127.39											
Rm	495 770	88.77	95.36	5.13	0.469	0.5038	0.0271	98.18	-14.88	117.1											
Gm	475 575	22.73	59.65	15.54	0.232	0.6091	0.1587	81.65	-117.81	53.3											
Cm	380 565	23.71	52.39	80.89	0.172	0.3522	0.5027	75.52	-75.93	-38.71											
Bm	380 495	13.29	4.63	75.92	0.1416	0.0493	0.809	25.58	73.84	-123.82											
Mm	575 475	79.33	40.34	65.51	0.4283	0.1712	0.3537	69.27	90.25	-38.5											
Go	495 565	14.41	47.76	50.7	0.2143	0.1702	0.0754	74.68	-130.41	76.9											
Go	565 495	86.75	52.23	75.98	0.406	0.2419	0.352	74.72	72.56	-34.66											
VC6000-5N_1											VG6000-6N_1										
P00	Range	X	Y	Z	x	y	z	L*	a*	b*											
Rm	565 770	74.35	47.6	0.06	0.6093	0.3901	0.0005	74.58	59.47	127.39											
Rm	495 770	88.77	95.36	5.13	0.469	0.5038	0.0271	98.18	-14.88	117.1											
Gm	475 575	22.73	59.65	15.54	0.232	0.6091	0.1587	81.65	-117.81	53.3											
Cm	380 565	23.71	52.39	80.89	0.172	0.3522	0.5027	75.52	-75.93	-38.71											
Bm	380 495	13.29	4.63	75.92	0.1416	0.0493	0.809	25.58	73.84	-123.82											
Mm	575 475	79.33	40.34	65.51	0.4283	0.1712	0.3537	69.27	90.25	-38.5											
Go	495 565	14.41	47.76	50.7	0.2143	0.1702	0.0754	74.68	-130.41	76.9											
Go	565 495	86.75	52.23	75.98	0.406	0.2419	0.352	74.72	72.56	-34.66											
VC6000-5N_1											VG6000-6N_1										
P00	Range	X	Y	Z	x	y	z	L*	a*	b*											
Rm	565 770	74.35	47.6	0.06	0.6093	0.3901	0.0005	74.58	59.47	127.39											
Rm	495 770	88.77	95.36	5.13	0.469	0.5038	0.0271	98.18	-14.88	117.1											
Gm	475 575	22.73	59.65	15.54	0.232	0.6091	0.1587	81.65	-117.81	53.3											
Cm	380 565	23.71	52.39	80.89	0.172	0.3522	0.5027	75.52	-75.93	-38.71											
Bm	380 495	13.29	4.63	75.92	0.1416	0.0493	0.809	25.58	73.84	-123.82											
Mm	575 475	79.33	40.34	65.51	0.4283	0.1712	0.3537	69.27	90.25	-38.5											
Go	495 565	14.41	47.76	50.7	0.2143	0.1702	0.0754	74.68	-130.41	76.9											
Go	565 495	86.75	52.23	75.98	0.406	0.2419	0.352	74.72	72.56	-34.66											
VC6000-5N_1											VG6000-6N_1										
P00	Range	X	Y	Z	x	y	z	L*	a*	b*											
Rm	565 770	74.35	47.6	0.06	0.6093	0.3901	0.0005	74.58	59.47	127.39											
Rm	495 770	88.77	95.36	5.13	0.469	0.5038	0.0271	98.18	-14.88	117.1											
Gm	475 575	22.73	59.65	15.54	0.232	0.6091	0.1587	81.65	-117.81	53.3											
Cm	380 565	23.71	52.39	80.89	0.172	0.3522	0.5027	75.52	-75.93	-38.71											
Bm	380 495	13.29	4.63	75.92	0.1416	0.0493	0.809	25.58	73.84	-123.82											
Mm	575 475	79.33	40.34	65.51	0.4283	0.1712	0.3537	69.27	90.25	-38.5											
Go	495 565	14.41	47.76	50.7	0.2143	0.1702	0.0754	74.68	-130.41	76.9											
Go	565 495	86.75	52.23	75.98	0.406	0.2419	0.352	74.72	72.56	-34.66											
VC6000-5N_1											VG6000-6N_1										
P00	Range	X	Y	Z	x	y	z	L*	a*	b*											
Rm	565 770	74.35	47.6	0.06	0.6093	0.3901	0.0005	74.58	59.47	127.39											
Rm	495 770	88.77	95.36	5.13	0.469	0.5038	0.0271	98.18	-14.88	117.1											
Gm	475 575	22.73	59.65	15.54	0.232	0.6091	0.1587	81.65	-117.81	53.3											
Cm	380 565	23.71	52.39	80.89	0.172	0.3522	0.5027	75.52	-75.93	-38.71											
Bm	380 495	13.29	4.63	75.92	0.1416	0.0493	0.809	25.58	73.84	-123.82											
Mm	575 475	79.33	40.34	65.51	0.4283	0.1712	0.3537	69.27	90.25	-38.5											
Go	495 565	14.41	47.76	50.7	0.2143	0.1702	0.0754	74.68	-130.41	76.9											
Go	565 495	86.75	52.23	75.98	0.406	0.2419	0.352	74.72	72.56	-34.66											
VC6000-5N_1											VG6000-6N_1										
P00	Range	X	Y	Z	x	y	z	L*	a*	b*											
Rm	565 770	74.35	47.6	0.06	0.6093	0.3901	0.0005	74.58	59.47	127.39											
Rm	495 770	88.77	95.36	5.13	0.469	0.5038	0.0271	98.18	-14.88	117.1											
Gm	475 575	22.73	59.65	15.54	0.232	0.6091	0.1587	81.65	-117.81	53.3											
Cm	380 565	23.71	52.39	80.89	0.172	0.3522	0.5027	75.52	-75.93	-38.71											
Bm	380 495	13.29	4.63	75.92	0.1416	0.0493	0.809	25.58	73.84	-123.82											
Mm	575 475	79.33	40.34	65.51	0.4283	0.1712	0.3537	69.27	90.25	-38.5											
Go	495 565	14.41	47.76	50.7	0.2143	0.1702	0.0754	74.68	-130.41	76.9											
Go	565 495	86.75	52.23	75.98	0.406	0.2419	0.352	74.72	72.56	-34.66											
VC6000-5N_1											VG6000-6N_1										
P00	Range	X	Y	Z	x	y	z	L*	a*	b*											
Rm	565 770	74.35	47.6	0.06	0.6093	0.3901	0.0005	74.58	59.47	127.39											
Rm	495 770	88.77	95.36	5.13	0.469	0.5038	0.0271	98.18	-14.88	117.1											
Gm	475 575	22.73	59.65	15.54	0.232	0.6091	0.1587	81.65	-117.81	53.3											
Cm	380 565	23.71	52.39	80.89	0.172	0.3522	0.5027	75.52	-75.93	-38.71											
Bm	380 495	13.29	4.63	75.92	0.1416	0.0493	0.809	25.58	73.84	-123.82											
Mm	575 475	79.33	40.34	65.51	0.4283	0.1712	0.3537	69.27	90.25	-38.5											
Go	495 565	14.41	47.76	50.7	0.2143	0.1702	0.0754	74.68	-130.41	76.9											
Go	565 495	86.75	52.23	75.98	0.406	0.2419	0.352	74.72	72.56	-34.66											
VC6000-5N_1											VG6000-6N_1										
P00	Range	X	Y	Z	x	y	z	L*	a*	b*											
Rm	565 770	74.35	47.6	0.06	0.6093	0.3901	0.0005	74.58	59.47	127.39											
Rm	495 770	88.77	95.36	5.13	0.469	0.5038	0.0271	98.18	-14.88	117.1											
Gm	475 575	22.73	59.65	15.54	0.232	0.6091	0.1587	81.65	-117.81	53.3											
Cm	380 565	23.71	52.39	80.89	0.172	0.3522	0.5027	75.52	-75.93	-38.71											
Bm	380 495	13.29	4.63	75.92	0.1416	0.0493	0.809	25.58	73.84	-123.82											
Mm	575 475	79.33	40.34	65.51	0.4283	0.1712	0.3537	69.27	90.25	-38.5											
Go	495 565	14.41	47.76	50.7	0.2143	0.1702	0.0754	74.68	-130.41	76.9											
Go	565 495	86.75	52.23	75.98	0.406	0.2419	0.352	74.72	72.56	-34.66											
VC6000-5N_1											VG6000-6N_1										
P00	Range	X	Y	Z	x	y	z	L*	a*	b*											
Rm	565 770	74.35	47.6	0.06	0.6093	0.3901	0.0005	74.58	59.47	127.39											
Rm	495 770	88.77	95.36	5.13	0.469	0.5038	0.0271	98.18	-14.88	117.1											
Gm	475 575	22.73	59.65	15.54	0.232	0.6091	0.1587	81.65	-117.81	53.3											
Cm	380 565	23.71	52.39	80.89	0.172	0.3522	0.5027	75.52	-75.93	-38.71											
Bm	380 495	13.29	4.63	75.92	0.1416	0.0493	0.809	25.58	73.84	-123.82											
Mm	575 475	79.33	40.34	65.51	0.4283	0.1712	0.3537	69.27	90.25	-38.5											
Go	495 565	14.41	47.76	50.7	0.2143	0.1702	0.0754	74.68	-130.41	76.9											
Go	565 495	86.75	52.23	75.98	0.406	0.2419	0.352	74.72	72.56	-34.66											
VC6000-5N_1											VG6000-6N_1										
P00	Range	X	Y	Z	x	y	z	L*	a*	b*											
Rm	565 770	74.35	47.6	0.06	0.6093	0.3901	0.0005	74.58	59.47	127.39											
Rm	495 770	88.77	95.36	5.13	0.469	0.5038	0.0271	98.18	-14.88	117.1											
Gm	475 575	22.73	59.65	15.54	0.232	0.6091	0.1587	81.65	-117.81	53.3											
Cm	380 565	23.71	52.39	80.89	0.172	0.3522	0.5027	75.52	-75.93	-38.71											
Bm	380 495	13.29	4.63	75.92	0.1416	0.0493	0.809	25.58	73.84	-123.82											
Mm	575 475	79.33	40.34	65.51	0.4283	0.1712	0.3537	69.27	90.25	-38.5											
Go	495 565	14.41	47.76	50.7	0.2143	0.1702	0.0754	74.68	-130.41	76.9											
Go	565 495	86.75	52.23	75.98	0.406	0.2419	0.352	74.72	72.56	-34.66											
VC6000-5N_1											VG6000-6N_1										
P00	Range	X	Y	Z	x	y	z	L*	a*	b*											
Rm	565 770	74.35	47.6	0.06	0.6093	0.3901	0.0005	74.58	59.47	127.39											
Rm	495 770	88.77	95.36	5.13	0.469	0.5038	0.0271	98.18	-14.88	117.1											
Gm	475 575	22.73	59.65	15.54	0.232	0.6091	0.1587	81.65	-117.81	53.3											
Cm	380 565	23.71	52.39	80.89	0.172	0.3522	0.5027	75.52	-75.93	-38.71											
Bm	380 495	13.29	4.63	75.92	0.1416	0.0493	0.809	25.58	73.84	-123.82											
Mm	575 475	79.33	40.34	65.51	0.4283	0.1712	0.3537	69.27	90.25	-38.5											
Go	495 565	14.41	47.76	50.7	0.2143	0.1702	0.0754	74.68	-130.41	76.9											
Go	565 495	86.75	52.23	75.98	0.406	0.2419	0.352	74.72	72.56	-34.66											
VC6000-5N_1											VG6000-6N_1										
P00	Range	X	Y	Z	x	y	z	L*	a*	b*											
Rm	565 770	74.35	47.6	0.06	0.6093	0.3901	0.0005	74.58	59.47	127.39											
Rm	495 770	88.77	95.36	5.13	0.469	0.5038	0.0271	98.18	-14.88	117.1											
Gm	475 575	22.73	59.65	15.54	0.232	0.6091	0.1587	81.65	-117.81	53.3											
Cm	380 565	23.71	52.39	80.89	0.172	0.3522	0.5027	75.52	-75.93	-38.71											
Bm	380 495	13.29	4.63	75.92	0.1416	0.0493	0.809	25.58	73.84	-123.82											
Mm	575 475	79.33	40.34	65.51	0.4283	0.1712	0.3537	69.27	90.25	-38.5											
Go	495 565	14.41	47.76	50.7	0.2143	0.1702	0.0754	74.68	-130.41	76.9											
Go	565 495	86.75	52.23	75.98	0.406	0.2419	0.352	74.72	72.56	-34.66											
VC6000-5N_1											VG6000-6N_1										
P00	Range	X</																			

B _m	585	495	13.29	4.63	75.92	0.1416	0.0493	0.809	25.58	73.84	-123.82
M _m	575	475	79.33	40.34	65.51	0.4283	0.2178	0.3537	69.27	90.25	-38.5
G _o	495	565	14.41	47.76	50.7	0.2143	0.1702	0.0754	74.68	-130.41	76.9
G _o	565	495	87.65	52.23	75.98	0.406	0.2419	0.352	74.72	72.56	-34.66
W ₁	380	770	102.06	100.0	81.06	0.3604	0.3531	0.2863	100.0	0.0	0.0
P00	Range	X	Y	Z	x	y	z	L*	a*	b*	
R _m	565	770	66.92	42.84	0.05	0.6093	0.3901	0.0005	71.5	57.42	122.12

B _m	585	495	10.01	6.28	1.1	0.1416	0.0493	0.809	25.58	73.84	-123.82
M _m	575	475	74.49	35.51	9.1	0.4283	0.2178	0.3537	69.27	90.25	-38.5
G _o	495	565	15.02	52.04	6.6	0.2143	0.1702	0.0754	74.68	-130.41	76.9
G _o	565	495	89.29	47.95	1.1	0.406	0.2419	0.352	74.72	72.56	-34.66
W ₁	380	770	97.93	100.0	1.1	0.3604	0.3531	0.2863	100.0	0.0	0.0
P00	Range	X	Y	Z	x	y	z	L*	a*	b*	
R _m	565	770	66.93	37.5	0.0	0.6093	0.3901	0.0005	71.5	57.42	122.12

Y_m	495	770	79.89	85.83	4.62	0.469	0.5038	0.0271	94.24	-14.37	113.06
Y_m	495	770	70.12	70.12	0.44	0.469	0.5038	0.0271	94.24	-14.37	113.06
Y_m	475	575	20.45	53.68	13.99	0.232	0.6091	0.1587	78.28	-113.74	51.17
Y_m	380	565	24.93	47.15	72.89	0.172	0.3252	0.5029	74.29	-76.57	-37.37
B_m	380	495	11.96	41.16	68.33	0.1416	0.0493	0.089	24.24	71.28	-119.54
B_m	380	495	11.96	41.16	68.33	0.1416	0.0493	0.089	24.24	71.28	-119.54
M_m	575	475	71.14	36.31	58.96	0.2833	0.2178	0.3537	66.76	87.14	-37.17
M_m	575	475	71.14	36.31	58.96	0.2833	0.2178	0.3537	66.76	87.14	-37.17
G_m	495	565	12.97	42.98	4.56	0.2483	0.1702	0.0754	71.55	-125.91	74.25
G_m	565	495	78.88	47.01	68.39	0.406	0.2419	0.352	74.2	70.06	-33.46
G_m	565	495	78.88	47.01	68.39	0.406	0.2419	0.352	74.2	70.06	-33.46
Y_m	495	770	79.89	85.83	4.62	0.469	0.5038	0.0271	94.24	-14.37	113.06
Y_m	495	770	70.12	70.12	0.44	0.469	0.5038	0.0271	94.24	-14.37	113.06
Y_m	475	575	20.45	53.68	13.99	0.232	0.6091	0.1587	78.28	-113.74	51.17
Y_m	380	565	24.93	47.15	72.89	0.172	0.3252	0.5029	74.29	-76.57	-37.37
B_m	380	495	11.96	41.16	68.33	0.1416	0.0493	0.089	24.24	71.28	-119.54
B_m	380	495	11.96	41.16	68.33	0.1416	0.0493	0.089	24.24	71.28	-119.54
M_m	575	475	71.14	36.31	58.96	0.2833	0.2178	0.3537	66.76	87.14	-37.17
M_m	575	475	71.14	36.31	58.96	0.2833	0.2178	0.3537	66.76	87.14	-37.17
G_m	495	565	12.97	42.98	4.56	0.2483	0.1702	0.0754	71.55	-125.91	74.25
G_m	565	495	78.88	47.01	68.39	0.406	0.2419	0.352	74.2	70.06	-33.46
G_m	565	495	78.88	47.01	68.39	0.406	0.2419	0.352	74.2	70.06	-33.46