

Siehe ähnliche Dateien: <http://130.149.60.45/~farbmeterik/VG00/VG00LONP.PDF> / .PS
Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmeterik>

TUB-Registrierung: 20130201-VG00/VG00LONP.PDF / .PS
Anwendung für Messung von Display-Ausgabe

D65	Range	X ₁₀	Y ₁₀	Z ₁₀	x	y	z	L*	a*	b*
R _m	565,770	61.78	41.0	0.05	0.6007	0.3987	0.0005	70.18	61.63	120.2
R _y	495,770	77.09	93.8	6.13	0.4534	0.5298	0.0046	97.55	-23.15	119.05
R _m	495,770	83.34	95.99	14.86	0.4732	0.5013	0.0025	98.43	-10.88	112.84
R _y	495,770	83.34	95.99	14.86	0.4732	0.5013	0.0025	98.43	-10.88	112.84
R _m	380,565	32.36	58.99	10.83	0.1654	0.2933	0.0514	81.29	-36.66	-32.22
R _y	380,565	32.36	58.99	10.83	0.1654	0.2933	0.0514	81.29	-36.66	-32.22
R _m	380,495	13.29	61.81	0.05	0.1414	0.0487	0.0097	29.91	89.01	-117.0
R _y	380,495	13.29	61.81	0.05	0.1414	0.0487	0.0097	29.91	89.01	-117.0
R _m	575,475	71.34	34.8	0.89	0.3657	0.1784	0.0545	66.57	102.7	-46.24
R _y	575,475	71.34	34.8	0.89	0.3657	0.1784	0.0545	66.57	102.7	-46.24
G ₀	495,565	13.51	52.79	6.08	0.2063	0.1716	0.0819	77.76	-132.02	85.16
G ₀	495,565	13.51	52.79	6.08	0.2063	0.1716	0.0819	77.76	-132.02	85.16
G ₀	565,495	79.73	47.2	10.28	0.347	0.2054	0.0444	74.73	82.25	-40.47
G ₀	565,495	79.73	47.2	10.28	0.347	0.2054	0.0444	74.73	82.25	-40.47
W ₁	380,770	95.04	100.0	10.89	0.3127	0.329	0.3582	100.0	0.0	0.0
W ₁	380,770	95.04	100.0	10.89	0.3127	0.329	0.3582	100.0	0.0	0.0
D65	Range	X ₁₀	Y ₁₀	Z ₁₀	x	y	z	L*	a*	b*
R _m	565,770	61.78	41.0	0.05	0.6007	0.3987	0.0005	70.18	61.63	120.2
R _y	495,770	77.09	93.8	6.13	0.4534	0.5298	0.0046	97.55	-23.15	119.05
R _m	495,770	83.34	95.99	14.86	0.4732	0.5013	0.0025	98.43	-10.88	112.84
R _y	495,770	83.34	95.99	14.86	0.4732	0.5013	0.0025	98.43	-10.88	112.84
R _m	380,565	29.32	58.67	17.99	0.1654	0.2933	0.0514	81.29	-36.66	-32.22
R _y	380,565	29.32	58.67	17.99	0.1654	0.2933	0.0514	81.29	-36.66	-32.22
R _m	380,495	13.29	61.81	0.05	0.1414	0.0487	0.0097	29.91	89.01	-117.0
R _y	380,495	13.29	61.81	0.05	0.1414	0.0487	0.0097	29.91	89.01	-117.0
R _m	575,475	71.34	34.8	0.89	0.3657	0.1784	0.0545	66.57	102.7	-46.24
R _y	575,475	71.34	34.8	0.89	0.3657	0.1784	0.0545	66.57	102.7	-46.24
G ₀	495,565	13.51	52.79	6.08	0.2063	0.1716	0.0819	77.76	-132.02	85.16
G ₀	495,565	13.51	52.79	6.08	0.2063	0.1716	0.0819	77.76	-132.02	85.16
G ₀	565,495	79.73	47.2	10.28	0.347	0.2054	0.0444	74.73	82.25	-40.47
G ₀	565,495	79.73	47.2	10.28	0.347	0.2054	0.0444	74.73	82.25	-40.47
W ₁	380,770	95.04	100.0	10.89	0.3127	0.329	0.3582	100.0	0.0	0.0
W ₁	380,770	95.04	100.0	10.89	0.3127	0.329	0.3582	100.0	0.0	0.0

D50	Range	X ₁₀	Y ₁₀	Z ₁₀	x	y	z	L*	a*	b*
R _m	565,770	68.07	44.27	0.05	0.6055	0.3938	0.0005	72.41	64.12	123.73
R _y	495,770	77.09	93.8	6.13	0.4534	0.5298	0.0046	97.55	-23.15	119.05
R _m	495,770	83.34	95.99	14.86	0.4732	0.5013	0.0025	98.43	-10.88	112.84
R _y	495,770	83.34	95.99	14.86	0.4732	0.5013	0.0025	98.43	-10.88	112.84
R _m	380,565	28.35	52.68	17.06	0.1702	0.3346	0.0495	79.46	-35.36	-35.36
R _y	380,565	28.35	52.68	17.06	0.1702	0.3346	0.0495	79.46	-35.36	-35.36
R _m	380,495	13.26	50.31	76.95	0.1392	0.0528	0.0878	26.85	74.36	-121.53
R _y	380,495	13.26	50.31	76.95	0.1392	0.0528	0.0878	26.85	74.36	-121.53
R _m	575,475	71.34	37.31	65.43	0.4155	0.2122	0.3722	67.51	95.82	-41.14
R _y	575,475	71.34	37.31	65.43	0.4155	0.2122	0.3722	67.51	95.82	-41.14
G ₀	495,565	15.08	50.69	5.48	0.2116	0.1713	0.0769	76.49	-129.23	78.43
G ₀	495,565	15.08	50.69	5.48	0.2116	0.1713	0.0769	76.49	-129.23	78.43
G ₀	565,495	81.33	49.3	77.01	0.3916	0.2374	0.3708	75.64	77.41	-37.46
G ₀	565,495	81.33	49.3	77.01	0.3916	0.2374	0.3708	75.64	77.41	-37.46
W ₁	380,770	96.42	100.0	82.49	0.3457	0.3585	0.2957	100.0	0.0	0.0
W ₁	380,770	96.42	100.0	82.49	0.3457	0.3585	0.2957	100.0	0.0	0.0
D50	Range	X ₁₀	Y ₁₀	Z ₁₀	x	y	z	L*	a*	b*
R _m	565,770	61.78	41.0	0.05	0.6055	0.3938	0.0005	69.36	61.9	118.58
R _y	495,770	77.09	93.8	6.13	0.4534	0.5298	0.0046	97.55	-23.15	119.05
R _m	495,770	83.34	95.99	14.86	0.4732	0.5013	0.0025	98.43	-10.88	112.84
R _y	495,770	83.34	95.99	14.86	0.4732	0.5013	0.0025	98.43	-10.88	112.84
R _m	380,565	29.32	58.67	17.99	0.1654	0.2933	0.0514	81.29	-36.66	-32.22
R _y	380,565	29.32	58.67	17.99	0.1654	0.2933	0.0514	81.29	-36.66	-32.22
R _m	380,495	13.29	61.81	0.05	0.1414	0.0487	0.0097	29.91	89.01	-117.0
R _y	380,495	13.29	61.81	0.05	0.1414	0.0487	0.0097	29.91	89.01	-117.0
R _m	575,475	71.34	34.8	0.89	0.3657	0.1784	0.0545	66.57	102.7	-46.24
R _y	575,475	71.34	34.8	0.89	0.3657	0.1784	0.0545	66.57	102.7	-46.24
G ₀	495,565	13.51	52.79	6.08	0.2063	0.1716	0.0819	77.76	-132.02	85.16
G ₀	495,565	13.51	52.79	6.08	0.2063	0.1716	0.0819	77.76	-132.02	85.16
G ₀	565,495	79.73	47.2	10.28	0.347	0.2054	0.0444	74.73	82.25	-40.47
G ₀	565,495	79.73	47.2	10.28	0.347	0.2054	0.0444	74.73	82.25	-40.47
W ₁	380,770	96.42	100.0	82.49	0.3457	0.3585	0.2957	100.0	0.0	0.0
W ₁	380,770	96.42	100.0	82.49	0.3457	0.3585	0.2957	100.0	0.0	0.0

D65	Range	X ₁₀	Y ₁₀	Z ₁₀	x	y	z	L*	a*	b*
R _m	565,770	58.96	38.15	0.0	0.6071	0.3928	0.0	68.13	64.13	117.48
R _y	495,770	77.09	93.8	6.13	0.4534	0.5298	0.0046	97.55	-23.15	119.05
R _m	495,770	83.34	95.99	14.86	0.4732	0.5013	0.0025	98.43	-10.88	112.84
R _y	495,770	83.34	95.99	14.86	0.4732	0.5013	0.0025	98.43	-10.88	112.84
R _m	380,565	28.35	52.68	17.06	0.1702	0.3346	0.0495	79.46	-35.36	-35.36
R _y	380,565	28.35	52.68	17.06	0.1702	0.3346	0.0495	79.46	-35.36	-35.36
R _m	380,495	13.26	50.31	76.95	0.1392	0.0528	0.0878	26.85	74.36	-121.53
R _y	380,495	13.26	50.31	76.95	0.1392	0.0528	0.0878	26.85	74.36	-121.53
R _m	575,475	71.34	37.31	65.43	0.4155	0.2122	0.3722	67.51	95.82	-41.14
R _y	575,475	71.34	37.31	65.43	0.4155	0.2122	0.3722	67.51	95.82	-41.14
G ₀	495,565	15.08	50.69	5.48	0.2116	0.1713	0.0769	76.49	-129.23	78.43
G ₀	495,565	15.08	50.69	5.48	0.2116	0.1713	0.0769	76.49	-129.23	78.43
G ₀	565,495	81.33	49.3	77.01	0.3916	0.2374	0.3708	75.64	77.41	-37.46
G ₀	565,495	81.33	49.3	77.01	0.3916	0.2374	0.3708	75.64	77.41	-37.46
W ₁	380,770	96.42	100.0	82.49	0.3457	0.3585	0.2957	100.0	0.0	0.0
W ₁	380,770	96.42	100.0	82.49	0.3457	0.3585	0.2957	100.0	0.0	0.0
D65	Range	X ₁₀	Y ₁₀	Z ₁₀	x	y	z	L*	a*	b*
R _m	565,770	58.96	38.15	0.0	0.6071	0.3928	0.0	68.13	64.13	117.48
R _y	495,770	77.09	93.8	6.13	0.4534	0.5298	0.0046	97.55	-23.15	119.05
R _m	495,770	83.34	95.99	14.86	0.4732	0.5013	0.0025	98.43	-10.88	112.84
R _y	495,770	83.34	95.99	14.86	0.4732	0.5013	0.0025	98.43	-10.88	112.84
R _m	380,565	28.35	52.68	17.06	0.1702	0.3346	0.0495	79.46	-35.36	-35.36
R _y	380,565	28.35	52.68	17.06	0.1702	0.3346	0.0495	79.46	-35.36	-35.36
R _m	380,495	13.26	50.31	76.95	0.1392	0.0528	0.0878	26.85	74.36	-121.53
R _y	380,495	13.26	50.31	76.95	0.1392	0.0528	0.0878	26.85	74.36	-121.53
R _m	575,475	71.34	37.31	65.43	0.4155	0.2122	0.3722	67.51	95.82	-41.14
R _y	575,475	71.34	37.31	65.43	0.4155	0.2122	0.3722	67.51	95.82	-41.14
G ₀	495,565	15.08	50.69	5.48	0.2116	0.1713	0.0769	76.49	-129.23	78.43
G ₀	495,565	15.08	50.69	5.48	0.2116	0.1713	0.0769	76.49	-129.23	78.43
G ₀	565,495	81.33	49.3	77.01	0.3916	0.2374	0.3708	75.64	77.41	-37.46
G ₀	565,495	81.33	49.3	77.01	0.3916	0.2374	0.3708	75.64	77.41	-37.46
W ₁	380,770	96.42	100.0	82.49	0.3457	0.3585	0.2957	100.0	0.0	0.0
W ₁	380,770	96.42	100.0	82.49	0.3457	0.3585	0.2957	100.0	0.0	0.0

||
||
||