

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =520_770, LINYAB-Daten														%
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code		%	
0	405	32	561	58.2	-22.74	-17.89	28.94	0.5596	-0.743	218.1	16 483	37 589	Cm	%
6	435	32	562	58.79	-26.78	-9.88	28.55	0.4948	-0.6036	200.2	17 486	42 610		%
10	450	32	563	59.42	-33.54	4.93	33.9	0.3859	-0.3525	171.6	19 496	-1 496c		%
12	460	33	565	60.32	-36.45	12.66	38.58	0.3461	-0.2256	160.8	21 505	-1 505c		%
12	465	33	567	61.66	-36.65	13.24	38.97	0.356	-0.2207	160.1	21 506	-1 506c		%
14	470	33	569	62.72	-38.14	19.32	42.76	0.3422	-0.1274	153.1	24 520	-1 520c		%
15	475	34	573	65.29	-38.28	22.47	44.39	0.364	-0.0913	149.5	25 528	-1 528c	Gm	%
16	480	36	580	69.95	-37.48	26.04	45.64	0.4146	-0.0632	145.2	27 537	-1 537c		%
17	485	39	595	78.75	-32.73	31.0	45.09	0.5347	-0.0418	136.5	29 548	-1 548c		%
18	490	-1	490c	93.8	-12.06	38.4	40.25	0.8218	-0.0261	107.4	33 565	11 459	max	%
19	495	-1	495c	92.3	-10.68	38.39	39.85	0.8346	-0.0195	105.5	33 566	12 462		%
20	500	-1	500c	90.42	-8.91	38.07	39.1	0.8518	-0.0144	103.1	33 567	12 464		%
22	510	-1	510c	85.27	-4.15	36.48	36.72	0.9016	-0.0076	96.5	33 569	13 469		%
23	520	-1	519c	81.98	-1.26	35.24	35.26	0.935	-0.0056	92.0	34 570	14 471	Ym	%
25	530	-1	529c	74.04	5.15	32.02	32.43	1.0201	-0.0031	80.8	34 573	15 475		%
27	540	-1	539c	64.9	11.57	28.16	30.44	1.1288	-0.0016	67.6	35 577	15 478		%
28	545	-1	544c	60.13	14.5	26.11	29.87	1.1917	-0.0012	60.9	35 579	15 479		%
29	550	-1	549c	55.26	17.18	24.01	29.53	1.2613	-0.0009	54.4	36 582	16 480		%
30	555	-1	554c	50.4	19.49	21.91	29.33	1.3372	-0.0007	48.3	36 584	16 481		%
32	560	-1	560c	41.0	22.8	17.83	28.95	1.5064	-0.0005	38.0	37 589	16 483		%
380	770	100.0	0.0	0.0	0.01	0.9504	-0.4355	0.0						%
Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =770_520, LINYAB komplementär														ß
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code		%	
32	561	0	405	41.79	22.74	17.89	28.94	1.4946	-0.0072	38.1	37 589	16 483	Rm	%
32	562	6	435	41.2	26.78	9.88	28.55	1.6006	-0.1956	20.2	42 610	17 486		%
32	563	10	450	40.57	33.54	-4.93	33.9	1.7771	-0.557	351.6	-1 496c	19 496		%
33	565	12	460	39.67	36.45	-12.66	38.58	1.8691	-0.7547	340.8	-1 505c	21 505		%
33	567	12	465	38.33	36.65	-13.24	38.97	1.9064	-0.781	340.1	-1 506c	21 506		%
33	569	14	470	37.27	38.14	-19.32	42.76	1.9738	-0.954	333.1	-1 520c	24 520		%
34	573	15	475	34.7	38.28	-22.47	44.39	2.0536	-1.083	329.5	-1 528c	25 528	Mm	%
36	580	16	480	30.04	37.48	-26.04	45.64	2.1982	-1.3026	325.2	-1 537c	27 537		%
39	595	17	485	21.24	32.73	-31.0	45.09	2.4914	-1.8952	316.5	-1 548c	29 548		%
-1	490c	18	490	6.19	12.06	-38.4	40.25	2.899	-6.6372	287.4	11 459	33 565	min	%
-1	495c	19	495	7.69	10.68	-38.39	39.85	2.3392	-5.4245	285.5	12 462	33 566		%
-1	500c	20	500	9.57	8.91	-38.07	39.1	1.8814	-4.4105	283.1	12 464	33 567		%
-1	510c	22	510	14.72	4.15	-36.48	36.72	1.2328	-2.9143	276.5	13 469	33 569		%
-1	519c	23	520	18.01	1.26	-35.24	35.26	1.0204	-2.3925	272.0	14 471	34 570	Bm	%
-1	529c	25	530	25.95	-5.15	-32.02	32.43	0.7516	-1.6693	260.8	15 475	34 573		%
-1	539c	27	540	35.09	-11.57	-28.16	30.44	0.6205	-1.238	247.6	15 478	35 577		%
-1	544c	28	545	39.86	-14.5	-26.11	29.87	0.5865	-1.0906	240.9	15 479	35 579		%
-1	549c	29	550	44.73	-17.18	-24.01	29.53	0.5663	-0.9725	234.4	16 480	36 582		%
-1	554c	30	555	49.59	-19.49	-21.91	29.33	0.5572	-0.8774	228.3	16 481	36 584		%
-1	560c	32	560	58.99	-22.8	-17.83	28.95	0.5638	-0.7379	218.0	16 483	37 589		%
380	770	100.0	0.0	0.0	0.01	0.9504	-0.4355	0.0						%
0-000000-L0										VG300-7X				

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =520_770, LINYAB-Daten														%
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code			
0	405	32	561	58.2	-22.74	-17.89	28.94	0.5596	-0.743	218.1	16 483 37 589	Cm	%	
6	435	32	562	58.79	-26.78	-9.88	28.55	0.4948	-0.6036	200.2	17 486 42 610		%	
10	450	32	563	59.42	-33.54	4.93	33.9	0.3859	-0.3525	171.6	19 496 -1 496c		%	
12	460	33	565	60.32	-36.45	12.66	38.58	0.3461	-0.2256	160.8	21 505 -1 505c		%	
12	465	33	567	61.66	-36.65	13.24	38.97	0.356	-0.2207	160.1	21 506 -1 506c		%	
14	470	33	569	62.72	-38.14	19.32	42.76	0.3422	-0.1274	153.1	24 520 -1 520c		%	
15	475	34	573	65.29	-38.28	22.47	44.39	0.364	-0.0913	149.5	25 528 -1 528c	Gm	%	
16	480	36	580	69.95	-37.48	26.04	45.64	0.4146	-0.0632	145.2	27 537 -1 537c		%	
17	485	39	595	78.75	-32.73	31.0	45.09	0.5347	-0.0418	136.5	29 548 -1 548c		%	
18	490	-1	490c	93.8	-12.06	38.4	40.25	0.8218	-0.0261	107.4	33 565 11 459	max	%	
19	495	-1	495c	92.3	-10.68	38.39	39.85	0.8346	-0.0195	105.5	33 566 12 462		%	
20	500	-1	500c	90.42	-8.91	38.07	39.1	0.8518	-0.0144	103.1	33 567 12 464		%	
22	510	-1	510c	85.27	-4.15	36.48	36.72	0.9016	-0.0076	96.5	33 569 13 469		%	
23	520	-1	519c	81.98	-1.26	35.24	35.26	0.935	-0.0056	92.0	34 570 14 471	Ym	%	
25	530	-1	529c	74.04	5.15	32.02	32.43	1.0201	-0.0031	80.8	34 573 15 475		%	
27	540	-1	539c	64.9	11.57	28.16	30.44	1.1288	-0.0016	67.6	35 577 15 478		%	
28	545	-1	544c	60.13	14.5	26.11	29.87	1.1917	-0.0012	60.9	35 579 15 479		%	
29	550	-1	549c	55.26	17.18	24.01	29.53	1.2613	-0.0009	54.4	36 582 16 480		%	
30	555	-1	554c	50.4	19.49	21.91	29.33	1.3372	-0.0007	48.3	36 584 16 481		%	
32	560	-1	560c	41.0	22.8	17.83	28.95	1.5064	-0.0005	38.0	37 589 16 483		%	
380	770	100.0	0.0	0.0	0.01	0.0	0.9504	-0.4355	0.0				%	

rgb* _{e,AB} und CIE-Daten eines Elementar-Bunttonkreises nach CIE R1-47 für Ostwald-Farben für CIE-Lichtart D65															
X _{xy} , abc _{AB} , ABC _{AB} LabC* _{ab} h _{AB} -Daten fü relative Stufung des Elementarbunttons h _{AB} von LINYAB für CIE-2-Grad Beobachter															
Elementar-Bunttonkreis mit 4 Ziel-Elementar-Bunttonwinkeln: h _{AB} = 17.7, 93.3, 159.1, 270.8 von LINYAB und 16 Ziel-Bunttonwinkeln:															
17.7 36.6 55.5 74.4 93.3 109.7 126.2 142.7 159.1 187.0 214.9 242.8 270.8 297.5 324.2 351.0															
LINYAB-Daten CIE-Testfarben 9 (R): 11.2 9.9 3.1, 10 (Y): 59.0 -1.2 20.9, 11 (G): 20.3 -7.2 7.2, 12 (B): 6.4 0.1 -8.2															
no _{AB} Y	x	y	a	b	c _{AB}	A	B	C _{AB}	h _{AB}	L*	a*	b*	C* _{ab}	rgb* _{e,AB}	Code _{AB}
000	41.1	0.508	0.314	1.615	-0.224	0.697	27.3	8.6	28.7	17.5	70.2	71.9	29.3	77.6	22.2 1.00 0.00 0.00 % R00Y #
001	41.7	0.59	0.393	1.499	-0.016	0.691	22.9	17.5	28.8	37.3	70.7	61.3	99.1	116.6	58.2 1.00 0.25 0.00 % R25Y #
002	56.0	0.554	0.444	1.249	0.0	0.527	16.7	24.3	29.5	55.5	79.6	39.3	135.2	140.8	73.7 1.00 0.50 0.00 % R50Y #
003	69.3	0.516	0.481	1.072	-0.002	0.45	8.5	30.0	31.2	74.2	86.7	18.2	143.3	144.5	82.7 1.00 0.75 0.00 % R75Y #
004	83.1	0.476	0.515	0.923	-0.006	0.43	-2.1	35.6	35.7	93.5	93.0	-4.4	142.7	142.8	91.7 1.00 1.00 0.00 % Y00G #
005	92.9	0.429	0.533	0.805	-0.027	0.433	-13.4	37.9	40.2	109.5	97.1	-26.2	117.8	120.7	102.5 0.75 1.00 0.00 % Y25G #
006	84.5	0.373	0.575	0.649	-0.035	0.5	-25.4	33.8	42.3	126.9	93.6	-56.2	107.3	121.2	117.6 0.50 1.00 0.00 % Y50G #
007	71.9	0.276	0.634	0.435	-0.056	0.639	-37.0	27.2	46.0	143.6	87.9	-102.5	88.5	135.4	139.2 0.25 1.00 0.00 % Y75G #
008	61.7	0.188	0.532	0.354	-0.21	0.637	-36.8	13.9	39.3	159.2	82.8	-119.3	36.7	124.8	162.8 0.00 1.00 0.00 % G00B #
009	59.0	0.166	0.375	0.443	-0.487	0.509	-29.9	-3.0	30.1	185.8	81.3	-94.1	-6.4	94.3	183.9 0.00 1.00 0.50 % G25B #
010	58.2	0.163	0.296	0.552	-0.727	0.494	-23.2	-17.0	28.7	216.2	80.8	-69.1	-31.1	75.8	204.2 0.00 1.00 1.00 % G50B #
011	38.6	0.134	0.227	0.592	-1.124	0.776	-13.8	-26.6	30.0	242.5	68.5	-53.0	-54.1	75.7	225.6 0.00 0.50 1.00 % G75B #
012	18.7	0.127	0.129	0.985	-2.302	1.867	0.6	-34.9	34.9	271.0	50.3	3.4	-84.8	84.9	272.3 0.00 0.00 1.00 % B00R #
013	10.6	0.204	0.075	2.711	-3.816	3.812	18.8	-36.1	40.7	297.5	39.0	99.2	-100.7	141.4	314.5 0.50 0.00 1.00 % B25R #
014	29.3	0.338	0.152	2.224	-1.338	1.561	37.3	-26.4	45.8	324.6	61.0	108.8	-60.3	124.4	331.0 1.00 0.00 1.00 % B50R #
015	40.5	0.423	0.237	1.784	-0.572	0.845	33.8	-5.5	34.2	350.6	69.8	86.4	-14.1	87.5	350.7 1.00 0.00 0.50 % B75R #
016	41.1	0.508	0.314	1.615	-0.224	0.697	27.3	8.6	28.7	17.5	70.2	71.9	29.3	77.6	22.2 1.00 0.00 0.00 % R00Y #
CIEXYZ-Daten of CIE-Testfarben 9 (R): 20.6 11.2 4.3, 10 (Y): 54.8 59.0 12.0, 11 (G): 12.1 20.3 15.3, 12 (B): 6.2 6.4 27.6															
5-stufige gleichabständige Graureihe mit Ziel-Helligkeit: L* = 0.0, 25.0, 50.0, 75.0, 100.0															
000	0.0	0.0	0.0	0.0	0.0	1.045	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.00 0.00 0.00 0.00 % N000W #
001	4.4	0.312	0.329	0.95	-0.435	0.01	0.0	0.0	0.0	77.1	25.0	0.0	0.0	0.0	0.0 0.25 0.25 0.25 % N025W #
002	18.4	0.312	0.329	0.95	-0.435	0.01	0.0	0.0	0.0	57.4	50.0	0.0	0.0	0.0	0.0 0.50 0.50 0.50 % N050W #
003	48.2	0.312	0.329	0.95	-0.435	0.01	0.0	0.0	0.0	22.9	75.0	0.0	0.0	0.0	0.0 0.75 0.75 0.75 % N075W #
004	100.0	0.312	0.329	0.95	-0.435	0.01	0.0	0.0	0.0	100.0	0.0	0.0	0.0	0.0	1.00 1.00 1.00 1.00 % N100W #

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _{w,10} =100, Y _m =520_770, LINYAB-Daten														%
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code		%	
0 405	31 556	56.57	-21.89	-18.32	28.54	0.5611	-0.7532	219.9	15 476	37 585	Cm		%	
6 435	31 557	57.41	-26.44	-8.79	27.86	0.4876	-0.5825	198.4	16 480	44 621			%	
10 450	31 559	57.53	-32.48	6.09	33.05	0.3834	-0.3234	169.3	18 491	-1 491c			%	
11 460	32 562	59.27	-33.9	10.52	35.5	0.3761	-0.2517	162.7	19 498	-1 498c			%	
12 465	33 565	60.91	-34.93	14.56	37.84	0.3747	-0.1903	157.3	21 506	-1 506c			%	
14 470	34 570	63.07	-35.18	20.67	40.8	0.3903	-0.1016	149.5	24 522	-1 522c			%	
15 475	35 579	68.64	-33.55	24.85	41.75	0.4593	-0.0672	143.4	26 533	-1 533c	Gm		%	
16 480	41 606	81.94	-23.65	31.88	39.7	0.6594	-0.0401	126.5	30 550	-1 550c			%	
16 485	-1 484c	92.3	-10.45	36.33	37.8	0.8348	-0.0356	106.0	32 560	10 454			%	
18 490	-1 490c	89.06	-7.57	36.55	37.33	0.863	-0.0188	101.7	32 562	11 459	max		%	
19 495	-1 495c	87.05	-5.68	36.18	36.62	0.8828	-0.0136	98.9	32 563	12 461			%	
19 500	-1 499c	87.05	-5.68	36.18	36.62	0.8828	-0.0136	98.9	32 563	12 461			%	
22 510	-1 510c	79.1	1.43	33.55	33.58	0.9662	-0.0051	87.5	33 567	13 466			%	
23 520	-1 519c	75.81	4.11	32.27	32.53	1.0024	-0.0036	82.7	33 568	13 468	Ym		%	
26 530	-1 530c	64.17	12.31	27.48	30.11	1.14	-0.001	65.8	34 573	14 472			%	
27 540	-1 539c	59.9	14.81	25.68	29.65	1.1955	-0.0005	60.0	35 576	14 473			%	
28 545	-1 544c	55.54	17.09	23.83	29.32	1.2559	-0.0002	54.3	35 578	14 474			%	
29 550	-1 549c	51.12	19.09	21.94	29.08	1.3215	-0.0001	48.9	36 580	15 475			%	
31 555	-1 555c	42.37	21.98	18.19	28.53	1.4668	0.0	39.6	37 586	15 476			%	
32 560	10 451	40.04	32.52	-6.18	33.11	1.7604	-0.5838	349.2	-1 492c	18 492			%	
380	770	100.0	0.0	0.0	0.01	0.9481	-0.4293	0.0					%	
Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _{w,10} =100, Y _m =770_520, LINYAB komplementär														%
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code		%	
31 556	0 405	43.42	21.89	18.32	28.54	1.4522	-0.0074	39.9	37 585	15 476	Rm		%	
31 557	6 435	42.58	26.44	8.79	27.86	1.5691	-0.2226	18.4	44 621	16 480			%	
31 559	10 450	42.46	32.48	-6.09	33.05	1.713	-0.5727	349.3	-1 491c	18 491			%	
32 562	11 460	40.72	33.9	-10.52	35.5	1.7807	-0.6879	342.7	-1 498c	19 498			%	
33 565	12 465	39.08	34.93	-14.56	37.84	1.8419	-0.8019	337.3	-1 506c	21 506			%	
34 570	14 470	36.92	35.18	-20.67	40.8	1.901	-0.9891	329.5	-1 522c	24 522			%	
35 579	15 475	31.35	33.55	-24.85	41.75	2.0184	-1.2222	323.4	-1 533c	26 533	Mm		%	
41 606	16 480	18.05	23.65	-31.88	39.7	2.2587	-2.1959	306.5	-1 550c	30 550			%	
-1 484c	16 485	7.69	10.45	-36.33	37.8	2.306	-5.1484	286.0	10 454	32 560			%	
-1 490c	18 490	10.93	7.57	-36.55	37.33	1.6407	-3.7725	281.7	11 459	32 562	min		%	
-1 495c	19 495	12.94	5.68	-36.18	36.62	1.3873	-3.2239	278.9	12 461	32 563			%	
-1 499c	19 500	12.94	5.68	-36.18	36.62	1.3873	-3.2239	278.9	12 461	32 563			%	
-1 510c	22 510	20.89	-1.43	-33.55	33.58	0.8795	-2.035	267.5	13 466	33 567			%	
-1 519c	23 520	24.18	-4.12	-32.27	32.53	0.7777	-1.7639	262.7	13 468	33 568	Bm		%	
-1 530c	26 530	35.82	-12.31	-27.48	30.11	0.6044	-1.1965	245.8	14 472	34 573			%	
-1 539c	27 540	40.09	-14.81	-25.68	29.65	0.5785	-1.0699	240.0	14 473	35 576			%	
-1 544c	28 545	44.45	-17.09	-23.83	29.32	0.5635	-0.9653	234.3	14 474	35 578			%	
-1 549c	29 550	48.87	-19.09	-21.94	29.08	0.5575	-0.8782	228.9	15 475	36 580			%	
-1 555c	31 555	57.62	-21.98	-18.19	28.53	0.5667	-0.745	219.6	15 476	37 586			%	
10 451	32 560	59.95	-32.52	6.18	33.11	0.4056	-0.3261	169.2	18 492	-1 492c			%	
380	770	100.0	0.0	0.0	0.01	0.9481	-0.4293	0.0					%	
0-001000-L0										VG300-7X				

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _{w,10} =100, Y _m =520_770, LINYAB-Daten															%
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code	%		%	
0 405	31 556	56.57	-21.89	-18.32	28.54	0.5611	-0.7532	219.9	15 476	37 585	Cm	%		%	
6 435	31 557	57.41	-26.44	-8.79	27.86	0.4876	-0.5825	198.4	16 480	44 621		%		%	
10 450	31 559	57.53	-32.48	6.09	33.05	0.3834	-0.3234	169.3	18 491	-1 491c		%		%	
11 460	32 562	59.27	-33.9	10.52	35.5	0.3761	-0.2517	162.7	19 498	-1 498c		%		%	
12 465	33 565	60.91	-34.93	14.56	37.84	0.3747	-0.1903	157.3	21 506	-1 506c		%		%	
14 470	34 570	63.07	-35.18	20.67	40.8	0.3903	-0.1016	149.5	24 522	-1 522c		%		%	
15 475	35 579	68.64	-33.55	24.85	41.75	0.4593	-0.0672	143.4	26 533	-1 533c	Gm	%		%	
16 480	41 606	81.94	-23.65	31.88	39.7	0.6594	-0.0401	126.5	30 550	-1 550c		%		%	
16 485	-1 484c	92.3	-10.45	36.33	37.8	0.8348	-0.0356	106.0	32 560	10 454		%		%	
18 490	-1 490c	89.06	-7.57	36.55	37.33	0.863	-0.0188	101.7	32 562	11 459	max	%		%	
19 495	-1 495c	87.05	-5.68	36.18	36.62	0.8828	-0.0136	98.9	32 563	12 461		%		%	
19 500	-1 499c	87.05	-5.68	36.18	36.62	0.8828	-0.0136	98.9	32 563	12 461		%		%	
22 510	-1 510c	79.1	1.43	33.55	33.58	0.9662	-0.0051	87.5	33 567	13 466		%		%	
23 520	-1 519c	75.81	4.11	32.27	32.53	1.0024	-0.0036	82.7	33 568	13 468	Ym	%		%	
26 530	-1 530c	64.17	12.31	27.48	30.11	1.14	-0.001	65.8	34 573	14 472		%		%	
27 540	-1 539c	59.9	14.81	25.68	29.65	1.1955	-0.0005	60.0	35 576	14 473		%		%	
28 545	-1 544c	55.54	17.09	23.83	29.32	1.2559	-0.0002	54.3	35 578	14 474		%		%	
29 550	-1 549c	51.12	19.09	21.94	29.08	1.3215	-0.0001	48.9	36 580	15 475		%		%	
31 555	-1 555c	42.37	21.98	18.19	28.53	1.4668	0.0	39.6	37 586	15 476		%		%	
32 560	10 451	40.04	32.52	-6.18	33.11	1.7604	-0.5838	349.2	-1 492c	18 492		%		%	
380	770	100.0	0.0	0.0	0.01	0.9481	-0.4293	0.0				%		%	

rgb* _{e,AB} und CIE-Daten eines Elementar-Bunttonkreises nach CIE R1-47 für Ostwald-Farben für CIE-Lichtart D65																	
X _{Yy} , abc _{AB} , ABC _{AB} , LabC* _{ab} , h _{ab} -Daten für relative Stufung des Elementarbunttons h _{AB} von LINYAB für CIE-10-Grad Beobachter																	
Elementar-Bunttonkreis mit 4 Ziel-Elementar-Bunttonwinkeln: h _{AB} = 18.2, 86.3, 156.2, 260.1 von LINYAB und 16 Ziel-Bunttonwinkeln:																	
18.2	35.2	52.2	69.2	86.3	103.7	121.2	138.7	156.2	182.2	208.1	234.1	260.1	289.6	319.1	348.7		
LINYAB-Daten CIE-Testfarben 9 (R): 10.8 8.7 2.8, 10 (Y): 55.9 1.2 19.6, 11 (G): 20.4 -6.8 3.0, 12 (B): 7.8 -1.2 -7.2																	
no. _{AB}	Y ₁₀₀	x ₁₀	y ₁₀	a ₁₀	b ₁₀	C _{AB,10}	A ₁₀	B ₁₀	C _{AB,10}	h _{AB,10}	L* ₁₀	a* ₁₀	b* ₁₀	C* _{ab,10}	h _{ab,10}	rgb* _{e,AB,10}	Code _{AB,10}
000	40.6	0.49	0.303	1.617	-0.273	0.687	27.1	6.3	27.9	13.1	69.9	72.1	20.7	75.0	16.0	1.00 0.00 0.00	% R00Y #
001	41.9	0.57	0.381	1.496	-0.049	0.667	22.9	15.9	27.9	34.6	70.8	61.4	76.6	98.2	51.2	1.00 0.25 0.00	% R25Y #
002	54.0	0.56	0.438	1.277	0.0	0.541	17.8	23.2	29.2	52.4	78.5	42.6	134.9	141.5	72.4	1.00 0.50 0.00	% R50Y #
003	66.4	0.525	0.473	1.109	-0.061	0.457	10.7	28.4	30.3	69.2	85.2	23.5	142.9	144.8	80.6	1.00 0.75 0.00	% R75Y #
004	78.3	0.491	0.503	0.975	-0.004	0.426	2.1	33.2	33.3	86.2	90.9	4.4	143.6	143.6	88.2	1.00 1.00 0.00	% Y00G #
005	91.3	0.445	0.519	0.857	-0.027	0.412	-8.2	36.7	37.6	102.6	96.5	-15.9	116.6	117.7	97.7	0.75 1.00 0.00	% Y25G #
006	85.3	0.394	0.552	0.713	-0.038	0.455	-20.0	33.3	38.8	120.9	94.0	-42.8	104.7	113.1	112.2	0.50 1.00 0.00	% Y50G #
007	72.0	0.309	0.603	0.511	-0.057	0.573	-31.4	26.7	41.2	139.5	87.9	-83.2	87.3	129.6	133.6	0.25 1.00 0.00	% Y75G #
008	42.1	0.501	0.319	1.567	-0.224	0.652	26.0	8.6	27.4	18.3	70.9	68.3	29.1	74.2	23.1	0.00 1.00 0.00	% G00B #
009	41.7	0.484	0.303	1.596	-0.279	0.665	27.0	6.2	27.8	13.0	70.7	70.9	19.9	73.6	15.6	0.00 1.00 0.50	% G25B #
010	41.4	0.469	0.288	1.626	-0.334	0.684	28.1	3.9	28.3	7.9	70.5	73.4	11.8	74.3	9.1	0.00 1.00 1.00	% G50B #
011	41.1	0.456	0.275	1.655	-0.389	0.708	29.1	1.6	29.1	3.2	70.2	75.8	4.7	76.0	3.6	0.00 0.50 1.00	% G75B #
012	40.8	0.444	0.264	1.683	-0.441	0.735	30.0	-0.4	30.0	359.0	70.0	78.2	-1.3	78.2	359.0	0.00 0.00 1.00	% B00R #
013	40.5	0.433	0.252	1.712	-0.496	0.767	31.0	-2.7	31.1	355.0	69.8	80.6	-7.2	80.9	354.8	0.50 0.00 1.00	% B25R #
014	40.2	0.424	0.243	1.738	-0.544	0.798	31.8	-4.6	32.1	351.7	69.6	82.7	-12.1	83.5	351.6	1.00 0.00 1.00	% B50R #
015	40.0	0.417	0.237	1.76	-0.583	0.826	32.5	-6.1	33.0	349.2	69.5	84.3	-15.8	85.8	349.3	1.00 0.00 0.50	% B75R #
016	40.6	0.49	0.303	1.617	-0.273	0.687	27.1	6.3	27.9	13.1	69.9	72.1	20.7	75.0	16.0	1.00 0.00 0.00	% R00Y #

CIEXYZ-Daten von CIE-Testfarben 9 (R): 19.0 10.8 4.3, 10 (Y): 54.3 55.9 11.0, 11 (G): 12.5 20.4 14.4, 12 (B): 6.1 7.8 26.5																
5-stufige gleichabständige Graureihe mit Ziel-Helligkeit: L* = 0.0, 25.0, 50.0, 75.0, 100.0																
000	0.0	0.0	0.0	0.0	0.0	1.04	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.00	0.00 0.00 % N000W #
001	4.4	0.313	0.33	0.948	-0.429	0.01	0.0	0.0	0.0	77.0	25.0	0.0	0.0	0.0	0.0	0.25 0.25 0.25 % N025W #
002	18.4	0.313	0.33	0.948	-0.429	0.01	0.0	0.0	0.0	55.3	50.0	0.0	0.0	0.0	0.0	0.50 0.50 0.50 % N050W #
003	48.2	0.313	0.33	0.948	-0.429	0.01	0.0	0.0	0.0	23.1	75.0	0.0	0.0	0.0	0.0	0.75 0.75 0.75 % N075W #
004	100.0	0.313	0.33	0.948	-0.429	0.01	0.0	0.0	0.0	0.0	100.0	0.0	0.0	0.0	0.0	1.00 1.00 1.00 % N100W #

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =520_770, CIELAB-Daten														%
i ₁ , λ ₁	i ₂ , λ ₂	L* ₁₀₀	a* ₁₀₀	b* ₁₀₀	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code	%		
0 405	32 561	80.85	-67.55	-32.54	74.98	0.1805	-0.1029	205.7	16 483	37 589	Cm	%		
6 435	32 562	81.18	-81.89	-19.25	84.12	0.1732	-0.096	193.2	17 486	42 610		%		
10 450	32 563	81.52	-109.06	11.43	109.66	0.1595	-0.0803	174.0	19 496	-1 496c		%		
12 460	33 565	82.01	-120.74	33.26	125.23	0.1538	-0.0692	164.5	21 505	-1 505c		%		
12 465	33 567	82.73	-118.76	34.5	123.67	0.1552	-0.0687	163.8	21 506	-1 506c		%		
14 470	33 569	83.3	-123.47	57.53	136.22	0.1532	-0.0572	155.0	24 520	-1 520c		%		
15 475	34 573	84.63	-118.73	70.39	138.03	0.1564	-0.0512	149.3	25 528	-1 528c	Gm	%		
16 480	36 580	86.98	-107.21	84.2	136.33	0.1633	-0.0452	141.8	27 537	-1 537c		%		
17 485	39 595	91.12	-80.53	100.07	128.45	0.1778	-0.0394	128.8	29 548	-1 548c		%		
18 490	-1 490c	97.55	-23.15	119.05	121.28	0.2052	-0.0337	101.0	33 565	11 459	max	%		
19 495	-1 495c	96.94	-20.63	125.42	127.1	0.2062	-0.0306	99.3	33 566	12 462		%		
20 500	-1 500c	96.17	-17.33	131.15	132.29	0.2076	-0.0277	97.5	33 567	12 464		%		
22 510	-1 510c	94.0	-8.24	140.17	140.41	0.2116	-0.0224	93.3	33 569	13 469		%		
23 520	-1 519c	92.57	-2.53	142.99	143.01	0.2142	-0.0202	91.0	34 570	14 471	Ym	%		
25 530	-1 529c	88.94	10.79	144.39	144.79	0.2205	-0.0165	85.7	34 573	15 475		%		
27 540	-1 539c	84.43	25.54	141.4	143.69	0.2281	-0.0134	79.7	35 577	15 478		%		
28 545	-1 544c	81.91	33.05	138.34	142.24	0.2322	-0.0121	76.5	35 579	15 479		%		
29 550	-1 549c	79.2	40.58	134.51	140.5	0.2367	-0.0111	73.2	36 582	16 480		%		
30 555	-1 554c	76.32	47.96	130.1	138.66	0.2413	-0.0103	69.7	36 584	16 481		%		
32 560	-1 560c	70.18	61.63	120.13	135.02	0.2511	-0.0093	62.8	37 589	16 483		%		
380	770	100.0	0.0	0.0	0.0	0.2154	-0.0861	0.0				%		
Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =770_520, CIELAB komplementär%														
i ₁ , λ ₁	i ₂ , λ ₂	L* ₁₀₀	a* ₁₀₀	b* ₁₀₀	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code	%		
32 561	0 405	70.73	60.88	110.08	125.79	0.2505	-0.022	61.0	37 589	16 483	Rm	%		
32 562	6 435	70.32	70.58	34.83	78.71	0.2562	-0.0659	26.2	42 610	17 486		%		
32 563	10 450	69.88	85.85	-12.65	86.78	0.2653	-0.0935	351.6	-1 496c	19 496		%		
33 565	12 460	69.24	92.89	-29.55	97.48	0.2698	-0.1035	342.3	-1 505c	21 505		%		
33 567	12 465	68.27	94.84	-31.22	99.85	0.2716	-0.1046	341.7	-1 506c	21 506		%		
33 569	14 470	67.49	99.24	-42.98	108.15	0.2748	-0.1119	336.5	-1 520c	24 520		%		
34 573	15 475	65.52	102.87	-49.85	114.31	0.2784	-0.1167	334.1	-1 528c	25 528	Mm	%		
36 580	16 480	61.69	107.96	-59.02	123.05	0.2848	-0.1241	331.3	-1 537c	27 537		%		
39 595	17 485	53.22	112.99	-75.47	135.88	0.297	-0.1406	326.2	-1 548c	29 548		%		
-1 490c	18 490	29.91	89.01	-117.0	147.01	0.3124	-0.2136	307.2	11 459	33 565	min	%		
-1 495c	19 495	33.36	74.42	-112.09	134.55	0.2908	-0.1997	303.5	12 462	33 566		%		
-1 500c	20 500	37.09	58.44	-106.44	121.43	0.2704	-0.1864	298.7	12 464	33 567		%		
-1 510c	22 510	45.26	23.9	-93.37	96.38	0.2349	-0.1623	284.3	13 469	33 569		%		
-1 519c	23 520	49.52	6.76	-86.32	86.58	0.2205	-0.152	274.4	14 471	34 570	Bm	%		
-1 529c	25 530	58.0	-23.98	-72.06	75.95	0.1992	-0.1348	251.5	15 475	34 573		%		
-1 539c	27 540	65.83	-46.7	-58.75	75.05	0.1868	-0.122	231.5	15 478	35 577		%		
-1 544c	28 545	69.38	-54.68	-52.68	75.93	0.1833	-0.117	223.9	15 479	35 579		%		
-1 549c	29 550	72.72	-60.59	-46.95	76.65	0.1812	-0.1126	217.7	16 480	36 582		%		
-1 554c	30 555	75.82	-64.5	-41.62	76.77	0.1803	-0.1088	212.8	16 481	36 584		%		
-1 560c	32 560	81.29	-66.96	-32.22	74.32	0.181	-0.1027	205.6	16 483	37 589		%		

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =520_770, CIELAB-Daten															%
i ₁ , λ ₁	i ₂ , λ ₂	L* ₁₀₀	a* ₁₀₀	b* ₁₀₀	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code				
0	405	32	561	80.85	-67.55	-32.54	74.98	0.1805	-0.1029	205.7	16 483	37 589	Cm	%	
6	435	32	562	81.18	-81.89	-19.25	84.12	0.1732	-0.096	193.2	17 486	42 610		%	
10	450	32	563	81.52	-109.06	11.43	109.66	0.1595	-0.0803	174.0	19 496	-1 496c		%	
12	460	33	565	82.01	-120.74	33.26	125.23	0.1538	-0.0692	164.5	21 505	-1 505c		%	
12	465	33	567	82.73	-118.76	34.5	123.67	0.1552	-0.0687	163.8	21 506	-1 506c		%	
14	470	33	569	83.3	-123.47	57.53	136.22	0.1532	-0.0572	155.0	24 520	-1 520c		%	
15	475	34	573	84.63	-118.73	70.39	138.03	0.1564	-0.0512	149.3	25 528	-1 528c	Gm	%	
16	480	36	580	86.98	-107.21	84.2	136.33	0.1633	-0.0452	141.8	27 537	-1 537c		%	
17	485	39	595	91.12	-80.53	100.07	128.45	0.1778	-0.0394	128.8	29 548	-1 548c		%	
18	490	-1 490c	97.55	-23.15	119.05	121.28	0.2052	-0.0337	101.0	33 565	11 459	max		%	
19	495	-1 495c	96.94	-20.63	125.42	127.1	0.2062	-0.0306	99.3	33 566	12 462			%	
20	500	-1 500c	96.17	-17.33	131.15	132.29	0.2076	-0.0277	97.5	33 567	12 464			%	
22	510	-1 510c	94.0	-8.24	140.17	140.41	0.2116	-0.0224	93.3	33 569	13 469			%	
23	520	-1 519c	92.57	-2.53	142.99	143.01	0.2142	-0.0202	91.0	34 570	14 471	Ym		%	
25	530	-1 529c	88.94	10.79	144.39	144.79	0.2205	-0.0165	85.7	34 573	15 475			%	
27	540	-1 539c	84.43	25.54	141.4	143.69	0.2281	-0.0134	79.7	35 577	15 478			%	
28	545	-1 544c	81.91	33.05	138.34	142.24	0.2322	-0.0121	76.5	35 579	15 479			%	
29	550	-1 549c	79.2	40.58	134.51	140.5	0.2367	-0.0111	73.2	36 582	16 480			%	
30	555	-1 554c	76.32	47.96	130.1	138.66	0.2413	-0.0103	69.7	36 584	16 481			%	
32	560	-1 560c	70.18	61.63	120.13	135.02	0.2511	-0.0093	62.8	37 589	16 483			%	
380	770	100.0	0.0	0.0	0.0	0.0	0.2154	-0.0861	0.0					%	

rgb* _{e,ab} - und CIE-Daten eines Elementar-Bunttonkreises nach CIE R1-47 für Ostwald-Farben für CIE-Lichtart D65																								
X _{xy} , abc _{AB} , ABC _{AB} LabC* _{ab} h _{ab} -Daten fü relative Stufung des Elementarbunttons h _{ab} von CIELAB für CIE-2-Grad Beobachter																								
Elementar-Bunttonkreis mit 4 Ziel-Elementar-Bunttonwinkeln: h _{ab} = 25.6, 92.4, 162.1, 271.5 von CIELAB und 16 Ziel-Bunttonwinkeln:																								
25.6 42.3 59.0 75.7 92.4 109.8 127.2 144.7 162.1 189.4 216.8 244.1 271.5 300.0 328.5 357.1																								
CIELAB-Daten CIE-Testfarben 9 (R): 40.0 58.9 28.3, 10 (Y): 81.3 -3.0 71.8, 11 (G): 52.2 -42.3 13.6, 12 (B): 30.5 1.2 -46.3																								
no. _{ab}	Y	x	y	a	b	c _{AB}	A	B	C _{AB}	h _{AB}	L*	a*	b*	C* _{ab}	h _{ab}	rgb* _{e,ab}	Code _{ab}							
000	41.2	0.516	0.321	1.603	-0.201	0.693	26.9	9.6	28.5	19.7	70.3	70.8	33.7	78.4	25.4	1.00 0.00 0.00	%	R00Y	#					
001	41.5	0.571	0.371	1.539	-0.06	0.698	24.5	15.5	29.0	32.4	70.5	65.1	71.7	96.9	47.7	1.00 0.25 0.00	%	R25Y	#					
002	41.7	0.593	0.396	1.497	-0.01	0.693	22.8	17.7	28.9	37.8	70.7	61.2	106.6	122.9	60.1	1.00 0.50 0.00	%	R50Y	#					
003	58.9	0.546	0.452	1.208	-0.001	0.505	15.2	25.5	29.7	59.2	81.2	34.9	137.4	141.8	75.7	1.00 0.75 0.00	%	R75Y	#					
004	84.1	0.473	0.517	0.913	-0.006	0.43	-3.0	36.0	36.2	94.8	93.5	-6.1	141.7	141.9	92.4	1.00 1.00 0.00	%	Y00G	#					
005	89.6	0.406	0.552	0.735	-0.03	0.459	-19.2	36.3	41.1	117.9	95.8	-39.5	113.6	120.3	109.1	0.75 1.00 0.00	%	Y25G	#					
006	79.6	0.332	0.605	0.549	-0.04	0.562	-31.9	31.4	44.7	135.4	91.5	-77.3	101.1	127.3	127.3	0.50 1.00 0.00	%	Y50G	#					
007	67.8	0.247	0.635	0.389	-0.073	0.667	-38.0	24.5	45.2	147.1	85.9	-112.9	78.7	137.6	145.1	0.25 1.00 0.00	%	Y75G	#					
008	61.8	0.189	0.536	0.353	-0.203	0.64	-36.9	14.3	39.6	158.7	82.8	-119.6	38.1	125.5	162.3	0.00 1.00 0.00	%	G00B	#					
009	58.9	0.165	0.35	0.472	-0.552	0.491	-28.1	-6.8	28.9	193.7	81.2	-87.0	-13.8	88.1	189.0	0.00 1.00 0.50	%	G25B	#					
010	45.5	0.142	0.253	0.563	-0.955	0.647	-17.6	-23.6	29.5	233.3	73.2	-61.4	-46.0	76.8	216.8	0.00 1.00 1.00	%	G50B	#					
011	29.4	0.128	0.186	0.69	-1.474	1.071	-7.6	-30.5	31.5	255.9	61.1	-33.6	-66.7	74.7	243.2	0.00 0.50 1.00	%	G75B	#					
012	18.8	0.127	0.129	0.981	-2.291	1.856	0.5	-34.9	34.9	278.9	50.4	3.1	-84.7	84.7	272.1	0.00 0.00 1.00	%	B00R	#					
013	8.9	0.136	0.067	2.02	-4.722	4.418	9.5	-38.2	39.4	284.0	35.8	63.8	-108.4	125.8	309.5	0.50 0.00 1.00	%	B25R	#					
014	26.3	0.329	0.14	2.344	-1.51	1.76	36.7	-28.3	46.3	323.3	58.3	112.5	-65.8	130.3	329.6	1.00 0.00 1.00	%	B50R	#					
015	40.6	0.437	0.249	1.75	-0.5	0.802	32.5	-2.6	32.6	355.3	69.9	83.6	-7.0	83.9	355.1	1.00 0.00 0.50	%	B75R	#					
016	41.2	0.516	0.321	1.603	-0.201	0.693	26.9	9.6	28.5	19.7	70.3	70.8	33.7	78.4	25.4	1.00 0.00 0.00	%	R00Y	#					
CIEXYZ-Daten of CIE-Testfarben 9 (R): 20.6 11.2 4.3, 10 (Y): 54.8 59.0 12.0, 11 (G): 12.1 20.3 15.3, 12 (B): 6.2 6.4 27.6																								
5-stufige gleichabständige Graureihe mit Ziel-Helligkeit: L* = 0.0, 25.0, 50.0, 75.0, 100.0																								
000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.00 0.00 0.00	%	N000W	#				
001	4.4	0.312	0.329	0.95	-0.435	0.01	0.0	0.0	0.0	77.1	25.0	0.0	0.0	0.0	0.0	0.0	0.25 0.25 0.25	%	N025W	#				
002	18.4	0.312	0.329	0.95	-0.435	0.01	0.0	0.0	0.0	57.4	50.0	0.0	0.0	0.0	0.0	0.0	0.50 0.50 0.50	%	N050W	#				
003	48.2	0.312	0.329	0.95	-0.435	0.01	0.0	0.0	0.0	22.9	75.0	0.0	0.0	0.0	0.0	0.0	0.75 0.75 0.75	%	N075W	#				
004	100.0	0.312	0.329	0.95	-0.435	0.01	0.0	0.0	0.0	100.0	0.0	0.0	0.0	0.0	0.0	0.0	1.00 1.00 1.00	%	N100W	#				

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _{w,10} =100, Y _m =520_770, CIELAB-Daten														%
i ₁ , λ ₁	i ₂ , λ ₂	L* ₁₀₀	a* ₁₀₀	b* ₁₀₀	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code		%	
0 405	31 556	79.94	-66.31	-34.08	74.56	0.1807	-0.1034	207.2	15 476	37 585	Cm		%	
6 435	31 557	80.42	-82.6	-17.8	84.5	0.1724	-0.0949	192.1	16 480	44 621			%	
10 450	31 559	80.48	-108.29	14.97	109.32	0.1591	-0.078	172.1	18 491	-1 491c			%	
11 460	32 562	81.44	-111.37	27.39	114.69	0.1581	-0.0717	166.1	19 498	-1 498c			%	
12 465	33 565	82.34	-112.77	40.26	119.75	0.1579	-0.0653	160.3	21 506	-1 506c			%	
14 470	34 570	83.48	-109.79	65.41	127.8	0.1601	-0.053	149.2	24 522	-1 522c			%	
15 475	35 579	86.33	-94.64	81.3	124.77	0.169	-0.0462	139.3	26 533	-1 533c	Gm		%	
16 480	41 606	92.55	-53.33	102.14	115.22	0.1907	-0.0389	117.5	30 550	-1 550c			%	
16 485	-1 484c	96.94	-20.21	109.71	111.55	0.2063	-0.0374	100.4	32 560	10 454			%	
18 490	-1 490c	95.61	-14.83	124.45	125.34	0.2086	-0.0302	96.7	32 562	11 459	max		%	
19 495	-1 495c	94.76	-11.22	130.34	130.82	0.2101	-0.0271	94.9	32 563	12 461			%	
19 500	-1 499c	94.76	-11.22	130.34	130.82	0.2101	-0.0271	94.9	32 563	12 461			%	
22 510	-1 510c	91.28	2.92	142.55	142.58	0.2166	-0.0195	88.8	33 567	13 466			%	
23 520	-1 519c	89.77	8.54	144.07	144.32	0.2192	-0.0174	86.6	33 568	13 468	Ym		%	
26 530	-1 530c	84.06	27.32	142.33	144.93	0.2288	-0.0115	79.1	34 573	14 472			%	
27 540	-1 539c	81.79	33.86	139.63	143.68	0.2325	-0.0095	76.3	35 576	14 473			%	
28 545	-1 544c	79.35	40.37	136.19	142.05	0.2363	-0.0075	73.4	35 578	14 474			%	
29 550	-1 549c	76.75	46.79	132.12	140.16	0.2404	-0.0054	70.4	36 580	15 475			%	
31 555	-1 555c	71.13	58.79	122.64	136.0	0.2489	0.0	64.3	37 586	15 476			%	
32 560	10 451	69.5	84.42	-15.9	85.9	0.2645	-0.095	349.3	-1 492c	18 492			%	
380	770	100.0	0.0	0.0	0.0	0.2152	-0.0857	0.0					%	
Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _{w,10} =100, Y _m =770_520, CIELAB komplementär														%
i ₁ , λ ₁	i ₂ , λ ₂	L* ₁₀₀	a* ₁₀₀	b* ₁₀₀	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code		%	
31 556	0 405	71.84	57.81	111.35	125.47	0.2481	-0.0221	62.5	37 585	15 476	Rm		%	
31 557	6 435	71.27	68.77	29.56	74.85	0.2546	-0.0689	23.2	44 621	16 480			%	
31 559	10 450	71.19	81.9	-15.15	83.29	0.2621	-0.0944	349.5	-1 491c	18 491			%	
32 562	11 460	69.98	86.63	-25.22	90.23	0.2655	-0.1003	343.7	-1 498c	19 498			%	
33 565	12 465	68.81	90.56	-33.85	96.68	0.2685	-0.1056	339.5	-1 506c	21 506			%	
34 570	14 470	67.22	93.6	-46.01	104.3	0.2714	-0.1132	333.8	-1 522c	24 522			%	
35 579	15 475	62.81	97.27	-56.68	112.58	0.2768	-0.1215	329.7	-1 533c	26 533	Mm		%	
41 606	16 480	49.57	94.8	-81.7	125.15	0.2874	-0.1477	319.2	-1 550c	30 550			%	
-1 484c	16 485	33.36	73.3	-109.63	131.88	0.2894	-0.1962	303.7	10 454	32 560			%	
-1 490c	18 490	39.48	47.93	-101.69	112.42	0.2584	-0.1769	295.2	11 459	32 562	min		%	
-1 495c	19 495	42.69	34.2	-96.93	102.79	0.2443	-0.1679	289.4	12 461	32 563			%	
-1 499c	19 500	42.69	34.2	-96.93	102.79	0.2443	-0.1679	289.4	12 461	32 563			%	
-1 510c	22 510	52.84	-7.33	-80.67	81.0	0.2099	-0.144	264.8	13 466	33 567			%	
-1 519c	23 520	56.28	-19.89	-74.95	77.55	0.2014	-0.1373	255.1	13 468	33 568	Bm		%	
-1 530c	26 530	66.39	-49.47	-57.84	76.11	0.1852	-0.1206	229.4	14 472	34 573			%	
-1 539c	27 540	69.54	-55.96	-52.46	76.71	0.1825	-0.1162	223.1	14 473	35 576			%	
-1 544c	28 545	72.53	-60.74	-47.32	77.0	0.1809	-0.1123	217.9	14 474	35 578			%	
-1 549c	29 550	75.38	-63.87	-42.44	76.68	0.1803	-0.1088	213.6	15 475	36 580			%	
-1 555c	31 555	80.53	-65.58	-33.56	73.67	0.1813	-0.103	207.1	15 476	37 586			%	
10 451	32 560	81.82	-103.91	14.76	104.95	0.1621	-0.0782	171.9	18 492	-1 492c			%	
380	770	100.0	0.0	0.0	0.0	0.2152	-0.0857	0.0					%	

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _{w,10} =100, Y _m =520_770, CIELAB-Daten															%
i ₁ , λ ₁	i ₂ , λ ₂	L* ₁₀₀	a* ₁₀₀	b* ₁₀₀	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code				%
0 405	31 556	79.94	-66.31	-34.08	74.56	0.1807	-0.1034	207.2	15 476	37 585	Cm				%
6 435	31 557	80.42	-82.6	-17.8	84.5	0.1724	-0.0949	192.1	16 480	44 621					%
10 450	31 559	80.48	-108.29	14.97	109.32	0.1591	-0.078	172.1	18 491	-1 491c					%
11 460	32 562	81.44	-111.37	27.39	114.69	0.1581	-0.0717	166.1	19 498	-1 498c					%
12 465	33 565	82.34	-112.77	40.26	119.75	0.1579	-0.0653	160.3	21 506	-1 506c					%
14 470	34 570	83.48	-109.79	65.41	127.8	0.1601	-0.053	149.2	24 522	-1 522c					%
15 475	35 579	86.33	-94.64	81.3	124.77	0.169	-0.0462	139.3	26 533	-1 533c	Gm				%
16 480	41 606	92.55	-53.33	102.14	115.22	0.1907	-0.0389	117.5	30 550	-1 550c					%
16 485	-1 484c	96.94	-20.21	109.71	111.55	0.2063	-0.0374	100.4	32 560	10 454					%
18 490	-1 490c	95.61	-14.83	124.45	125.34	0.2086	-0.0302	96.7	32 562	11 459	max				%
19 495	-1 495c	94.76	-11.22	130.34	130.82	0.2101	-0.0271	94.9	32 563	12 461					%
19 500	-1 499c	94.76	-11.22	130.34	130.82	0.2101	-0.0271	94.9	32 563	12 461					%
22 510	-1 510c	91.28	2.92	142.55	142.58	0.2166	-0.0195	88.8	33 567	13 466					%
23 520	-1 519c	89.77	8.54	144.07	144.32	0.2192	-0.0174	86.6	33 568	13 468	Ym				%
26 530	-1 530c	84.06	27.32	142.33	144.93	0.2288	-0.0115	79.1	34 573	14 472					%
27 540	-1 539c	81.79	33.86	139.63	143.68	0.2325	-0.0095	76.3	35 576	14 473					%
28 545	-1 544c	79.35	40.37	136.19	142.05	0.2363	-0.0075	73.4	35 578	14 474					%
29 550	-1 549c	76.75	46.79	132.12	140.16	0.2404	-0.0054	70.4	36 580	15 475					%
31 555	-1 555c	71.13	58.79	122.64	136.0	0.2489	0.0	64.3	37 586	15 476					%
32 560	10 451	69.5	84.42	-15.9	85.9	0.2645	-0.095	349.3	-1 492c	18 492					%
380	770	100.0	0.0	0.0	0.0	0.2152	-0.0857	0.0							%

rgb _{e,ab} - und CIE-Daten eines Elementar-Bunttonkreises nach CIE R1-47 für Ostwald-Farben für CIE-Lichtart D65																	
X _{Yy} , abc _{AB} , ABC _{AB} , LabC* _{ab} h _{ab} -Daten für relative Stufung des Elementarbunttons h _{ab} von CIELAB für CIE-10-Grad Beobachter																	
Elementar-Bunttonkreis mit 4 Ziel-Elementar-Bunttonwinkeln: h _{ab} = 25.9, 87.3, 158.8, 252.1 von CIELAB und 16 Ziel-Bunttonwinkeln:																	
25.9	41.2	56.6	72.0	87.3	105.2	123.1	140.9	158.8	182.1	205.4	228.8	252.1	285.5	319.0	352.4		
CIELAB-Daten CIE-Testfarben 9 (R): 39.2 54.5 26.4, 10 (Y): 79.5 3.2 71.0, 11 (G): 52.3 -39.6 15.3, 12 (B): 33.6 -12.8 -39.9																	
no _{ab}	X ₁₀₀	x ₁₀	y ₁₀	a ₁₀	b ₁₀	C _{AB,10}	A ₁₀	B ₁₀	C _{AB,10}	h _{AB,10}	L* ₁₀	a* ₁₀	b* ₁₀	C* _{ab,10}	h _{ab,10}	rgb _{e,ab,10}	Code _{ab,10}
000	40.4	0.542	0.33	1.642	-0.153	0.747	28.1	11.1	30.2	21.6	69.8	74.3	42.8	85.8	29.9	1.00 0.00 0.00	% R00Y #
001	41.0	0.582	0.37	1.572	-0.051	0.73	25.6	15.5	29.9	31.1	70.2	68.2	75.3	101.7	47.8	1.00 0.25 0.00	% R25Y #
002	41.8	0.594	0.396	1.501	-0.009	0.694	23.1	17.5	29.0	37.1	70.7	61.9	107.5	124.1	60.0	1.00 0.50 0.00	% R50Y #
003	53.6	0.562	0.437	1.283	0.0	0.544	18.0	23.0	29.2	51.9	78.2	43.2	134.5	141.3	72.1	1.00 0.75 0.00	% R75Y #
004	77.3	0.494	0.5	0.987	-0.004	0.427	3.0	32.8	33.0	84.7	90.4	6.2	144.2	144.4	87.5	1.00 1.00 0.00	% Y00G #
005	90.3	0.421	0.529	0.795	-0.037	0.421	-13.8	35.4	38.0	111.3	96.1	-27.5	107.7	111.2	104.3	0.75 1.00 0.00	% Y25G #
006	78.3	0.351	0.582	0.603	-0.045	0.516	-27.0	30.1	40.4	131.8	90.9	-64.4	97.3	116.7	123.5	0.50 1.00 0.00	% Y50G #
007	42.4	0.576	0.376	1.531	-0.049	0.696	24.7	16.1	29.5	33.0	71.2	65.1	77.2	101.0	49.8	0.25 1.00 0.00	% Y75G #
008	42.2	0.569	0.366	1.552	-0.069	0.703	25.5	15.2	29.7	30.7	71.0	67.0	68.3	95.7	45.5	0.00 1.00 0.00	% G00B #
009	41.9	0.556	0.352	1.58	-0.103	0.711	26.5	13.6	29.8	27.2	70.8	69.5	56.4	89.5	39.0	0.00 1.00 0.50	% G25B #
010	41.6	0.539	0.335	1.609	-0.148	0.718	27.5	11.6	29.8	22.9	70.6	71.9	44.4	84.5	31.6	0.00 1.00 1.00	% G50B #
011	41.3	0.519	0.317	1.637	-0.204	0.725	28.4	9.2	29.9	18.0	70.4	74.4	32.5	81.2	23.6	0.00 0.50 1.00	% G75B #
012	41.0	0.498	0.299	1.665	-0.27	0.734	29.4	6.5	30.1	12.4	70.2	76.7	21.1	79.6	15.4	0.00 0.00 1.00	% B00R #
013	40.6	0.466	0.274	1.703	-0.378	0.756	30.6	2.0	30.7	3.8	69.9	79.8	6.1	80.0	4.3	0.50 0.00 1.00	% B25R #
014	40.3	0.438	0.252	1.736	-0.49	0.79	31.7	-2.4	31.8	355.5	69.6	82.5	-6.7	82.7	355.3	1.00 0.00 1.00	% B50R #
015	40.0	0.424	0.242	1.754	-0.55	0.815	32.2	-4.8	32.6	351.4	69.4	83.9	-12.7	84.8	351.3	1.00 0.00 0.50	% B75R #
016	40.4	0.542	0.33	1.642	-0.153	0.747	28.1	11.1	30.2	21.6	69.8	74.3	42.8	85.8	29.9	1.00 0.00 0.00	% R00Y #
CIEXYZ-Daten von CIE-Testfarben 9 (R): 19.0 10.8 4.3, 10 (Y): 54.3 55.9 11.0, 11 (G): 12.5 20.4 14.4, 12 (B): 6.1 7.8 26.5																	
5-stufige gleichabständige Graureihe mit Ziel-Helligkeit: L* = 0.0, 25.0, 50.0, 75.0, 100.0																	
000	0.0	0.0	0.0	0.0	0.0	0.0	1.04	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.00 0.00 0.00	% N000W #
001	4.4	0.313	0.33	0.948	-0.429	0.01	0.0	0.0	0.0	77.0	25.0	0.0	0.0	0.0	0.0	0.25 0.25 0.25	% N025W #
002	18.4	0.313	0.33	0.948	-0.429	0.01	0.0	0.0	0.0	55.3	50.0	0.0	0.0	0.0	0.0	0.50 0.50 0.50	% N050W #
003	48.2	0.313	0.33	0.948	-0.429	0.01	0.0	0.0	0.0	23.1	75.0	0.0	0.0	0.0	0.0	0.75 0.75 0.75	% N075W #
004	100.0	0.313	0.33	0.948	-0.429	0.01	0.0	0.0	0.0	0.0	100.0	0.0	0.0	0.0	0.0	1.00 1.00 1.00	% N100W #