

Siehe ähnliche Dateien: <http://130.149.60.45/~farbmetrik/VG30/VG30LONP.PDF> /PS
Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =520_770, LINYAB-Daten															%
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code		%		
0	405	32 561	58.2	-22.74	-17.89	28.94	0.5596	-0.743	218.1	16 483	37 589	Cm	%		
6	435	32 562	58.79	-26.78	-9.88	28.55	0.4948	-0.6036	200.2	17 486	42 610		%		
10	450	32 563	59.42	-33.54	4.93	33.9	0.3859	-0.3525	171.6	19 496	-1 496c		%		
12	460	33 565	60.32	-36.45	12.66	38.58	0.3461	-0.2256	160.8	21 505	-1 505c		%		
12	465	33 567	61.66	-36.65	13.24	38.97	0.356	-0.2207	160.1	21 506	-1 506c		%		
14	470	33 569	62.72	-38.14	19.32	42.76	0.3422	-0.1274	153.1	24 520	-1 520c		%		
15	475	34 573	65.29	-38.28	22.47	44.39	0.364	-0.0913	149.5	25 528	-1 528c	Gm	%		
16	480	36 580	69.95	-37.48	26.04	45.64	0.4146	-0.0632	145.2	27 537	-1 537c		%		
17	485	39 595	78.75	-32.73	31.0	45.09	0.5347	-0.0418	136.5	29 548	-1 548c		%		
18	490	-1 490c	93.8	-12.06	38.4	40.25	0.8218	-0.0261	107.4	33 565	11 459	max	%		
19	495	-1 495c	92.3	-10.68	38.39	39.85	0.8346	-0.0195	105.5	33 566	12 462		%		
20	500	-1 500c	90.42	-8.91	38.07	39.1	0.8518	-0.0144	103.1	33 567	12 464		%		
22	510	-1 510c	85.27	-4.15	36.48	36.72	0.9016	-0.0076	96.5	33 569	13 469		%		
23	520	-1 519c	81.98	-1.26	35.24	35.26	0.935	-0.0056	92.0	34 570	14 471	Ym	%		
25	530	-1 529c	74.04	5.15	32.02	32.43	1.0201	-0.0031	80.8	34 573	15 475		%		
27	540	-1 539c	64.9	11.57	28.16	30.44	1.1288	-0.0016	67.6	35 577	15 478		%		
28	545	-1 544c	60.13	14.5	26.11	29.87	1.1917	-0.0012	60.9	35 579	15 479		%		
29	550	-1 549c	55.26	17.18	24.01	29.53	1.2613	-0.0009	54.4	36 582	16 480		%		
30	555	-1 554c	50.4	19.49	21.91	29.33	1.3372	-0.0007	48.3	36 584	16 481		%		
32	560	-1 560c	41.0	22.8	17.83	28.95	1.5064	-0.0005	38.0	37 589	16 483		%		
380	770	100.0	0.0	0.0	0.0	0.01	0.9504	-0.4355	0.0				%		

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =770_520, LINYAB komplementär%														
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code	%		
32 561	0 405	41.79	22.74	17.89	28.94	1.4946	-0.0072	38.1	37 589	16 483	Rm	%		
32 562	6 435	41.2	26.78	9.88	28.55	1.6006	-0.1956	20.2	42 610	17 486		%		
32 563	10 450	40.57	33.54	-4.93	33.9	1.7771	-0.557	351.6	-1 496c	19 496		%		
33 565	12 460	39.67	36.45	-12.66	38.58	1.8691	-0.7547	340.8	-1 505c	21 505		%		
33 567	12 465	38.33	36.65	-13.24	38.97	1.9064	-0.781	340.1	-1 506c	21 506		%		
33 569	14 470	37.27	38.14	-19.32	42.76	1.9738	-0.954	333.1	-1 520c	24 520		%		
34 573	15 475	34.7	38.28	-22.47	44.39	2.0536	-1.083	329.5	-1 528c	25 528	Mm	%		
36 580	16 480	30.04	37.48	-26.04	45.64	2.1982	-1.3026	325.2	-1 537c	27 537		%		
39 595	17 485	21.24	32.73	-31.0	45.09	2.4914	-1.8952	316.5	-1 548c	29 548		%		
-1 490c	18 490	6.19	12.06	-38.4	40.25	2.899	-6.6372	287.4	11 459	33 565	min	%		
-1 495c	19 495	7.69	10.68	-38.39	39.85	2.3392	-5.4245	285.5	12 462	33 566		%		
-1 500c	20 500	9.57	8.91	-38.07	39.1	1.8814	-4.4105	283.1	12 464	33 567		%		
-1 510c	22 510	14.72	4.15	-36.48	36.72	1.2328	-2.9143	276.5	13 469	33 569		%		
-1 519c	23 520	18.01	1.26	-35.24	35.26	1.0204	-2.3925	272.0	14 471	34 570	Bm	%		
-1 529c	25 530	25.95	-5.15	-32.02	32.43	0.7516	-1.6693	260.8	15 475	34 573		%		
-1 539c	27 540	35.09	-11.57	-28.16	30.44	0.6205	-1.238	247.6	15 478	35 577		%		
-1 544c	28 545	39.86	-14.5	-26.11	29.87	0.5865	-1.0906	240.9	15 479	35 579		%		
-1 549c	29 550	44.73	-17.18	-24.01	29.53	0.5663	-0.9725	234.4	16 480	36 582		%		
-1 554c	30 555	49.59	-19.49	-21.91	29.33	0.5572	-0.8774	228.3	16 481	36 584		%		
-1 560c	32 560	58.99	-22.8	-17.83	28.95	0.5638	-0.7379	218.0	16 483	37 589		%		
380	770	100.0	0.0	0.0	0.01	0.9504	-0.4355	0.0				%		

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _{w,10} =100, Y _m =520_770, LINYAB-Daten														%
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code		%	
0 405	31 556	56.57	-21.89	-18.32	28.54	0.5611	-0.7532	219.9	15 476	37 585	Cm		%	
6 435	31 557	57.41	-26.44	-8.79	27.86	0.4876	-0.5825	198.4	16 480	44 621			%	
10 450	31 559	57.53	-32.48	6.09	33.05	0.3834	-0.3234	169.3	18 491	-1 491c			%	
11 460	32 562	59.27	-33.9	10.52	35.5	0.3761	-0.2517	162.7	19 498	-1 498c			%	
12 465	33 565	60.91	-34.93	14.56	37.84	0.3747	-0.1903	157.3	21 506	-1 506c			%	
14 470	34 570	63.07	-35.18	20.67	40.8	0.3903	-0.1016	149.5	24 522	-1 522c			%	
15 475	35 579	68.64	-33.55	24.85	41.75	0.4593	-0.0672	143.4	26 533	-1 533c	Gm		%	
16 480	41 606	81.94	-23.65	31.88	39.7	0.6594	-0.0401	126.5	30 550	-1 550c			%	
16 485	-1 484c	92.3	-10.45	36.33	37.8	0.8348	-0.0356	106.0	32 560	10 454			%	
18 490	-1 490c	89.06	-7.57	36.55	37.33	0.863	-0.0188	101.7	32 562	11 459	max		%	
19 495	-1 495c	87.05	-5.68	36.18	36.62	0.8828	-0.0136	98.9	32 563	12 461			%	
19 500	-1 499c	87.05	-5.68	36.18	36.62	0.8828	-0.0136	98.9	32 563	12 461			%	
22 510	-1 510c	79.1	1.43	33.55	33.58	0.9662	-0.0051	87.5	33 567	13 466			%	
23 520	-1 519c	75.81	4.11	32.27	32.53	1.0024	-0.0036	82.7	33 568	13 468	Ym		%	
26 530	-1 530c	64.17	12.31	27.48	30.11	1.14	-0.001	65.8	34 573	14 472			%	
27 540	-1 539c	59.9	14.81	25.68	29.65	1.1955	-0.0005	60.0	35 576	14 473			%	
28 545	-1 544c	55.54	17.09	23.83	29.32	1.2559	-0.0002	54.3	35 578	14 474			%	
29 550	-1 549c	51.12	19.09	21.94	29.08	1.3215	-0.0001	48.9	36 580	15 475			%	
31 555	-1 555c	42.37	21.98	18.19	28.53	1.4668	0.0	39.6	37 586	15 476			%	
32 560	10 451	40.04	32.52	-6.18	33.11	1.7604	-0.5838	349.2	-1 492c	18 492			%	
380	770	100.0	0.0	0.0	0.01	0.9481	-0.4293	0.0					%	

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _{w,10} =100, Y _m =770_520, LINYAB komplementär														
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code	%		
31 556	0 405	43.42	21.89	18.32	28.54	1.4522	-0.0074	39.9	37 585	15 476	Rm	%		
31 557	6 435	42.58	26.44	8.79	27.86	1.5691	-0.2226	18.4	44 621	16 480		%		
31 559	10 450	42.46	32.48	-6.09	33.05	1.713	-0.5727	349.3	-1 491c	18 491		%		
32 562	11 460	40.72	33.9	-10.52	35.5	1.7807	-0.6879	342.7	-1 498c	19 498		%		
33 565	12 465	39.08	34.93	-14.56	37.84	1.8419	-0.8019	337.3	-1 506c	21 506		%		
34 570	14 470	36.92	35.18	-20.67	40.8	1.901	-0.9891	329.5	-1 522c	24 522		%		
35 579	15 475	31.35	33.55	-24.85	41.75	2.0184	-1.2222	323.4	-1 533c	26 533	Mm	%		
41 606	16 480	18.05	23.65	-31.88	39.7	2.2587	-2.1959	306.5	-1 550c	30 550		%		
-1 484c	16 485	7.69	10.45	-36.33	37.8	2.306	-5.1484	286.0	10 454	32 560		%		
-1 490c	18 490	10.93	7.57	-36.55	37.33	1.6407	-3.7725	281.7	11 459	32 562	min	%		
-1 495c	19 495	12.94	5.68	-36.18	36.62	1.3873	-3.2239	278.9	12 461	32 563		%		
-1 499c	19 500	12.94	5.68	-36.18	36.62	1.3873	-3.2239	278.9	12 461	32 563		%		
-1 510c	22 510	20.89	-1.43	-33.55	33.58	0.8795	-2.035	267.5	13 466	33 567		%		
-1 519c	23 520	24.18	-4.12	-32.27	32.53	0.7777	-1.7639	262.7	13 468	33 568	Bm	%		
-1 530c	26 530	35.82	-12.31	-27.48	30.11	0.6044	-1.1965	245.8	14 472	34 573		%		
-1 539c	27 540	40.09	-14.81	-25.68	29.65	0.5785	-1.0699	240.0	14 473	35 576		%		
-1 544c	28 545	44.45	-17.09	-23.83	29.32	0.5635	-0.9653	234.3	14 474	35 578		%		
-1 549c	29 550	48.87	-19.09	-21.94	29.08	0.5575	-0.8782	228.9	15 475	36 580		%		
-1 555c	31 555	57.62	-21.98	-18.19	28.53	0.5667	-0.745	219.6	15 476	37 586		%		
10 451	32 560	59.95	-32.52	6.18	33.11	0.4056	-0.3261	169.2	18 492	-1 492c		%		
380	770	100.0	0.0	0.0	0.01	0.9481	-0.4293	0.0				%		

Siehe ähnliche Dateien: <http://130.149.60.45/~farbmetrik/VG30/VG30LONP.PDF>
Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =520_770, LINYAB-Daten																				%
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code	%								%
0 405	32 561	58.2	-22.74	-17.89	28.94	0.5596	-0.743	218.1	16 483	37 589	Cm	%								%
6 435	32 562	58.79	-26.78	-9.88	28.55	0.4948	-0.6036	200.2	17 486	42 610		%								%
10 450	32 563	59.42	-33.54	4.93	33.9	0.3859	-0.3525	171.6	19 496	-1 496c		%								%
12 460	33 565	60.32	-36.45	12.66	38.58	0.3461	-0.2256	160.8	21 505	-1 505c		%								%
12 465	33 567	61.66	-36.65	13.24	38.97	0.356	-0.2207	160.1	21 506	-1 506c		%								%
14 470	33 569	62.72	-38.14	19.32	42.76	0.3422	-0.1274	153.1	24 520	-1 520c		%								%
15 475	34 573	65.29	-38.28	22.47	44.39	0.364	-0.0913	149.5	25 528	-1 528c	Gm	%								%
16 480	36 580	69.95	-37.48	26.04	45.64	0.4146	-0.0632	145.2	27 537	-1 537c		%								%
17 485	39 595	78.75	-32.73	31.0	45.09	0.5347	-0.0418	136.5	29 548	-1 548c		%								%
18 490	-1 490c	93.8	-12.06	38.4	40.25	0.8218	-0.0261	107.4	33 565	11 459	max	%								%
19 495	-1 495c	92.3	-10.68	38.39	39.85	0.8346	-0.0195	105.5	33 566	12 462		%								%
20 500	-1 500c	90.42	-8.91	38.07	39.1	0.8518	-0.0144	103.1	33 567	12 464		%								%
22 510	-1 510c	85.27	-4.15	36.48	36.72	0.9016	-0.0076	96.5	33 569	13 469		%								%
23 520	-1 519c	81.98	-1.26	35.24	35.26	0.935	-0.0056	92.0	34 570	14 471	Ym	%								%
25 530	-1 529c	74.04	5.15	32.02	32.43	1.0201	-0.0031	80.8	34 573	15 475		%								%
27 540	-1 539c	64.9	11.57	28.16	30.44	1.1288	-0.0016	67.6	35 577	15 478		%								%
28 545	-1 544c	60.13	14.5	26.11	29.87	1.1917	-0.0012	60.9	35 579	15 479		%								%
29 550	-1 549c	55.26	17.18	24.01	29.53	1.2613	-0.0009	54.4	36 582	16 480		%								%
30 555	-1 554c	50.4	19.49	21.91	29.33	1.3372	-0.0007	48.3	36 584	16 481		%								%
32 560	-1 560c	41.0	22.8	17.83	28.95	1.5064	-0.0005	38.0	37 589	16 483		%								%
380	770	100.0	0.0	0.0	0.01	0.9504	-0.4355	0.0				%								%

rgb* _{e,AB} und CIE-Daten eines Elementar-Bunttonkreises nach CIE R1-47 für Ostwald-Farben für CIE-Lichtart D65																			
Yxy, abc _{AB} , ABC _{AB} , LabC* _{ab} h _{ab} -Daten für relative Stufung des Elementarbunttons h _{AB} von LINYAB für CIE-2-Grad Beobachter																			
Elementar-Bunttonkreis mit 4 Ziel-Elementar-Bunttonwinkeln: h _{AB} = 17.7, 93.3, 159.1, 270.8 von LINYAB und 16 Ziel-Bunttonwinkeln:																			
17.7	36.6	55.5	74.4	93.3	109.7	126.2	142.7	159.1	187.0	214.9	242.8	270.8	297.5	324.2	351.0				
LINYAB-Daten CIE-Testfarben 9 (R): 11.2 9.9 3.1, 10 (Y): 59.0 -1.2 20.9, 11 (G): 20.3 -7.2 2.7, 12 (B): 6.4 0.1 -8.2																			
no _{AB}	Y	x	y	a	b	C _{AB}	A	B	C _{AB}	h _{AB}	L*	a*	b*	C* _{ab}	h _{ab}	rgb* _{e,AB}	Code _{AB}		
000	41.1	0.508	0.314	1.615	-0.224	0.697	27.3	8.6	28.7	17.5	70.2	71.9	29.3	77.6	22.2	1.00 0.00 0.00	% R00Y	#	
001	41.7	0.59	0.393	1.499	-0.016	0.691	22.9	17.5	28.8	37.3	70.7	61.3	99.1	116.6	58.2	1.00 0.25 0.00	% R25Y	#	
002	56.0	0.554	0.444	1.249	0.0	0.527	16.7	24.3	29.5	55.5	79.6	39.3	135.2	144.8	73.7	1.00 0.50 0.00	% R50Y	#	
003	69.3	0.516	0.481	1.072	-0.092	0.45	8.5	30.0	31.2	74.2	86.7	18.2	143.3	140.5	82.7	1.00 0.75 0.00	% R75Y	#	
004	83.1	0.476	0.515	0.923	-0.086	0.43	-2.1	35.6	35.7	93.5	93.0	-4.4	142.7	142.8	91.7	1.00 1.00 0.00	% Y00G	#	
005	92.9	0.429	0.533	0.805	-0.027	0.433	-13.4	37.9	40.2	109.5	97.1	-26.2	117.8	120.7	102.5	0.75 1.00 0.00	% Y25G	#	
006	84.5	0.373	0.575	0.649	-0.035	0.5	-25.4	33.8	42.3	126.9	93.6	-56.2	107.3	121.2	117.6	0.50 1.00 0.00	% Y50G	#	
007	71.9	0.276	0.634	0.435	-0.056	0.639	-37.0	27.2	46.0	143.6	87.9	-102.5	88.5	135.4	139.2	0.25 1.00 0.00	% Y75G	#	
008	61.7	0.188	0.532	0.354	-0.21	0.637	-36.8	13.9	39.3	159.2	82.8	-119.3	36.7	124.8	162.8	0.00 1.00 0.00	% G00B	#	
009	59.0	0.166	0.375	0.443	-0.487	0.599	-29.9	-3.0	30.1	185.8	81.3	-94.1	-6.4	94.3	183.9	0.00 1.00 0.50	% G25B	#	
010	58.2	0.163	0.296	0.552	-0.727	0.484	-23.2	-17.0	28.7	216.2	80.8	-69.1	-31.1	75.8	204.2	0.00 1.00 1.00	% G50B	#	
011	38.6	0.134	0.227	0.592	-1.124	0.776	-13.8	-26.6	30.0	242.5	68.5	-53.0	-54.1	75.7	225.6	0.00 0.50 1.00	% G75B	#	
012	18.7	0.127	0.129	0.985	-2.392	1.867	0.6	-34.9	34.9	271.0	59.3	3.4	-84.8	84.9	272.3	0.00 0.00 1.00	% B00R	#	
013	10.6	0.204	0.075	2.711	-3.816	3.812	18.8	-36.1	40.7	297.5	39.0	99.2	-106.7	141.4	314.5	0.50 0.00 1.00	% B25R	#	
014	29.3	0.338	0.152	2.224	-1.338	1.561	37.3	-26.4	45.8	324.6	61.0	108.8	-60.3	124.4	331.0	1.00 0.00 1.00	% B50R	#	
015	40.5	0.423	0.237	1.784	-0.572	0.845	33.8	-5.5	34.2	356.6	69.8	86.4	-14.1	87.5	350.7	1.00 0.00 0.50	% B75R	#	
016	41.1	0.508	0.314	1.615	-0.224	0.697	27.3	8.6	28.7	17.5	70.2	71.9	29.3	77.6	22.2	1.00 0.00 0.00	% R00Y	#	
CIEXYZ-Daten von CIE-Testfarben 9 (R): 20.6 11.2 4.3, 10 (Y): 54.8 59.0 12.0, 11 (G): 12.1 20.3 15.3, 12 (B): 6.2 6.4 27.6																			
5-stufige gleichabständige Graureihe mit Ziel-Helligkeit: L* = 0.0, 25.0, 50.0, 75.0, 100.0																			
000	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.00 0.00 0.00	% N000W	#	
001	4.4	0.312	0.329	0.95	-0.435	0.81	0.0	0.0	0.0	77.1	25.0	0.0	0.0	0.0	0.0	0.25 0.25 0.25	% N025W	#	
002	18.4	0.312	0.329	0.95	-0.435	0.81	0.0	0.0	0.0	57.4	50.0	0.0	0.0	0.0	0.0	0.50 0.50 0.50	% N050W	#	
003	48.2	0.312	0.329	0.95	-0.435	0.81	0.0	0.0	0.0	22.9	75.0	0.0	0.0	0.0	0.0	0.75 0.75 0.75	% N075W	#	
004	100.0	0.312	0.329	0.95	-0.435	0.81	0.0	0.0	0.0	0.0	100.0	0.0	0.0	0.0	0.0	1.00 1.00 1.00	% N100W	#	

0-000010-L0

VG300-7N

TUB-Prüfvorlage VG30; CIE-Daten für 16 Ostwald-Farben Eingabe: w/rgb/cmyk ->
LINYAB, Yxy, YABCABh, LabCabh-Daten, D65, 2- und 10-Grad-Beobachter

0-000010-F0

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _{w,10} =100, Y _m =520_770, LINYAB-Daten													%
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code	%	
0 405	31 556	56.57	-21.89	-18.32	28.54	0.5611	-0.7532	219.9	15 476	37 585	Cm	%	
6 435	31 557	57.41	-26.44	-8.79	27.86	0.4876	-0.5825	198.4	16 480	44 621		%	
10 450	31 559	57.53	-32.48	6.09	33.05	0.3834	-0.3234	169.3	18 491	-1 491c		%	
11 460	32 562	59.27	-33.9	10.52	35.5	0.3761	-0.2517	162.7	19 498	-1 498c		%	
12 465	33 565	60.91	-34.93	14.56	37.84	0.3747	-0.1903	157.3	21 506	-1 506c		%	
14 470	34 570	63.07	-35.18	20.67	40.8	0.3903	-0.1016	149.5	24 522	-1 522c		%	
15 475	35 579	68.64	-33.55	24.85	41.75	0.4593	-0.0672	143.4	26 533	-1 533c	Gm	%	
16 480	41 606	81.94	-23.65	31.88	39.7	0.6594	-0.0401	126.5	30 550	-1 550c		%	
16 485	-1 484c	92.3	-10.45	36.33	37.8	0.8348	-0.0356	106.0	32 560	10 454		%	
18 490	-1 490c	89.06	-7.57	36.55	37.33	0.863	-0.0188	101.7	32 562	11 459	max	%	
19 495	-1 495c	87.05	-5.68	36.18	36.62	0.8828	-0.0136	98.9	32 563	12 461		%	
19 500	-1 499c	87.05	-5.68	36.18	36.62	0.8828	-0.0136	98.9	32 563	12 461		%	
22 510	-1 510c	79.1	1.43	33.55	33.58	0.9662	-0.0051	87.5	33 567	13 466		%	
23 520	-1 519c	75.81	4.11	32.27	32.53	1.0024	-0.0036	82.7	33 568	13 468	Ym	%	
26 530	-1 530c	64.17	12.31	27.48	30.11	1.14	-0.001	65.8	34 573	14 472		%	
27 540	-1 539c	59.9	14.81	25.68	29.65	1.1955	-0.0005	60.0	35 576	14 473		%	
28 545	-1 544c	55.54	17.09	23.83	29.32	1.2559	-0.0002	54.3	35 578	14 474		%	
29 550	-1 549c	51.12	19.09	21.94	29.08	1.3215	-0.0001	48.9	36 580	15 475		%	
31 555	-1 555c	42.37	21.98	18.19	28.53	1.4668	0.0	39.6	37 586	15 476		%	
32 560	10 451	40.04	32.52	-6.18	33.11	1.7604	-0.5838	349.2	-1 492c	18 492		%	
380	770	100.0	0.0	0.0	0.01	0.9481	-0.4293	0.0				%	