

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D50, Y _w =100, Y _m =520_770, LINYAB-Daten													%	
i: λ ₁	i: λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d	i _c	i _c	Code	%	
1	405	32	564	57.81	-26.12	-13.56	29.43	0.5124	-0.5646	207.4	17	486	38 592 Cm	%
7	435	33	565	58.18	-29.76	-6.19	30.4	0.4526	-0.4365	191.7	18	490	46 634	%
10	450	33	566	58.68	-33.54	2.37	33.63	0.3924	-0.2895	175.9	19	497	-1 497c	%
12	460	33	567	59.3	-35.7	8.25	36.64	0.3621	-0.1907	166.9	21	506	-1 506c	%
13	465	33	568	59.95	-36.49	10.91	38.09	0.3555	-0.1478	163.3	22	511	-1 511c	%
14	470	34	570	61.04	-36.99	13.31	39.32	0.3581	-0.1117	160.1	23	519	-1 519c	%
15	475	34	573	62.89	-37.08	15.59	40.23	0.3745	-0.0821	157.2	25	527	-1 527c Gm	%
15	480	35	578	66.91	-36.91	16.91	40.6	0.4125	-0.0772	155.3	26	531	-1 531c	%
17	485	37	587	72.24	-34.33	20.9	41.09	0.4189	-0.0405	148.6	28	544	-1 544c	%
18	490	44	620	88.02	-19.26	26.82	33.02	0.7454	-0.0251	125.6	32	561	-1 561c max	%
19	495	-1 495c	93.65	-7.19	29.25	30.12	0.8874	-0.0176	103.8	33	568	12 463	%	
20	500	-1 500c	91.98	-5.59	29.14	29.67	0.9033	-0.0131	100.8	33	569	13 466	%	
22	510	-1 510c	87.33	-1.23	28.19	28.22	0.95	-0.0071	92.5	34	571	14 471	%	
23	520	-1 519c	84.29	1.48	27.36	27.41	0.9818	-0.0053	86.8	34	572	14 473 Ym	%	
25	530	-1 529c	76.8	7.64	25.11	26.25	1.0637	-0.0029	73.0	35	575	15 477	%	
27	540	-1 539c	68.0	13.94	22.33	26.32	1.1692	-0.0015	58.8	35	579	16 480	%	
28	545	-1 544c	63.34	16.86	20.82	26.8	1.2304	-0.0011	50.9	36	581	17 481	%	
30	550	-1 549c	58.55	19.56	19.26	27.45	1.2983	-0.0009	44.5	36	583	16 483	%	
30	555	-1 554c	53.72	21.93	17.68	28.17	1.3724	-0.0007	38.8	37	585	16 484	%	
32	560	-1 560c	44.27	25.38	14.58	29.27	1.5375	-0.0005	29.8	38	590	17 486	%	
380	770	100.0	0.0	0.0	0.0	0.0	0.9642	-0.3299	0.0				%	

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D50, Y _w =100, Y _m =770_520, LINYAB komplementär													%
i: λ ₁	i: λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d	i _d	i _c	i _c	Code %
32	564	1	405	42.18	26.12	13.56	29.43	1.5834	-0.0084	27.4	38	592	17 486 Rm %
33	565	7	435	41.81	29.76	6.19	30.4	1.6761	-0.1817	11.7	46	634	18 490 %
33	566	10	450	41.31	33.54	-2.37	33.63	1.7761	-0.3874	355.9	-1 497c	19	497 %
33	567	12	460	40.69	35.7	-8.25	36.64	1.8416	-0.5329	346.9	-1 506c	21	506 %
33	568	13	465	40.04	36.49	-10.91	38.09	1.8756	-0.6026	343.3	-1 511c	22	511 %
34	570	14	470	38.95	36.99	-13.31	39.32	1.9138	-0.6718	340.1	-1 519c	23	519 %
34	573	15	475	37.1	37.08	-15.59	40.23	1.9639	-0.7502	337.2	-1 527c	25	527 Mm %
35	578	15	480	33.08	36.91	-16.91	40.6	2.0799	-0.8412	335.3	-1 531c	26	531 %
37	587	17	485	27.75	34.33	-20.9	41.09	2.201	-1.0832	328.6	-1 544c	28	544 %
44	620	18	490	11.97	19.26	-26.82	33.02	2.5752	-2.5696	305.6	-1 561c	32	561 min %
-1 495c	19	495	6.34	7.19	-29.25	30.12	2.0975	-4.9398	283.8	12	463	33	568 %
-1 500c	20	500	8.01	5.59	-29.14	29.67	1.6629	-3.9666	280.8	13	466	33	569 %
-1 510c	22	510	12.66	1.23	-28.19	28.22	1.0617	-2.5572	272.5	14	471	34	571 %
-1 519c	23	520	15.7	-1.48	-27.36	27.41	0.8696	-2.073	266.8	14	473	34	572 Bm %
-1 529c	25	530	23.19	-7.64	-25.11	26.25	0.6346	-1.4127	253.0	15	477	35	575 %
-1 539c	27	540	31.99	-13.94	-22.33	26.32	0.5285	-1.0279	238.0	16	480	35	579 %
-1 544c	28	545	36.65	-16.86	-20.82	26.8	0.504	-0.8982	230.9	16	481	36	581 %
-1 549c	29	550	41.44	-19.56	-19.26	27.45	0.4922	-0.7949	224.5	16	483	36	583 %
-1 554c	30	555	46.27	-21.93	-17.68	28.17	0.4903	-0.7122	218.8	16	484	37	585 %
-1 560c	32	560	55.72	-25.38	-14.58	29.27	0.5087	-0.5917	209.8	17	486	38	590 %
380	770	100.0	0.0	0.0	0.0	0.0	0.9642	-0.3299	0.0				%

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D50, Y _w =100, Y _m =520_770, LINYAB-Daten													%		
i: λ ₁	i: λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d	i _d	i _c	i _c	Code	%	
1	405	31	559	55.95	-25.08	-13.86	28.66	0.5189	-0.5733	208.9	15	479	37	589 Cm	%
7	435	32	561	56.42	-28.9	-5.53	29.42	0.455	-0.4238	190.8	16	484	58	693	%
10	450	32	562	56.65	-32.28	3.24	32.45	0.3973	-0.2684	174.2	18	493	-1	493c	%
12	460	32	564	57.41	-33.96	8.98	35.12	0.3757	-0.1691	165.1	20	503	-1	503c	%
13	465	33	566	58.48	-34.34	11.63	36.25	0.38	-0.1267	161.2	22	512	-1	512c	%
14	470	34	570	60.63	-34.33	14.23	37.16	0.401	-0.0909	157.4	24	521	-1	521c	%
15	475	35	576	64.51	-33.34	16.97	37.41	0.4504	-0.0624	153.0	26	531	-1	531c Gm	%
16	480	38	590	72.88	-29.2	20.81	35.86	0.5665	-0.04	144.5	28	543	-1	543c	%
17	485	-1 485c	92.6	-6.09	28.04	28.69	0.9014	-0.0228	102.2	32	563	11	458	%	
18	490	-1 490c	91.1	-6.69	28.13	28.52	0.9157	-0.0168	99.4	32	564	12	460 max	%	
19	495	-1 495c	89.32	-2.98	27.98	28.14	0.9338	-0.0123	96.0	33	565	12	462	%	
20	500	-1 500c	87.23	-1.0	27.62	27.64	0.9556	-0.0089	92.0	33	566	12	464	%	
21	510	-1 509c	84.82	1.2	27.07	27.09	0.9814	-0.0065	87.4	33	567	13	466	%	
24	520	-1 520c	75.59	8.88	24.43	26.0	1.0847	-0.0023	70.0	34	571	14	471 Ym	%	
25	530	-1 529c	71.83	11.6	23.28	26.01	1.1288	-0.0015	63.4	34	573	14	473	%	
28	540	-1 540c	59.32	19.15	19.3	27.19	1.29	-0.0002	45.2	35	579	15	476	%	
29	545	-1 545c	54.91	21.22	17.87	27.75	1.3537	-0.0001	40.1	36	581	15	477	%	
29	550	-1 549c	54.91	21.22	17.87	27.75	1.3537	-0.0001	40.1	36	581	15	477	%	
31	555	-1 555c	46.06	24.31	15.0	28.56	1.4949	0.0	31.6	37	587	15	479	%	
32	560	2	411	41.79	25.61	12.8	28.63	1.5801	-0.0192	26.5	38	591	16	480	%
380	770	99.99	0.0	0.0	0.0	0.0	0.9672	-0.3256	0.0					%	

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D50, Y _w =100, Y _m =770_520, LINYAB komplementär													
i: λ ₁	i: λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d	i _c	i _c	Code %	
31	559	1	405	44.04	25.08	13.86	28.66	1.5368	-0.0108	28.9	37	589	15 479 Rm %
32	561	7	435	43.57	28.9	5.53	29.42	1.6305	-0.1985	10.8	58	693	16 484 %
32	562	10	450	43.34	32.28	-3.24	32.45	1.7122	-0.4004	354.2	-1 493c	18	493 %
32	564	12	460	42.58	35.95	-8.98	35.12	1.7646	-0.5366	345.1	-1 503c	20	503 %
33	566	13	465	41.51	34.34	-11.63	36.25	1.7943	-0.6057	341.2	-1 512c	22	512 %
34	570	14	470	39.36	34.33	-14.23	37.16	1.8395	-0.6872	337.4	-1 521c	24	521 %
35	576	15	475	35.48	33.34	-16.97	37.41	1.9607	-0.804	333.0	-1 531c	26	531 Mm %
38	590	16	480	27.11	29.2	-20.81	35.86	2.0442	-1.0933	324.5	-1 543c	28	543 %
-1 485c	17	485	7.39	6.09	-28.04	28.69	1.7911	-1.1155	282.2	11	458	32	563 %
-1 490c	18	490	8.89	6.69	-28.13	28.52	1.4945	-3.4884	279.4	12	460	32	564 min %
-1 495c	19	495	10.67	2.98	-27.98	28.14	1.247	-2.9472	276.0	12	462	33	565 %
-1 500c	20	500	12.76	1.0	-27.62	27.64	1.0462	-2.49	272.0	12	464	33	566 %
-1 509c	21	510	15.17	-1.2	-27.07	27.09	0.8876	-2.1102	267.4	13	466	33	567 %
-1 520c	24	520	24.4	-8.88	-24.43	26.0	1.0633	-1.3269	250.0	14	471	34	571 Bm %
-1 529c	25	530	28.16	-11.6	-23.28	26.01	0.555	-1.1521	243.4	14	473	34	573 %
-1 540c	28	540	40.67	-19.15	-19.3	27.19	0.4963	-0.8002	225.2	15	476	35	579 %
-1 545c	29	545	45.08	-21.22	-17.87	27.75	0.4964	-0.7221	220.1	15	477	36	581 %
-1 549c	29	550	45.08	-21.22	-17.87	27.75	0.4964	-0.7221	220.1	15	477	36	581 %
-1 555c	31	555	53.93	-24.31	-15.0	28.56	0.5164	-0.6038	211.6	15	479	37	587 %
2 411	32	560	58.2	-25.61	-12.8	28.63	0.5271	-0.5456	206.5	16	480	38	591 %
380	770	99.99	0.0	0.0	0.0	0.0	0.9672	-0.3256	0.0				