

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =520_770, LINYAB-Daten														%
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code		%	
0 405	32 561	58.2	-22.74	-17.89	28.94	0.5596	-0.743	218.1	16 483	37 589	Cm		%	
6 435	32 562	58.79	-26.78	-9.88	28.55	0.4948	-0.6036	200.2	17 486	42 610			%	
10 450	32 563	59.42	-33.54	4.93	33.9	0.3859	-0.3525	171.6	19 496	-1 496c			%	
12 460	33 565	60.32	-36.45	12.66	38.58	0.3461	-0.2256	160.8	21 505	-1 505c			%	
12 465	33 567	61.66	-36.65	13.24	38.97	0.356	-0.2207	160.1	21 506	-1 506c			%	
14 470	33 569	62.72	-38.14	19.32	42.76	0.3422	-0.1274	153.1	24 520	-1 520c			%	
15 475	34 573	65.29	-38.28	22.47	44.39	0.364	-0.0913	149.5	25 528	-1 528c	Gm		%	
16 480	36 580	69.95	-37.48	26.04	45.64	0.4146	-0.0632	145.2	27 537	-1 537c			%	
17 485	39 595	78.75	-32.73	31.0	45.09	0.5347	-0.0418	136.5	29 548	-1 548c			%	
18 490	-1 490c	93.8	-12.06	38.4	40.25	0.8218	-0.0261	107.4	33 565	11 459	max		%	
19 495	-1 495c	92.3	-10.68	38.39	39.85	0.8346	-0.0195	105.5	33 566	12 462			%	
20 500	-1 500c	90.42	-8.91	38.07	39.1	0.8518	-0.0144	103.1	33 567	12 464			%	
22 510	-1 510c	85.27	-4.15	36.48	36.72	0.9016	-0.0076	96.5	33 569	13 469			%	
23 520	-1 519c	81.98	-1.26	35.24	35.26	0.935	-0.0056	92.0	34 570	14 471	Ym		%	
25 530	-1 529c	74.04	5.15	32.02	32.43	1.0201	-0.0031	80.8	34 573	15 475			%	
27 540	-1 539c	64.9	11.57	28.16	30.44	1.1288	-0.0016	67.6	35 577	15 478			%	
28 545	-1 544c	60.13	14.5	26.11	29.87	1.1917	-0.0012	60.9	35 579	15 479			%	
29 550	-1 549c	55.26	17.18	24.01	29.53	1.2613	-0.0009	54.4	36 582	16 480			%	
30 555	-1 554c	50.4	19.49	21.91	29.33	1.3372	-0.0007	48.3	36 584	16 481			%	
32 560	-1 560c	41.0	22.8	17.83	28.95	1.5064	-0.0005	38.0	37 589	16 483			%	
380	770	100.0	0.0	0.0	0.01	0.9504	-0.4355	0.0					%	

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für D65, Y _w =100, Y _m =770_520, LINYAB komplementär%														
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀₀	A ₁₀₀	B ₁₀₀	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code		%	
32 561	0 405	41.79	22.74	17.89	28.94	1.4946	-0.0072	38.1	37 589	16 483	Rm		%	
32 562	6 435	41.2	26.78	9.88	28.55	1.6006	-0.1956	20.2	42 610	17 486			%	
32 563	10 450	40.57	33.54	-4.93	33.9	1.7771	-0.557	351.6	-1 496c	19 496			%	
33 565	12 460	39.67	36.45	-12.66	38.58	1.8691	-0.7547	340.8	-1 505c	21 505			%	
33 567	12 465	38.33	36.65	-13.24	38.97	1.9064	-0.781	340.1	-1 506c	21 506			%	
33 569	14 470	37.27	38.14	-19.32	42.76	1.9738	-0.954	333.1	-1 520c	24 520			%	
34 573	15 475	34.7	38.28	-22.47	44.39	2.0536	-1.083	329.5	-1 528c	25 528	Mm		%	
36 580	16 480	30.04	37.48	-26.04	45.64	2.1982	-1.3026	325.2	-1 537c	27 537			%	
39 595	17 485	21.24	32.73	-31.0	45.09	2.4914	-1.8952	316.5	-1 548c	29 548			%	
-1 490c	18 490	6.19	12.06	-38.4	40.25	2.899	-6.6372	287.4	11 459	33 565	min		%	
-1 495c	19 495	7.69	10.68	-38.39	39.85	2.3392	-5.4245	285.5	12 462	33 566			%	
-1 500c	20 500	9.57	8.91	-38.07	39.1	1.8814	-4.4105	283.1	12 464	33 567			%	
-1 510c	22 510	14.72	4.15	-36.48	36.72	1.2328	-2.9143	276.5	13 469	33 569			%	
-1 519c	23 520	18.01	1.26	-35.24	35.26	1.0204	-2.3925	272.0	14 471	34 570	Bm		%	
-1 529c	25 530	25.95	-5.15	-32.02	32.43	0.7516	-1.6693	260.8	15 475	34 573			%	
-1 539c	27 540	35.09	-11.57	-28.16	30.44	0.6205	-1.238	247.6	15 478	35 577			%	
-1 544c	28 545	39.86	-14.5	-26.11	29.87	0.5865	-1.0906	240.9	15 479	35 579			%	
-1 549c	29 550	44.73	-17.18	-24.01	29.53	0.5663	-0.9725	234.4	16 480	36 582			%	
-1 554c	30 555	49.59	-19.49	-21.91	29.33	0.5572	-0.8774	228.3	16 481	36 584			%	
-1 560c	32 560	58.99	-22.8	-17.83	28.95	0.5638	-0.7379	218.0	16 483	37 589			%	
380	770	100.0	0.0	0.0	0.01	0.9504	-0.4355	0.0					%	