

Siehe ähnliche Dateien: <http://130.149.60.45/~farbmetrik/VG50/VG50L0N1.TXT /PS>
Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmetrik>

iimp=330, RI=RICHTER colour difference pairs %

im	ia	d_rangeLAB	LABmin,max,ave	STRESS	CMCmin,max,ave	STRESS	C94min,max,ave	STRESS	C00min,max,ave	STRESS	C85min,max,ave	STRESS										
330	330	0.0 to 99	0.05	4.85	0.9	61.04	0.04	2.49	0.73	50.04	0.05	1.71	0.52	47.78	0.05	1.71	0.59	52.49	0.54	3.91	1.86	30.26
330	330	0.0 to 5.0	0.05	4.85	0.9	61.04	0.04	2.49	0.73	50.04	0.05	1.71	0.52	47.78	0.05	1.71	0.59	52.49	0.54	3.91	1.86	30.26
330	87	0.0 to 0.5	0.05	0.49	0.23	60.16	0.04	0.73	0.24	49.5	0.05	0.48	0.18	47.84	0.05	0.73	0.17	48.28	0.54	2.21	1.32	23.7
330	137	0.5 to 1.0	0.5	0.99	0.76	56.38	0.22	1.44	0.85	42.75	0.2	0.97	0.58	41.34	0.2	1.31	0.72	42.61	0.79	3.13	1.84	21.53
330	67	1.0 to 1.5	1.01	1.46	1.18	63.16	0.33	1.98	0.97	51.35	0.2	1.24	0.69	49.36	0.2	1.63	0.77	50.66	1.31	3.37	2.34	23.89
330	14	1.5 to 2.0	1.5	1.89	1.69	69.53	0.58	2.49	0.92	50.95	0.46	1.71	0.75	43.02	0.46	1.71	0.76	45.06	1.46	2.86	2.32	15.8
330	0	5.0 to 10																				
330	0	10 to 15																				
330	0	15 to 20																				
330	0	20 to 25																				
330	0	25 to 30																				
330	0	30 to 99																				

iimp=330, RI=RICHTER colour difference pairs %

im	ia	d_rangeC00	LABmin,max,ave	STRESS	CMCmin,max,ave	STRESS	C94min,max,ave	STRESS	C00min,max,ave	STRESS	C85min,max,ave	STRESS
330	330	0.0 to 99	0.05 4.85	0.9 61.04	0.04 2.49	0.73 50.04	0.05 1.71	0.52 47.78	0.05 1.71	0.59 52.49	0.54 3.91	1.86 30.26
330	330	0.0 to 5.0	0.05 4.85	0.9 61.04	0.04 2.49	0.73 50.04	0.05 1.71	0.52 47.78	0.05 1.71	0.59 52.49	0.54 3.91	1.86 30.26
330	144	0.0 to 0.5	0.05 1.54	0.49 56.38	0.04 0.96	0.35 42.18	0.05 0.56	0.25 40.51	0.05 0.49	0.24 42.13	0.54 3.37	1.66 21.06
330	128	0.5 to 1.0	0.49 3.78	1.23 57.52	0.59 1.44	0.92 43.41	0.46 1.16	0.66 41.56	0.5 0.99	0.76 42.01	1.06 3.91	2.06 22.15
330	55	1.0 to 1.5	0.69 4.85	1.17 68.79	0.95 1.88	1.24 44.17	0.66 1.24	0.85 36.82	1.0 1.49	1.1 38.93	1.12 3.19	1.92 25.16
330	3	1.5 to 2.0	1.13 1.75	1.41 10.31	1.59 2.49	2.02 19.92	1.08 1.71	1.31 19.07	1.6 1.71	1.65 19.72	1.31 3.22	2.08 9.79

iimp=330, RI=RICHTER colour difference pairs %

im	ia	d_rangeC85	LABmin,max,ave		STRESS		CMCmin,max,ave		STRESS		C94min,max,ave		STRESS		C00min,max,ave		STRESS		C85min,max,ave		STRESS	
330	330	0.0 to 99	0.05	4.85	0.9	61.04	0.04	2.49	0.73	50.04	0.05	1.71	0.52	47.78	0.05	1.71	0.59	52.49	0.54	3.91	1.86	30.26
330	330	0.0 to 5.0	0.05	4.85	0.9	61.04	0.04	2.49	0.73	50.04	0.05	1.71	0.52	47.78	0.05	1.71	0.59	52.49	0.54	3.91	1.86	30.26
330	0	0.0 to 0.5																				
330	22	0.5 to 1.0	0.05	0.8	0.15	70.58	0.04	0.37	0.1	51.98	0.05	0.24	0.1	40.5	0.05	0.25	0.1	42.7	0.54	0.99	0.78	14.6
330	70	1.0 to 1.5	0.09	1.54	0.48	61.95	0.09	1.59	0.58	50.74	0.09	1.08	0.41	48.94	0.07	1.63	0.52	50.12	1.04	1.49	1.3	23.39
330	109	1.5 to 2.0	0.14	4.85	0.87	58.35	0.13	2.49	0.79	45.87	0.11	1.71	0.56	43.84	0.09	1.71	0.65	44.36	1.51	1.99	1.73	22.83
330	0	5.0 to 10																				
330	0	10 to 15																				
330	0	15 to 20																				
330	0	20 to 25																				
330	0	25 to 30																				
330	0	30 to 99																				

TUB-Registrierung: 20140801-VG50/VG50L0N1.TXT /PS
Anwendung für Messung von Display- oder Drucker-Ausgabe

TUB-Material: Code=th41a