

Farbreize für gerade unterscheidbare Farb-Schwellen (p=50%) in 4 Richtungen

Nummer Farb- Serie	Farbreize Normfarbwerte			Farbreiz-Differenzen an der Schwelle				Bemerkungen Experiment- Serie
	Y	x	y	Δx _TM	Δy _TM	Δx _BY	Δy _BY	
0 GDV	17.42	0.2192	0.6811	-0.0064	0.0066	-0.0054	0.014	_TM, _BY graues Umfeld CIE-Daten Nr. 05 mit weissem Rand
1 GDV	16.9	0.2577	0.5648	-0.005	0.0044	-0.0029	0.0076	
2 GDV	16.4	0.2875	0.4664	-0.0025	0.0019	-0.0018	0.0046	
3 GDV	16.91	0.3051	0.4122	-0.0023	0.0016	-0.0015	0.0037	
4 GDV	16.7	0.3165	0.3791	-0.002	0.0013	-0.0013	0.0029	
5 GDV	16.51	0.3234	0.3568	-0.0017	0.0011	-0.0009	0.002	
6 GDV	15.06	0.3311	0.3322	-0.0021	0.0011	-0.001	0.0024	
7 GDV	14.17	0.3387	0.301	-0.002	0.001	-0.001	0.0022	
8 GDV	14.06	0.344	0.2792	-0.002	0.0009	-0.0011	0.0024	
9 GDV	13.57	0.3482	0.2641	-0.002	0.0008	-0.001	0.0023	
10 GDV	13.26	0.3515	0.2516	-0.0019	0.0008	-0.001	0.0021	
11 RDC	16.44	0.6152	0.3414	-0.0013	0.0017	0.0007	0.0031	_TM, _BY graues Umfeld CIE-Daten Nr. 16 mit weissem Rand
12 RDC	15.81	0.5421	0.3436	-0.0018	0.0018	0.0001	0.0026	
13 RDC	16.2	0.4549	0.3285	-0.0015	0.0012	-0.0003	0.0025	
14 RDC	16.72	0.4097	0.3512	-0.0017	0.0012	-0.0006	0.0027	
15 RDC	16.79	0.362	0.3542	-0.0017	0.0011	-0.0007	0.002	
16 RDC	16.64	0.3222	0.3567	-0.0015	0.0009	-0.0008	0.002	
17 RDC	16.05	0.2876	0.3649	-0.0021	0.0012	-0.0013	0.0027	
18 RDC	16.69	0.2386	0.3769	-0.0025	0.0014	-0.0022	0.0036	
19 RDC	17.71	0.213	0.3831	-0.0027	0.0014	-0.0024	0.0036	
20 RDC	18.02	0.1875	0.3897	-0.0029	0.0016	-0.0025	0.0037	
21 RDC	18.33	0.1664	0.3949	-0.0037	0.0019	-0.003	0.0042	
				_GV	_GV	_RC	_RC	
22 GDV	17.42	0.2174	0.6877	-0.0029	-0.0064	0.0084	0.0	_GV, _RC graues Umfeld CIE-Daten Nr. 27 mit weissem Rand
23 GDV	16.91	0.2564	0.5691	-0.0025	-0.004	0.0057	-0.0001	
24 GDV	16.41	0.2874	0.4688	-0.0022	-0.0028	0.0049	-0.0001	
25 GDV	16.92	0.305	0.4141	-0.002	-0.0022	0.0033	-0.0001	
26 GDV	16.71	0.3164	0.3807	-0.0018	-0.0018	0.0028	-0.0001	
27 GDV	16.52	0.3234	0.3581	-0.0017	-0.0015	0.0023	-0.0001	
28 GDV	15.06	0.3311	0.3336	-0.0021	-0.0017	0.0029	-0.0001	
29 GDV	14.18	0.3388	0.3023	-0.002	-0.0013	0.0032	-0.0001	
30 GDV	14.06	0.344	0.2804	-0.0021	-0.0013	0.003	-0.0001	
31 GDV	13.57	0.3483	0.2652	-0.0021	-0.0013	0.0031	0.0	
32 GDV	13.26	0.3515	0.2527	-0.002	-0.0012	0.003	0.0	
33 RDC	16.44	0.6162	0.3431	-0.0035	-0.0017	0.0059	-0.0001	_GV, _RC graues Umfeld CIE-Daten Nr. 38 mit weissem Rand
34 RDC	15.81	0.543	0.3455	-0.0034	-0.0018	0.0047	0.0	
35 RDC	16.2	0.4556	0.3301	-0.0029	-0.0018	0.0042	-0.0001	
36 RDC	16.72	0.4102	0.3528	-0.0025	-0.0018	0.0033	-0.0001	
37 RDC	16.8	0.3622	0.3556	-0.002	-0.0017	0.0027	-0.0001	
38 RDC	16.65	0.3223	0.3579	-0.0017	-0.0013	0.002	-0.0001	
39 RDC	16.05	0.2874	0.3664	-0.0016	-0.0016	0.0041	-0.0001	
40 RDC	16.7	0.2382	0.3787	-0.0017	-0.0019	0.0039	-0.0001	
41 RDC	17.72	0.2123	0.3848	-0.0013	-0.0018	0.0045	-0.0001	
42 RDC	18.03	0.1867	0.3914	-0.0012	-0.0019	0.005	0.0	
43 RDC	18.33	0.1652	0.3969	-0.0012	-0.002	0.0057	-0.0001	

Muster: Grün (G, Nr. 00 oder 22), Violett V (Nr. 10 oder 32), Rot (R, Nr. 11 oder 33)
Cyan (C, Nr. 21 oder 43), Grau (Nr. 05, 16, 27 oder 38), Weiss (Y=100)
Quelle: BAM-Forschungsbericht Nr. 115 (1985), Tabellen 5.40;1 bis 11