

Güte (STRESS-Werte) für kleine (small) Farbdifferenzdaten (SCD)

iimp=418, WI=WITT colour difference pairs %

ia	d_rangeLAB	LABmin,max,mean	STRESS	CMCmin,max,mean	STRESS	C94min,max,mean	STRESS	C00min,max,mean	STRESS	C85min,max,mean	STRESS
418 418	0.0 to <99	0.11	10.62 1.86 51.7	0.08 4.7	1.25 39.5	0.08 3.72	1.07 31.6	0.08 3.75	1.09 33.7	0.55 29.71	6.85 55.1 %
418 400	0.0 to <5.0	0.11	4.94 1.67 51.9	0.08 4.7	1.19 38.8	0.08 3.72	1.02 31.9	0.08 3.75	1.04 33.8	0.55 29.71	6.63 55.7 %
418 38	0.0 to <0.5	0.11	0.49 0.36 51.4	0.08 0.72	0.32 33.8	0.08 0.47	0.28 29.1	0.08 0.62	0.29 22.7	0.55 4.44	2.0 52.4 %
418 88	0.5 to <10	0.51	0.99 0.74 57.7	0.27 1.53	0.64 37.8	0.23 0.99	0.55 33.1	0.23 1.42	0.58 30.3	0.79 8.71	3.56 55.4 %
418 91	1.0 to <1.5	1.01	1.49 1.26 57.7	0.42 2.15	1.06 37.7	0.34 1.49	0.91 32.9	0.34 1.86	0.92 30.2	1.45 13.86	6.02 55.2 %
418 57	1.5 to <2.0	1.51	1.99 1.74 56.4	0.78 2.77	1.44 34.9	0.62 1.92	1.26 28.5	0.63 2.82	1.3 23.6	2.34 15.67	8.34 53.6 %
418 126	2.0 to <5.0	2.03	4.94 2.98 56.8	0.83 4.7	1.83 42.0	0.66 3.72	1.55 34.0	0.66 3.75	1.55 32.6	2.8 29.71	9.83 58.3 %
418 17	5.0 to <10	5.03	8.75 5.89 43.7	2.02 3.38	2.55 29.0	1.69 2.66	2.14 28.8	1.63 2.83	2.17 24.8	6.98 26.87	11.5 41.5 %
418 1	10 to <15	10.62	10.62 10.62 0.1	4.07 4.07	4.07 0.1	3.18 3.18	3.18 0.1	3.43 3.43	3.43 0.1	14.9 14.9	14.9 0.1 %
418 0	15 to <20 %										
418 0	20 to <25 %										
418 0	25 to <30 %										
418 0	30 to <99 %										

iimp=418, WI=WITT colour difference pairs %

ia	d_rangeC00	LABmin,max,mean	STRESS	CMCmin,max,mean	STRESS	C94min,max,mean	STRESS	C00min,max,mean	STRESS	C85min,max,mean	STRESS
418 418	0.0 to <99	0.11	10.62 1.86 51.7	0.08 4.7	1.25 39.5	0.08 3.72	1.07 31.6	0.08 3.75	1.09 33.7	0.55 29.71	6.85 55.1 %
418 418	0.0 to <5.0	0.11	10.62 1.86 51.7	0.08 4.7	1.25 39.5	0.08 3.72	1.07 31.6	0.08 3.75	1.09 33.7	0.55 29.71	6.85 55.1 %
418 83	0.0 to <0.5	0.11	1.21 0.58 58.6	0.08 0.69	0.37 38.5	0.08 0.54	0.34 33.1	0.08 0.49	0.33 30.4	0.55 6.24	2.51 52.7 %
418 123	0.5 to <1.0	0.44	3.69 1.26 56.7	0.42 1.5	0.84 41.9	0.44 1.34	0.75 33.8	0.5 0.99	0.74 32.4	1.08 12.7	4.99 57.8 %
418 107	1.0 to <1.5	0.76	4.45 2.09 57.2	0.84 2.38	1.41 41.2	0.75 2.1	1.22 32.8	1.0 1.49	1.22 30.9	1.83 17.41	8.11 53.4 %
418 69	1.5 to <2.0	1.17	5.72 2.98 59.4	1.2 2.96	2.01 38.8	1.15 2.94	1.7 32.4	1.5 1.99	1.71 29.4	2.47 25.7	10.36 51.9 %
418 36	2.0 to <5.0	1.54	10.62 4.08 50.8	1.69 4.7	2.8 34.4	1.52 3.72	2.26 29.4	2.0 3.75	2.43 23.1	3.82 29.71	12.7 52.7 %
418 0	5.0 to <10 %										
418 0	10 to <15 %										
418 0	15 to <20 %										
418 0	20 to <25 %										
418 0	25 to <30 %										
418 0	30 to <99 %										

iimp=418, WI=WITT colour difference pairs %

ia	d_rangeC85	LABmin,max,mean	STRESS	CMCmin,max,mean	STRESS	C94min,max,mean	STRESS	C00min,max,mean	STRESS	C85min,max,mean	STRESS
418 418	0.0 to <99	0.11	10.62 1.86 51.7	0.08 4.7	1.25 39.5	0.08 3.72	1.07 31.6	0.08 3.75	1.09 33.7	0.55 29.71	6.85 55.1 %
418 189	0.0 to <5.0	0.11	4.39 1.11 54.5	0.08 2.75	0.83 40.0	0.08 1.88	0.64 33.2	0.08 2.82	0.7 32.9	0.55 4.97	2.91 57.9 %
418 0	0.0 to <0.5 %										
418 8	0.5 to <1.0	0.11	0.56 0.31 12.6	0.08 0.3	0.2 12.3	0.08 0.24	0.17 12.3	0.08 0.27	0.19 11.0	0.55 0.88	0.76 11.1 %
418 18	1.0 to <1.5	0.23	1.03 0.61 45.8	0.13 0.82	0.42 30.1	0.13 0.52	0.33 29.9	0.13 0.78	0.37 25.6	1.08 1.49	1.34 43.6 %
418 20	1.5 to <2.0	0.24	1.12 0.72 49.3	0.2 1.43	0.62 30.4	0.19 0.92	0.45 30.3	0.17 1.35	0.55 25.5	1.5 1.99	1.72 46.9 %
418 143	2.0 to <5.0	0.21	4.39 1.27 56.7	0.19 2.75	0.95 42.1	0.19 1.88	0.73 34.6	0.17 2.82	0.79 33.9	5.01 9.74	7.03 59.5 %
418 132	5.0 to <10	0.59	6.68 2.3 57.1	0.43 4.51	1.54 42.4	0.49 2.51	1.24 34.6	0.45 3.75	1.27 33.7	2.01 14.94	12.38 51.8 %
418 71	10 to <15	1.08	10.62 2.54 59.8	0.78 4.7	1.58 39.3	0.95 3.31	1.54 33.2	0.81 3.43	1.47 30.5	15.0 19.58	16.71 39.2 %
418 16	15 to <20	1.84	7.51 3.27 41.4	1.22 3.2	1.92 27.3	1.39 2.52	1.93 27.1	1.36 2.61	1.8 23.2	20.36 23.8	21.7 13.2 %
418 6	20 to <25	2.12	4.25 2.95 14.2	1.69 2.23	1.87 13.9	1.86 2.94	2.28 13.9	1.56 2.28	2.02 12.9	25.7 29.71	27.26 11.4 %
418 4	25 to <30	2.64	5.67 3.92 12.3	2.14 2.96	2.45 12.1	2.34 3.72	2.85 12.1	1.96 2.73	2.46 11.5		
418 0	30 to <99 %										

Siehe ähnliche Dateien: <http://130.149.60.45/~farbmtrik/VG92/VG92L0N1.TXT /PS>
Technische Information: <http://www.ps.bam.de> oder <http://130.149.60.45/~farbmtrik>

TUB-Registrierung: 20140801-VG92/VG92L0N1.TXT /PS
Anwendung für Messung von Display- oder Drucker-Ausgabe

TUB-Material: Code=th4ta